

**nokian<sup>®</sup>**  
**TYRES**


**NOKIAN TYRES**

SILENT SIDEWALL TECHNOLOGY

M ARABIA

335 733

**PASSENGER CAR & LIGHT TRUCK TIRES  
PRODUCT CATALOG 2026**





**nokian<sup>®</sup>  
TYRES**

**PEACE OF MIND FOR EVERY CONDITION**


## TABLE OF CONTENTS

<b>SUCCESS STORY</b>	3
<b>WINTER</b>	4
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> 10	4
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> 10 EV	6
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> 10 SUV	7
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> C4	9
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> CR4	10
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> LT3	11
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> R5	12
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> R5 EV	14
NOKIAN TYRES HAKKAPELIITTA <sup>®</sup> R5 SUV	16
<b>ALL-SEASON</b>	18
NOKIAN TYRES ONE	18
NOKIAN TYRES ONE HT	20
NOKIAN TYRES OUTPOST APT	27
NOKIAN TYRES OUTPOST NAT	29
NOKIAN TYRES SURPASS <sup>®</sup> ASO1	22
<b>ALL-WEATHER</b>	24
NOKIAN TYRES OUTPOST APT	27
NOKIAN TYRES OUTPOST NAT	29
NOKIAN TYRES REMEDY WRG5	24
NOKIAN TYRES WR C3	26
<b>ALL-TERRAIN</b>	27
NOKIAN TYRES OUTPOST APT	27
NOKIAN TYRES OUTPOST NAT	29
<b>ARTICLES</b>	31
FEATURED PRODUCT	32
TESTING FUTURE LEGENDS	33
<b>RESOURCES</b>	34
CONSUMER PROMISES OVERVIEW	35
CONSUMER PROMISES	36
LIMITED WARRANTY	38
QUICK TIRE SIZE REFERENCE	41



### ALL-SEASON TIRES

Built for wet roads or dry heat. Your go-to tire for warmer climates and conditions.



### ALL-WEATHER TIRES

Designed for safety in rain, dry heat and snow. The only tire suitable for all driving conditions.



### WINTER TIRES

Renowned safety and performance in snow and ice. Our studded and studless options excel in harsh winter conditions.



# NOKIAN TYRES NORTH AMERICA SUCCESS STORY

**FROM NORTH AMERICA, FOR NORTH AMERICA.** Finnish Innovation. North American grit. Millions of tires roll from our award-winning factory in Dayton, Tennessee to tire shops across the U.S. and Canada. Because drivers here deserve tires made with their unique needs in mind.

[NOKIANTYRES.COM/DAYTONFACTORY](http://NOKIANTYRES.COM/DAYTONFACTORY)



## CONSUMER REPORTS RECOMMENDS

# 2

### NOKIAN TYRES PRODUCTS

The Nokian Tyres Hakkapeliitta R5 winter tire and Nokian Tyres Surpass AS01 ultra-high performance all-season tire are CR Recommended® tires.

## WORLD-RENOWNED TEST FACILITIES

# 2

### ONE IN THE FINNISH ARCTIC, ONE IN SPAIN

Nokian Tyres built two world-renowned company-owned test facilities -- one in the Finnish Arctic, and one in Spain.

## INVENTOR OF THE ALL-WEATHER TIRE

# 4

### FOUR-SEASON DRIVING SOLUTION

Nokian Tyres introduced the only true four-season driving solution to North America: the all-weather tire.

## WITH YOU WHERE YOUR ROADS TAKE YOU

# 5

### SEGMENTS

All-Season, Ultra-High Performance All-Season, All-Terrain, All-Weather and Winter



## NOKIAN TYRES INVENTED THE WINTER TIRE

# 90+

YEARS AGO

Nokian Tyres invented the winter tire more than 90 years ago, and we hold more patents on winter tire technology than any other tire maker.

# WINTER

## NOKIAN TYRES HAKKAPELIITTA® 10 NEXT-GENERATION SAFETY

PASSENGER



WINTER

- ULTIMATE SAFETY – SUPERIOR GRIP ON ICE AND SNOW
- STABLE AND PRECISE HANDLING, EVEN ON BARE ROADS
- MAXIMUM DRIVING COMFORT WITH PLEASANT SOUND LEVELS
- IMPROVED MILEAGE AND LOW FUEL CONSUMPTION



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi		
14	175/65 R 14 86T XL	TS32421	16.5	23.0	7.0	5	6	5	1168	86	T	11.5	51	877	545
15	175/65 R 15 88T XL	TS32423	17.6	24.0	7.0	5	6	5	1235	88	T	11.5	51	840	522
	185/60 R 15 88T XL	TS32422	17.6	23.7	7.4	5	6.5	5.5	1235	88	T	11.5	51	851	529
	185/65 R 15 92T XL	TS32424	18.7	24.5	7.4	5	6.5	5.5	1390	92	T	11.5	51	823	512
	195/65 R 15 95T XL	TS32425	19.8	25.0	7.9	5.5	7	6	1520	95	T	11.5	51	807	501
16	195/55 R 16 91T XL	TS32426	19.8	24.4	7.9	5.5	7	6	1355	91	T	11.5	51	827	514
	205/55 R 16 94T XL	TS32427	20.9	24.9	8.4	5.5	7.5	6.5	1477	94	T	11.5	51	810	503
	205/60 R 16 96T XL	TS32430	22.0	25.7	8.2	5.5	7.5	6	1565	96	T	11.5	51	785	488
	205/65 R 16 95T	TS32432	27.6	26.5	8.2	5.5	7.5	6	1520	95	T	11.5	47	761	473
	215/55 R 16 97T XL	TS32428	23.1	25.3	8.9	6	7.5	7	1610	97	T	11.5	51	797	495
	215/60 R 16 99T XL	TS32431	27.6	26.1	8.7	6	7.5	6.5	1710	99	T	11.5	51	773	480
	225/55 R 16 99T XL	TS32429	25.4	25.8	9.2	6	8	7	1710	99	T	11.5	51	782	486
17	175/65 R 17 87T	TS32804	19.8	26.0	7.0	5	6	5	1200	87	T	11.5	47	776	482
	205/50 R 17 93T XL	TS32436	22.0	25.1	8.4	5.5	7.5	6.5	1435	93	T	11.5	51	804	499
	205/55 R 17 95T XL	TS32439	23.1	25.9	8.4	5.5	7.5	6.5	1520	95	T	11.5	51	779	484
	215/50 R 17 95T XL	TS32437	23.1	25.5	8.9	6	7.5	7	1520	95	T	11.5	51	791	491
	215/55 R 17 98T XL	TS32440	27.6	26.3	8.9	6	7.5	7	1655	98	T	11.5	51	767	476
	225/45 R 17 94T XL	TS32433	24.3	25.0	8.9	7	8.5	7.5	1477	94	T	11.5	51	807	501
	225/50 R 17 98T XL	TS32438	26.5	25.9	9.2	6	8	7	1655	98	T	11.5	51	779	484
	225/55 R 17 101T XL	TS32441	28.7	26.8	9.2	6	8	7	1820	101	T	11.5	51	753	468
	235/45 R 17 97T XL	TS32434	26.5	25.4	9.3	7.5	9	8	1610	97	T	11.5	51	794	493
	245/45 R 17 99T XL	TS32435	28.7	25.7	9.6	7.5	9	8	1710	99	T	11.5	51	785	488
18	225/40 R 18 92T XL	TS32442	24.3	25.1	9.1	7.5	9	8	1390	92	T	11.5	51	804	499
	225/45 R 18 95T XL	TS32445	25.4	25.9	8.9	7	8.5	7.5	1520	95	T	11.5	51	779	484
	225/50 R 18 99T XL	TS32448	28.7	26.9	9.2	6	8	7	1710	99	T	11.5	51	750	466
	235/40 R 18 95T XL	TS32443	27.6	25.4	9.5	8	9.5	8.5	1520	95	T	11.5	51	794	493
	235/45 R 18 98T XL	TS32446	29.8	26.3	9.3	7.5	9	8	1655	98	T	11.5	51	767	476
	245/40 R 18 97T XL	TS32444	27.6	25.7	9.8	8	9.5	8.5	1610	97	T	11.5	51	785	488
	245/45 R 18 100T XL	TS32447	29.8	26.6	9.6	7.5	9	8	1765	100	T	11.5	51	758	471
19	235/40 R 19 96T XL	TS32452	28.7	26.4	9.5	8	9.5	8.5	1565	96	T	11.5	51	764	475
	245/40 R 19 98T XL	TS32453	28.7	26.7	9.8	8	9.5	8.5	1655	98	T	11.5	51	755	469
	245/45 R 19 102T XL	TS32455	30.9	27.7	9.6	7.5	9	8	1875	102	T	11.5	51	728	452
	255/40 R 19 100T XL	TS32454	32.0	27.0	10.2	8.5	10	9	1765	100	T	11.5	51	747	464
	275/40 R 19 105T XL	TS32842	32.0	27.7	10.9	9	11	9.5	2040	105	T	11.5	51	728	452
20	245/40 R 20 99T XL	TS32458	30.9	27.7	9.8	8	9.5	8.5	1710	99	T	11.5	51	728	452
	245/35 R 20 95T XL	TS32775	29.8	26.8	9.8	8	9.5	8.5	1520	95	T	11.5	51	753	468

Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi		
	275/35 R 20 102T XL	TS32457	35.3	27.6	10.9	9	11	9.5	1875	102	T	11.5	51	731	454



FOR ELECTRIC CARS



3PMSF



ICE GRIP



14-20"



T 118 mph



[WWW.NOKIANTYRES.COM/  
HAKKAPELIITTA10](http://WWW.NOKIANTYRES.COM/HAKKAPELIITTA10)

# NOKIAN TYRES HAKKAPELIITTA® 10 EV

## NEXT-GENERATION SAFETY

CUV / SUV / LIGHT TRUCK / PASSENGER



- ULTIMATE SAFETY – SUPERIOR GRIP ON ICE AND SNOW
- NOKIAN TYRES SILENTDRIVE™ TECHNOLOGY – ULTRA-LOW SOUND LEVELS
- INCREASED RANGE, EXCELLENT STABILITY



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi	mile	km
18	235/60 R 18 107T XL SilentDrive	TSF00025	33.1	29.1	9.4	6.5	8.5	7	2150	107	T	12.0	51	693	431
	235/45 R 18 98T XL SilentDrive	TSF00001	28.7	26.3	9.3	7.5	9	8	1655	98	T	12.0	51	767	476
19	215/50 R 19 93T SilentDrive	TSF00003	26.5	27.5	8.9	6	7.5	7	1435	93	T	12.0	47	733	456
	235/55 R 19 105T XL SilentDrive	TSF00026	32.0	29.2	9.6	6.5	8.5	7.5	2040	105	T	12.0	51	691	429
	235/40 R 19 96T XL SilentDrive	TSF00029	27.6	26.4	9.5	8	9.5	8.5	1565	96	T	12.0	51	764	475
	245/45 R 19 102T XL SilentDrive	TSF00002	32.0	27.7	9.6	7.5	9	8	1875	102	T	12.0	51	728	452
	255/55 R 19 111T XL SilentDrive	TSF00018	37.5	30.0	10.4	7	9	8	2405	111	T	12.0	51	672	418
	255/45 R 19 104T XL SilentDrive	TSF00019	33.1	28.1	10.0	8	9.5	8.5	1985	104	T	12.0	51	718	446
	265/35 R 19 98T XL SilentDrive	TSF00030	30.9	26.3	10.7	9	10.5	9.5	1655	98	T	12.0	51	767	476
	285/40 R 19 107T XL SilentDrive	TSF00020	38.6	28.0	11.4	9.5	11	10	2150	107	T	12.0	51	720	448
20	235/35 R 20 92T XL SilentDrive	TSF00004	29.8	26.5	9.5	8	9.5	8.5	1390	92	T	12.0	51	761	473
	235/45 R 20 100T XL SilentDrive	TSF00008	30.9	28.4	9.3	7.5	9	8	1765	100	T	12.0	51	710	441
	235/50 R 20 104T XL SilentDrive	TSF00012	33.1	29.3	9.7	6.5	8.5	7.5	1985	104	T	12.0	51	688	428
	245/45 R 20 103T XL SilentDrive	TSF00009	33.1	28.7	9.6	7.5	9	8	1930	103	T	12.0	51	703	437
	255/40 R 20 101T XL SilentDrive	TSF00005	33.1	28.0	10.2	8.5	10	9	1820	101	T	12.0	51	720	448
	255/45 R 20 105T XL SilentDrive	TSF00010	35.3	29.1	10.0	8	9.5	8.5	2040	105	T	12.0	51	693	431
	255/50 R 20 109T XL SilentDrive	TSF00022	37.5	30.1	10.4	7	9	8	2270	109	T	12.0	51	670	416
	265/45 R 20 108T XL SilentDrive	TSF00024	38.6	29.4	10.5	8.5	10	9	2205	108	T	12.0	51	686	426
	275/45 R 20 110T XL SilentDrive	TSF00011	38.6	29.8	10.8	8.5	10.5	9	2335	110	T	12.0	51	677	421
21	285/40 R 20 108T XL SilentDrive	TSF00006	40.8	29.0	11.4	9.5	11	10	2205	108	T	12.0	51	695	432
	255/45 R 21 106T XL SilentDrive	TSF00027	35.3	30.0	10.0	8	9.5	8.5	2095	106	T	12.0	51	672	418
	255/35 R 21 98T XL SilentDrive	TSF00016	34.2	28.0	10.2	8.5	10	9	1655	98	T	12.0	51	720	448
	255/50 R 21 109T XL SilentDrive	TSF00023	39.7	31.1	10.4	7	9	8	2270	109	T	12.0	51	648	403
	265/35 R 21 101T XL SilentDrive	TSF00014	34.2	28.3	10.7	9	10.5	9.5	1820	101	T	12.0	51	713	443
	265/45 R 21 108T XL SilentDrive	TSF00015	39.7	30.4	10.5	8.5	10	9	2205	108	T	12.0	51	663	412
	275/35 R 21 103T XL SilentDrive	TSF00017	37.5	28.5	10.9	9	11	9.5	1930	103	T	12.0	51	708	440
	285/40 R 21 109T XL SilentDrive	TSF00028	37.5	30.0	11.4	9.5	11	10	2270	109	T	12.0	51	672	418
	295/30 R 21 102T XL SilentDrive	TSF00021	39.7	28.0	11.9	10	11	10.5	1875	102	T	12.0	51	720	448



[WWW.NOKIANTYRES.COM/HAKKAPELIITTA10EV](http://WWW.NOKIANTYRES.COM/HAKKAPELIITTA10EV)

# NOKIAN TYRES HAKKAPELIITTA® 10 SUV

## NEXT-GENERATION SAFETY

CUV / SUV / LIGHT TRUCK



WINTER

- ULTIMATE SAFETY – SUPERIOR GRIP ON ICE AND SNOW
- MAXIMUM STABILITY AND DRIVING COMFORT
- IMPROVED MILEAGE AND LOW FUEL CONSUMPTION
- ARAMID SIDEWALLS – TOUGHNESS & DURABILITY

**nokian TYRES**  
**ELECTRIC FIT™**  
TESTED TO FIT ELECTRIC CARS

**nokian TYRES**  
**SATISFACTION GUARANTEE**  
30-DAY RETURN WITH FULL REFUND

**nokian TYRES**  
**POTHOLE PROTECTION™**  
FREE TIRE REPLACEMENT IF BEYOND REPAIR



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi		
16	215/65 R 16 102T XL	TS32468	28.7	27.0	8.7	6	7.5	6.5	1875	102	T	12.0	51	747	464
	215/70 R 16 100T	TS32469	28.7	27.9	8.7	5.5	7	6.5	1765	100	T	12.0	47	723	449
	245/70 R 16 111T XL	TS32470	34.2	29.5	9.8	6.5	8	7	2405	111	T	12.0	51	684	425
	265/70 R 16 112T	TS32471	38.6	30.6	10.7	7	9	8	2470	112	T	12.0	47	659	410
17	215/60 R 17 100T XL	TS32473	27.6	27.2	8.7	6	7.5	6.5	1765	100	T	12.0	51	741	461
	215/65 R 17 103T XL	TS32476	28.7	28.0	8.7	6	7.5	6.5	1930	103	T	12.0	51	720	448
	225/60 R 17 103T XL	TS32474	29.8	27.6	9.0	6	8	6.5	1930	103	T	12.0	51	731	454
	225/65 R 17 106T XL	TS32477	29.8	28.5	9.0	6	8	6.5	2095	106	T	12.0	51	708	440
	235/55 R 17 103T XL	TS32472	30.9	27.2	9.6	6.5	8.5	7.5	1930	103	T	12.0	51	741	461
	235/60 R 17 106T XL	TS32475	32.0	28.1	9.4	6.5	8.5	7	2095	106	T	12.0	51	718	446
	235/65 R 17 108T XL	TS32478	33.1	29.1	9.4	6.5	8.5	7	2205	108	T	12.0	51	693	431
	245/65 R 17 111T XL	TS32479	35.3	29.5	9.8	7	8.5	7	2405	111	T	12.0	51	684	425
	245/70 R 17 110T	TS32482	36.4	30.5	9.8	6.5	8	7	2335	110	T	12.0	47	661	411
	255/65 R 17 114T XL	TS32480	37.5	30.1	10.2	7	9	7.5	2600	114	T	12.0	51	670	416
18	265/65 R 17 116T XL	TS32481	39.7	30.5	10.7	7.5	9.5	8	2755	116	T	12.0	51	661	411
	265/70 R 17 115T	TS32483	40.8	31.6	10.7	7	9	8	2680	115	T	12.0	47	638	397
	215/55 R 18 99T XL	TS32485	29.8	27.3	8.9	6	7.5	7	1710	99	T	12.0	51	739	459
	215/60 R 18 102T XL	TS32782	29.8	28.1	8.7	6	7.5	6.5	1875	102	T	12.0	51	718	446
	225/55 R 18 102T XL	TS32486	29.8	27.8	9.2	6	8	7	1875	102	T	12.0	51	725	451
	225/60 R 18 104T XL	TS32489	29.8	28.6	9.0	6	8	6.5	1985	104	T	12.0	51	705	438
	235/50 R 18 101T XL	TS32484	30.9	27.3	9.6	6.5	8.5	7.5	1820	101	T	12.0	51	739	459
	235/55 R 18 104T XL	TS32487	30.9	28.1	9.6	6.5	8.5	7.5	1985	104	T	12.0	51	718	446
	235/60 R 18 107T XL	TS32490	34.2	29.1	9.4	6.5	8.5	7	2150	107	T	12.0	51	693	431
	235/65 R 18 110T XL	TS32495	34.2	30.0	9.4	6.5	8.5	7	2335	110	T	12.0	51	672	418
	245/60 R 18 109T XL	TS32491	36.4	29.6	9.8	7	8.5	7	2270	109	T	12.0	51	681	423
	255/55 R 18 109T XL	TS32488	36.4	29.0	10.4	7	9	8	2270	109	T	12.0	51	695	432
19	255/60 R 18 112T XL	TS32492	36.4	30.0	10.2	7	9	7.5	2470	112	T	12.0	51	672	418
	265/60 R 18 114T XL	TS32493	38.6	30.5	10.7	7	9.5	8	2600	114	T	12.0	51	661	411
	275/65 R 18 116T	TS32776	41.9	32.1	11.0	7.5	9.5	8	2755	116	T	12.0	47	628	390
	225/55 R 19 103T XL	TS32501	30.9	28.8	9.2	6	8	7	1930	103	T	12.0	51	700	435
	235/60 R 19 107T XL	TS32852	34.2	30.1	9.4	6.5	8.5	7	2150	107	T	12.0	51	670	416
	235/50 R 19 103T XL	TS32497	32.0	28.3	9.6	6.5	8.5	7.5	1930	103	T	12.0	51	713	443
20	235/55 R 19 105T XL	TS32502	33.1	29.2	9.6	6.5	8.5	7.5	2040	105	T	12.0	51	691	429
	245/50 R 19 105T XL	TS32498	33.1	28.7	10.0	7	8.5	7.5	2040	105	T	12.0	51	703	437
	255/45 R 19 104T XL	TS32496	34.2	28.1	10.0	8	9.5	8.5	1985	104	T	12.0	51	718	446
	255/50 R 19 107T XL	TS32499	36.4	29.1	10.4	7	9	7.5	2150	107	T	12.0	51	693	431
	255/55 R 19 111T XL	TS32504	36.4	30.0	10.4	7	9	8	2405	111	T	12.0	51	672	418
	265/50 R 19 110T XL	TS32500	37.5	29.5	10.9	7.5	9.5	8.5	2335	110	T	12.0	51	684	425
	235/55 R 20 105T XL	TS32851	33.1	30.2	9.6	6.5	8.5	7.5	2040	105	T	12.0	51	668	415
245/45 R 20 103T XL	TS32508	33.1	28.7	9.6	7.5	9	8	1930	103	T	12.0	51	703	437	

Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi	mile	km
	245/50 R 20 105T XL	TS32513	35.3	29.7	10.0	7	8.5	7.5	2040	105	T	12.0	51	679	422
	255/45 R 20 105T XL	TS32509	35.3	29.1	10.0	8	9.5	8.5	2040	105	T	12.0	51	693	431
	255/50 R 20 109T XL	TS32514	37.5	30.1	10.4	7	9	8	2270	109	T	12.0	51	670	416
	255/55 R 20 110T XL	TS32519	39.7	31.0	10.4	7	9	8	2335	110	T	12.0	51	651	404
	265/50 R 20 111T XL	TS32515	38.6	30.5	10.9	7.5	9.5	8.5	2405	111	T	12.0	51	661	411
	275/45 R 20 110T XL	TS32511	38.6	29.8	10.8	8.5	10.5	9	2335	110	T	12.0	51	677	421
	275/50 R 20 113T XL	TS32516	41.9	30.9	11.2	7.5	9.5	8.5	2535	113	T	12.0	51	653	406
	275/55 R 20 117T XL	TS32520	41.9	31.9	11.2	7.5	9.5	8.5	2835	117	T	12.0	51	632	393
	275/60 R 20 115T	TS32521	44.1	33.0	11.0	7.5	9.5	8	2680	115	T	12.0	47	611	380
285/45 R 20 112T XL	TS32512	40.8	30.1	11.2	9	10.5	9.5	2470	112	T	12.0	51	670	416	
21	235/50 R 21 104T XL	TS32840	33.1	30.3	9.7	6.5	8.5	7.5	1985	104	T	12.0	51	666	414
	265/40 R 21 105T XL	TS32524	36.4	29.3	10.7	9	10.5	9.5	2040	105	T	12.0	51	688	428
	275/40 R 21 107T XL	TS32525	37.5	29.6	10.9	9	11	9.5	2150	107	T	12.0	51	681	423
	275/45 R 21 110T XL	TS32530	40.8	30.7	10.7	8.5	10.5	9	2335	110	T	12.0	51	657	408
	285/45 R 21 113T XL	TS32531	41.9	31.1	11.2	9	10.5	9.5	2535	113	T	12.0	51	648	403
	315/35 R 21 111T XL	TS32523	43.0	29.6	12.6	10.5	12.5	11	2405	111	T	12.0	47	681	423
	315/40 R 21 115T XL	TS32528	46.3	30.9	12.6	10.5	12.5	11	2680	115	T	12.0	51	653	406
22	275/50 R 22 115T XL	TS32535	44.1	32.9	11.2	7.5	9.5	8.5	2680	115	T	12.0	51	613	381
	275/40 R 22 107T XL	TS32805	38.6	30.7	10.9	9	11	9.5	2150	107	T	12.0	51	657	408
	285/40 R 22 110T XL	TS32533	40.8	31.0	11.4	9.5	11	10	2335	110	T	12.0	51	651	404
	285/45 R 22 114T XL	TS32534	43.0	32.1	11.2	9	10.5	9.5	2600	114	T	12.0	51	628	390
	315/35 R 22 111T XL	TS32806	43.0	30.7	12.6	10.5	12.5	11	2405	111	T	12.0	51	657	408



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
**HAKKAPELIITTA10SUV**

# NOKIAN TYRES HAKKAPELIITTA® C4

## STAINLESS WINTER GRIP

VAN / CARGO



WINTER

- UNIQUE GRIP ON ICE AND SNOW – STAINLESS STEEL SQUARE STUDS OFFER GRIP AND DURABILITY
- PRECISE, BALANCED, AND STABLE EVEN UNDER HEAVY LOADS
- BETTER MILEAGE, ARAMID STRONG SIDEWALLS OFFER ADDITIONAL DURABILITY EVEN FOR HEAVY-DUTY USE



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring								mile	km
			lbs	inch	inch	inch	inch	inch		lbs			1/32 inch	psi			
15	185/65 R 15 C 97/95R	TS32841	18.7	24.4	7.4	5	6	5.5	C(6)	1610	97	95	R	12.5	54	827	514
	195/70 R 15 C 104/102R	TS32788	27.6	25.8	7.9	5	6	6	C(6)	1985	104	102	R	12.5	65	782	486
	205/70 R 15 C 106/104R	TS32789	29.8	26.3	8.2	5.5	6.5	6	C(6)	2095	106	104	R	12.5	65	767	476
	215/70 R 15 C 109/107R	TS32790	30.9	26.9	8.7	5.5	7	6.5	D(8)	2270	109	107	R	12.5	65	750	466
	215/65 R 15 C 104/102R	TS32792	29.8	26.0	8.7	6	7	6.5	C(6)	1985	104	102	R	12.5	54	776	482
	225/70 R 15 C 112/110R	TS32791	34.2	27.4	9.0	6	7	6.5	D(8)	2470	112	110	R	12.5	65	736	457
16	195/75 R 16 C 107/105R	TS32784	28.7	27.5	7.7	5	6	5.5	C(6)	2150	107	105	R	12.5	69	733	456
	195/65 R 16 C 104/102R	TS32793	27.6	26.0	7.9	5.5	6.5	6	D(8)	1985	104	102	R	12.5	69	776	482
	205 R 16 C 110/108Q	TS32783	33.1	29.0	8.2	5.5	6.5	6	D(8)	2335	110	108	Q	12.5	65	695	432
	205/75 R 16 C 113/111R	TS32785	33.1	28.1	8.0	5.5	6.5	5.5	D(8)	2535	113	111	R	12.5	76	718	446
	205/65 R 16 C 107/105R	TS32794	29.8	26.5	8.2	5.5	6.5	6	D(8)	2150	107	105	R	12.5	69	761	473
	215/75 R 16 C 116/114R	TS32786	35.3	28.7	8.5	5.5	7	6	D(8)	2755	116	114	R	12.5	76	703	437
	215/65 R 16 C 109/107R	TS32795	30.9	27.0	8.7	6	7	6.5	D(8)	2270	109	107	R	12.5	69	747	464
	215/60 R 16 C 108/106R	TS32798	30.9	26.1	8.7	6	7	6.5	D(8)	2205	108	106	R	12.5	69	773	480
		225/75 R 16 C 121/120R	TS32787	37.5	29.3	8.8	6	7	6	E(10)	3195	121	120	R	12.5	83	688
	225/65 R 16 C 112/110R	TS32796	34.2	27.5	9.0	6	7	6.5	D(8)	2470	112	110	R	12.5	69	733	456
	235/65 R 16 C 121/119R	TS32797	37.5	28.0	9.4	6.5	7.5	7	E(10)	3195	121	119	R	12.5	83	720	448
17	215/60 R 17 C 109/107R	TS32799	32.0	27.2	8.7	6	7	6.5	D(8)	2270	109	107	R	12.5	69	741	461
	225/55 R 17 C 109/107R	TS32801	30.9	26.8	9.2	6.5	7.5	7	D(8)	2270	109	107	R	12.5	69	753	468
	235/60 R 17 C 117/115R	TS32800	36.4	28.1	9.4	6.5	7.5	7	D(8)	2835	117	115	R	12.5	76	718	446
18	255/55 R 18 C 117/115R	TS32802	39.7	28.2	10.4	7	9	8	D(8)	2835	117	115	R	12.5	69	715	444



Q 100 - R 106 mph



[WWW.NOKIANTYRES.COM/HAKKAPELIITTAC4](http://WWW.NOKIANTYRES.COM/HAKKAPELIITTAC4)

# NOKIAN TYRES HAKKAPELIITTA® CR4

STABLE HANDLING, COMFORTABLY QUIET

VAN / CARGO



WINTER

- EASY AND RELIABLE HANDLING IN ANY WINTER WEATHER
- SILENT, WILL CARRY EVEN HEAVY LOADS WHILE SAVING FUEL
- EXCELLENT WEAR RESISTANCE, ARAMID STRONG SIDEWALLS PROTECT AGAINST IMPACTS AND CUTS

**nokian TYRES**  
**ELECTRIC FIT™**  
TESTED TO FIT ELECTRIC CARS

**nokian TYRES**  
**SATISFACTION GUARANTEE**  
30-DAY RETURN WITH FULL REFUND

**nokian TYRES**  
**POTHOLE PROTECTION™**  
FREE TIRE REPLACEMENT IF BEYOND REPAIR



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring								mile	km
			lbs	inch	inch	inch	inch	inch		lbs				1/32 inch	psi		
15	185/65 R 15 C 97/95R	T432366	19.8	24.4	7.4	5	6	5.5	C(6)	1610	97	95	R	11.5	54	827	514
	195/70 R 15 C 104/102R	T432371	26.5	25.8	7.9	5	6	6	C(6)	1985	104	102	R	11.5	65	782	486
	215/70 R 15 C 109/107R	T432372	29.8	26.9	8.7	5.5	7	6.5	D(8)	2270	109	107	R	11.5	65	750	466
	215/65 R 15 C 104/102R	T432374	27.6	26.0	8.7	6	7	6.5	C(6)	1985	104	102	R	11.5	54	776	482
	225/70 R 15 C 112/110R	T432373	32.0	27.4	9.0	6	7	6.5	D(8)	2470	112	110	R	11.5	65	736	457
16	195/65 R 16 C 104/102R	T432375	26.5	26.0	7.9	5.5	6.5	6	D(8)	1985	104	102	R	11.5	69	776	482
	195/75 R 16 C 107/105R	T432367	27.6	27.5	7.7	5	6	5.5	C(6)	2150	107	105	R	11.5	69	733	456
	205/65 R 16 C 107/105R	T432376	27.6	26.5	8.2	5.5	6.5	6	D(8)	2150	107	105	R	11.5	69	761	473
	205/75 R 16 C 113/111R	T432368	29.8	28.1	8.0	5.5	6.5	5.5	D(8)	2535	113	111	R	11.5	76	718	446
	215/75 R 16 C 116/114R	T432369	34.2	28.7	8.5	5.5	7	6	D(8)	2755	116	114	R	11.5	76	703	437
	215/65 R 16 C 109/107R	T432377	29.8	27.0	8.7	6	7	6.5	D(8)	2270	109	107	R	11.5	69	747	464
	225/75 R 16 C 121/120R	T432370	35.3	29.3	8.8	6	7	6	E(10)	3195	121	120	R	11.5	83	688	428
	225/65 R 16 C 112/110R	T432378	33.1	27.5	9.0	6	7	6.5	D(8)	2470	112	110	R	11.5	69	733	456
235/65 R 16 C 121/119R	T432379	35.3	28.0	9.4	6.5	7.5	7	E(10)	3195	121	119	R	11.5	83	720	448	
17	215/60 R 17 C 109/107R	T432380	29.8	27.2	8.7	6	7	6.5	D(8)	2270	109	107	R	11.5	69	741	461
	225/55 R 17 C 109/107R	T432381	29.8	26.8	9.2	6.5	7.5	7	D(8)	2270	109	107	R	11.5	69	753	468

FOR ELECTRIC CARS

3PMSF

15-17"

R 106 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
**HAKKAPELIITTACR4**

# NOKIAN TYRES HAKKAPELIITTA® LT3

## PREMIUM WINTER TIRE FOR PICKUP TRUCKS

CUV / SUV / LIGHT TRUCK / VAN / CARGO



WINTER

- SAFETY AND RELIABILITY FOR EXTREME WINTER CONDITIONS
- WORLD'S FIRST STAINLESS STEEL STUDS REDUCE CORROSION FROM SALTY ROADS
- EASY ROLLING SAVES FUEL AND PRESERVES THE ENVIRONMENT
- STRENGTH AND DURABILITY FOR HEAVY LOADS

**nokian TYRES**  
**ELECTRIC FIT™**  
TESTED TO FIT ELECTRIC CARS

**nokian TYRES**  
**SATISFACTION GUARANTEE**  
30-DAY RETURN WITH FULL REFUND

**nokian TYRES**  
**POTHOLE PROTECTION™**  
FREE TIRE REPLACEMENT IF BEYOND REPAIR



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring								mile	km
			lbs	inch	inch	inch	inch	inch		lbs				1/32 inch	psi	mile	km
16	LT225/75 R 16 115/112Q	TS32394	36.4	29.3	8.8	6	7	6	E (10)	2680	115	112	Q	16.5	80	688	428
	LT235/85 R 16 120/116Q	TS32392	41.9	31.7	9.3	6	7.5	6.5	E (10)	3085	120	116	Q	16.5	80	636	395
	LT245/75 R 16 120/116Q	TS32395	41.9	30.5	9.8	6.5	8	7	E (10)	3085	120	116	Q	16.5	80	661	411
	LT265/75 R 16 119/116Q	TS32396	46.3	31.6	10.5	7	8	7.5	D (8)	3000	119	116	Q	16.5	65	638	397
17	LT235/80 R 17 120/117Q	TS32393	43.0	31.8	9.3	6	7.5	6.5	E (10)	3085	120	117	Q	16.5	80	634	394
	LT245/75 R 17 121/118Q	TS32398	44.1	31.5	9.8	6.5	7.5	7	E (10)	3195	121	118	Q	16.5	80	640	398
	LT245/70 R 17 119/116Q	TS32399	41.9	30.5	9.8	6.5	8	7	E (10)	3000	119	116	Q	16.5	80	661	411
	LT265/70 R 17 121/118Q	TS32400	47.4	31.6	10.7	7	8.5	8	E (10)	3195	121	118	Q	16.5	80	638	397
	LT285/70 R 17 121/118Q	TS32401	49.6	32.8	11.5	7.5	9	8.5	D (8)	3195	121	118	Q	16.5	65	615	382
	LT315/70 R 17 121/118Q	TS32402	58.4	34.4	12.7	8	11	9.5	D (8)	3195	121	118	Q	16.5	50	586	364
18	LT265/70 R 18 124/121Q	TS32403	51.8	32.6	10.7	7	9	8	E (10)	3525	124	121	Q	17.5	80	619	384
	LT275/65 R 18 123/120Q	TS32405	51.8	32.1	11.0	7.5	9	8	E (10)	3415	123	120	Q	17.5	80	628	390
	LT275/70 R 18 125/122Q	TS32404	52.9	33.2	11.0	7	8.5	8	E (10)	3640	125	122	Q	17.5	80	607	377
20	LT275/65 R 20 126/123Q	TS32406	54.0	34.1	11.0	7.5	9.5	8	E (10)	3750	126	123	Q	17.5	80	591	368



3PMSF



FOR ELECTRIC CARS



16-18", 20"



Q 100 mph



[WWW.NOKIANTYRES.COM/HAKKAPELIITTALT3](http://WWW.NOKIANTYRES.COM/HAKKAPELIITTALT3)

# NOKIAN TYRES HAKKAPELIITTA® R5

CONSUMER REPORTS® RECOMMENDED

PASSENGER



WINTER

- A CONSUMER REPORTS RECOMMENDED WINTER TIRE
- PURE WINTER GRIP AND BALANCED HANDLING
- SUPREME DRIVING COMFORT AND SILENCE
- ECO-FRIENDLY MOBILITY WITH FUEL SAVINGS



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi		
14	175/65 R 14 82R	T432135	15.4	23.0	7.0	5	6	5	1047	82	R	10.5	47	877	545
	175/65 R 15 88R XL	T432140	16.5	24.0	7.0	5	6	5	1235	88	R	10.5	51	840	522
15	185/60 R 15 88R XL	T432138	16.5	23.7	7.4	5	6.5	5.5	1235	88	R	10.5	51	851	529
	185/65 R 15 88R	T432141	16.5	24.5	7.4	5	6.5	5.5	1235	88	R	10.5	47	823	512
	195/65 R 15 95R XL	T432142	17.6	25.0	7.9	5.5	7	6	1520	95	R	10.5	51	807	501
	195/60 R 15 88R	T432139	16.5	24.2	7.9	5.5	7	6	1235	88	R	10.5	47	833	518
	205/65 R 15 94R	T432143	20.9	25.5	8.2	5.5	7.5	6	1477	94	R	10.5	47	791	491
	195/55 R 16 91R XL	T432145	17.6	24.4	7.9	5.5	7	6	1355	91	R	10.5	51	827	514
16	205/55 R 16 94R XL	T432146	19.8	24.9	8.4	5.5	7.5	6.5	1477	94	R	10.5	51	810	503
	205/60 R 16 96R XL	T432150	20.9	25.7	8.2	5.5	7.5	6	1565	96	R	10.5	51	785	488
	205/65 R 16 99R XL	T432153	22.0	26.5	8.2	5.5	7.5	6	1710	99	R	10.5	51	761	473
	215/55 R 16 97R XL	T432147	19.8	25.3	8.9	6	7.5	7	1610	97	R	10.5	51	797	495
	215/60 R 16 99R XL	T432151	22.0	26.1	8.7	6	7.5	6.5	1710	99	R	10.5	51	773	480
	225/55 R 16 99R XL	T432148	22.0	25.8	9.2	6	8	7	1710	99	R	10.5	51	782	486
	225/60 R 16 102R XL	T432152	25.4	26.6	9.0	6	8	6.5	1875	102	R	10.5	51	758	471
	175/65 R 17 87R	T432505	18.7	26.0	7.0	5	6	5	1200	87	R	10.5	47	776	482
17	205/50 R 17 93R XL	T432157	19.8	25.1	8.4	5.5	7.5	6.5	1435	93	R	10.5	51	804	499
	205/55 R 17 95R XL	T432161	20.9	25.9	8.4	5.5	7.5	6.5	1520	95	R	10.5	51	779	484
	205/65 R 17 100R XL	T433802	21.0	27.0	8.0	-	-	-	-	100	R	11.0	51	747	464
	215/45 R 17 91T XL	T432154	19.8	24.6	8.4	7	8	7	1355	91	T	10.5	51	820	509
	215/50 R 17 95R XL	T432158	20.9	25.5	8.9	6	7.5	7	1520	95	R	10.5	51	791	491
	215/55 R 17 98R XL	T432162	22.0	26.3	8.9	6	7.5	7	1655	98	R	10.5	51	767	476
	225/45 R 17 94T XL	T432155	22.0	25.0	8.9	7	8.5	7.5	1477	94	T	10.5	51	807	501
	225/50 R 17 98R XL	T432159	25.4	25.9	9.2	6	8	7	1655	98	R	10.5	51	779	484
	225/55 R 17 101R XL	T432163	26.5	26.8	9.2	6	8	7	1820	101	R	10.5	51	753	468
	235/45 R 17 97T XL	T432156	24.3	25.4	9.3	7.5	9	8	1610	97	T	10.5	51	794	493
	235/55 R 17 103R XL	T432164	26.5	27.2	9.6	6.5	8.5	7.5	1930	103	R	10.5	51	741	461
	245/55 R 17 106R XL	T432165	29.8	27.6	10.0	7	8.5	7.5	2095	106	R	10.5	51	731	454
	245/45 R 17 99T XL	T432996	24.3	25.7	9.6	7.5	9	8	1710	99	T	10.5	51	785	488
18	225/50 R 18 99R XL	T432173	25.4	26.9	9.2	6	8	7	1710	99	R	10.5	51	750	466
	225/40 R 18 92T XL	T432166	22.0	25.1	9.1	7.5	9	8	1390	92	T	10.5	51	804	499
	225/45 R 18 95T XL	T432170	23.1	25.9	8.9	7	8.5	7.5	1520	95	T	10.5	51	779	484
	235/40 R 18 95T XL	T432167	24.3	25.4	9.5	8	9.5	8.5	1520	95	T	10.5	51	794	493
	235/45 R 18 98T XL	T432171	26.5	26.3	9.3	7.5	9	8	1655	98	T	10.5	51	767	476
	245/40 R 18 97T XL	T432168	25.4	25.7	9.8	8	9.5	8.5	1610	97	T	10.5	51	785	488
	245/45 R 18 100T XL	T432172	26.5	26.6	9.6	7.5	9	8	1765	100	T	10.5	51	758	471
	245/50 R 18 104R XL	T432174	29.8	27.7	10.0	7	8.5	7.5	1985	104	R	10.5	51	728	452
	255/40 R 18 99T XL	T433792	23.0	26.0	10.0	-	-	-	-	99	T	11.0	51	776	482
275/40 R 18 103T XL	T432169	30.9	26.6	10.9	9	11	9.5	1930	103	T	10.5	51	758	471	

Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per			
						Min	Max	Measuring						1/32 inch	psi	mile	km
						inch	inch	inch									
19	155/70 R 19 88Q XL	T432187	17.6	27.6	6.2	4	5	4.5	1235	88	Q	10.5	51	731	454		
	225/40 R 19 93T XL	T432177	23.1	26.1	9.1	7.5	9	8	1435	93	T	10.5	51	773	480		
	225/45 R 19 96T XL	T432182	24.3	27.0	8.9	7	8.5	7.5	1565	96	T	10.5	51	747	464		
	235/40 R 19 96T XL	T432178	26.5	26.4	9.5	8	9.5	8.5	1565	96	T	10.5	51	764	475		
	235/45 R 19 99T XL	T432183	27.6	27.4	9.3	7.5	9	8	1710	99	T	10.5	51	736	457		
	245/40 R 19 98T XL	T432179	26.5	26.7	9.8	8	9.5	8.5	1655	98	T	10.5	51	755	469		
	245/45 R 19 102T XL	T432184	27.6	27.7	9.6	7.5	9	8	1875	102	T	10.5	51	728	452		
	255/45 R 19 104T XL	T432185	29.8	28.1	10.0	8	9.5	8.5	1985	104	T	10.5	51	718	446		
	255/35 R 19 96T XL	T432175	26.5	26.0	10.2	8.5	10	9	1565	96	T	10.5	51	776	482		
	255/40 R 19 100T XL	T432180	29.8	27.0	10.2	8.5	10	9	1765	100	T	10.5	51	747	464		
	275/35 R 19 100T XL	T432176	29.8	26.6	10.9	9	11	9.5	1765	100	T	10.5	51	758	471		
275/40 R 19 105T XL	T433196	32.0	27.7	10.9	9	11	9.5	2040	105	T	10.5	51	728	452			
20	245/40 R 20 99T XL	T432191	27.6	27.7	9.8	8	9.5	8.5	1710	99	T	10.5	51	728	452		
	275/35 R 20 102T XL	T432190	32.0	27.6	10.9	9	11	9.5	1875	102	T	10.5	51	731	454		

● New



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
**HAKKAPELIITTAR5**

# NOKIAN TYRES HAKKAPELIITTA® R5 EV

PURE SAFETY

PASSENGER / CUV / SUV / LIGHT TRUCK



WINTER

- PURE WINTER GRIP AND BALANCED HANDLING
- ECO-FRIENDLY MOBILITY AND INCREASED RANGE
- ULTRA-LOW SOUND LEVELS WITH NOKIAN TYRES SILENTDRIVE™ TECHNOLOGY



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi	mile	km
18	215/55 R 18 99R XL SilentDrive	TF00028	26.5	27.3	8.9	6	7.5	7	1710	99	R	11.5	51	739	459
	235/60 R 18 107R XL SilentDrive	TF00049	30.9	29.1	9.4	6.5	8.5	7	2150	107	R	11.5	51	693	431
	235/55 R 18 104R XL SilentDrive	TF00062	28.7	28.1	9.6	6.5	8.5	7.5	1985	104	R	10.5	51	718	446
	235/45 R 18 98T XL SilentDrive	TF00005	26.5	26.3	9.3	7.5	9	8	1655	98	T	10.5	51	767	476
19	215/50 R 19 97R XL SilentDrive	TF00015	20.9	27.5	8.9	6	7.5	7	1610	97	R	10.5	51	733	456
	225/55 R 19 103R XL SilentDrive	TF00007	26.5	28.8	9.2	6	8	7	1930	103	R	11.5	51	700	435
	235/50 R 19 103T XL SilentDrive	TF00008	27.6	28.3	9.6	6.5	8.5	7.5	1930	103	T	10.5	51	713	443
	235/55 R 19 105R XL SilentDrive	TF00029	29.8	29.2	9.6	6.5	8.5	7.5	2040	105	R	11.5	51	691	429
	235/40 R 19 96T XL SilentDrive	TF00052	25.4	26.4	9.5	8	9.5	8.5	1565	96	T	11.5	51	764	475
	245/50 R 19 105R XL SilentDrive	TF00009	29.8	28.7	10.0	7	8.5	7.5	2040	105	R	11.5	51	703	437
	245/55 R 19 107R XL SilentDrive	TF00061	33.1	29.6	10.0	7	8.5	7.5	2150	107	R	11.5	51	681	423
	245/45 R 19 102T XL SilentDrive	TF00006	28.7	27.7	9.6	7.5	9	8	1875	102	T	10.5	51	728	452
	255/45 R 19 104T XL SilentDrive	TF00002	29.8	28.1	10.0	8	9.5	8.5	1985	104	T	10.5	51	718	446
	255/50 R 19 107R XL SilentDrive	TF00030	32.0	29.1	10.4	7	9	7.5	2150	107	R	11.5	51	693	431
20	265/35 R 19 98T XL SilentDrive	TF00053	27.6	26.3	10.7	9	10.5	9.5	1655	98	T	10.5	51	767	476
	285/40 R 19 107T XL SilentDrive	TF00001	35.3	28.0	11.4	9.5	11	10	2150	107	T	10.5	51	720	448
	235/50 R 20 104T XL SilentDrive	TF00010	28.7	29.3	9.7	6.5	8.5	7.5	1985	104	T	11.5	51	688	428
	235/45 R 20 100T XL SilentDrive	TF00016	26.5	28.4	9.3	7.5	9	8	1765	100	T	10.5	51	710	441
	235/35 R 20 92T XL SilentDrive	TF00018	26.5	26.5	9.5	8	9.5	8.5	1390	92	T	10.5	51	761	473
	245/45 R 20 103R XL SilentDrive	TF00026	29.8	28.7	9.6	7.5	9	8	1930	103	R	10.0	51	703	437
	255/50 R 20 109R XL SilentDrive	TF00011	33.1	30.1	10.4	7	9	8	2270	109	R	11.5	51	670	416
	255/40 R 20 101T XL SilentDrive	TF00017	28.7	28.0	10.2	8.5	10	9	1820	101	T	10.5	51	720	448
	255/45 R 20 105T XL SilentDrive	TF00012	32.0	29.1	10.0	8	9.5	8.5	2040	105	T	11.5	51	693	431
	265/45 R 20 108T XL SilentDrive	TF00031	33.1	29.4	10.5	8.5	10	9	2205	108	T	11.5	51	686	426
21	275/45 R 20 110T XL SilentDrive	TF00013	33.1	29.8	10.8	8.5	10.5	9	2335	110	T	11.5	51	677	421
	275/30 R 20 97T XL SilentDrive	TF00037	28.7	26.5	10.9	9	10	9.5	1610	97	T	10.5	51	761	473
	285/40 R 20 108R XL SilentDrive	TF00027	33.1	29.0	11.4	9.5	11	10	2205	108	R	10.0	51	695	432
	235/45 R 21 101T XL SilentDrive	TF00051	28.7	29.3	9.3	7.5	9	8	1820	101	T	11.5	51	688	428
	255/50 R 21 109R XL SilentDrive	TF00014	35.3	31.1	10.4	7	9	8	2270	109	R	11.5	51	648	403
	255/45 R 21 106T XL SilentDrive	TF00048	33.1	30.0	10.0	8	9.5	8.5	2095	106	T	11.5	51	672	418
	255/40 R 21 102T XL SilentDrive	TF00020	30.9	29.0	10.2	8.5	10	9	1875	102	T	11.5	51	695	432
	255/35 R 21 98T XL SilentDrive	TF00022	29.8	28.0	10.2	8.5	10	9	1655	98	T	11.5	51	720	448
	265/35 R 21 101T XL SilentDrive	TF00003	29.8	28.3	10.7	9	10.5	9.5	1820	101	T	10.5	51	713	443
	265/45 R 21 108T XL SilentDrive	TF00019	33.1	30.4	10.5	8.5	10	9	2205	108	T	11.5	51	663	412
21	275/35 R 21 103T XL SilentDrive	TF00023	32.0	28.5	10.9	9	11	9.5	1930	103	T	11.5	51	708	440
	275/45 R 21 110T XL SilentDrive	TF00060	35.3	30.7	10.7	8.5	10.5	9	2335	110	T	11.5	51	657	408
	285/40 R 21 109T XL SilentDrive	TF00050	35.3	30.0	11.4	9.5	11	10	2270	109	T	11.5	51	672	418
	295/30 R 21 102T XL SilentDrive	TF00004	33.1	28.0	11.9	10	11	10.5	1875	102	T	10.5	51	720	448
	295/40 R 21 111T XL SilentDrive	TF00021	36.4	30.3	11.9	10	11.5	10.5	2405	111	T	11.5	51	666	414

Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi	mile	km
22	265/40 R 22 106T XL SilentDrive	TF00024	35.3	30.4	10.7	9	10.5	9.5	2095	106	T	11.5	51	663	412
	295/35 R 22 108T XL SilentDrive	TF00025	38.6	30.1	11.9	10	11.5	10.5	2205	108	T	11.5	51	670	416

● New



18-22"



R 106 - T 118 mph



[WWW.NOKIANTYRES.COM/  
HAKKAPELIITTAR5EV](http://WWW.NOKIANTYRES.COM/HAKKAPELIITTAR5EV)

# NOKIAN TYRES HAKKAPELIITTA® R5 SUV

PURE SAFETY

CUV / SUV / LIGHT TRUCK



WINTER

- PURE WINTER GRIP AND BALANCED HANDLING
- INCREASED STABILITY AND SUPREME DRIVING COMFORT
- ECO-FRIENDLY MOBILITY WITH FUEL SAVINGS
- ARAMID STRONG SIDEWALLS FOR DURABILITY AND PROTECTION



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring						mile	km
			lbs	inch	inch	inch	inch	inch	lbs			1/32 inch	psi		
16	215/65 R 16 102R XL	T432195	24.3	27.0	8.7	6	7.5	6.5	1875	102	R	11.5	51	747	464
	215/70 R 16 100R	T432196	27.6	27.9	8.7	5.5	7	6.5	1765	100	R	11.5	47	723	449
	265/70 R 16 112R	T432197	36.4	30.6	10.7	7	9	8	2470	112	R	11.5	47	659	410
17	215/60 R 17 100R XL	T432198	23.1	27.2	8.7	6	7.5	6.5	1765	100	R	11.5	51	741	461
	215/65 R 17 103R XL	T432201	27.6	28.0	8.7	6	7.5	6.5	1930	103	R	11.5	51	720	448
	225/65 R 17 106R XL	T432202	28.7	28.5	9.0	6	8	6.5	2095	106	R	11.5	51	708	440
	225/60 R 17 103R XL	T432199	27.6	27.6	9.0	6	8	6.5	1930	103	R	11.5	51	731	454
	235/60 R 17 106R XL	T432200	30.9	28.1	9.4	6.5	8.5	7	2095	106	R	11.5	51	718	446
	235/65 R 17 108R XL	T432203	29.8	29.1	9.4	6.5	8.5	7	2205	108	R	11.5	51	693	431
	245/65 R 17 111R XL	T432204	32.0	29.5	9.8	7	8.5	7	2405	111	R	11.5	51	684	425
	245/70 R 17 110R	T432207	33.1	30.5	9.8	6.5	8	7	2335	110	R	11.5	47	661	411
	255/65 R 17 114R XL	T432205	35.3	30.1	10.2	7	9	7.5	2600	114	R	11.5	51	670	416
	265/65 R 17 116R XL	T432206	36.4	30.5	10.7	7.5	9.5	8	2755	116	R	11.5	51	661	411
265/70 R 17 115R	T432208	38.6	31.6	10.7	7	9	8	2680	115	R	11.5	47	638	397	
18	215/60 R 18 102R XL	T432338	27.6	28.1	8.7	6	7.5	6.5	1875	102	R	11.5	51	718	446
	215/55 R 18 99R XL	T432210	27.6	27.3	8.9	6	7.5	7	1710	99	R	11.5	51	739	459
	225/55 R 18 102R XL	T432211	27.6	27.8	9.2	6	8	7	1875	102	R	11.5	51	725	451
	225/60 R 18 104R XL	T432214	27.6	28.6	9.0	6	8	6.5	1985	104	R	11.5	51	705	438
	235/65 R 18 110R XL	T432220	32.0	30.0	9.4	6.5	8.5	7	2335	110	R	11.5	51	672	418
	235/50 R 18 101R XL	T432209	28.7	27.3	9.6	6.5	8.5	7.5	1820	101	R	11.5	51	739	459
	235/55 R 18 104R XL	T432212	28.7	28.1	9.6	6.5	8.5	7.5	1985	104	R	11.5	51	718	446
	235/60 R 18 107R XL	T432215	32.0	29.1	9.4	6.5	8.5	7	2150	107	R	11.5	51	693	431
	245/60 R 18 109R XL	T432216	33.1	29.6	9.8	7	8.5	7	2270	109	R	11.5	51	681	423
	255/60 R 18 112R XL	T432217	34.2	30.0	10.2	7	9	7.5	2470	112	R	11.5	51	672	418
	255/55 R 18 109R XL	T432213	33.1	29.0	10.4	7	9	8	2270	109	R	11.5	51	695	432
	265/60 R 18 114R XL	T432218	36.4	30.5	10.7	7	9.5	8	2600	114	R	11.5	51	661	411
	265/65 R 18 114R	T432221	37.5	31.5	10.7	7.5	9.5	8	2600	114	R	11.5	47	640	398
275/65 R 18 116R XL	T432222	39.7	32.1	11.0	7.5	9.5	8	2755	116	R	11.5	51	628	390	
19	225/55 R 19 103R XL	T432229	27.6	28.8	9.2	6	8	7	1930	103	R	11.5	51	700	435
	235/60 R 19 107R XL	T433493	33.1	30.1	9.4	6.5	8.5	7	2150	107	R	11.5	51	670	416
	235/55 R 19 105R XL	T432230	30.9	29.2	9.6	6.5	8.5	7.5	2040	105	R	11.5	51	691	429
	235/50 R 19 103R XL	T432225	28.7	28.3	9.6	6.5	8.5	7.5	1930	103	R	11.5	51	713	443
	245/55 R 19 107R XL	T432231	35.3	29.6	10.0	7	8.5	7.5	2150	107	R	11.5	51	681	423
	245/50 R 19 105R XL	T432226	30.9	28.7	10.0	7	8.5	7.5	2040	105	R	11.5	51	703	437
	255/55 R 19 111R XL	T432232	35.3	30.0	10.4	7	9	8	2405	111	R	11.5	51	672	418
	255/50 R 19 107R XL	T432227	34.2	29.1	10.4	7	9	7.5	2150	107	R	11.5	51	693	431
265/50 R 19 110R XL	T432228	35.3	29.5	10.9	7.5	9.5	8.5	2335	110	R	11.5	51	684	425	
20	235/50 R 20 104T XL	T432243	30.9	29.3	9.7	6.5	8.5	7.5	1985	104	T	11.5	51	688	428
	235/55 R 20 105R XL	T433492	30.9	30.2	9.6	6.5	8.5	7.5	2040	105	R	11.5	51	668	415
	245/50 R 20 105R XL	T432244	32.0	29.7	10.0	7	8.5	7.5	2040	105	R	11.5	51	679	422

Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per			
						Min	Max	Measuring						1/32 inch	psi	mile	km
						inch	inch	inch									
	245/45 R 20 103T XL	T432238	30.9	28.7	9.6	7.5	9	8	1930	103	T	11.5	51	703	437		
	255/55 R 20 110R XL	T432250	36.4	31.0	10.4	7	9	8	2335	110	R	11.5	51	651	404		
	255/45 R 20 105T XL	T432239	33.1	29.1	10.0	8	9.5	8.5	2040	105	T	11.5	51	693	431		
	255/50 R 20 109R XL	T432245	35.3	30.1	10.4	7	9	8	2270	109	R	11.5	51	670	416		
	265/50 R 20 111R XL	T432246	36.4	30.5	10.9	7.5	9.5	8.5	2405	111	R	11.5	51	661	411		
	265/45 R 20 108T XL	T432240	34.2	29.4	10.5	8.5	10	9	2205	108	T	11.5	51	686	426		
	275/40 R 20 106T XL	T432236	33.1	28.7	10.9	9	11	9.5	2095	106	T	11.5	51	703	437		
	275/50 R 20 113R XL	T432247	38.6	30.9	11.2	7.5	9.5	8.5	2535	113	R	11.5	51	653	406		
	275/55 R 20 117R XL	T432251	39.7	31.9	11.2	7.5	9.5	8.5	2835	117	R	11.5	51	632	393		
	275/60 R 20 116T XL	T433369	40.8	33.0	11.0	7.5	9.5	8	2755	116	T	11.5	51	611	380		
	275/45 R 20 110T XL	T432241	35.3	29.8	10.8	8.5	10.5	9	2335	110	T	11.5	51	677	421		
	285/45 R 20 112T XL	T432242	37.5	30.1	11.2	9	10.5	9.5	2470	112	T	11.5	51	670	416		
	285/40 R 20 108T XL	T432508	35.3	29.0	11.4	9.5	11	10	2205	108	T	11.5	51	695	432		
21	235/50 R 21 104R XL	T433131	33.1	30.3	9.7	6.5	8.5	7.5	1985	104	R	11.5	51	666	414		
	265/40 R 21 105T XL	T432257	34.2	29.3	10.7	9	10.5	9.5	2040	105	T	11.5	51	688	428		
	275/40 R 21 107T XL	T432258	34.2	29.6	10.9	9	11	9.5	2150	107	T	11.5	51	681	423		
	275/45 R 21 110T XL	T432263	37.5	30.7	10.7	8.5	10.5	9	2335	110	T	11.5	51	657	408		
	285/45 R 21 113T XL	T432264	38.6	31.1	11.2	9	10.5	9.5	2535	113	T	11.5	51	648	403		
	285/40 R 21 109T XL	T432259	36.4	30.0	11.4	9.5	11	10	2270	109	T	11.5	51	672	418		
	315/35 R 21 111T XL	T432256	39.7	29.6	12.6	10.5	12.5	11	2405	111	T	11.5	51	681	423		
	315/40 R 21 115T XL	T432261	41.9	30.9	12.6	10.5	12.5	11	2680	115	T	11.5	51	653	406		
22	HL275/50 R 22 116T XL	T433380	39.7	32.9	11.2	8	9	8.5	2755	116	T	11.5	51	613	381		
	275/40 R 22 107T XL	T432760	36.4	30.7	10.9	9	11	9.5	2150	107	T	11.5	51	657	408		
	285/45 R 22 114T XL	T432267	39.7	32.1	11.2	9	10.5	9.5	2600	114	T	11.5	51	628	390		
	285/40 R 22 110T XL	T432266	38.6	31.0	11.4	9.5	11	10	2335	110	T	11.5	51	651	404		
	315/35 R 22 111T XL	T432761	40.8	30.7	12.6	10.5	12.5	11	2405	111	T	11.5	51	657	408		



16-22"



R 106 - T 118 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
**HAKKAPELIITTAR5SUV**

# ALL-SEASON

## NOKIAN TYRES ONE

PEACE OF MIND IN EVERY MOMENT

UTQG: 720 A A CUV / SUV / LIGHT TRUCK / PASSENGER



ALL-SEASON

- THE ONE FOR SAFETY: EXCELLENT GRIP AND HANDLING IN ALL CONDITIONS
- THE ONE FOR DURABILITY: POTHOLE PROTECTION THANKS TO ARAMID SIDEWALL TECHNOLOGY
- THE ONE FOR YOU
- 80,000 MILE / 130,000 KM TREADWEAR LIMITED WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi			
15	185/65 R 15 88H	T431340	17.6	720/A/A	24.5	7.4	5	6.5	5.5	1235	88	H	11.5	51	823	512
	185/60 R 15 84H	T431343	16.5	720/A/A	23.7	7.4	5	6.5	5.5	1102	84	H	11.5	51	851	529
	195/60 R 15 88H	T431344	18.7	720/A/A	24.2	7.9	5.5	7	6	1235	88	H	11.5	51	833	518
	195/65 R 15 91H	T431341	18.7	720/A/A	25.0	7.9	5.5	7	6	1355	91	H	11.5	51	807	501
	205/70 R 15 96T	T431338	23.1	720/A/A	26.3	8.2	5	7	6	1565	96	T	11.5	47	767	476
	205/65 R 15 94H	T431342	20.9	720/A/A	25.5	8.2	5.5	7.5	6	1477	94	H	11.5	51	791	491
16	205/55 R 16 91V	T431354	19.8	720/A/A	24.9	8.4	5.5	7.5	6.5	1355	91	V	11.5	51	810	503
	205/65 R 16 95H	T431347	23.1	720/A/A	26.5	8.2	5.5	7.5	6	1520	95	H	11.5	51	761	473
	205/60 R 16 92V	T431350	22.0	720/A/A	25.7	8.2	5.5	7.5	6	1390	92	V	11.5	51	785	488
	205/70 R 16 97H	T432133	24.3	720/A/A	27.3	8.2	5	7	6	1610	97	H	11.5	51	739	459
	215/55 R 16 97H XL	T431355	23.1	720/A/A	25.3	8.9	6	7.5	7	1610	97	H	11.5	51	797	495
	215/70 R 16 100H	T431335	26.5	720/A/A	27.9	8.7	5.5	7	6.5	1765	100	H	11.5	51	723	449
	215/60 R 16 95V	T431351	23.1	720/A/A	26.1	8.7	6	7.5	6.5	1520	95	V	11.5	51	773	480
	215/65 R 16 98H	T431336	25.4	720/A/A	27.0	8.7	6	7.5	6.5	1655	98	H	11.5	51	747	464
	225/70 R 16 103H	T431345	27.6	720/A/A	28.4	9.0	6	7.5	6.5	1930	103	H	11.5	51	710	441
	225/65 R 16 100H	T431348	26.5	720/A/A	27.5	9.0	6	8	6.5	1765	100	H	11.5	51	733	456
	225/60 R 16 98V	T431352	25.4	720/A/A	26.6	9.0	6	8	6.5	1655	98	V	11.5	51	758	471
	235/70 R 16 106T	T431346	29.8	720/A/A	29.0	9.4	6	8	7	2095	106	T	11.5	47	695	432
235/60 R 16 100H	T431353	27.6	720/A/A	27.1	9.4	6.5	8.5	7	1765	100	H	11.5	51	744	462	
17	205/50 R 17 93V XL	T431359	20.9	720/A/A	25.1	8.4	5.5	7.5	6.5	1435	93	V	11.5	51	804	499
	215/50 R 17 95V XL	T431360	23.1	720/A/A	25.5	8.9	6	7.5	7	1520	95	V	11.5	51	791	491
	215/55 R 17 94V	T431357	23.1	720/A/A	26.3	8.9	6	7.5	7	1477	94	V	11.5	51	767	476
	215/45 R 17 91V XL	T431363	22.0	720/A/A	24.6	8.4	7	8	7	1355	91	V	11.5	51	820	509
	215/65 R 17 99T	T431330	25.4	720/A/A	28.0	8.7	6	7.5	6.5	1710	99	T	11.5	47	720	448
	215/60 R 17 96H	T431333	24.3	720/A/A	27.2	8.7	6	7.5	6.5	1565	96	H	11.5	51	741	461
	225/55 R 17 97V	T431358	26.5	720/A/A	26.8	9.2	6	8	7	1610	97	V	11.5	51	753	468
	225/50 R 17 98V XL	T431361	23.1	720/A/A	25.9	9.2	6	8	7	1655	98	V	11.5	51	779	484
	225/45 R 17 94V XL	T431364	23.1	720/A/A	25.0	8.9	7	8.5	7.5	1477	94	V	11.5	51	807	501
	225/65 R 17 102H	T431329	27.6	720/A/A	28.5	9.0	6	8	6.5	1875	102	H	11.5	51	708	440
	225/60 R 17 99H	T431332	27.6	720/A/A	27.6	9.0	6	8	6.5	1710	99	H	11.5	51	731	454
	235/45 R 17 97V XL	T431365	25.4	720/A/A	25.4	9.3	7.5	9	8	1610	97	V	11.5	51	794	493
	235/50 R 17 96V	T431362	26.5	720/A/A	26.3	9.6	6.5	8.5	7.5	1565	96	V	11.5	51	767	476
	235/65 R 17 104H	T431328	29.8	720/A/A	29.1	9.4	6.5	8.5	7	1985	104	H	11.5	51	693	431
	235/60 R 17 102H	T431331	29.8	720/A/A	28.1	9.4	6.5	8.5	7	1875	102	H	11.5	51	718	446
	235/55 R 17 99V	T431334	27.6	720/A/A	27.2	9.6	6.5	8.5	7.5	1710	99	V	11.5	51	741	461
	245/65 R 17 107H	T431327	30.9	720/A/A	29.5	9.8	7	8.5	7	2150	107	H	11.5	51	684	425

Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per			
							Min	Max	Measuring						1/32 inch	psi	mile	km
							inch	inch	inch									
18	215/55 R 18 99V XL	T431325	26.5	720/A/A	27.3	8.9	6	7.5	7	1710	99	V	11.5	51	739	459		
	225/60 R 18 104H XL	T431322	27.6	720/A/A	28.6	9.0	6	8	6.5	1985	104	H	11.5	51	705	438		
	225/40 R 18 92V XL	T431369	24.3	720/A/A	25.1	9.1	7.5	9	8	1390	92	V	11.5	51	804	499		
	225/45 R 18 95V XL	T431366	24.3	720/A/A	25.9	8.9	7	8.5	7.5	1520	95	V	11.5	51	779	484		
	225/50 R 18 99V XL	T432003	26.5	720/A/A	26.9	9.2	6	8	7	1710	99	V	11.5	51	750	466		
	225/55 R 18 98V	T431324	27.6	720/A/A	27.8	9.2	6	8	7	1655	98	V	11.5	51	725	451		
	235/45 R 18 98V XL	T431367	25.4	720/A/A	26.3	9.3	7.5	9	8	1655	98	V	11.5	51	767	476		
	235/65 R 18 106V	T431318	32.0	720/A/A	30.0	9.4	6.5	8.5	7	2095	106	V	11.5	51	672	418		
	235/60 R 18 107V XL	T431321	30.9	720/A/A	29.1	9.4	6.5	8.5	7	2150	107	V	11.5	51	693	431		
	235/55 R 18 104V XL	T431323	28.7	720/A/A	28.1	9.6	6.5	8.5	7.5	1985	104	V	11.5	51	718	446		
	235/50 R 18 97V	T431326	27.6	720/A/A	27.3	9.6	6.5	8.5	7.5	1610	97	V	11.5	51	739	459		
	245/60 R 18 105H	T431320	33.1	720/A/A	29.6	9.8	7	8.5	7	2040	105	H	11.5	51	681	423		
	245/40 R 18 97V XL	T431370	25.4	720/A/A	25.7	9.8	8	9.5	8.5	1610	97	V	11.5	51	785	488		
	245/45 R 18 100V XL	T431368	27.6	720/A/A	26.6	9.6	7.5	9	8	1765	100	V	11.5	51	758	471		
	255/65 R 18 111T	T431317	34.2	720/A/A	31.1	10.2	7	9	7.5	2405	111	T	11.5	47	648	403		
265/60 R 18 110V	T431319	35.3	720/A/A	30.5	10.7	7	9.5	8	2335	110	V	11.5	51	661	411			
19	225/55 R 19 99V	T431316	27.6	720/A/A	28.8	9.2	6	8	7	1710	99	V	11.5	51	700	435		
	235/40 R 19 96V XL	T432006	26.5	720/A/A	26.4	9.5	8	9.5	8.5	1565	96	V	11.5	51	764	475		
	235/55 R 19 105V XL	T431315	29.8	720/A/A	29.2	9.6	6.5	8.5	7.5	2040	105	V	11.5	51	691	429		
	245/40 R 19 98V XL	T432008	27.6	720/A/A	26.7	9.8	8	9.5	8.5	1655	98	V	11.5	51	755	469		
	245/45 R 19 102V XL	T432007	28.7	720/A/A	27.7	9.6	7.5	9	8	1875	102	V	11.5	51	728	452		
	245/55 R 19 103H	T431314	33.1	720/A/A	29.6	10.0	7	8.5	7.5	1930	103	H	11.5	51	681	423		
	255/60 R 19 113H XL	T431313	35.3	720/A/A	31.1	10.2	7	9	7.5	2535	113	H	11.5	51	648	403		
	255/50 R 19 107V XL	T432004	32.0	720/A/A	29.1	10.4	7	9	7.5	2150	107	V	11.5	51	693	431		
20	235/55 R 20 102V	T431308	32.0	720/A/A	30.2	9.6	6.5	8.5	7.5	1875	102	V	11.5	51	668	415		
	245/50 R 20 102V	T431311	32.0	720/A/A	29.7	10.0	7	8.5	7.5	1875	102	V	11.5	51	679	422		
	245/45 R 20 103V XL	T432009	29.8	720/A/A	28.7	9.6	7.5	9	8	1930	103	V	11.5	51	703	437		
	255/55 R 20 110V XL	T432005	35.3	720/A/A	31.0	10.4	7	9	8	2335	110	V	11.5	51	651	404		
	255/50 R 20 109V XL	T431310	34.2	720/A/A	30.1	10.4	7	9	8	2270	109	V	11.5	51	670	416		
	255/45 R 20 105V XL	T431312	30.9	720/A/A	29.1	10.0	8	9.5	8.5	2040	105	V	11.5	51	693	431		
265/50 R 20 111V XL	T431309	35.3	720/A/A	30.5	10.9	7.5	9.5	8.5	2405	111	V	11.5	51	661	411			



FOR ELECTRIC CARS



15-20"



H 130 - V 149 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)

ONE

# NOKIAN TYRES ONE HT

## PEACE OF MIND IN EVERY MOMENT

CUV / SUV / LIGHT TRUCK / VAN / CARGO



ALL-SEASON

- THE ONE FOR SAFETY: EXCELLENT GRIP IN ALL CONDITIONS
- THE ONE FOR TOUGHNESS: POTHOLE PROTECTION THANKS TO ARAMID TECHNOLOGY
- THE ONE FOR YOU: DESIGNED WITH THE PICKUP TRUCK DRIVER IN MIND
- P-METRIC > 70,000 MILE / 115,000 KM TREADWEAR LIMITED WARRANTY
- LT-METRIC & CARGO > 55,000 MILE / 90,000 KM TREADWEAR LIMITED WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring								mile	km
			lbs		inch	inch	inch	inch	inch	lbs				1/32 inch	psi			
15	185/60 R 15 C 94/92T	T431201	19.8	-	23.7	7.4	5.5	6	5.5	C (6)	1477	94	92	T	12.5	54	851	529
	205/65 R 15 C 102/100T	T432433	26.5	-	25.5	8.2	5.5	6.5	6	C (6)	1875	102	100	T	12.5	54	791	491
16	195/75 R 16 C 107/105S	T431202	27.6	-	27.5	7.7	5	6	5.5	D (8)	2150	107	105	S	12.5	69	733	456
	LT215/85 R 16 115/112S	T431168	38.6	-	30.4	8.5	5.5	7	6	E (10)	2680	115	112	S	15.0	80	663	412
	225/75 R 16 C 121/120R	T432434	35.3	-	29.3	8.8	6	7	6	E (10)	3195	121	120	R	12.5	83	688	428
	LT225/75 R 16 115/112S	T431170	36.4	-	29.3	8.8	6	7	6	E (10)	2680	115	112	S	15.0	80	688	428
	235/65 R 16 C 121/119R	T431203	35.3	-	28.0	9.4	6.5	7.5	7	E (10)	3195	121	119	R	12.5	83	720	448
	LT235/85 R 16 120/116S	T431169	41.9	-	31.7	9.3	6	7.5	6.5	E (10)	3085	120	116	S	15.0	80	636	395
	235/70 R 16 106T	T431196	29.8	720/A/A	29.0	9.4	6	8	7	-	2095	106	-	T	12.5	47	695	432
	245/75 R 16 111T	T431172	33.1	720/A/A	30.5	9.8	6.5	8	7	-	2405	111	-	T	12.5	47	661	411
	245/70 R 16 107T	T431197	33.1	720/A/A	29.5	9.8	6.5	8	7	-	2150	107	-	T	12.5	47	684	425
	LT245/75 R 16 120/116S	T431171	41.9	-	30.5	9.8	6.5	8	7	E (10)	3085	120	116	S	15.0	80	661	411
17	255/70 R 16 111H	T431174	33.1	720/A/A	30.1	10.2	6.5	8.5	7.5	-	2405	111	-	H	12.5	51	670	416
	LT265/75 R 16 123/120S	T431173	46.3	-	31.6	10.5	7	8	7.5	E (10)	3415	123	120	S	15.0	80	638	397
	265/70 R 16 112T	T431175	36.4	720/A/A	30.6	10.7	7	9	8	-	2470	112	-	T	12.5	47	659	410
	265/75 R 16 116T	T431195	38.6	720/A/A	31.6	10.5	7	9	7.5	-	2755	116	-	T	12.5	47	638	397
	LT235/80 R 17 120/117R	T431176	43.0	-	31.8	9.3	6	7.5	6.5	E (10)	3085	120	117	R	15.0	80	634	394
	245/70 R 17 110T	T431179	33.1	720/A/A	30.5	9.8	6.5	8	7	-	2335	110	-	T	12.5	47	661	411
	245/65 R 17 107H	T431182	32.0	720/A/A	29.5	9.8	7	8.5	7	-	2150	107	-	H	12.5	51	684	425
	LT245/75 R 17 121/118S	T431177	44.1	-	31.5	9.8	6.5	7.5	7	E (10)	3195	121	118	S	15.0	80	640	398
	LT245/70 R 17 119/116S	T431178	41.9	-	30.5	9.8	6.5	8	7	E (10)	3000	119	116	S	15.0	80	661	411
	255/70 R 17 112S	T431198	35.3	720/A/A	31.1	10.2	6.5	8.5	7.5	-	2470	112	-	S	12.5	47	648	403
18	255/65 R 17 110T	T431199	35.3	720/A/A	30.1	10.2	7	9	7.5	-	2335	110	-	T	12.5	47	670	416
	LT265/70 R 17 121/118S	T431180	47.4	-	31.6	10.7	7	8.5	8	E (10)	3195	121	118	S	15.0	80	638	397
	265/70 R 17 115H	T431181	38.6	720/A/A	31.6	10.7	7	9	8	-	2680	115	-	H	12.5	51	638	397
	265/65 R 17 112T	T431183	36.4	720/A/A	30.5	10.7	7.5	9.5	8	-	2470	112	-	T	12.5	47	661	411
	255/70 R 18 116H XL	T433076	36.4	720/A/A	32.1	10.2	6.5	8.5	7.5	-	2755	116	-	H	12.5	51	628	390
	LT265/70 R 18 124/121S	T431185	49.6	-	32.6	10.7	7	9	8	E (10)	3525	124	121	S	15.0	80	619	384
20	265/65 R 18 114H	T431187	37.5	720/A/A	31.5	10.7	7.5	9.5	8	-	2600	114	-	H	12.5	51	640	398
	265/60 R 18 110H	T431190	35.3	720/A/A	30.5	10.7	7	9.5	8	-	2335	110	-	H	12.5	51	661	411
	LT275/65 R 18 123/120S	T431188	49.6	-	32.1	11.0	7.5	9	8	E (10)	3415	123	120	S	15.0	80	628	390
	LT275/70 R 18 125/122S	T431186	51.8	-	33.2	11.0	7	8.5	8	E (10)	3640	125	122	S	15.0	80	607	377
	275/65 R 18 116H	T431189	40.8	720/A/A	32.1	11.0	7.5	9.5	8	-	2755	116	-	H	12.5	51	628	390
22	LT265/60 R 20 121/118S	T431200	49.6	-	32.5	10.7	7.5	9.5	8	E (10)	3195	121	118	S	15.0	80	621	386
	LT275/65 R 20 126/123S	T431191	52.9	-	34.1	11.0	7.5	9.5	8	E (10)	3750	126	123	S	15.0	80	591	368
	275/60 R 20 115H	T431192	41.9	720/A/A	33.0	11.0	7.5	9.5	8	-	2680	115	-	H	12.5	51	611	380
	275/55 R 20 113H	T431193	39.7	720/A/A	31.9	11.2	7.5	9.5	8.5	-	2535	113	-	H	12.5	51	632	393
22	HL275/50 R 22 116H XL	T433487	39.7	720/A/A	32.9	11.2	8	9	8.5	-	2755	116	-	H	12.5	51	613	381
	285/45 R 22 114H XL	T431194	40.8	720/A/A	32.1	11.2	9	10.5	9.5	-	2600	114	-	H	12.5	51	628	390



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/ONEHT)  
**ONEHT**



FOR ELECTRIC CARS



15-18", 20", 22"



H 130 - T 118 mph

# NOKIAN TYRES SURPASS® AS01

CONSUMER REPORTS RECOMMENDED®

UTQG: 560 AA A PASSENGER / CUV / SUV / LIGHT TRUCK



ALL-SEASON

- A CONSUMER REPORTS RECOMMENDED ULTRA-HIGH PERFORMANCE ALL-SEASON TIRE
- EXPERIENCE PERFORMANCE: STABILITY AND HANDLING FOR ALL CONDITIONS
- EXPERIENCE SAFETY: PEACE OF MIND FOR VARYING WEATHER
- EXPERIENCE DURABILITY: RELIABILITY, LONGEVITY AND STRENGTH
- 55,000 MILE / 90,000 KM LIMITED TREADWEAR WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi			
16	205/55 R 16 91W	T433018	18.7	560/AA/A	24.9	8.4	5.5	7.5	6.5	1355	91	W	10.0	51	810	503
	215/55 R 16 97W XL	T433063	20.9	560/AA/A	25.3	8.9	6	7.5	7	1610	97	W	10.0	51	797	495
	225/50 R 16 92W	T433068	20.9	560/AA/A	24.9	9.2	6	8	7	1390	92	W	10.0	51	810	503
17	205/45 R 17 88W XL	T433040	20.9	560/AA/A	24.3	8.1	6.5	7.5	7	1235	88	W	10.0	51	830	516
	205/50 R 17 93W XL	T433051	19.8	560/AA/A	25.1	8.4	5.5	7.5	6.5	1435	93	W	10.0	51	804	499
	215/50 R 17 95W XL	T433034	20.9	560/AA/A	25.5	8.9	6	7.5	7	1520	95	W	10.0	51	791	491
	215/45 R 17 91W XL	T433020	20.9	560/AA/A	24.6	8.4	7	8	7	1355	91	W	10.0	51	820	509
	215/55 R 17 94W	T433059	22.0	560/AA/A	26.3	8.9	6	7.5	7	1477	94	W	10.0	51	767	476
	225/45 R 17 94W XL	T433016	23.1	560/AA/A	25.0	8.9	7	8.5	7.5	1477	94	W	10.0	51	807	501
	225/55 R 17 101W XL	T433030	25.4	560/AA/A	26.8	9.2	6	8	7	1820	101	W	10.0	51	753	468
	225/50 R 17 98W XL	T433031	23.1	560/AA/A	25.9	9.2	6	8	7	1655	98	W	10.0	51	779	484
	235/55 R 17 103W XL	T433043	26.5	560/AA/A	27.2	9.6	6.5	8.5	7.5	1930	103	W	10.0	51	741	461
	235/45 R 17 97W XL	T433042	24.3	560/AA/A	25.4	9.3	7.5	9	8	1610	97	W	10.0	51	794	493
	235/50 R 17 96W	T433060	25.4	560/AA/A	26.3	9.6	6.5	8.5	7.5	1565	96	W	10.0	51	767	476
	18	245/40 R 17 91W	T433045	23.1	560/AA/A	24.7	9.8	8	9.5	8.5	1355	91	W	10.0	51	817
245/45 R 17 99W XL		T433056	24.3	560/AA/A	25.7	9.6	7.5	9	8	1710	99	W	10.0	51	785	488
215/45 R 18 93W XL		T433037	19.8	560/AA/A	25.6	8.4	7	8	7	1435	93	W	10.0	51	788	490
215/40 R 18 89W XL		T433067	20.9	560/AA/A	24.8	8.6	7	8.5	7.5	1280	89	W	10.0	51	813	505
225/40 R 18 92W XL		T433017	23.1	560/AA/A	25.1	9.1	7.5	9	8	1390	92	W	10.0	51	804	499
225/60 R 18 100W		T433061	28.7	560/AA/A	28.6	9.0	6	8	6.5	1765	100	W	10.0	51	705	438
225/45 R 18 95W XL		T433025	23.1	560/AA/A	25.9	8.9	7	8.5	7.5	1520	95	W	10.0	51	779	484
225/50 R 18 99W XL		T433028	25.4	560/AA/A	26.9	9.2	6	8	7	1710	99	W	10.0	51	750	466
235/55 R 18 100W		T433066	28.7	560/AA/A	28.1	9.6	6.5	8.5	7.5	1765	100	W	10.0	51	718	446
235/40 R 18 95W XL		T433033	24.3	560/AA/A	25.4	9.5	8	9.5	8.5	1520	95	W	10.0	51	794	493
235/45 R 18 98W XL		T433019	25.4	560/AA/A	26.3	9.3	7.5	9	8	1655	98	W	10.0	51	767	476
235/50 R 18 101W XL		T433032	26.5	560/AA/A	27.3	9.6	6.5	8.5	7.5	1820	101	W	10.0	51	739	459
235/60 R 18 107W XL		T433049	30.9	560/AA/A	29.1	9.4	6.5	8.5	7	2150	107	W	10.0	51	693	431
245/40 R 18 97W XL		T433027	25.4	560/AA/A	25.7	9.8	8	9.5	8.5	1610	97	W	10.0	51	785	488
245/50 R 18 100Y		T433047	28.7	560/AA/A	27.7	10.0	7	8.5	7.5	1765	100	Y	10.0	51	728	452
245/60 R 18 105V		T433058	32.0	560/AA/A	29.6	9.8	7	8.5	7	2040	105	V	10.0	51	681	423
245/45 R 18 100W XL		T433024	26.5	560/AA/A	26.6	9.6	7.5	9	8	1765	100	W	10.0	51	758	471
255/35 R 18 94W XL		T433038	25.4	560/AA/A	25.0	10.2	8.5	10	9	1477	94	W	10.0	51	807	501
255/40 R 18 99W XL	T433052	26.5	560/AA/A	26.0	10.2	8.5	10	9	1710	99	W	10.0	51	776	482	
255/55 R 18 109W XL	T433035	32.0	560/AA/A	29.0	10.4	7	9	8	2270	109	W	10.0	51	695	432	
265/35 R 18 97W XL	T433064	26.5	560/AA/A	25.3	10.7	9	10.5	9.5	1610	97	W	10.0	51	797	495	
19	225/45 R 19 96W XL	T433041	24.3	560/AA/A	27.0	8.9	7	8.5	7.5	1565	96	W	10.0	51	747	464
	225/40 R 19 93W XL	T433046	25.4	560/AA/A	26.1	9.1	7.5	9	8	1435	93	W	10.0	51	773	480
	235/40 R 19 96W XL	T433023	25.4	560/AA/A	26.4	9.5	8	9.5	8.5	1565	96	W	10.0	51	764	475
	235/55 R 19 105W XL	T433036	29.8	560/AA/A	29.2	9.6	6.5	8.5	7.5	2040	105	W	10.0	51	691	429
	235/35 R 19 91W XL	T433050	25.4	560/AA/A	25.5	9.5	8	9.5	8.5	1355	91	W	10.0	51	791	491

Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi	mile	km	
20	245/40 R 19 98W XL	T433022	26.5	560/AA/A	26.7	9.8	8	9.5	8.5	1655	98	W	10.0	51	755	469
	245/45 R 19 102W XL	T433026	28.7	560/AA/A	27.7	9.6	7.5	9	8	1875	102	W	10.0	51	728	452
	245/50 R 19 105W XL	T433070	28.7	560/AA/A	28.7	10.0	7	8.5	7.5	2040	105	W	10.0	51	703	437
	245/35 R 19 93W XL	T433065	25.4	560/AA/A	25.8	9.8	8	9.5	8.5	1435	93	W	10.0	51	782	486
	255/45 R 19 104W XL	T433054	27.6	560/AA/A	28.1	10.0	8	9.5	8.5	1985	104	W	10.0	51	718	446
	255/50 R 19 107W XL	T433029	32.0	560/AA/A	29.1	10.4	7	9	7.5	2150	107	W	10.0	51	693	431
	255/55 R 19 111W XL	T433071	34.2	560/AA/A	30.0	10.4	7	9	8	2405	111	W	10.0	51	672	418
	255/40 R 19 100W XL	T433039	27.6	560/AA/A	27.0	10.2	8.5	10	9	1765	100	W	10.0	51	747	464
	255/35 R 19 96W XL	T433044	26.5	560/AA/A	26.0	10.2	8.5	10	9	1565	96	W	10.0	51	776	482
275/40 R 19 105W XL	T433075	30.9	560/AA/A	27.7	10.9	9	11	9.5	2040	105	W	10.0	51	728	452	
20	245/45 R 20 103W XL	T433021	29.8	560/AA/A	28.7	9.6	7.5	9	8	1930	103	W	10.0	51	703	437
	245/50 R 20 102V	T433057	30.9	560/AA/A	29.7	10.0	7	8.5	7.5	1875	102	V	10.0	51	679	422
	245/40 R 20 99W XL	T433062	27.6	560/AA/A	27.7	9.8	8	9.5	8.5	1710	99	W	10.0	51	728	452
	255/35 R 20 97W XL	T433048	27.6	560/AA/A	27.0	10.2	8.5	10	9	1610	97	W	10.0	51	747	464
	255/45 R 20 105W XL	T433055	30.9	560/AA/A	29.1	10.0	8	9.5	8.5	2040	105	W	10.0	51	693	431
	255/50 R 20 109W XL	T433069	34.2	560/AA/A	30.1	10.4	7	9	8	2270	109	W	10.0	51	670	416
	255/40 R 20 101W XL	T433072	29.8	560/AA/A	28.0	10.2	8.5	10	9	1820	101	W	10.0	51	720	448
	265/45 R 20 108W XL	T433053	33.1	560/AA/A	29.4	10.5	8.5	10	9	2205	108	W	10.0	51	686	426
	275/35 R 20 102W XL	T433073	32.0	560/AA/A	27.6	10.9	9	11	9.5	1875	102	W	10.0	51	731	454
275/45 R 20 110W XL	T433074	34.2	560/AA/A	29.8	10.8	8.5	10.5	9	2335	110	W	10.0	51	677	421	
21	255/40 R 21 102W XL	T433400	30.9	560/AA/A	29.0	10.2	8.5	10	9	1875	102	W	10.0	51	695	432
	265/40 R 21 105W XL	T433403	34.2	560/AA/A	29.3	10.7	9	10.5	9.5	2040	105	W	10.0	51	688	428
	265/45 R 21 108W XL	T433399	34.2	560/AA/A	30.4	10.5	8.5	10	9	2205	108	W	10.0	51	663	412
	275/45 R 21 110W XL	T433401	36.4	560/AA/A	30.7	10.7	8.5	10.5	9	2335	110	W	10.0	51	657	408
	275/40 R 21 107W XL	T433402	33.1	560/AA/A	29.6	10.9	9	11	9.5	2150	107	W	10.0	51	681	423



FOR ELECTRIC CARS



16-21"



V 149 - Y 186 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
SURPASSASO1

# ALL-WEATHER

## NOKIAN TYRES REMEDY WRG5 NATURAL VERSATILITY

UTQG: 600 A A PASSENGER / CUV / SUV / LIGHT TRUCK



- NATURAL CONFIDENCE. PREDICTABLE SAFETY IN ALL WEATHER CONDITIONS
- NATURAL PERFORMANCE. PRECISE HANDLING AND FOUR-SEASON STABILITY
- NATURAL RESILIENCE. DURABILITY, MILEAGE AND LOW ROLLING RESISTANCE
- 60,000 MILE / 100,000 KM TREADWEAR LIMITED WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi	mile	km	
15	195/65 R 15 91H	T432532	18.7	600/A/A	25.0	7.9	5.5	7	6	1355	91	H	10.5	51	807	501
16	205/55 R 16 91V	T432534	19.8	600/A/A	24.9	8.4	5.5	7.5	6.5	1355	91	V	10.5	51	810	503
	205/60 R 16 92V	T432535	20.9	600/A/A	25.7	8.2	5.5	7.5	6	1390	92	V	10.5	51	785	488
	205/65 R 16 95H	T432536	23.1	600/A/A	26.5	8.2	5.5	7.5	6	1520	95	H	10.5	51	761	473
	205/70 R 16 97H	T432930	24.3	600/A/A	27.3	8.2	5	7	6	1610	97	H	10.5	51	739	459
	215/55 R 16 97H XL	T432539	22.0	600/A/A	25.3	8.9	6	7.5	7	1610	97	H	10.5	51	797	495
	215/60 R 16 95H	T432542	23.1	600/A/A	26.1	8.7	6	7.5	6.5	1520	95	H	10.5	51	773	480
	225/60 R 16 98H	T432553	25.4	600/A/A	26.6	9.0	6	8	6.5	1655	98	H	10.5	51	758	471
	265/70 R 16 112H	T432599	34.2	600/A/A	30.6	10.7	7	9	8	2470	112	H	10.5	51	659	410
17	205/50 R 17 93V XL	T432533	20.9	600/A/A	25.1	8.4	5.5	7.5	6.5	1435	93	V	10.5	51	804	499
	215/45 R 17 91V XL	T432537	20.9	600/A/A	24.6	8.4	7	8	7	1355	91	V	10.5	51	820	509
	215/50 R 17 95V XL	T432538	22.0	600/A/A	25.5	8.9	6	7.5	7	1520	95	V	10.5	51	791	491
	215/55 R 17 94V	T432540	22.0	600/A/A	26.3	8.9	6	7.5	7	1477	94	V	10.5	51	767	476
	215/60 R 17 96H	T432543	23.1	600/A/A	27.2	8.7	6	7.5	6.5	1565	96	H	10.5	51	741	461
	215/65 R 17 99H	T432544	24.3	600/A/A	28.0	8.7	6	7.5	6.5	1710	99	H	10.5	51	720	448
	225/45 R 17 94V XL	T432546	22.0	600/A/A	25.0	8.9	7	8.5	7.5	1477	94	V	10.5	51	807	501
	225/50 R 17 98V XL	T432548	22.0	600/A/A	25.9	9.2	6	8	7	1655	98	V	10.5	51	779	484
	225/55 R 17 101V XL	T432550	25.4	600/A/A	26.8	9.2	6	8	7	1820	101	V	10.5	51	753	468
	225/60 R 17 103H XL	T432554	26.5	600/A/A	27.6	9.0	6	8	6.5	1930	103	H	10.5	51	731	454
	225/65 R 17 106H XL	T432556	26.5	600/A/A	28.5	9.0	6	8	6.5	2095	106	H	10.5	51	708	440
	235/45 R 17 97V XL	T432559	23.1	600/A/A	25.4	9.3	7.5	9	8	1610	97	V	10.5	51	794	493
	235/55 R 17 99V	T432564	26.5	600/A/A	27.2	9.6	6.5	8.5	7.5	1710	99	V	10.5	51	741	461
	235/60 R 17 102H	T432568	29.8	600/A/A	28.1	9.4	6.5	8.5	7	1875	102	H	10.5	51	718	446
	235/65 R 17 108H XL	T432570	29.8	600/A/A	29.1	9.4	6.5	8.5	7	2205	108	H	10.5	51	693	431
	245/45 R 17 99V XL	T432575	24.3	600/A/A	25.7	9.6	7.5	9	8	1710	99	V	10.5	51	785	488
265/60 R 17 108V	T432596	35.3	600/A/A	29.5	10.7	7	9.5	8	2205	108	V	10.5	51	684	425	
265/65 R 17 112H	T432598	34.2	600/A/A	30.5	10.7	7.5	9.5	8	2470	112	H	10.5	51	661	411	
265/70 R 17 115H	T432600	37.5	600/A/A	31.6	10.7	7	9	8	2680	115	H	10.5	51	638	397	
18	215/55 R 18 99V XL	T432541	26.5	600/A/A	27.3	8.9	6	7.5	7	1710	99	V	10.5	51	739	459
	225/45 R 18 95V XL	T432547	23.1	600/A/A	25.9	8.9	7	8.5	7.5	1520	95	V	10.5	51	779	484
	225/40 R 18 92V XL	T432545	23.1	600/A/A	25.1	9.1	7.5	9	8	1390	92	V	10.5	51	804	499
	225/50 R 18 99V XL	T432549	25.4	600/A/A	26.9	9.2	6	8	7	1710	99	V	10.5	51	750	466
	225/55 R 18 98V	T432551	26.5	600/A/A	27.8	9.2	6	8	7	1655	98	V	10.5	51	725	451
	225/60 R 18 100W	T432555	26.5	600/A/A	28.6	9.0	6	8	6.5	1765	100	W	10.5	51	705	438
	235/40 R 18 95V XL	T432557	24.3	600/A/A	25.4	9.5	8	9.5	8.5	1520	95	V	10.5	51	794	493

Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi	mile	km	
	235/45 R 18 98V XL	T432560	24.3	600/A/A	26.3	9.3	7.5	9	8	1655	98	V	10.5	51	767	476
	235/50 R 18 101V XL	T432562	26.5	600/A/A	27.3	9.6	6.5	8.5	7.5	1820	101	V	10.5	51	739	459
	235/55 R 18 104H XL	T432565	28.7	600/A/A	28.1	9.6	6.5	8.5	7.5	1985	104	H	10.5	51	718	446
	235/60 R 18 107V XL	T432569	29.8	600/A/A	29.1	9.4	6.5	8.5	7	2150	107	V	10.5	51	693	431
	235/65 R 18 106V	T432571	32.0	600/A/A	30.0	9.4	6.5	8.5	7	2095	106	V	10.5	51	672	418
	245/50 R 18 104V XL	T432579	28.7	600/A/A	27.7	10.0	7	8.5	7.5	1985	104	V	10.5	51	728	452
	245/40 R 18 97V XL	T432572	24.3	600/A/A	25.7	9.8	8	9.5	8.5	1610	97	V	10.5	51	785	488
	245/45 R 18 100V XL	T432576	26.5	600/A/A	26.6	9.6	7.5	9	8	1765	100	V	10.5	51	758	471
	245/55 R 18 103W	T432581	29.8	600/A/A	28.6	10.0	7	8.5	7.5	1930	103	W	10.5	51	705	438
	245/60 R 18 105H	T432583	32.0	600/A/A	29.6	9.8	7	8.5	7	2040	105	H	10.5	51	681	423
	255/55 R 18 109V XL	T432589	32.0	600/A/A	29.0	10.4	7	9	8	2270	109	V	10.5	51	695	432
	255/60 R 18 112V XL	T432592	33.1	600/A/A	30.0	10.2	7	9	7.5	2470	112	V	10.5	51	672	418
	255/65 R 18 111H	T432593	33.1	600/A/A	31.1	10.2	7	9	7.5	2405	111	H	10.5	51	648	403
	265/60 R 18 110H	T432597	34.2	600/A/A	30.5	10.7	7	9.5	8	2335	110	H	10.5	51	661	411
19	225/55 R 19 103V XL	T432552	26.5	600/A/A	28.8	9.2	6	8	7	1930	103	V	10.5	51	700	435
	235/40 R 19 96W XL	T432558	26.5	600/A/A	26.4	9.5	8	9.5	8.5	1565	96	W	10.5	51	764	475
	235/45 R 19 99V XL	T432561	25.4	600/A/A	27.4	9.3	7.5	9	8	1710	99	V	10.5	51	736	457
	235/50 R 19 103V XL	T432563	28.7	600/A/A	28.3	9.6	6.5	8.5	7.5	1930	103	V	10.5	51	713	443
	235/55 R 19 105V XL	T432566	28.7	600/A/A	29.2	9.6	6.5	8.5	7.5	2040	105	V	10.5	51	691	429
	245/40 R 19 98W XL	T432573	26.5	600/A/A	26.7	9.8	8	9.5	8.5	1655	98	W	10.5	51	755	469
	245/45 R 19 102V XL	T432577	27.6	600/A/A	27.7	9.6	7.5	9	8	1875	102	V	10.5	51	728	452
	245/55 R 19 103H	T432582	33.1	600/A/A	29.6	10.0	7	8.5	7.5	1930	103	H	10.5	51	681	423
	255/35 R 19 96V XL	T432584	26.5	600/A/A	26.0	10.2	8.5	10	9	1565	96	V	10.5	51	776	482
	255/40 R 19 100V XL	T432585	27.6	600/A/A	27.0	10.2	8.5	10	9	1765	100	V	10.5	51	747	464
	255/50 R 19 107V XL	T432587	32.0	600/A/A	29.1	10.4	7	9	7.5	2150	107	V	10.5	51	693	431
255/55 R 19 111V XL	T432590	33.1	600/A/A	30.0	10.4	7	9	8	2405	111	V	10.5	51	672	418	
20	235/55 R 20 102V	T432567	30.9	600/A/A	30.2	9.6	6.5	8.5	7.5	1875	102	V	10.5	51	668	415
	245/40 R 20 99W XL	T432574	27.6	600/A/A	27.7	9.8	8	9.5	8.5	1710	99	W	10.5	51	728	452
	245/45 R 20 103V XL	T432578	29.8	600/A/A	28.7	9.6	7.5	9	8	1930	103	V	10.5	51	703	437
	245/50 R 20 102V	T432580	30.9	600/A/A	29.7	10.0	7	8.5	7.5	1875	102	V	10.5	51	679	422
	255/45 R 20 105V XL	T432586	30.9	600/A/A	29.1	10.0	8	9.5	8.5	2040	105	V	10.5	51	693	431
	255/50 R 20 109V XL	T432588	34.2	600/A/A	30.1	10.4	7	9	8	2270	109	V	10.5	51	670	416
	255/55 R 20 110V XL	T432591	35.3	600/A/A	31.0	10.4	7	9	8	2335	110	V	10.5	51	651	404
	265/45 R 20 108V XL	T432594	32.0	600/A/A	29.4	10.5	8.5	10	9	2205	108	V	10.5	51	686	426
	265/50 R 20 111V XL	T432595	34.2	600/A/A	30.5	10.9	7.5	9.5	8.5	2405	111	V	10.5	51	661	411
21	275/45 R 20 110V XL	T432601	33.1	600/A/A	29.8	10.8	8.5	10.5	9	2335	110	V	10.5	51	677	421
	275/55 R 20 113V	T432602	37.5	600/A/A	31.9	11.2	7.5	9.5	8.5	2535	113	V	10.5	51	632	393
	255/40 R 21 102W XL	T433396	29.8	600/A/A	29.0	10.2	8.5	10	9	1875	102	W	10.5	51	695	432
	265/45 R 21 108V XL	T433395	34.2	600/A/A	30.4	10.5	8.5	10	9	2205	108	V	10.5	51	663	412
	265/40 R 21 105W XL	T433398	32.0	600/A/A	29.3	10.7	9	10.5	9.5	2040	105	W	10.5	51	688	428
	275/40 R 21 107V XL	T433397	33.1	600/A/A	29.6	10.9	9	11	9.5	2150	107	V	10.5	51	681	423
	275/45 R 21 110W XL	T433803	36.4	600/A/A	30.7	10.7	8.5	10.5	9	2335	110	W	10.5	51	657	408

● New



[WWW.NOKIATYRES.COM/](http://WWW.NOKIATYRES.COM/)  
REMEDYWRG5

# NOKIAN TYRES WR C3

## TOUGH PERFORMANCE

VAN / CARGO



- MAXIMUM WINTER SAFETY AND COMFORT
- PRECISE AND STABLE HANDLING
- EXCELLENT DURABILITY, EVEN WITH HEAVY LOADS

**nokian TYRES**  
**ELECTRIC FIT™**  
TESTED TO FIT ELECTRIC CARS

**nokian TYRES**  
**SATISFACTION GUARANTEE**  
30-DAY RETURN WITH FULL REFUND

**nokian TYRES**  
**POTHOLE PROTECTION™**  
FREE TIRE REPLACEMENT IF BEYOND REPAIR



Rim	Size/Speed Rating	Product Code	Weight	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
						Min	Max	Measuring								mile	km
			lbs	inch	inch	inch	inch	inch		lbs			1/32 inch	psi			
15	185/60 R 15 C 94/92T	T429939	18.7	23.7	7.4	5.5	6	5.5	C (6)	1477	94	92	T	11.5	54	851	529
	205/65 R 15 C 102/100T	T429136	26.5	25.5	8.2	5.5	6.5	6	C (6)	1875	102	100	T	11.5	54	791	491
16	195/75 R 16 C 107/105S	T429127	26.5	27.5	7.7	5	6	5.5	D (8)	2150	107	105	S	11.5	69	733	456
	225/75 R 16 C 121/120R	T429130	34.2	29.3	8.8	6	7	6	E (10)	3195	121	120	R	11.5	83	688	428
	235/65 R 16 C 121/119R	T429142	34.2	28.0	9.4	6.5	7.5	7	E (10)	3195	121	119	R	11.5	83	720	448
18	LT265/70 R 18 124/121S	T433489	45.2	32.6	10.7	7	9	8	E (10)	3525	124	121	S	13.0	80	619	384



15-16", 18"



R 106 - T 118 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
**WRC3**

# ALL-TERRAIN

## NOKIAN TYRES OUTPOST APT EXTEND YOUR ADVENTURES

UTQG: 700 A A CUV / SUV / LIGHT TRUCK



- EXTEND YOUR TERRAIN WITH YEAR-ROUND VERSATILITY
- EXTEND YOUR TOUGHNESS WITH POTHOLE PROTECTION
- EXTEND YOUR TRAVEL WITH DURABLE COMPOUND
- EXTEND YOUR ADVENTURES AND DRIVE IN ALL FOUR SEASONS
- 65,000 MILE / 105,000 KM TREADWEAR LIMITED WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
			lbs		inch	inch	inch	inch	inch	lbs		1/32 inch	psi			
16	205/70 R 16 97H	T432129	25.4	700/A/A	27.3	8.2	5	7	6	1610	97	H	13.0	51	739	459
	215/65 R 16 98H	T432105	25.4	700/A/A	27.0	8.7	6	7.5	6.5	1655	98	H	13.0	51	747	464
	215/70 R 16 100H	T432111	27.6	700/A/A	27.9	8.7	5.5	7	6.5	1765	100	H	13.0	51	723	449
	225/70 R 16 107T XL	T432929	29.8	700/A/A	28.4	9.0	6	7.5	6.5	2150	107	T	13.0	51	710	441
	235/70 R 16 106T	T432106	30.9	700/A/A	29.0	9.4	6	8	7	2095	106	T	13.0	47	695	432
	265/70 R 16 112T	T432109	36.4	700/A/A	30.6	10.7	7	9	8	2470	112	T	13.0	47	659	410
17	215/60 R 17 96H	T432118	25.4	700/A/A	27.2	8.7	6	7.5	6.5	1565	96	H	13.0	51	741	461
	215/65 R 17 99H	T432123	26.5	700/A/A	28.0	8.7	6	7.5	6.5	1710	99	H	13.0	51	720	448
	225/60 R 17 99H	T432101	28.7	700/A/A	27.6	9.0	6	8	6.5	1710	99	H	13.0	51	731	454
	225/65 R 17 102H	T432099	28.7	700/A/A	28.5	9.0	6	8	6.5	1875	102	H	13.0	51	708	440
	225/55 R 17 97H	T432103	26.5	700/A/A	26.8	9.2	6	8	7	1610	97	H	13.0	51	753	468
	235/65 R 17 104H	T432100	30.9	700/A/A	29.1	9.4	6.5	8.5	7	1985	104	H	13.0	51	693	431
	235/60 R 17 102H	T432112	30.9	700/A/A	28.1	9.4	6.5	8.5	7	1875	102	H	13.0	51	718	446
	245/65 R 17 107H	T432108	32.0	700/A/A	29.5	9.8	7	8.5	7	2150	107	H	13.0	51	684	425
	255/65 R 17 110T	T432131	35.3	700/A/A	30.1	10.2	7	9	7.5	2335	110	T	13.0	47	670	416
	265/65 R 17 112H	T432122	36.4	700/A/A	30.5	10.7	7.5	9.5	8	2470	112	H	13.0	51	661	411
18	215/55 R 18 95H	T432130	27.6	700/A/A	27.3	8.9	6	7.5	7	1520	95	H	13.0	51	739	459
	225/60 R 18 104H XL	T432110	29.8	700/A/A	28.6	9.0	6	8	6.5	1985	104	H	13.0	51	705	438
	225/55 R 18 98H	T432120	28.7	700/A/A	27.8	9.2	6	8	7	1655	98	H	13.0	51	725	451
	235/55 R 18 100H	T432104	29.8	700/A/A	28.1	9.6	6.5	8.5	7.5	1765	100	H	13.0	51	718	446
	235/65 R 18 106H	T432114	33.1	700/A/A	30.0	9.4	6.5	8.5	7	2095	106	H	13.0	51	672	418
	235/60 R 18 107H XL	T432102	32.0	700/A/A	29.1	9.4	6.5	8.5	7	2150	107	H	13.0	51	693	431
	235/50 R 18 97H	T432117	28.7	700/A/A	27.3	9.6	6.5	8.5	7.5	1610	97	H	13.0	51	739	459
	245/60 R 18 105H	T432107	34.2	700/A/A	29.6	9.8	7	8.5	7	2040	105	H	13.0	51	681	423
	255/65 R 18 111H	T432124	36.4	700/A/A	31.1	10.2	7	9	7.5	2405	111	H	13.0	51	648	403
	265/60 R 18 110H	T432113	36.4	700/A/A	30.5	10.7	7	9.5	8	2335	110	H	13.0	51	661	411
19	225/55 R 19 99H	T432128	28.7	700/A/A	28.8	9.2	6	8	7	1710	99	H	13.0	51	700	435
	235/55 R 19 105H XL	T432115	30.9	700/A/A	29.2	9.6	6.5	8.5	7.5	2040	105	H	13.0	51	691	429
	245/55 R 19 103H	T432119	34.2	700/A/A	29.6	10.0	7	8.5	7.5	1930	103	H	13.0	51	681	423
	255/60 R 19 113H XL	T432126	36.4	700/A/A	31.1	10.2	7	9	7.5	2535	113	H	13.0	51	648	403
20	235/55 R 20 102H	T432125	32.0	700/A/A	30.2	9.6	6.5	8.5	7.5	1875	102	H	13.0	51	668	415
	245/50 R 20 102H	T432121	33.1	700/A/A	29.7	10.0	7	8.5	7.5	1875	102	H	13.0	51	679	422
	255/55 R 20 110H XL	T432127	36.4	700/A/A	31.0	10.4	7	9	8	2335	110	H	13.0	51	651	404
	255/50 R 20 109H XL	T432116	35.3	700/A/A	30.1	10.4	7	9	8	2270	109	H	13.0	51	670	416
	265/50 R 20 107T	T432310	36.4	700/A/A	30.5	10.9	7.5	9.5	8.5	2150	107	T	13.0	47	661	411
21	265/45 R 21 108H XL	T433393	36.4	700/A/A	30.4	10.5	8.5	10	9	2205	108	H	13.0	51	663	412

Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Max Load	Load Index	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring						mile	km
							inch	inch	inch							
	275/45 R 21 110H XL	T433394	45.2 lbs	700/A/A	30.7 inch	10.7 inch	8.5 inch	10.5 inch	9 inch	2335 lbs	110	H	13.0 1/32 inch	51 psi	657 mile	408 km



3PMSF



FOR ELECTRIC CARS



16-21"



H 130 - T 118 mph



[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
OUTPOSTART

# NOKIAN TYRES OUTPOST NAT

EXTEND YOUR ADVENTURES

CUV / SUV / LIGHT TRUCK / VAN / CARGO



- EXTEND YOUR TERRAIN WITH EXCELLENT GRIP ON ALL SURFACES
- EXTEND YOUR TOUGHNESS WITH ARAMID TOUGH SHIELD'S EXTREME DURABILITY
- EXTEND YOUR TRAVEL WITH ENHANCED SERVICE LIFE
- EXTEND YOUR ADVENTURES AND DRIVE IN ALL FOUR SEASONS
- 60,000 MILE / 100,000 KM TREADWEAR LIMITED WARRANTY



Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring								mile	km
			lbs		inch	inch	inch	inch	inch		lbs			1/32 inch	psi	mile	km	
15	31x10.50 R 15 LT 109S	T432868	46.3	-	30.5	10.5	7	9	8.5	C (6)	2270	109	-	S	18.0	50	661	411
	235/75 R 15 109T XL	T432846	33.1	700/A/A	28.9	9.3	6	8	6.5	-	2270	109	-	T	14.0	51	698	434
16	LT215/85 R 16 115/112S	T432869	40.8	-	30.4	8.5	5.5	7	6	E (10)	2680	115	112	S	18.0	80	663	412
	LT225/75 R 16 115/112S	T432871	40.8	-	29.3	8.8	6	7	6	E (10)	2680	115	112	S	18.0	80	688	428
	LT235/85 R 16 120/116S	T432870	44.1	-	31.7	9.3	6	7.5	6.5	E (10)	3085	120	116	S	18.0	80	636	395
	235/70 R 16 109T XL	T432892	33.1	700/A/A	29.0	9.4	6	8	7	-	2270	109	-	T	14.0	51	695	432
	LT245/75 R 16 120/116S	T432863	44.1	-	30.5	9.8	6.5	8	7	E (10)	3085	120	116	S	18.0	80	661	411
	245/75 R 16 111T	T432848	36.4	700/A/A	30.5	9.8	6.5	8	7	-	2405	111	-	T	14.0	44	661	411
	245/70 R 16 111T XL	T432862	36.4	700/A/A	29.5	9.8	6.5	8	7	-	2405	111	-	T	14.0	51	684	425
	255/70 R 16 111T	T432893	36.4	700/A/A	30.1	10.2	6.5	8.5	7.5	-	2405	111	-	T	14.0	44	670	416
	LT265/75 R 16 123/120S	T432865	49.6	-	31.6	10.5	7	8	7.5	E (10)	3415	123	120	S	18.0	80	638	397
	265/75 R 16 116T	T432847	41.9	700/A/A	31.6	10.5	7	9	7.5	-	2755	116	-	T	14.0	44	638	397
265/70 R 16 112T	T432849	39.7	700/A/A	30.6	10.7	7	9	8	-	2470	112	-	T	14.0	44	659	410	
LT285/75 R 16 126/123S	T432866	52.9	-	32.8	11.3	7.5	9	8	E (10)	3750	126	123	S	18.0	80	615	382	
17	35x12.50 R 17 LT 128R	T432838	61.7	-	34.5	12.5	8.5	11	10	F (12)	3970	128	-	R	18.0	80	585	363
	LT235/80 R 17 120/117S	T432882	45.2	-	31.8	9.3	6	7.5	6.5	E (10)	3085	120	117	S	18.0	80	634	394
	235/75 R 17 109S	T432850	36.4	700/A/A	30.9	9.3	6	8	6.5	-	2270	109	-	S	14.0	44	653	406
	235/65 R 17 108T XL	T432895	34.2	700/A/A	29.1	9.4	6.5	8.5	7	-	2205	108	-	T	14.0	51	693	431
	LT245/75 R 17 121/118S	T432864	47.4	-	31.5	9.8	6.5	7.5	7	E (10)	3195	121	118	S	18.0	80	640	398
	LT245/70 R 17 119/116S	T432877	45.2	-	30.5	9.8	6.5	8	7	E (10)	3000	119	116	S	18.0	80	661	411
	245/70 R 17 110T	T432853	37.5	700/A/A	30.5	9.8	6.5	8	7	-	2335	110	-	T	14.0	44	661	411
	245/65 R 17 111T XL	T432855	35.3	700/A/A	29.5	9.8	7	8.5	7	-	2405	111	-	T	14.0	51	684	425
	255/70 R 17 112T	T432851	38.6	700/A/A	31.1	10.2	6.5	8.5	7.5	-	2470	112	-	T	14.0	44	648	403
	255/65 R 17 110T	T432856	38.6	700/A/A	30.1	10.2	7	9	7.5	-	2335	110	-	T	14.0	44	670	416
	255/75 R 17 115S	T432894	41.9	700/A/A	32.0	10.0	6.5	8.5	7	-	2680	115	-	S	14.0	44	630	392
	LT265/70 R 17 123/120S	T432878	50.7	-	31.6	10.7	7	8.5	8	E (10)	3415	123	120	S	18.0	80	638	397
	265/70 R 17 115T	T432852	40.8	700/A/A	31.6	10.7	7	9	8	-	2680	115	-	T	14.0	44	638	397
	265/65 R 17 116T XL	T432857	39.7	700/A/A	30.5	10.7	7.5	9.5	8	-	2755	116	-	T	14.0	51	661	411
	LT275/70 R 17 124/121S	T432879	50.7	-	32.2	11.0	7	8.5	8	E (10)	3525	124	121	S	18.0	80	626	389
LT285/75 R 17 128/125S	T432861	55.1	-	33.9	11.3	7.5	9.5	8	E (10)	3970	128	125	S	18.0	80	595	370	
LT285/70 R 17 126/123S	T432875	54.0	-	32.8	11.5	7.5	9	8.5	E (10)	3750	126	123	S	18.0	80	615	382	
285/70 R 17 116T	T432854	45.2	700/A/A	32.8	11.5	7.5	9.5	8.5	-	2755	116	-	T	14.0	44	615	382	
LT315/70 R 17 128/125S	T432876	61.7	-	34.4	12.7	8	11	9.5	F (12)	3970	128	125	S	18.0	80	586	364	
18	35x12.50 R 18 LT 128R	T432887	61.7	-	34.5	12.5	8.5	11	10	F (12)	3970	128	-	R	18.0	80	585	363
	255/70 R 18 116H XL	T432858	40.8	700/A/A	32.1	10.2	6.5	8.5	7.5	-	2755	116	-	H	14.0	51	628	390
	255/60 R 18 112H XL	T432896	37.5	700/A/A	30.0	10.2	7	9	7.5	-	2470	112	-	H	14.0	51	672	418
	LT265/70 R 18 124/121S	T432872	52.9	-	32.6	10.7	7	9	8	E (10)	3525	124	121	S	18.0	80	619	384
	265/65 R 18 114H	T432841	39.7	700/A/A	31.5	10.7	7.5	9.5	8	-	2600	114	-	H	14.0	51	640	398
	265/60 R 18 114T XL	T432843	39.7	700/A/A	30.5	10.7	7	9.5	8	-	2600	114	-	T	14.0	51	661	411
	265/70 R 18 116S	T432859	43.0	700/A/A	32.6	10.7	7	9	8	-	2755	116	-	S	14.0	44	619	384

Rim	Size/Speed Rating	Product Code	Weight	UTQG	Overall Diameter	Section Width	Rim Width			Load Rating	Max Load	Load Index	Load Index Dual	Speed Rating	Tread Depth	Max. Inflation	Revolutions Per	
							Min	Max	Measuring								mile	km
			lbs		inch	inch	inch	inch		lbs				1/32 inch	psi			
	LT275/70 R 18 125/122S	T432873	54.0	-	33.2	11.0	7	8.5	8	E (10)	3640	125	122	S	18.0	80	607	377
	LT275/65 R 18 123/120S	T432890	52.9	-	32.1	11.0	7.5	9	8	E (10)	3415	123	120	S	18.0	80	628	390
	275/65 R 18 116T	T432842	44.1	700/A/A	32.1	11.0	7.5	9.5	8	-	2755	116	-	T	14.0	44	628	390
	LT285/75 R 18 129/126S	T432837	58.4	-	34.8	11.3	7.5	9.5	8	E (10)	4080	129	126	S	18.0	80	580	360
	LT285/65 R 18 125/122S	T432891	54.0	-	32.6	11.5	8	10	8.5	E (10)	3640	125	122	S	18.0	80	619	384
	LT295/70 R 18 129/126S	T432874	58.4	-	34.3	11.8	7.5	10	8.5	E (10)	4080	129	126	S	18.0	80	588	365
20	35x12.50 R 20 LT 125R	T432883	62.8	-	34.5	12.5	8.5	11	10	F (12)	3640	125	-	R	18.0	80	585	363
	LT265/60 R 20 121/118S	T432889	52.9	-	32.5	10.7	7.5	9.5	8	E (10)	3195	121	118	S	18.0	80	621	386
	LT275/65 R 20 126/123S	T432888	56.2	-	34.1	11.0	7.5	9.5	8	E (10)	3750	126	123	S	18.0	80	591	368
	LT275/60 R 20 123/120S	T432880	56.2	-	33.0	11.0	7.5	9.5	8	E (10)	3415	123	120	S	18.0	80	611	380
	LT275/55 R 20 120/117S	T432884	51.8	-	31.9	11.2	7.5	9.5	8.5	E (10)	3085	120	117	S	18.0	80	632	393
	275/55 R 20 117T XL	T432844	41.9	700/A/A	31.9	11.2	7.5	9.5	8.5	-	2835	117	-	T	14.0	51	632	393
	275/60 R 20 115H	T432845	45.2	700/A/A	33.0	11.0	7.5	9.5	8	-	2680	115	-	H	14.0	51	611	380
	LT285/65 R 20 127/124S	T432860	58.4	-	34.6	11.5	8	10	8.5	E (10)	3860	127	124	S	18.0	80	583	362
	LT285/60 R 20 125/122S	T432881	57.3	-	33.5	11.5	8	10	8.5	E (10)	3640	125	122	S	18.0	80	602	374
	LT285/55 R 20 122/119S	T432885	55.1	-	32.4	11.7	8	10	9	E (10)	3305	122	119	S	18.0	80	622	387
	LT295/60 R 20 126/123S	T432839	58.4	-	33.9	11.8	8	10	8.5	E (10)	3750	126	123	S	18.0	80	595	370
LT305/55 R 20 125/122S	T432886	59.5	-	33.2	12.4	8.5	11	9.5	F (12)	3640	125	122	S	18.0	80	607	377	
22	HL275/50 R 22 116H XL	T433488	44.1	700/A/A	32.9	11.2	8	9	8.5	-	2755	116	-	H	14.0	51	613	381
	285/45 R 22 114H XL	T432840	41.9	700/A/A	32.1	11.2	9	10.5	9.5	-	2600	114	-	H	14.0	51	628	390




[WWW.NOKIANTYRES.COM/](http://WWW.NOKIANTYRES.COM/)  
OUTPOSTNAT



## NEED RETAIL RESOURCES? UTILIZE DEALER SERVICES

The **Nokian Tyres Dealer Services** portal is a one-stop shop for online tire ordering, product information, product training courses, marketing materials, and more.\*

\*Not available to non-dealers or end consumers.



### WHAT'S AVAILABLE ON DEALER SERVICES?

- ✔ TIRE ORDERING & ORDER HISTORY
- ✔ TIRE INFORMATION & eACADEMY TRAINING PORTAL
- ✔ VIDEO, PRINT, RADIO & DIGITAL ADS
- ✔ SHOWROOM LOOPS
- ✔ SOCIAL MEDIA POSTS & GRAPHICS
- ✔ BRAND GUIDELINES & CO-OP POLICY

REQUEST AN ACCOUNT OR VISIT [DEALERSERVICES.NOKIANTYRES.COM](https://dealerservices.nokiantyres.com)

ALL-SEASON



**nokian**<sup>®</sup>  
**TYRES**

# NOKIAN TYRES SURPASS<sup>®</sup> AS01

EXPAND YOUR EXPECTATIONS<sup>™</sup>



The Nokian Tyres Surpass AS01 is built with EVs in mind. It comes with Nokian Tyres' Electric Fit emblem, which signifies the tire is a seamless fit for electric vehicles. The Surpass AS01 comes in a wide range of sizes tailored to some of the most popular EVs on the market, making it an ideal replacement tire for EV drivers who want to balance efficiency, durability and performance.

## IT'S TIME TO EXPAND YOUR EXPECTATIONS OF WHAT AN ULTRA-HIGH PERFORMANCE TIRE CAN DO

### FEATURES & BENEFITS

SILICA SENSE TREAD COMPOUND

POTHOLE PROTECTION

TREAD DESIGN

SUSTAINABLE FUTURE



Nokian Tyres' highest-ever proportion of silica in an all-season tire improves wet and dry handling, bolsters longevity and reduces rolling resistance



Ultimate peace of mind thanks to Aramid fibers that mechanically reinforce the sidewalls; it's the first Nokian Tyres ultra-high-performance tire to come with Pothole Protection



A solid center rib, wide circumferential grooves and tailored shoulder construction prepare the tire to experience all conditions



More recycled and renewable content, as part of Nokian Tyres' quest for all tires to have 50% renewable or recycled materials by 2030.

IT IS TIME TO IMAGINE THE EXPERIENCE WITH THE NOKIAN TYRES SURPASS AS01.



Nokian Tyres offers the Surpass AS01 in 65 sizes, ranging from 16 to 21 inches.

VISIT [NOKIANTYRES.COM/SURPASS](https://www.nokiantyres.com/surpass)

# TESTING FUTURE LEGENDS

Tires engineered through rigorous testing at our 3 global test centers:

<p><b>HAKKA RING</b></p>  <p><b>HAKKA RING</b></p> <p>SPAIN TEST CENTER Santa Cruz de la Zarza</p>	<p><b>WHITE HELL</b></p>  <p><b>WHITE HELL</b></p> <p>IVALO TEST CENTER Finland</p>
<p><b>NOKIA TEST CENTER</b></p>  <p>NOKIA, FINLAND</p>	<p><b>UNCOMPROMISING TESTING FOR SAFETY AND PERFORMANCE</b></p> 
<p><b>TESTING WINTER TIRES IN EXTREME CONDITIONS</b></p> 	<p><b>ALL SEASON TIRE TESTING AROUND THE WORLD</b></p> 

**TESTED TO THE LIMIT. PROVEN IN EVERY  
CONDITION.**

Relentless tire testing around the world delivers dependable performance in all conditions.

# RESOURCES

## A GUIDE TO NOKIAN TYRES TECHNOLOGY

### DRIVING SAFETY INDICATOR (DSI)

 40% 60% 80%

Easy **tread depth** measurement at a glance

### WINTER SAFETY INDICATOR (WSI)

 4 6 8

Snowflake represents safe **winter tread depth** limit

### ICE GRIP SYMBOL



Tested and certified for superior **ice performance**

### ARAMID TECH



Aramid fibers provide **puncture resistance**

### ELECTRIC FIT



Certified **safety fit** for EVs and hybrids

### SILENTDRIVE TECH



Acoustic foam **absorbs sound** for EVs and hybrids

**NOKIAN TYRES' PIONEERING ACCOMPLISHMENTS REPRESENT OUR SPIRIT OF TIRE INNOVATION**



# NOKIAN TYRES CONSUMER PROMISES

30-DAY  
SATISFACTION  
GUARANTEE



POTHOLE  
PROTECTION  
WARRANTY



LIMITED  
TREADWEAR  
WARRANTY



TIRE REGISTRATION:  
REGISTER YOUR  
TIRES!

DOT

READ MORE ABOUT NOKIAN TYRES  
WARRANTIES

SATISFACTION GUARANTEE

POTHOLE PROTECTION WARRANTY

LIMITED WARRANTY

BOOKMARK OUR TIRE REGISTRATION PAGE!

## CONSUMER PROMISES

### POTHOLE PROTECTION PROGRAM



In addition to the warranties described herein, as of January 1, 2024, Nokian Tyres also offers a Pothole Protection Program for Nokian Tyres products built with Aramid Technology that are damaged beyond repair by a roadside hazard, for the following products:

- **NOKIAN TYRES SURPASS AS01**
- **NOKIAN TYRES ONE**
- **NOKIAN TYRES ONE HT**
- **NOKIAN TYRES OUTPOST APT**
- **NOKIAN TYRES OUTPOST NAT**
- **NOKIAN TYRES REMEDY WRG5**
- **NOKIAN TYRES WRC3**
- **NOKIAN TYRES HAKKAPELIITTA 10 SUV**
- **NOKIAN TYRES HAKKAPELIITTA R5 SUV**
- **NOKIAN TYRES HAKKAPELIITTA LT3**
- **NOKIAN TYRES HAKKAPELIITTA C4**
- **NOKIAN TYRES HAKKAPELIITTA CR4**
- **NOKIAN TYRES HAKKAPELIITTA O1\*** (\*only available 18"-22")

If, upon examination by an authorized Nokian Tyres retailer, it is discovered that an eligible tire is unserviceable as a result of a roadside hazard and cannot be repaired, that the coverage period (described below) has not expired, and that no Exceptions to Warranty Coverage<sup>1</sup> apply, the tire will be replaced at no charge (conditions apply) with an equivalent new Nokian Tyres tire by an authorized Nokian Tyres retailer. The Pothole Protection Program is not a warranty that your tire will not suffer damage, fail, or otherwise become unserviceable due to a road hazard.

For purposes of the Pothole Protection Program, the coverage period shall extend until: i) the original usable and remaining tread is less than 60% as evidenced by the built-in wear indicators in the tread grooves (60% no longer visible) or a tire tread depth tool; or ii) twelve (12) months from date of retail purchase, whichever comes first. Roadside hazard shall mean puncture, cut, snag, stone drill, impact, bruise break, or similar damage.

Eligible tires must be presented to an authorized retailer along with proof-of-purchase showing the date of purchase. The retailer, in retailer's sole discretion, will determine if the tire is repairable. If repair is possible, Customer is responsible for the cost of such repair. If the

retailer, in retailer's sole discretion, determines the tire cannot be repaired, a replacement Nokian Tyres branded tire will be offered to Customer at no cost. Customer shall be responsible for mounting and balancing costs, towing, road service, valve stems, and applicable taxes. **\*\*Additionally, tires used in commercial applications are not covered.**

### NOKIAN TYRES SATISFACTION GUARANTEE



In addition to the warranties described herein, Nokian Tyres also offers a 30-Day Satisfaction Guarantee. If, within 30 days of purchase, you're not satisfied with their performance, just return the tires along with your original sales receipt to the place of purchase.

Nokian Tyres offers a 30-day satisfaction guarantee on eligible Nokian Tyres products. If, within 30 days of purchase, a retail customer of Nokian Tyres is not completely satisfied with the Nokian Tyres products purchased, the customer may return the products to the location from where originally purchased for a full refund of the purchase price (excluding taxes and mounting and balancing costs). This 30-Day Satisfaction Guarantee applies only to full sets (4) of Nokian Tyres purchased from an authorized Nokian Tyres retailer.

The guarantee and refund eligibility provided herein shall not apply if any tire within the set has experienced more than 2/32 of an inch of treadwear. This guarantee shall also not apply if any tire within the set has experienced damage or irregular wear due to conditions delineated in the Exceptions to Warranty Coverage<sup>1</sup> of Nokian Tyres Limited Warranty. Additionally, tires used in commercial applications are not covered.

Original proof of purchase is required for any returns and only original purchasers of Nokian Tyres products are eligible for any refund under this guarantee. Customers who elect, within 30 days of purchase, to return Nokian Tyres products due to dissatisfaction may be required to address their reasons for return on a dealer supplied claim form.

This 30-Day Satisfaction Guarantee is in addition to any other warranty coverages offered by Nokian Tyres. Limit of one (1) set of tires originally purchased to be replaced by the 30-day satisfaction guarantee. Tires replaced pursuant to this 30-day satisfaction guarantee shall NOT thereafter be eligible for coverage under this 30-day satisfaction guarantee.

### **90-Day Satisfaction Guarantee (U.S. Only)**

For retail customer purchase on, or before December 31, 2026, the Nokian Tyres Surpass AS01 carries a 90-Day Satisfaction Guarantee. All other terms and coverage remain unchanged.

<sup>1</sup> See Exceptions to Warranty Coverage in "**WARRANTY COVERAGE FOR WORKMANSHIP AND MATERIAL**"

## CONSUMER PROMISES: LIMITED WARRANTY

### LIMITED TREADWEAR WARRANTY COVERAGE FOR SELECT TIRES<sup>1</sup>

In addition to the Warranty Coverage for Workmanship and Material, Nokian Tyres also offers treadwear warranty coverage for selected eligible tires purchased in North America and used in non-feet, non-commercial service when submitted as a set of 4, evenly worn tires. The selected tires and associated warranties for U.S. customers are:

- **NOKIAN TYRES SURPASS AS01:** 55,000 Mile (90,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES ONE:** 80,000 Mile (130,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES ONE HT (P-Metric):** 70,000 Mile (115,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES ONE HT (LT-Metric & Cargo):** 55,000 Mile (90,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES OUTPOST APT:** 65,000 Mile (105,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES OUTPOST <sup>N</sup>AT:** 60,000 Mile (100,000 km) Limited Treadwear Warranty
- **NOKIAN TYRES REMEDY WRG5:** 60,000 Mile (100,000 km) Limited Treadwear Warranty
- **NORDMAN SOLSTICE 4:** 50,000 Mile (80,000 km) Limited Treadwear Warranty

Replacement with an equivalent new Nokian Tyres tire for treadwear warranty coverage<sup>2</sup> will occur when an evenly worn eligible tire reaches a tread depth of 2/32" at a mileage level less than specified per series above, and no Exceptions to Warranty Coverage apply. Tires which wear out evenly before delivering the specified treadwear will be replaced on a pro rata basis only if the tires have been rotated and inspected by a participating Nokian Tyres retailer on a regular basis as specified in "Owner Obligations"<sup>3</sup>. Vehicles that come OE with split tments (dierent sizes) on the front and rear axles are eligible for Nokian Tyres' limited treadwear warranty. However, because tire rotation is not possible with vehicles with split tments, the mileage warranty on each rear tire will cover half of the miles/kms as the standard mileage warranty for that particular tire model.

### WARRANTLY ELIGIBILITY

Any new tire manufactured by Nokian Tyres that: i) is owned by the original purchaser; and ii) has remained mounted on the vehicle identified on the receipt of installation is eligible for warranty coverage, subject to the conditions and limitations set forth below. Products sold through on-line auctions or by unauthorized dealers are not eligible for warranty coverage from Nokian Tyres. Consumers are encouraged to visit our Dealer Locator, found on our website [WWW.NOKIANTYRES.COM/DEALERLOCATOR](http://WWW.NOKIANTYRES.COM/DEALERLOCATOR), to verify whether

particular sellers are authorized dealers of Nokian Tyres products.

### WARRANTY PERIOD

The period of warranty coverage for eligible tires extends until: i) the original usable and remaining tread reaches a depth of 2/32" or less, as evidenced by the built-in wear indicators in the tread grooves or a tire tread depth tool; or ii) five (5) years from the date of retail purchase (proof of tire purchase required); or iii) six (6) years from the date of manufacture, whichever occurs first.

### WARRANTY COVERAGE FOR WORKMANSHIP AND MATERIAL

If, upon examination by an authorized Nokian Tyres retailer, it is discovered that an eligible tire is unserviceable as a result of workmanship or material related conditions, that the warranty period for the tire has not expired (five (5) years from date of purchase or six (6) years from date of manufacture), and that no Exceptions to Warranty Coverage apply, the tire will be replaced at no charge (conditions apply) or at prorated cost (determined by reason of claim using mileage and/or tread depth) with an equivalent new Nokian Tyres tire by an authorized Nokian Tyres retailer. Eligibility for no charge replacement and details of prorated calculation can be found under section **TIRE REPLACEMENT AND RELATED COSTS**.

### EXCEPTIONS TO WARRANTY COVERAGE

This Limited Warranty shall not apply if an eligible tire shows uneven wear across the tread down to the treadwear indicators (2/32" of tread remaining), or the tire damage or wear condition is due to any one or more of the following:

- Road hazards, such as puncture, cut, snag, stone drill, impact or bruise break (broken or shifted belts). Please note, certain products are covered by the Pothole Protection Program. Please refer to that program for the coverage details
- Use of tire chains or other additional device(s).
- Cutting or wheel spinning.
- Apparent overload or improper inflation pressure.
- Wheel misalignment or tire/wheel assembly imbalance.
- Use of improper equipment.
- Vehicle conditions, defects, or characteristics.
- Improper mounting or demounting.
- Improper repair, insertion of sealant, improper balancing, or use of filler materials other than air, nitrogen or carbon dioxide.
- Intentional alteration of either the appearance or physical characteristics of the tire.
- Conditions caused by aging or improper storage.
- Vandalism, racing, exceptional use, wreck, collision or ire.

- Use on an emergency vehicle.
- Exposure or contact with solvents, oils, greases, excessive heat or ozone generating devices.
- Faulty or incomplete product advice or instruction not confirmed or approved by Nokian Tyres plc.
- Failure to observe the maintenance and tire care obligations described under “Owner Obligations” or elsewhere herein.

## TIRE REPLACEMENT AND RELATED COSTS

An equivalent new Nokian Tyres tire shall be either: i) the same line of tire; or ii) a tire of the same general construction and quality. If warranty coverage is applicable as a result of workmanship or material related conditions, the eligible tire will be replaced at no charge to the customer if: i) the warranty claim is submitted within twelve (12) months from the date of purchase; and ii) the amount of tread worn from the tire is twenty-five percent (25%) or less of the original usable tread. Mounting and balancing costs, and applicable taxes, will be the responsibility of the customer. If a warranty claim as a result of workmanship or material related conditions does not qualify for free replacement, the customer will be responsible for the replacement cost, mounting and balancing costs, and applicable taxes. Replacement cost shall be calculated by multiplying the Nokian Tyres retailer's then current selling price for the replacement tire by the percentage of original usable tread that has been worn from the replaced tire. If treadwear warranty coverage is provided, the customer will be responsible for the replacement cost, mounting and balancing costs and applicable taxes.

## WARRANTY FOR REPLACEMENT TIRES

Any replacement tires provided pursuant to this Limited Warranty shall be covered by the Nokian Tyres warranty in effect at time of replacement.

## OBTAINING REPLACEMENT TIRES

Any authorized Nokian Tyres retailer in North America can provide replacement tires. To obtain a replacement tire, you must present to the authorized Nokian Tyres retailer the original invoice for the tire being replaced and the tire. No tire replacement will be recognized unless submitted on a Nokian Tyres, Inc. - Claim Form, which must be filled out and signed by the vehicle owner or authorized representative. Nokian Tyres encourages registration of its tires as soon as possible after purchase by visiting [WWW.NOKIANTYRES.COM/TIREREGISTRATION](http://WWW.NOKIANTYRES.COM/TIREREGISTRATION).

## OWNER OBLIGATIONS

Proper tire care is necessary to obtain the maximum mileage and wear from a tire. For this Limited Warranty to be valid, Nokian Tyres requires that vehicle owners have their tires rotated and inspected by a qualified technician after the first 5,000 miles of use. Thereafter, tires should be rotated and inspected at least every 7,500 miles of use by a

qualified technician. Evidence of tire rotation and inspection shall be furnished at time of making a warranty claim. Such proof must show the date, mileage and the servicing location. A properly completed Mileage and Rotation Record form or similar record will constitute sufficient documentation. Vehicle owners must ensure that tire and wheel assemblies are in balance and that tires are operated at proper inflation pressures. Tire pressures, including for spares, should be checked monthly. Pressure testing should be done when tires are cool and adjustments should be done in accordance with specifications set forth in owner's manual.

## TREADWEAR

When the remaining tread anywhere on a tire reaches a depth of 2/32" or less, the tire is fully worn out and should be removed from service.

## CONDITIONS AND EXCLUSIONS

In accordance with federal law, this warranty has been designated a “Limited Warranty.” Nothing in this Limited Warranty is intended as a representation by Nokian Tyres that tire failures cannot occur or a representation that you will receive the level of mileage warranted. Any tire, no matter how well manufactured, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer.

This Limited Warranty is intended to be in lieu of any and all other warranties and representations, whether express or implied, including, but not limited to, any warranty of merchantability or fitness for a particular purpose. No other warranties or representations of any kind are made by Nokian Tyres, and none are to be implied by law. Unless preempted by applicable law or otherwise prohibited by mandatory rights, Nokian Tyres disclaims liability for all indirect, consequential, special and incidental damages that are or may be associated with manufacturing and design defects in workmanship or material, including, but not limited to, loss of use, lost profits and loss of business. Some states or provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. The obligations under this warranty may not be enlarged upon or altered.

## LEGAL RIGHTS

This Limited Warranty gives you specific legal rights. You may have additional rights that vary from state to state, or province to province. This Limited Warranty is applicable in Canada and the United States only. This Limited Warranty is not transferable.

## WARNINGS

To avoid property damage, personal injury or death:

- Always have your tires mounted and demounted by specially trained technicians.

- Always mount your tires on approved rims that meet ETRTO/TRA standards.
- Always have your tires rotated and inspected regularly.
- Always follow rules and recommendations in your vehicle's owner's manual.
- Always mount studded tires in sets of four (4).
- Never simultaneously mount studded and non-studded tires on a vehicle.
- Never mount mixed tire brands on a vehicle.

Warning: It is specifically recommended that studded tires be sold and mounted in sets of four (4). Never mount two (2) studded tires on a vehicle with two (2) nonstudded tires. This could lead to severe handling problems due to differences in tire rubber compounds. It is not recommended to mix brands, product lines, or tires with differing speed ratings. This may lead to handling problems for your vehicle.

## TIRE AGING

All tires experience age degradation, a condition where the physical

and chemical properties of tires change over time. Age degradation can lead to a sudden tire failure. To avoid tire failures caused by age degradation, Nokian Tyres recommends tires (including spares) be removed from service and replaced 10 years after their date of the manufacture, regardless of tread depth or usable condition. The age of a tire can be determined by examining the DOT code on the tire sidewall, or by consulting a tire service professional.

<sup>1</sup> Although Nokian Tyres offers treadwear warranty coverage for the stated mileage on the terms and conditions described herein, treadwear may vary based on a variety of factors, including maintenance, driving habits, and road conditions.

<sup>2</sup> See Exceptions to Warranty Coverage in "Warranty Coverage for Workmanship and Material"

<sup>3</sup> See Owner Obligations in "Warranty Coverage for Workmanship and Material"

For the most up-to-date warranty information visit:

**[WWW.NOKIANTYRES.COM/WARRANTY](http://WWW.NOKIANTYRES.COM/WARRANTY)**

QUICK TIRE SIZE REFERENCE

Rim	SUV, CUV & Metric truck tire size	Hakkapelilitta 10	Hakkapelilitta 10 EV	Hakkapelilitta 10 SUV	Hakkapelilitta C4	Hakkapelilitta CR4	Hakkapelilitta LT3	Hakkapelilitta R5	Hakkapelilitta R5 EV	Hakkapelilitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WR C3	Outpost AP1	Outpost nAT	
14	175/65R14	X						X										
15	31x10.50R15																X	
	175/65R15	X						X										
	185/60R15	X						X			X	X			X			
	185/65R15	X			X	X		X			X							
	195/60R15							X			X							
	195/65R15	X						X			X			X				
	195/70R15				X	X												
	205/65R15							X			X	X			X			
	205/70R15				X						X							
	215/65R15				X	X												
	215/70R15				X	X												
	225/70R15				X	X												
	235/75R15																	X
	16	195/55R16	X						X									
195/65R16					X	X												
195/75R16					X	X						X			X			
205/0R16					X													
205/55R16		X						X			X		X	X				
205/60R16		X						X			X			X				
205/65R16		X			X	X		X			X			X				
205/70R16											X			X		X		
205/75R16					X	X												
215/55R16		X						X			X		X	X				
215/60R16		X				X		X			X			X				
215/65R16				X	X	X			X	X	X						X	
215/70R16				X					X	X							X	
215/75R16					X	X												
215/85R16												X						X
225/50R16														X				
225/55R16	X							X										
225/60R16								X			X		X					
225/65R16				X	X						X							

Rim	SUV, CUV & Metric truck tire size	Hakkapeliitta 10	Hakkapeliitta 10 EV	Hakkapeliitta 10 SUV	Hakkapeliitta C4	Hakkapeliitta CR4	Hakkapeliitta LT3	Hakkapeliitta R5	Hakkapeliitta R5 EV	Hakkapeliitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WRC3	Outpost APT	Outpost nAT
	225/70R16										X					X	
	225/75R16				X	X	X					X			X		X
	235/60R16										X						
	235/65R16				X	X						X			X		
	235/70R16										X	X				X	X
	235/85R16						X					X					X
	245/70R16			X								X					X
	245/75R16						X					X					X
	255/70R16											X					X
	265/70R16			X						X		X		X		X	X
	265/75R16						X					X					X
	285/75R16																X
	35x12.50R17																X
	175/65R17	X						X									
	205/45R17												X				
	205/50R17	X						X			X		X	X			
	205/55R17	X						X									
	205/65R17							X									
	215/45R17							X			X		X	X			
	215/50R17	X						X			X		X	X			
	215/55R17	X						X			X		X	X			
	215/60R17			X	X	X				X	X			X		X	
	215/65R17			X						X	X			X		X	
17	225/45R17	X						X			X		X	X			
	225/50R17	X						X			X		X	X			
	225/55R17	X			X	X		X			X		X	X		X	
	225/60R17			X						X	X			X		X	
	225/65R17			X						X	X			X		X	
	235/45R17	X						X			X		X	X			
	235/50R17										X		X				
	235/55R17			X				X			X		X	X			
	235/60R17			X	X					X	X			X		X	
	235/65R17			X						X	X			X		X	X
	235/75R17																X
	235/80R17						X					X					X

Rim	SUV, CUV & Metric truck tire size	Hakkapeliitta 10	Hakkapeliitta 10 EV	Hakkapeliitta 10 SUV	Hakkapeliitta C4	Hakkapeliitta CR4	Hakkapeliitta LT3	Hakkapeliitta R5	Hakkapeliitta R5 EV	Hakkapeliitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WRC3	Outpost APT	Outpost nAT
	245/40R17												X				
	245/45R17	X						X					X	X			
	245/55R17							X									
	245/65R17			X					X	X	X					X	X
	245/70R17			X			X		X		X						X
	245/75R17						X					X					X
	255/65R17			X					X	X						X	X
	255/70R17											X					X
	255/75R17																X
	265/60R17													X			
	265/65R17			X					X	X	X		X	X		X	X
	265/70R17			X			X		X	X	X		X	X			X
	275/70R17																X
	285/70R17						X										X
	285/75R17																X
	315/70R17						X										X
	35x12.50R18																X
	215/40R18												X				
	215/45R18												X				
	215/55R18			X				X	X	X	X		X	X		X	
	215/60R18			X					X								
	225/40R18	X						X			X		X	X			
	225/45R18	X						X			X		X	X			
	225/50R18	X						X			X		X	X			
	225/55R18			X					X	X				X		X	
	225/60R18			X					X	X			X	X		X	
	235/40R18	X						X					X	X			
	235/45R18	X	X					X	X		X		X	X			
	235/50R18			X					X	X	X		X	X		X	
	235/55R18			X					X	X	X		X	X		X	
	235/60R18		X	X					X	X	X		X	X		X	
	235/65R18			X					X	X				X		X	
	245/40R18	X						X			X		X	X			
	245/45R18	X						X			X		X	X			
	245/50R18							X					X	X			

Rim	SUV, CUV & Metric truck tire size	Hakkapeliitta 10	Hakkapeliitta 10 EV	Hakkapeliitta 10 SUV	Hakkapeliitta C4	Hakkapeliitta CR4	Hakkapeliitta LT3	Hakkapeliitta R5	Hakkapeliitta R5 EV	Hakkapeliitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WR C3	Outpost APT	Outpost nAT
	245/55R18													X			
	245/60R18			X					X	X			X	X		X	
	255/35R18												X				
	255/40R18							X					X				
	255/55R18			X	X				X				X	X			
	255/60R18			X					X					X			X
	255/65R18										X			X		X	
	255/70R18											X					X
	265/35R18												X				
	265/60R18			X					X	X	X			X		X	X
	265/65R18								X		X						X
	265/70R18						X					X			X		X
	275/40R18							X									
	275/65R18			X			X		X		X						X
	275/70R18						X					X					X
	285/65R18																X
	285/75R18																X
	295/70R18																X
	155/70R19							X									
	215/50R19		X						X								
	225/40R19							X					X				
	225/45R19							X					X				
	225/55R19			X					X	X	X			X		X	
	235/35R19												X				
	235/40R19	X	X					X	X		X		X	X			
	235/45R19							X						X			
19	235/50R19			X					X	X				X			
	235/55R19		X	X					X	X	X		X	X		X	
	235/60R19			X						X							
	245/35R19												X				
	245/40R19	X						X			X		X	X			
	245/45R19	X	X					X	X		X		X	X			
	245/50R19			X					X	X			X				
	245/55R19								X	X	X			X		X	
	255/35R19							X					X	X			

Rim	SUV, CUV & Metric truck tire size	Hakkapeliitta 10	Hakkapeliitta 10 EV	Hakkapeliitta 10 SUV	Hakkapeliitta C4	Hakkapeliitta CR4	Hakkapeliitta LT3	Hakkapeliitta R5	Hakkapeliitta R5 EV	Hakkapeliitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WRC3	Outpost APT	Outpost nAT
	255/40R19	X						X					X	X			
	255/45R19		X	X				X	X				X				
	255/50R19			X					X	X	X		X	X			
	255/55R19		X	X						X			X	X			
	255/60R19										X					X	
	265/35R19		X						X								
	265/50R19			X						X							
	275/35R19							X									
	275/40R19	X						X					X				
	285/40R19		X						X								
	35x12.50R20																X
	235/35R20		X						X								
	235/45R20		X						X								
	235/50R20		X						X	X							
	235/55R20			X						X	X			X		X	
	245/35R20	X															
	245/40R20	X						X					X	X			
	245/45R20		X	X					X	X	X		X	X			
	245/50R20			X						X	X		X	X		X	
	255/35R20												X				
	255/40R20		X						X				X				
	255/45R20		X	X					X	X	X		X	X			
20	255/50R20		X	X					X	X	X		X	X		X	
	255/55R20			X						X	X			X		X	
	265/45R20		X						X	X			X	X			
	265/50R20			X						X	X			X		X	
	265/60R20											X					X
	275/30R20								X								
	275/35R20	X						X					X				
	275/40R20									X							
	275/45R20		X	X					X	X			X	X			
	275/50R20			X						X							
	275/55R20			X						X		X		X			X
	275/60R20			X						X		X					X
	275/65R20						X					X					X

Rim	SUV, CUV & Metric truck tire size	Hakkapeliitta 10	Hakkapeliitta 10 EV	Hakkapeliitta 10 SUV	Hakkapeliitta C4	Hakkapeliitta CR4	Hakkapeliitta LT3	Hakkapeliitta R5	Hakkapeliitta R5 EV	Hakkapeliitta R5 SUV	One	One HT	Surpass AS01	Remedy WRG5	WR C3	Outpost APT	Outpost nAT
	285/40R20		X						X	X							
	285/45R20			X						X							
	285/55R20																X
	285/60R20																X
	285/65R20																X
	295/60R20																X
	305/55R20																X
	235/45R21								X								
	235/50R21			X						X							
	255/35R21		X						X								
	255/40R21								X				X	X			
	255/45R21		X						X								
	255/50R21		X						X								
	265/35R21		X						X								
	265/40R21			X						X			X	X			
	265/45R21		X						X				X	X		X	
21	275/35R21		X						X								
	275/40R21			X						X			X	X			
	275/45R21			X					X	X			X	X		X	
	285/40R21		X						X	X							
	285/45R21			X						X							
	295/30R21		X						X								
	295/40R21								X								
	315/35R21			X						X							
	315/40R21			X						X							
	265/40R22								X								
	275/40R22			X						X							
	275/50R22			X						X		X					X
22	285/40R22			X						X							
	285/45R22			X						X		X					X
	295/35R22								X								
	315/35R22			X						X							



## CONTACT INFORMATION

**Nokian Tyres, North America**  
520 Nokian Tyres Drive  
Dayton, TN 37321  
U.S.A.

**HELLO@NOKIANTYRES.COM**  
Tel. 800 565 2525  
**VISIT NOKIANTYRES.COM**

Follow us on social media!  
**@NOKIANTYRESNA**

