



# TECHNICAL MANUAL

UPDATED: 2026-05-24

NOKIAN HEAVY TYRES

**nokian**<sup>®</sup>  
**TYRES**

# TABLE OF CONTENTS

|                                     |           |   |           |
|-------------------------------------|-----------|---|-----------|
| <b>FORESTRY</b>                     | <b>4</b>  | <b>COUNTRY KING G2</b>                  | <b>50</b> |
| FOREST KING F2                      | 5         | CT                                      | 52        |
| FOREST KING TRS 2                   | 7         | ELS                                     | 54        |
| FOREST KING TRS 2+                  | 9         | FLOAT KING VF                           | 56        |
| FOREST KING TRS L-2                 | 11        | <b>UNDERGROUND MINING</b>               | <b>58</b> |
| NORDMAN FOREST ELS L-2              | 13        | ARMOR GARD 2 MINE                       | 59        |
| NORDMAN FOREST F                    | 15        | MINE KING E-4                           | 61        |
| NORDMAN FOREST TRS L-2              | 17        | MINE KING L-5S                          | 63        |
| FOREST KING TRS LS-2                | 19        | MINE L-3S                               | 65        |
| LOGGER KING LS-2                    | 21        | NORDMAN MINE E-4                        | 67        |
| LOGGER KING LS-2 EXTREME            | 23        | <b>PORTS AND TERMINALS</b>              | <b>69</b> |
| FOREST KING T                       | 25        | HTS G2 E-4                              | 70        |
| TR FOREST 2                         | 27        | HTS G2 L-4S                             | 72        |
| TR MULTIPLUS                        | 29        | HTS G2 L-5S                             | 74        |
| TRACTOR KING                        | 31        | ARMOR GARD                              | 76        |
| <b>AGRICULTURAL AND CONTRACTING</b> | <b>33</b> | RTG                                     | 78        |
| TR MULTIPLUS                        | 34        | HTS TUGGER                              | 80        |
| GROUND KING                         | 36        | ARMOR GARD 2                            | 82        |
| HAKKAPELIITTA TRI                   | 38        | <b>EARTHMOVING AND ROAD MAINTENANCE</b> | <b>84</b> |
| SOIL KING VF                        | 41        | GROUND KING LOADER                      | 85        |
| TRI 2                               | 43        | HAKKAPELIITTA LOADER                    | 87        |
| TRI STEEL                           | 46        |   |           |
| COUNTRY KING                        | 48        |   |           |

|   |            |                        |     |
|---|------------|------------------------|-----|
| LOADER GRIP                                     | 89         | E-TRUCK STEER 17.5     | 125 |
| LOADER GRIP 2                                   | 91         | E-TRUCK STEER 19.5     | 127 |
| GROUND KARE                                     | 93         | R-TRUCK STEER          | 129 |
| GROUND KARE SEMI-SLICK                          | 95         | HAKKAPELIITTA TRUCK D  | 131 |
| ARMOR GARD 2                                    | 97         | HAKKAPELIITTA TRUCK D2 | 133 |
| EXCAVATOR                                       | 99         | HAKKAPELIITTA TRUCK E2 | 135 |
| <b>ALL TERRAIN TRUCKS AND MILITARY VEHICLES</b> | <b>101</b> | HAKKA TRUCK DRIVE      | 138 |
| MPT AGILE                                       | 102        | HAKKA TRUCK DRIVE 2    | 141 |
| MPT AGILE 2                                     | 104        | E-TRUCK DRIVE          | 143 |
| <b>TRUCKS AND BUSES</b>                         | <b>106</b> | E-TRUCK DRIVE 17.5     | 146 |
| HAKKAPELIITTA CITY BUS                          | 107        | E-TRUCK DRIVE 19.5     | 148 |
| HAKKAPELIITTA TRUCK F2                          | 110        | R-TRUCK DRIVE          | 150 |
| HAKKA CITY BUS                                  | 113        | HAKKAPELIITTA TRUCK T  | 152 |
| HAKKA TRUCK COACH                               | 115        | HAKKA TRUCK 844+       | 154 |
| HAKKA TRUCK STEER                               | 117        | HAKKA TRUCK TRAILER    | 156 |
| HAKKA TRUCK STEER 2                             | 120        | HAKKA TRUCK TRAILER 2  | 158 |
| E-TRUCK STEER                                   | 122        | E-TRUCK TRAILER        | 160 |
|   |            | R-TRUCK TRAILER        | 164 |

# FORESTRY TIRES

## FORWARDER AND HARVESTER



**5**  
Nokian Tyres  
Forest King F2



**17**  
Nokian Tyres  
Nordman  
Forest TRS L-2



**7**  
Nokian Tyres  
Forest King  
TRS 2



**9**  
Nokian Tyres  
Forest King  
TRS 2+



**11**  
Nokian Tyres  
Forest King  
TRS L-2



**13**  
Nokian Tyres  
Nordman  
Forest ELS L-2



**15**  
Nokian Tyres  
Nordman  
Forest F

## SKIDDER AND FELLER BUNCHER



**19**  
Nokian Tyres  
Forest King  
TRS LS-2



**21**  
Nokian Tyres  
Logger King  
LS-2



**23**  
Nokian Tyres  
Logger King  
LS-2 Extreme

## TRACTOR



**25**  
Nokian Tyres  
Forest King T



**27**  
Nokian Tyres  
TR Forest 2



**29**  
Nokian Tyres  
TR Multiplus




**31**  
Nokian Tyres  
Tractor King

# NOKIAN TYRES FOREST KING F2

## TRACK TIRE FOR HARVESTERS AND FORWARDERS

- Protective tread design with strong shoulders gives excellent functionality in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound in tread and especially in shoulder.
- High load-bearing capacity and comprehensive selection of sizes fills the needs of existing forest machinery – from smallest to heaviest.



## AVAILABLE SIZES

- 600/50-22.5 - T445619
- 710/40-22.5 - T445608
- 710/40-24.5 - T445572
- 800/40-24.5 - T445717
- 600/55-26.5 - T445573
- 710/45-26.5 - T445589
- 710/45-26.5 - T445571
- 710/55-26.5 - T445800
- 750/55-26.5 - T445574
- 800/40-26.5 - T445603
- 710/55-28.5 - T445570
- 780/50-28.5 - T445537
- 780/55-30.5 - T445846

# NOKIAN TYRES FOREST KING F2


## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt), lb |       |       |       |
|--------------|-------------|---------------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|-------|-------|-------|
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 |       |       |       |
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   | 5   | 12    | 17.5  | 25    |
| T445619      | 600/50-22.5 | 159A8 (167A2) | 20         | SF              | TT    | AG20.00 |                | 23.8       | 45.9          | 21.2                      | 139.5                      | 73             | 80                            | 38                    | LS-2       | T55089            | 12015                                       | 11860 | 10320 | 9645  |
| T445608      | 710/40-22.5 | 161A8 (168A2) | 20         | SF              | TT    | AG24.00 |                | 27.9       | 45.9          | 21.1                      | 139.8                      | 73             | 80                            | 38                    | LS-2       | T55092            | 12345                                       | 12545 | 10915 | 10195 |
| T445572      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT    | AG24.00 |                | 27.5       | 48.4          | 22.4                      | 147.2                      | 73             | 80                            | 44                    | LS-2       | T545448           | 13230                                       | 13215 | 11495 | 10750 |
| T445717      | 800/40-24.5 | 169A8 (176A2) | 20         | SF              | TT    | AG28.00 |                | 30.9       | 49.2          | 22.4                      | 149.4                      | 73             | 80                            | 44                    | LS-2       | T545448           | 15655                                       | 15730 | 13680 | 12785 |
| T445573      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT    | AG20.00 |                | 23.7       | 52.8          | 24.3                      | 160.3                      | 73             | 80                            | 44                    | LS-2       | T55098            | 13890                                       | 13965 | 12145 | 11355 |
| T445589      | 710/45-26.5 | 173A8 (180A2) | 24         | SF              | TT    | AG24.00 |                | 27.9       | 53            | 24.4                      | 160.8                      | 87             | 87                            | 44                    | LS-2       | T55099            | 17635                                       | 17625 | 15335 | 14330 |
| T445571      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT    | AG24.00 |                | 27.8       | 53            | 24.5                      | 160.8                      | 73             | 80                            | 44                    | LS-2       | T55099            | 15210                                       | 15190 | 13205 | 12345 |
| T445800      | 710/55-26.5 | 179A8 (186A2) | 24         | SF              | TT    | AG24.00 | AG22.00        | 27.4       | 59.3          | 27                        | 179.5                      | 87             | 87                            | 44                    | LS-2       | T55102            | 20945                                       | 21020 | 18285 | 17085 |
| T445574      | 750/55-26.5 | 182A8 (189A2) | 24         | SF              | TT    | AG24.00 |                | 30.3       | 58            | 26.5                      | 176.6                      | 87             | 87                            | 44                    | LS-2       | T55102            | 23370                                       | 23050 | 20050 | 18740 |
| T445603      | 800/40-26.5 | 170A8 (177A2) | 20         | SF              | TT    | AG28.00 |                | 31.8       | 52.7          | 24.4                      | 160.8                      | 73             | 80                            | 44                    | LS-2       | T545312           | 16095                                       | 16270 | 14155 | 13230 |
| T445570      | 710/55-28.5 | 180A8 (187A2) | 24         | SF              | TT    | AG24.00 |                | 28.3       | 59.6          | 27.4                      | 181.8                      | 87             | 87                            | 44                    | LS-2       | T545543           | 21495                                       | 21695 | 18870 | 17635 |
| T445537      | 780/50-28.5 | 182A8 (190A2) | 24         | SF              | TT    | AG26.00 |                | 30.8       | 59.6          | 27.4                      | 181.8                      | 87             | 87                            | 44                    | LS-2       | T545543           | 23370                                       | 23050 | 20050 | 18740 |
| T445846      | 780/55-30.5 | 187A8 (195A2) | 24         | SF              | TT    | AG26.00 |                | 30.7       | 64.2          | 29.3                      | 195.8                      | 87             | 87                            | 44                    |            | T55891            | 26785                                       | 26445 | 23005 | 21495 |

# NOKIAN TYRES FOREST KING TRS 2

## TRACTION TIRE FOR HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip.
- Wide lug ends, lifted groove bottom in shoulder and considered pitch length give good performance in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound on shoulders.



## AVAILABLE SIZES

- 600/50-22.5 - T445618
- 710/40-22.5 - T445607
- 600/50-24.5 - T445639
- 710/40-24.5 - T445568
- 800/40-24.5 - T445718
- 600/55-26.5 - T445567
- 710/45-26.5 - T445566
- 710/45-26.5 - T445640
- 710/55-26.5 - T445801
- 750/55-26.5 - T445602
- 800/40-26.5 - T445594
- 710/55-28.5 - T445612
- 780/50-28.5 - T445581

# NOKIAN TYRES FOREST KING TRS 2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt), lb | Load capacity for road, lb |       |       |
|--------------|-------------|---------------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|-------|-------|
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 | Speed (mph)                |       |       |
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   |   | 5                          | 12    | 17.5  |
| T445618      | 600/50-22.5 | 159A8 (167A2) | 20         | SF              | TT    | AG20.00 |                | 23.5       | 46            | 21                        | 139.8                      | 73             | 80                            | 53                    | LS-2       | T55089            | 12015                                       | 11860                      | 10320 | 9645  |
| T445607      | 710/40-22.5 | 161A8 (168A2) | 20         | SF              | TT    | AG24.00 |                | 27.8       | 46.1          | 21.1                      | 140.5                      | 73             | 80                            | 53                    | LS-2       | T55092            | 12345                                       | 12545                      | 10915 | 10195 |
| T445639      | 600/50-24.5 | 164A8 (171A2) | 20         | SF              | TT    | AG20.00 | AG22.00        | 23.7       | 48.4          | 22.3                      | 147.2                      | 80             | 80                            | 60                    | LS-2       | T545447           | 12345                                       | 12205                      | 10615 | 9920  |
| T445568      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT    | AG24.00 |                | 27.3       | 48.5          | 22.4                      | 147.9                      | 73             | 80                            | 60                    | LS-2       | T545448           | 13230                                       | 13215                      | 11495 | 10750 |
| T445718      | 800/40-24.5 | 169A8 (176A2) | 20         | SF              | TT    | AG28.00 |                | 30.9       | 49.3          | 22.3                      | 149.9                      | 73             | 80                            | 60                    | LS-2       | T545448           | 15655                                       | 15730                      | 13680 | 12785 |
| T445567      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT    | AG20.00 |                | 23.5       | 53            | 24.4                      | 161.3                      | 73             | 80                            | 60                    | LS-2       | T55098            | 13890                                       | 13965                      | 12145 | 11355 |
| T445566      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT    | AG24.00 |                | 27.7       | 52.9          | 24.3                      | 161.5                      | 73             | 80                            | 60                    | LS-2       | T55099            | 15210                                       | 15190                      | 13205 | 12345 |
| T445640      | 710/45-26.5 | 173A8 (180A2) | 24         | SF              | TT    | AG24.00 |                | 27.6       | 53            | 24.3                      | 162                        | 87             | 87                            | 60                    | LS-2       | T55099            | 17635                                       | 17625                      | 15335 | 14330 |
| T445801      | 710/55-26.5 | 179A8 (186A2) | 24         | SF              | TT    | AG24.00 | AG22.00        | 27.4       | 59.2          | 27.1                      | 179                        | 87             | 87                            | 62                    | LS-2       | T55102            | 20945                                       | 21020                      | 18285 | 17085 |
| T445602      | 750/55-26.5 | 182A8 (189A2) | 24         | SF              | TT    | AG24.00 |                | 29.7       | 58.1          | 26.5                      | 177.1                      | 87             | 87                            | 62                    | LS-2       | T55102            | 23370                                       | 23050                      | 20050 | 18740 |
| T445594      | 800/40-26.5 | 170A8 (177A2) | 20         | SF              | TT    | AG28.00 |                | 31.4       | 52.9          | 24.4                      | 161.3                      | 73             | 80                            | 60                    | LS-2       | T545312           | 16095                                       | 16270                      | 14155 | 13230 |
| T445612      | 710/55-28.5 | 180A8 (187A2) | 24         | SF              | TT    | AG24.00 |                | 28         | 59.6          | 27.3                      | 181.8                      | 87             | 87                            | 62                    | LS-2       | T545543           | 21495                                       | 21695                      | 18870 | 17635 |
| T445581      | 780/50-28.5 | 182A8 (190A2) | 24         | SF              | TT    | AG26.00 |                | 30.8       | 59.6          | 27.2                      | 181.5                      | 87             | 87                            | 62                    | LS-2       | T545543           | 23370                                       | 23050                      | 20050 | 18740 |

# NOKIAN TYRES FOREST KING TRS 2+

## TRACTION TIRE FOR 6WD HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip
- Special tread design with extra wing bars give excellent support, traction and protection in chain and wheel track use
- Strong 24PR diagonal structure with steel fortification gives excellent puncture protection and impressive stability



### AVAILABLE SIZES

- 600/65-34 - T445714
- 710/70-34 - T445716
- 710/55-34 - T445715

# NOKIAN TYRES FOREST KING TRS 2+

## ALL SIZES

| Product code | Size      | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt), lb | Load capacity for road, lb |       |       |       |       |
|--------------|-----------|---------------|------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|-------|-------|-------|-------|
|              |           |               |            |                 |       |       |                |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 | Speed (mph)                |       |       |       |       |
|              |           |               |            |                 |       |       |                |            |               |                           |                            |                |                               |                       |            |                   |   | 5                          | 5     | 12    | 17.5  | 25    |
| T445714      | 600/65-34 | 169A8 (176A2) | 24         | SF              | TT    | DW20B |                | 24.2       | 64.5          | 29.3                      | 195.4                      | 58             | 58                            | 63                    | LS-2       | T55394            | 15655                                       | 19180                      | 15730 | 13680 | 12785 | 11640 |
| T445715      | 710/55-34 | 173A8 (180A2) | 24         | SF              | TT    | DW24B | DW23B          | 28.1       | 64.3          | 29.1                      | 195.2                      | 58             | 58                            | 63                    | LS-2       | T55394            | 17635                                       | 21495                      | 17625 | 15335 | 14330 | 13040 |
| T445716      | 710/70-34 | 181A8 (188A2) | 24         | SF              | TT    | DW23B | DW24B, DW25B   | 29.3       | 72.2          | 32.3                      | 218.7                      | 58             | 58                            | 67                    | LS-2       | T55892            | 22045                                       | 27280                      | 22375 | 19465 | 18190 | 16555 |


# NOKIAN TYRES FOREST KING TRS L-2

## RELIABLE GRIP AND TRACTION

- Wide and high pattern lugs for good mobility and operating comfort
- Optimised lug angle and sharp tire shoulders providing excellent lateral grip
- Steel protection against punctures



2026-05-24



## AVAILABLE SIZES

- 650/60-26.5 - T445395

# NOKIAN TYRES FOREST KING TRS L-2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt, lb) | Load capacity for road, lb |       |       |
|--------------|-------------|---------------|------------|-----------------|-------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|-------|-------|
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 | Speed (mph)                |       |       |
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | 5   | 12                         | 17.5  | 25    |
| T445395      | 650/60-26.5 | 172A8 (179A2) | 20         | SF              | TT    | AG20.00 | 25.8       | 58.2          | 26.6                      | 175.9                      | 73             | 80                            | 63                    | L-2        | T55102            | 17085                                       | 17085                      | 14860 | 13890 |

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King ELS L-2 are applicable to Nordman Forest ELS L-2, making it a perfect option as a replacement tire.
- The design of the tire provides good performance in track and chain use.



## AVAILABLE SIZES

- 600/50-22.5 - T445623

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt), lb | Load capacity for road, lb |      |      |
|--------------|-------------|---------------|------------|-----------------|-------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|------|------|
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 | Speed (mph)                |      |      |
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | 5   | 12                         | 17.5 | 25   |
| T445623      | 600/50-22.5 | 149A8 (156A2) | 16         | SF              | TT    | AG20.00 | 23.9       | 45.8          | 21.4                      | 139.5                      | 46             | 58                            | 40                    | LS-2       | T55089            | 8820  | 8820                       | 7670 | 7165 |


# NOKIAN TYRES NORDMAN FOREST F

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The design of the tire provides good performance in track and chain use.



2026-05-24



## AVAILABLE SIZES

- 710/40-22.5 - T445625
- 710/40-24.5 - T445599
- 600/55-26.5 - T445598
- 710/45-26.5 - T445565
- 750/55-26.5 - T445597

# NOKIAN TYRES NORDMAN FOREST F


## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt, lb) |       |       |       |
|--------------|-------------|---------------|------------|-----------------|-------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|-------|-------|-------|
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 |       |       |       |
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                       |            |                   | 5   | 12    | 17.5  | 25    |
| T445625      | 710/40-22.5 | 151A8 (158A2) | 16         | SF              | TT    | AG24.00 | 27.6       | 45.8          | 21.2                      | 139.5                      | 46             | 58                            | 35                    | LS-2       | T55092            | 9370  | 9360  | 8135  | 7605  |
| T445599      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT    | AG24.00 | 27.8       | 48.1          | 22.6                      | 146.8                      | 73             | 80                            | 37                    | LS-2       | T545448           | 13230                                       | 13215 | 11495 | 10750 |
| T445598      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT    | AG20.00 | 24.2       | 52.7          | 24.6                      | 160                        | 73             | 80                            | 40                    | LS-2       | T55098            | 13890                                       | 13965 | 12145 | 11355 |
| T445565      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT    | AG24.00 | 28         | 53            | 24.5                      | 159.3                      | 73             | 80                            | 38                    | LS-2       | T55099            | 15210                                       | 15190 | 13205 | 12345 |
| T445597      | 750/55-26.5 | 177A8 (184A2) | 20         | SF              | TT    | AG24.00 | 30         | 58.1          | 26.8                      | 175.9                      | 73             | 80                            | 40                    | LS-2       | T55102            | 19840                                       | 19800 | 17220 | 16095 |

# NOKIAN TYRES NORDMAN FOREST TRS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King TRS L-2 are applicable to Nordman Forest TRS L-2, making it a perfect option as a replacement tire.
- Good terrain mobility due to aggressive tread design with high tread depth.



## AVAILABLE SIZES

- 600/50-22.5 - T445622
- 710/40-22.5 - T445624
- 600/55-26.5 - T445527
- 710/45-26.5 - T445541
- 750/55-26.5 - T445528
- 600/65-34 - T445475
- 700/55-34 - T445476
- 700/70-34 - T445596



# NOKIAN TYRES NORDMAN FOREST TRS L-2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt, lb) | Load capacity for road, lb |       |       |
|--------------|-------------|---------------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|-------|-------|
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)                                 | Speed (mph)                |       |       |
|              |             |               |            |                 |       |         |                |            |               |                           |                            |                |                               |                       |            |                   | 5   | 12                         | 17.5  | 25    |
| T445622      | 600/50-22.5 | 149A8 (156A2) | 16         | SF              | TT    | AG20.00 |                | 23.8       | 46            | 21.5                      | 139.5                      | 46             | 58                            | 53                    | LS-2       | T55089            | 8820  | 8820                       | 7670  | 7165  |
| T445624      | 710/40-22.5 | 151A8 (158A2) | 16         | SF              | TT    | AG24.00 |                | 27.8       | 46            | 21.2                      | 139.3                      | 46             | 58                            | 53                    | LS-2       | T55092            | 9370  | 9360                       | 8135  | 7605  |
| T445527      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT    | AG20.00 |                | 24.1       | 53            | 24.3                      | 160                        | 73             | 80                            | 60                    | LS-2       | T55098            | 13890                                       | 13965                      | 12145 | 11355 |
| T445541      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT    | AG24.00 |                | 28         | 53            | 23.9                      | 160.5                      | 73             | 80                            | 60                    | LS-2       | T55099            | 15210                                       | 15190                      | 13205 | 12345 |
| T445528      | 750/55-26.5 | 177A8 (184A2) | 20         | SF              | TT    | AG24.00 |                | 29.6       | 58.3          | 26.5                      | 175.6                      | 73             | 80                            | 63                    | LS-2       | T55102            | 19840                                       | 19800                      | 17220 | 16095 |
| T445475      | 600/65-34   | 163A8 (170A2) | 20         | SF              | TT    | DW20B   |                | 24.2       | 64.7          | 29.7                      | 195.4                      | 46             | 52                            | 64                    | LS-2       | T55394            | 13230                                       | 13215                      | 11495 | 10750 |
| T445476      | 700/55-34   | 166A8 (173A2) | 20         | SF              | TT    | DW24B   | DW23B          | 27.9       | 64.3          | 29.6                      | 194.4                      | 46             | 52                            | 64                    | LS-2       | T55394            | 14330                                       | 14375                      | 12500 | 11685 |
| T445596      | 700/70-34   | 173A8 (180A2) | 20         | SF              | TT    | DW20B   | DW23B, DW24B   | 28.5       | 72.8          | 33.1                      | 218.2                      | 46             | 52                            | 67                    | LS-2       | T55892            | 17635                                       | 17625                      | 15335 | 14330 |

# NOKIAN TYRES FOREST KING TRS LS-2

A FORESTRY AND EARTHMOVING MACHINE TRACTION TIRE WITH A STRONG TRACTION BAR AND EXCELLENT GRIP. WELLCLEANING, OPEN-CENTRE TREAD DESIGN. DURABLE SPECIAL RUBBER COMPOUND AND EFFICIENT STEEL FORTIFICATION

- Tires for log skidders, wide tread with high traction lugs
- Special cut and crack resistant compound
- Steel fortification against punctures



## AVAILABLE SIZES

- 28L-26 - T445516



# NOKIAN TYRES FOREST KING TRS LS-2


## ALL SIZES

| Product code | Size   | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim   | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, lb | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, lb |    |    |      |    |       |       |       |       |
|--------------|--------|---------------|------------|-----------------|-------|-------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|--|----|----|------|----|-------|-------|-------|-------|
|              |        |               |            |                 |       |       |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)   | Speed (mph)  |    |    |      |    |       |       |       |       |
| T445516      | 28L-26 | 173A6 (185A2) | 26         | SF              | TL    | DW25B | 29.2       | 64.6          | 29.4                      | 194.7                      | 49             | 58                            | 67                    | LS-2       | T55101            | 20285   | 5  | 10 | 15 | 17.5 | 25 | 17195 | 15765 | 14330 | 12895 |

# NOKIAN TYRES LOGGER KING LS-2

## FORESTRY TIRE FOR FULL-TREE MACHINES, SUCH AS SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.



## AVAILABLE SIZES

- 23.1-26 - T445616
- 24.5-32 - T445614
- 28L-26 - T445615
- 30.5L-32 - T445621

# NOKIAN TYRES LOGGER KING LS-2


## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim   | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, lb | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, lb |       |       |       |
|--------------|----------|---------------|------------|-----------------|-------|-------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|--|-------|-------|-------|
|              |          |               |            |                 |       |       |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)   | Speed (mph)  |       |       |       |
|              |          |               |            |                 |       |       |            |               |                           |                            |                |                               |                       |            |                   | 5   | 10   | 15    | 17.5  | 25    |
| T445616      | 23.1-26  | 160A6 (156A8) | 16         | SF              | TL    | DW20B | 23.8       | 63.9          | 29.5                      | 192.2                      | 41             | 41                            | 68                    | LS-2       | T55102            | 13890   | 11905  | 10915 | 9920  | 8930  |
| T445615      | 28L-26   | 165A6 (161A8) | 20         | SF              | TL    | DW25B | 28.3       | 64.8          | 29.7                      | 194.7                      | 41             | 41                            | 73                    | LS-2       | T55101            | 15985   | 13670  | 12565 | 11355 | 10250 |
| T445614      | 24.5-32  | 169A6 (167A8) | 20         | SF              | TL    | DH21  | 25.1       | 72            | 33.3                      | 217.2                      | 41             | 45                            | 73                    | LS-2       | T55393            | 18080   | 15430  | 14220 | 12895 | 11575 |
| T445621      | 30.5L-32 | 170A6 (167A8) | 20         | SF              | TL    | DH27  | 30.4       | 72.6          | 33.6                      | 218.2                      | 35             | 35                            | 84                    | LS-2       | T55388            | 18520   | 15875  | 14550 | 13230 | 11905 |

# NOKIAN TYRES LOGGER KING LS-2 EXTREME

## TIRE FOR FULL-TREE MACHINES, I. A. SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.



### AVAILABLE SIZES

- 30.5L-32 - T445613
- 35.5L-32 - T445620

# NOKIAN TYRES LOGGER KING LS-2 EXTREME

## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim  | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, lb | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, lb |       |       |       |       |
|--------------|----------|---------------|------------|-----------------|-------|------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|---|--|-------|-------|-------|-------|
|              |          |               |            |                 |       |      |            |               |                           |                            |                |                               |                       |            |                   | Speed (mph)   | Speed (mph)  |       |       |       |       |
|              |          |               |            |                 |       |      |            |               |                           |                            |                |                               |                       |            |                   | 5   | 5  | 10    | 15    | 17.5  | 25    |
| T445613      | 30.5L-32 | 176A6 (172A8) | 26         | SF              | TL    | DH27 | 30.6       | 72.5          | 33.4                      | 218.4                      | 45             | 45                            | 84                    | LS-2       | T55388            | 22045   | 18850  |       | 17305 | 15655 | 14110 |
| T445620      | 35.5L-32 | 183A6 (180A8) | 26         | SF              | TL    | DH31 | 36         | 79.1          | 36.2                      | 238.7                      | 41             | 41                            | 84                    | LS-2       | T55879            | 27005   | 23150  | 21275 | 19290 | 17305 |       |

# NOKIAN TYRES FOREST KING T

FOR TRACTORS AND SKIDDERS USED IN FORESTRY, FOREST CLEARANCE OR ROAD CONSTRUCTION

- Strong and wide lugs enable good traction and tolerate high tractive forces.
- Steel fortifications together with strong diagonal construction give excellent puncture resistance.
- Stiff diagonal construction enables better stability.



## AVAILABLE SIZES

- 500/70-28 - T445335
- 650/75-38 - T445313
- 540/70-30 - T445314



# NOKIAN TYRES FOREST KING T

## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for forestry service (lt, lb) | Load capacity for road, lb |       |       |       |       |
|--------------|-----------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|---|----------------------------|-------|-------|-------|-------|
|              |           |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                       |            |                   |   | Speed (mph)                |       |       |       |       |
|              |           |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                       |            |                   |   | 5                          | 12    | 17.5  | 25    | 30    |
| T445335      | 500/70-28 | 146A8        | SF              | TT    | DW16L |                | 20.1       | 55.2          | 25.6                      | 167                        | 675 | 35             | 41                            | 62                    | LS-2       | T545229           | 8045  | 9920                       | 8135  | 7075  | 6615  | 6020  |
| T445314      | 540/70-30 | 152A8 (149B) | SF              | TT    | DW16L | DW18B          | 21         | 59.8          | 27.8                      | 177.4                      | 725 | 35             | 41                            | 63                    | LS-2       | T55371            | 9645  | 11740                      | 9625  | 8380  | 7825  | 7120  |
| T445313      | 650/75-38 | 168A8 (165B) | SF              | TT    | DW20B | DW23B          | 25.5       | 77            | 35.4                      | 231.9                      | 925 | 35             | 41                            | 67                    | LS-2       | T55893            | 15210                                       | 18520                      | 15190 | 13205 | 12345 | 11235 |

# NOKIAN TYRES TR FOREST 2

FOR SMALL AND MEDIUM SIZE TRACTORS USED IN VERSATILE TASKS F.EX IN FORESTRY

- Cut and crack resistant compound together with strong cross-ply construction to tolerate rough conditions.
- Stiff diagonal construction enables great stability.
- Tractive tread design with good self-cleaning properties.



## AVAILABLE SIZES

- 320/85-24 - T445784
- 340/85-24 - T445780
- 380/85-24 - T445778
- 340/85-28 - T445785
- 380/85-28 - T445790
- 420/85-28 - T445789
- 420/85-30 - T445786
- 420/85-34 - T445779
- 460/85-34 - T445777
- 420/85-38 - T445793
- 460/85-38 - T445788
- 520/85-38 - T445787

# NOKIAN TYRES TR FOREST 2

## ALL SIZES

| Product code | Size      | Equivalent size | LI/SS        | Ply rating | TL/TT | Rim   | Permitted rims     | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Load capacity for tractor, lb |       |       |       |       |       |
|--------------|-----------|-----------------|--------------|------------|-------|-------|--------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------------------|-------|-------|-------|-------|-------|
|              |           |                 |              |            |       |       |                    |            |               |                           |                            |     |                |                               |                       |            | Speed (mph)                   |       |       |       |       |       |
|              |           |                 |              |            |       |       |                    |            |               |                           |                            |     |                |                               |                       |            | 15                            | 17.5  | 22.5  | 25    | 27.5  | 30    |
| T445784      | 320/85-24 | 12.4-24         | 130A8 (127B) | 16         | TL    | DW11  | DW10               | 12.8       | 46.2          | 20.8                      | 139.1                      | 550 | 41             | 41                            | 45                    | R-1        | 4650                          | 4485  | 4310  | 4190  | 4025  | 3815  |
| T445780      | 340/85-24 | 13.6-24         | 134A8 (131B) | 16         | TL    | DW12  | DW11               | 13.7       | 48.1          | 21.7                      | 145                        | 575 | 41             | 41                            | 48                    | R-1        | 5190                          | 5005  | 4815  | 4675  | 4485  | 4255  |
| T445778      | 380/85-24 | 14.9-24         | 140A8 (137B) | 16         | TL    | DW13  | DW13L, DW11, DW12  | 15.4       | 49.8          | 22.3                      | 150.1                      | 600 | 41             | 41                            | 53                    | R-1        | 6120                          | 5895  | 5675  | 5510  | 5290  | 5015  |
| T445785      | 340/85-28 | 13.6-28         | 136A8 (133B) | 16         | TL    | DW12  | DW11               | 13.9       | 51.5          | 23.3                      | 155.4                      | 625 | 41             | 41                            | 53                    | R-1        | 5480                          | 5280  | 5080  | 4940  | 4740  | 4495  |
| T445790      | 380/85-28 | 14.9-28         | 142A8 (139B) | 16         | TL    | DW13  | DW13L, DW11, DW12  | 15.4       | 53.5          | 24.1                      | 161.7                      | 650 | 41             | 41                            | 53                    | R-1        | 6480                          | 6250  | 6020  | 5840  | 5610  | 5315  |
| T445789      | 420/85-28 | 16.9-28         | 148A8 (145B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 17.1       | 56            | 25.2                      | 169.7                      | 675 | 41             | 41                            | 58                    | R-1        | 7705                          | 7430  | 7155  | 6945  | 6670  | 6315  |
| T445786      | 420/85-30 | 16.9-30         | 149A8 (146B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 16.9       | 58.7          | 26.3                      | 176.5                      | 700 | 41             | 41                            | 59                    | R-1        | 7960                          | 7670  | 7385  | 7165  | 6880  | 6525  |
| T445779      | 420/85-34 | 16.9-34         | 151A8 (148B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 16.9       | 62.1          | 27.8                      | 186.8                      | 750 | 41             | 41                            | 59                    | R-1        | 8445                          | 8135  | 7835  | 7605  | 7295  | 6925  |
| T445777      | 460/85-34 | 18.4-34         | 155A8 (152B) | 16         | TL    | DW16L | DW15L              | 18.3       | 64.5          | 29.8                      | 194.9                      | 775 | 41             | 41                            | 63                    | R-1        | 9480                          | 9140  | 8795  | 8545  | 8200  | 7770  |
| T445793      | 420/85-38 | 16.9-38         | 152A8 (149B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 17         | 65.9          | 29.9                      | 200                        | 800 | 41             | 41                            | 63                    | R-1        | 8685                          | 8380  | 8060  | 7825  | 7520  | 7120  |
| T445788      | 460/85-38 | 18.4-38         | 157A8 (154B) | 16         | TL    | DW16L | DW15L              | 18.5       | 68.5          | 30.9                      | 207.4                      | 825 | 41             | 41                            | 67                    | R-1        | 10095                         | 9735  | 9370  | 9095  | 8730  | 8280  |
| T445787      | 520/85-38 | 20.8-38         | 164A8 (160B) | 16         | TL    | DW18L | DW16L              | 21.1       | 72.1          | 32.2                      | 217.5                      | 875 | 41             | 41                            | 68                    | R-1        | 12235                         | 11795 | 11355 | 11025 | 10580 | 10030 |

# NOKIAN TYRES TR MULTIPLUS

FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.



## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415



# NOKIAN TYRES TR MULTIPLUS

## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims                      | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for tractor, lb |       |       |       |       |      |
|--------------|-----------|--------------|-----------------|-------|-------|-------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|-------------------------------|-------|-------|-------|-------|------|
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                       |            |                   | Speed (mph)                   |       |       |       |       |      |
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                       |            |                   | 15                            | 17.5  | 22.5  | 25    | 27.5  | 30   |
| T445410      | 500/65R24 | 142A8 (139B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 19.3       | 48.9          | 22.6                      | 147                        | 600 | 35             | 46                            | 60                    | R-1        |                   | 6480                          | 6250  | 6020  | 5840  | 5610  | 5370 |
| T445411      | 500/65R28 | 144A8 (141B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, W13        | 19.3       | 52.8          | 24.5                      | 159.6                      | 650 | 35             | 46                            | 60                    | R-1        | T55097            | 6855                          | 6605  | 6360  | 6175  | 5930  | 5620 |
| T445412      | 540/65R28 | 149A8 (146B) | SB              | TL    | DW16  | W15L, W16L, DW18L, W18L, DW16L      | 20.6       | 55.5          | 25.7                      | 167.5                      | 675 | 35             | 46                            | 64                    | R-1        | T545229           | 7960                          | 7670  | 7385  | 7165  | 6880  | 6520 |
| T445413      | 600/65R34 | 157A8 (154B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 23         | 64.6          | 29.5                      | 194.1                      | 775 | 35             | 46                            | 66                    | R-1        | T55395            | 10095                         | 9735  | 9370  | 9095  | 8730  | 8280 |
| T445414      | 600/65R38 | 159A8 (156B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 23         | 68.6          | 31.9                      | 208.3                      | 825 | 35             | 46                            | 66                    | R-1        |                   | 10705                         | 10320 | 9930  | 9645  | 9260  | 8770 |
| T445415      | 650/65R38 | 164A8 (160B) | SB              | TL    | DW20B | DW18                                | 25.2       | 71.2          | 33                        | 215.9                      | 875 | 35             | 46                            | 67                    | R-1        | T545322           | 11925                         | 11495 | 11065 | 10750 | 10320 | 9780 |

# NOKIAN TYRES TRACTOR KING

## VERSATILE HEAVY-DUTY RADIAL TRACTION TIRE FOR DEMANDING OFF-ROAD APPLICATIONS AND HIGH-SPEED ROAD TRANSITS

- Strong steel belted radial carcass strengthened with forest tread compound. 400 kPa max pressure enabling high load carrying capacity and stability.
- Wide tread and radically increased amount of tractive edges for supreme traction.
- Innovative tread design with even ground contact resulting in comfortable drive. Durability up to 65 km/h speeds.



### AVAILABLE SIZES

- 480/65R28 - T445806
- 500/65R28 - T445673
- 540/65R28 - T445674
- 600/60R28 - T445675
- 600/65R28 - T445851
- 540/65R30 - T445676
- 540/70R30 - T445677
- 600/70R30 - T445678
- 620/75R30 - T445679
- 600/65R34 - T445680
- 600/70R34 - T445681
- 600/65R38 - T445682
- 650/65R38 - T445683
- 650/75R38 - T445684
- 650/85R38 - T445685
- 710/70R38 - T445741
- 800/70R38 - T445852
- 650/65R42 - T445740
- 710/70R42 - T445686
- 710/75R42 - T445687

# NOKIAN TYRES TRACTOR KING

## ALL SIZES

| Product code | Size      | LI/SS | Reinforced code | TL/TT | Rim   | Permitted rims      | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI  | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Load capacity for tractor, lb |       |       |       |       |       |
|--------------|-----------|-------|-----------------|-------|-------|---------------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|-----------------------|------------|-------------------------------|-------|-------|-------|-------|-------|
|              |           |       |                 |       |       |                     |            |               |                           |                            |      |                |                               |                       |            | Speed (mph)                   |       |       |       |       |       |
|              |           |       |                 |       |       |                     |            |               |                           |                            |      |                |                               |                       |            | 25                            | 27.5  | 30    | 35    | 37.5  | 40    |
| T445806      | 480/65R28 | 148D  | SB              | TL    | DW15L | DW16L, DW14L, DW18L | 19.2       | 53.5          | 24.8                      | 161.5                      | 650  | 46             | 58                            | 60                    | R-1W       | 7605                          | 7430  | 7295  | 7155  | 7045  | 6945  |
| T445673      | 500/65R28 | 150D  | SB              | TL    | DW16L | DW15L, DW18L        | 19.4       | 53.5          | 24.8                      | 161.5                      | 650  | 46             | 58                            | 60                    | R-1W       | 8090                          | 7905  | 7760  | 7605  | 7495  | 7385  |
| T445674      | 540/65R28 | 154D  | SB              | TL    | DW18L | DW16L               | 21.3       | 55.5          | 25.6                      | 167.2                      | 675  | 46             | 58                            | 60                    | R-1W       | 9050                          | 8850  | 8685  | 8520  | 8390  | 8265  |
| T445675      | 600/60R28 | 157D  | SB              | TL    | DW18L | DW20B               | 23         | 56            | 24.3                      | 167.5                      | 675  | 46             | 58                            | 62                    | R-1W       | 9955                          | 9735  | 9545  | 9370  | 9225  | 9095  |
| T445851      | 600/65R28 | 160D  | SB              | TL    | DW20B | DW18L               | 23.9       | 59.1          | 27.2                      | 178.3                      | 700  | 46             | 58                            | 63                    | R-1W       | 10870                         | 10615 | 10415 | 10220 | 10075 | 9920  |
| T445676      | 540/65R30 | 155D  | SB              | TL    | DW18L | DW16L               | 21.1       | 57.6          | 26.7                      | 174.3                      | 700  | 46             | 58                            | 62                    | R-1W       | 9360                          | 9140  | 8975  | 8795  | 8675  | 8545  |
| T445677      | 540/70R30 | 159D  | SB              | TL    | DW18L | DW16L               | 21.4       | 59.3          | 27.3                      | 178.7                      | 725  | 46             | 58                            | 63                    | R-1W       | 10560                         | 10320 | 10130 | 9930  | 9790  | 9645  |
| T445678      | 600/70R30 | 165D  | SB              | TL    | DW18L | DW20B               | 22.8       | 63.1          | 28.7                      | 190                        | 750  | 46             | 58                            | 64                    | R-1W       | 12435                         | 12145 | 11925 | 11695 | 11520 | 11355 |
| T445679      | 620/75R30 | 169D  | SB              | TL    | DW20B |                     | 24.6       | 66.5          | 30.3                      | 200.7                      | 800  | 46             | 58                            | 66                    | R-1        | 14000                         | 13680 | 13425 | 13175 | 12975 | 12785 |
| T445680      | 600/65R34 | 163D  | SB              | TL    | DW18L | DW20B               | 22.9       | 64.6          | 29.7                      | 195.3                      | 775  | 46             | 58                            | 66                    | R-1W       | 11775                         | 11495 | 11290 | 11065 | 10915 | 10750 |
| T445681      | 600/70R34 | 167D  | SB              | TL    | DW18L | DW20B               | 23         | 67            | 30.5                      | 202.3                      | 800  | 46             | 58                            | 66                    | R-1W       | 13160                         | 12855 | 12620 | 12380 | 12190 | 12015 |
| T445682      | 600/65R38 | 165D  | SB              | TL    | DW18L | DW20B               | 22.8       | 68.7          | 31.7                      | 208                        | 825  | 46             | 58                            | 67                    | R-1W       | 12435                         | 12145 | 11925 | 11695 | 11520 | 11355 |
| T445683      | 650/65R38 | 169D  | SB              | TL    | DW20B |                     | 24.9       | 71.3          | 32.7                      | 215.7                      | 875  | 46             | 58                            | 67                    | R-1W       | 14000                         | 13680 | 13425 | 13175 | 12975 | 12785 |
| T445684      | 650/75R38 | 175D  | SB              | TL    | DW20B | DW23B, DW21B        | 25.4       | 76.5          | 34.6                      | 232                        | 925  | 46             | 58                            | 69                    | R-1W       | 16655                         | 16280 | 15975 | 15665 | 15445 | 15210 |
| T445685      | 650/85R38 | 178D  | SB              | TL    | DW20B | DW23B, DW21B        | 25.3       | 81.3          | 37                        | 246.9                      | 975  | 46             | 58                            | 69                    | R-1        | 18110                         | 17690 | 17360 | 17030 | 16790 | 16535 |
| T445741      | 710/70R38 | 177D  | SB              | TL    | DW23B | DW25B               | 28.2       | 77            | 35                        | 233.1                      | 925  | 46             | 58                            | 69                    | R-1W       | 17625                         | 17220 | 16900 | 16580 | 16335 | 16095 |
| T445852      | 800/70R38 | 183D  | SB              | TL    | DW27B | DW25B               | 32.5       | 82            | 37.4                      | 248                        | 975  | 46             | 58                            | 71                    | R-1        | 21120                         | 20645 | 20260 | 19875 | 19575 | 19290 |
| T445740      | 650/65R42 | 170D  | SB              | TL    | DW20B | DW21B, DW23B        | 24.9       | 75.3          | 34.7                      | 228.3                      | 925  | 46             | 58                            | 69                    | R-1W       | 14485                         | 14155 | 13890 | 13625 | 13425 | 13230 |
| T445686      | 710/70R42 | 179D  | SB              | TL    | DW23B | DW25B               | 28.2       | 81.1          | 37.1                      | 245.5                      | 975  | 46             | 58                            | 71                    | R-1W       | 18705                         | 18285 | 17945 | 17605 | 17340 | 17085 |
| T445687      | 710/75R42 | 181D  | SB              | TL    | DW23B | DW25B               | 28.2       | 83.9          | 38.3                      | 254.3                      | 1000 | 46             | 58                            | 72                    | R-1W       | 19920                         | 19465 | 19105 | 18740 | 18465 | 18190 |

# AGRICULTURAL AND CONTRACTING TIRES

## TRACTOR



34  
Nokian Tyres  
TR Multiplus



36  
Nokian Tyres  
Ground King



38  
Nokian Tyres  
Hakkapeliitta  
TRI



41  
Nokian Tyres  
Soil King VF



43  
Nokian Tyres  
TRI 2



46  
Nokian Tyres  
TRI Steel

## TRAILER



48  
Nokian Tyres  
Country King



50  
Nokian Tyres  
Country King  
G2



52  
Nokian Tyres  
CT



54  
Nokian Tyres  
ELS



56  
Nokian Tyres  
Float King VF

## WHEEL LOADER




38  
Nokian Tyres  
Hakkapeliitta  
TRI

# NOKIAN TYRES TR MULTIPLUS

FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.



## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415



# NOKIAN TYRES TR MULTIPLUS


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims                      | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Load capacity for tractor, lb |       |       |       |       |      |
|--------------|-----------|--------------|-----------------|-------|-------|-------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|-------------------------------|-------|-------|-------|-------|------|
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                       |            |                   | Speed (mph)                   |       |       |       |       |      |
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                       |            |                   | 15                            | 17.5  | 22.5  | 25    | 27.5  | 30   |
| T445410      | 500/65R24 | 142A8 (139B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 19.3       | 48.9          | 22.6                      | 147                        | 600 | 35             | 46                            | 60                    | R-1        |                   | 6480                          | 6250  | 6020  | 5840  | 5610  | 5370 |
| T445411      | 500/65R28 | 144A8 (141B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, W13        | 19.3       | 52.8          | 24.5                      | 159.6                      | 650 | 35             | 46                            | 60                    | R-1        | T55097            | 6855                          | 6605  | 6360  | 6175  | 5930  | 5620 |
| T445412      | 540/65R28 | 149A8 (146B) | SB              | TL    | DW16  | W15L, W16L, DW18L, W18L, DW16L      | 20.6       | 55.5          | 25.7                      | 167.5                      | 675 | 35             | 46                            | 64                    | R-1        | T545229           | 7960                          | 7670  | 7385  | 7165  | 6880  | 6520 |
| T445413      | 600/65R34 | 157A8 (154B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 23         | 64.6          | 29.5                      | 194.1                      | 775 | 35             | 46                            | 66                    | R-1        | T55395            | 10095                         | 9735  | 9370  | 9095  | 8730  | 8280 |
| T445414      | 600/65R38 | 159A8 (156B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 23         | 68.6          | 31.9                      | 208.3                      | 825 | 35             | 46                            | 66                    | R-1        |                   | 10705                         | 10320 | 9930  | 9645  | 9260  | 8770 |
| T445415      | 650/65R38 | 164A8 (160B) | SB              | TL    | DW20B | DW18                                | 25.2       | 71.2          | 33                        | 215.9                      | 875 | 35             | 46                            | 67                    | R-1        | T545322           | 11925                         | 11495 | 11065 | 10750 | 10320 | 9780 |

# NOKIAN TYRES GROUND KING

## CROSSOVER TIRE FOR MIXED AGRICULTURAL WORK

- Advanced alternative for the lug pattern traction tire that combines the features and benefits of two pattern types.
- Solid performance on fields and roads with traction, multi-directional grip and continuous contact.
- Supports the versatile use of implements with stability, high strength and load capacity.



## AVAILABLE SIZES

- 420/70R28 - T445733
- 480/65R28 - T445764
- 480/70R28 - T445735
- 540/65R28 - T445737
- 600/65R28 - T445762
- 600/70R28 - T445763
- 540/65R30 - T445728
- 600/70R30 - T445726
- 600/65R34 - T445729
- 600/70R34 - T445730
- 650/65R34 - T445731
- 520/70R38 - T445732
- 580/70R38 - T445734
- 600/65R38 - T445765
- 650/65R38 - T445738
- 650/85R38 - T445743
- 710/70R38 - T445744
- 650/65R42 - T445727
- 710/70R42 - T445725
- 710/75R42 - T445722

# NOKIAN TYRES GROUND KING

## ALL SIZES

| Product code | Size      | LI/SS       | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI  | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | M+S | Load capacity for tractor, lb |       |       |       |       |       |
|--------------|-----------|-------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|-----------------------|------------|-----|-------------------------------|-------|-------|-------|-------|-------|
|              |           |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                       |            |     | Speed (mph)                   |       |       |       |       |       |
|              |           |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                       |            |     | 27.5                          | 30    | 35    | 37.5  | 40    | 42.5  |
| T445733      | 420/70R28 | 144D (141E) | SB              | TL    | DW13  | DW14L, DW12    | 16.1       | 53.2          | 24.4                      | 161.5                      | 650  | 46             | 46                            | 58                    | R-1W       | Yes | 6605                          | 6480  | 6360  | 6260  | 6175  | 5620  |
| T445764      | 480/65R28 | 148D (145E) | SB              | TL    | DW15L | DW14L          | 18.7       | 53.1          | 24.3                      | 161.1                      | 650  | 46             | 46                            | 57                    | R-1W       | Yes | 7430                          | 7295  | 7155  | 7045  | 6945  | 6315  |
| T445735      | 480/70R28 | 151D (148E) | SB              | TL    | DW15L | DW16L, DW14L   | 18.5       | 55.5          | 25.3                      | 168.1                      | 675  | 46             | 46                            | 60                    | R-1W       | Yes | 8135                          | 7990  | 7835  | 7715  | 7605  | 6925  |
| T445737      | 540/65R28 | 154D (151E) | SB              | TL    | DW18L | DW16L          | 21.1       | 55.2          | 25.1                      | 167.1                      | 675  | 46             | 46                            | 63                    | R-1W       | Yes | 8850                          | 8685  | 8520  | 8390  | 8265  | 7530  |
| T445762      | 600/65R28 | 160D (156E) | SB              | TL    | DW20B | DW18L          | 23.6       | 59.3          | 26.9                      | 179.7                      | 700  | 46             | 46                            | 69                    | R-1W       | Yes | 10615                         | 10415 | 10220 | 10075 | 9920  | 9030  |
| T445763      | 600/70R28 | 164D (160E) | SB              | TL    | DW20B | DW18L          | 23.7       | 61.5          | 27.9                      | 187.2                      | 725  | 46             | 46                            | 69                    | R-1W       | Yes | 11795                         | 11575 | 11355 | 11190 | 11025 | 10030 |
| T445728      | 540/65R30 | 155D (152E) | SB              | TL    | DW18L | DW16L          | 21.1       | 58.1          | 26.7                      | 175.2                      | 700  | 46             | 46                            | 63                    | R-1W       | Yes | 9140                          | 8975  | 8795  | 8675  | 8545  | 7770  |
| T445726      | 600/70R30 | 165D (161E) | SB              | TL    | DW20B | DW18L          | 23.6       | 62.5          | 28.1                      | 189.8                      | 750  | 46             | 46                            | 69                    | R-1W       | Yes | 12145                         | 11925 | 11695 | 11520 | 11355 | 10330 |
| T445729      | 600/65R34 | 163D (159E) | SB              | TL    | DW20B | DW18L          | 23.6       | 64.7          | 29.6                      | 197.5                      | 775  | 46             | 46                            | 69                    | R-1W       | Yes | 11495                         | 11290 | 11065 | 10915 | 10750 | 9780  |
| T445730      | 600/70R34 | 167D (163E) | SB              | TL    | DW20B | DW18L          | 23.4       | 67            | 30.4                      | 203.5                      | 800  | 46             | 46                            | 69                    | R-1W       | Yes | 12855                         | 12620 | 12380 | 12190 | 12015 | 10935 |
| T445731      | 650/65R34 | 167D (164E) | SB              | TL    | DW20B |                | 24.9       | 66.9          | 30.3                      | 203.7                      | 825  | 46             | 46                            | 69                    | R-1W       | Yes | 12855                         | 12620 | 12380 | 12190 | 12015 | 10935 |
| T445732      | 520/70R38 | 160D (157E) | SB              | TL    | DW16L | DW18L, DW15L   | 20.3       | 69            | 31.6                      | 210.3                      | 825  | 46             | 46                            | 69                    | R-1W       | Yes | 10615                         | 10415 | 10220 | 10075 | 9920  | 9030  |
| T445734      | 580/70R38 | 166D (163E) | SB              | TL    | DW18L |                | 22.7       | 72            | 32.9                      | 219.4                      | 875  | 46             | 46                            | 71                    | R-1W       | Yes | 12500                         | 12270 | 12035 | 11860 | 11685 | 10635 |
| T445765      | 600/65R38 | 165D (161E) | SB              | TL    | DW20B | DW18L          | 23.7       | 68.7          | 31.4                      | 209.5                      | 825  | 46             | 46                            | 69                    | R-1W       | Yes | 12145                         | 11925 | 11695 | 11520 | 11355 | 10330 |
| T445738      | 650/65R38 | 169D (166E) | SB              | TL    | DW20B |                | 25         | 71.7          | 32.6                      | 218.1                      | 875  | 46             | 46                            | 74                    | R-1W       | Yes | 13680                         | 13425 | 13175 | 12975 | 12785 | 11640 |
| T445743      | 650/85R38 | 178D (175E) | SB              | TL    | DW20B | DW21B, DW23B   | 25.4       | 81.5          | 36.7                      | 246.9                      | 975  | 46             | 46                            | 79                    | R-1W       | Yes | 17690                         | 17360 | 17030 | 16790 | 16535 | 15045 |
| T445744      | 710/70R38 | 177D (174E) | SB              | TL    | DW23B | DW25B          | 27.8       | 76.9          | 34.8                      | 233.6                      | 925  | 46             | 46                            | 78                    | R-1W       | Yes | 17220                         | 16900 | 16580 | 16335 | 16095 | 14650 |
| T445727      | 650/65R42 | 170D (167E) | SB              | TL    | DW20B |                | 25         | 75.3          | 34.3                      | 228.8                      | 925  | 46             | 46                            | 74                    | R-1W       | Yes | 14155                         | 13890 | 13625 | 13425 | 13230 | 12035 |
| T445725      | 710/70R42 | 179D (175E) | SB              | TL    | DW23B |                | 27.8       | 81.1          | 36.7                      | 245.9                      | 975  | 46             | 46                            | 78                    | R-1W       | Yes | 18285                         | 17945 | 17605 | 17340 | 17085 | 15555 |
| T445722      | 710/75R42 | 181D (178E) | SB              | TL    | DW23B |                | 27.7       | 83.9          | 38                        | 255                        | 1000 | 46             | 46                            | 78                    | R-1W       | Yes | 19465                         | 19105 | 18740 | 18465 | 18190 | 16555 |


# NOKIAN TYRES HAKKAPELIITTA TRI

## A M+S BLOCK PATTERNED TIRE WITH SUPERIOR WINTER GRIP FOR YEAR- ROUND WORK IN BUILT ENVIRONMENTS

- Safety and effectivity with siped M+S block pattern and all-season grip compound.
- High level comfort due to low noise and vibration design.
- Use economy in year round use with long service life tread compound and energy efficiency.



2026-05-24



## AVAILABLE SIZES

- 250/75R16 - T845540
- 250/80R16 - T845541
- 340/80R18 - T445665
- 400/60R18 - T445667
- 400/70R18 - T445832
- 360/70R20 - T445756
- 360/80R20 - T445666
- 400/70R20 - T445636
- 300/80R24 - T445757
- 340/80R24 - T445753
- 360/80R24 - T445587
- 400/80R24 - T445582
- 420/65R24 - T445586
- 440/80R24 - T445634
- 460/70R24 - T445669
- 500/70R24 - T445671
- 540/70R24 - T445672
- 360/80R28 - T445752
- 400/80R28 - T445584
- 440/80R28 - T445563
- 540/65R28 - T445772
- 440/80R30 - T445758
- 480/80R30 - T445754
- 540/65R30 - T445609
- 540/65R30 - T445736
- 600/70R30 - T445848
- 440/80R34 - T445588
- 480/80R34 - T445583
- 600/70R34 - T445700
- 480/80R38 - T445585
- 540/80R38 - T445564
- 650/65R38 - T445773
- 650/65R42 - T445595
- 710/70R42 - T445847

# NOKIAN TYRES HAKKAPELIITTA TRI

## ALL SIZES FOR TRACTOR

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims               | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | M+S | Load capacity for constant load, lb |       |       |       |       |       |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-----|-------------------------------------|-------|-------|-------|-------|-------|
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                       |            |     | Speed (mph)                         |       |       |       |       |       |
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                       |            |     | 25                                  | 27.5  | 30    | 35    | 37.5  | 40    |
| T845540      | 250/75R16 |                 | 120G         |                 | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 10.2       | 30.8          | 14.3                      | 94.1                       | 370 | 65             | 65                            | 20                    | R-4        | Yes | 3680                                | 3585  | 3450  | 3360  | 3295  | 3195  |
| T845541      | 250/80R16 | 7.5R16          | 119G         |                 | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 10.8       | 32.2          | 14.8                      | 98.2                       | 390 | 65             | 65                            | 21                    | R-4        | Yes | 3935                                | 3825  | 3695  | 3595  | 3515  | 3415  |
| T445667      | 400/60R18 |                 | 148A8 (143D) | SB              | TL    | 13    |                              | 15.7       | 37.4          | 16.8                      | 113                        | 450 | 73             | 73                            | 33                    | R-4        | Yes | 6910                                | 6725  | 6495  | 6305  | 6185  | 6010  |
| T445756      | 360/70R20 |                 | 136A8 (131D) | SB              | TL    | W11   | 10, W10, 12, W12             | 13.5       | 40.5          | 18.3                      | 122.5                      | 475 | 46             | 46                            | 30                    | R-4        | Yes | 4950                                | 4815  | 4640  | 4520  | 4430  | 4300  |
| T445757      | 300/80R24 | 11.2R24         | 133A8 (128D) | SB              | TL    | DW10  | W9, W10, W11, DW11           | 11.9       | 42.4          | 19.4                      | 128.3                      | 525 | 46             | 46                            | 30                    | R-4        | Yes | 4565                                | 4440  | 4290  | 4165  | 4090  | 3970  |
| T445753      | 340/80R24 | 12.4R24         | 140A8 (135D) | SB              | TL    | DW11  | DW10, DW12                   | 13.1       | 44.8          | 20.4                      | 135.6                      | 550 | 46             | 46                            | 30                    | R-4        | Yes | 5525                                | 5380  | 5190  | 5050  | 4950  | 4805  |
| T445587      | 360/80R24 | 13.6R24         | 143A8 (138D) | SB              | TL    | DW11  | DW10, DW12, DW13             | 14.1       | 46.7          | 21.4                      | 141.7                      | 575 | 46             | 46                            | 30                    | R-4        | Yes | 6160                                | 5995  | 5785  | 5620  | 5525  | 5355  |
| T445582      | 400/80R24 | 14.9R24         | 149A8 (144D) | SB              | TL    | DW13  | DW12, DW14L                  | 15.7       | 49.1          | 22.3                      | 148.4                      | 600 | 46             | 46                            | 31                    | R-4        | Yes | 7100                                | 6910  | 6670  | 6480  | 6360  | 6175  |
| T445634      | 440/80R24 | 16.9R24         | 154A8 (149D) | SB              | TL    | DW14L | DW15L                        | 17.1       | 50.9          | 23                        | 154.4                      | 625 | 46             | 46                            | 33                    | R-4        | Yes | 8245                                | 8025  | 7740  | 7530  | 7385  | 7165  |
| T445752      | 360/80R28 | 13.6R28         | 146A8 (142D) | SB              | TL    | DW11  | DW12, DW13                   | 13.7       | 51.6          | 23.4                      | 157.4                      | 625 | 46             | 46                            | 30                    | R-4        | Yes | 6525                                | 6360  | 6130  | 5965  | 5840  | 5675  |
| T445584      | 400/80R28 | 14.9R28         | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L                  | 15.7       | 53.2          | 24.3                      | 161.5                      | 650 | 46             | 46                            | 31                    | R-4        | Yes | 7795                                | 7595  | 7320  | 7120  | 6980  | 6780  |
| T445563      | 440/80R28 | 16.9R28         | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 17.3       | 55.7          | 25.2                      | 168.7                      | 675 | 46             | 46                            | 33                    | R-4        | Yes | 9005                                | 8765  | 8455  | 8225  | 8060  | 7825  |
| T445772      | 540/65R28 |                 | 160A8 (155D) | SB              | TL    | DW18L | DW16L                        | 21.1       | 55            | 25                        | 167                        | 675 | 46             | 46                            | 35                    | R-4        | Yes | 9820                                | 9570  | 9225  | 8975  | 8795  | 8545  |
| T445758      | 440/80R30 | 16.9R30         | 157A8 (153D) | SB              | TL    | DW14L | DW15L, W16L                  | 17.1       | 57.3          | 25.9                      | 174.3                      | 700 | 46             | 46                            | 33                    | R-4        | Yes | 9260                                | 9015  | 8685  | 8455  | 8290  | 8045  |
| T445754      | 480/80R30 | 18.4R30         | 162A8 (157D) | SB              | TL    | DW15L | DW16L, DW18L                 | 18.3       | 60.5          | 27.2                      | 183.9                      | 725 | 46             | 46                            | 34                    | R-4        | Yes | 10460                               | 10185 | 9820  | 9545  | 9370  | 9095  |
| T445609      | 540/65R30 |                 | 161A8 (156D) | SB              | TL    | DW18L | DW16L                        | 20.9       | 57.6          | 26.2                      | 174.4                      | 700 | 46             | 46                            | 35                    | R-4        | Yes | 10140                               | 9875  | 9525  | 9260  | 9085  | 8820  |
| T445736      | 540/65R30 |                 | 171A8 (166D) | SB              | TL    | DW18L | DW16L                        | 21         | 57.5          | 26.3                      | 174.9                      | 700 | 65             | 65                            | 35                    | R-4        | Yes | 13435                               | 13085 | 12620 | 12270 | 12035 | 11685 |
| T445848      | 600/70R30 |                 | 171A8 (166D) | SB              | TL    | DW20B | DW18L                        | 23.7       | 62.2          | 27.9                      | 187.9                      | 750 | 46             | 46                            | 38                    | R-4        | Yes | 13435                               | 13085 | 12620 | 12270 | 12035 | 11685 |
| T445588      | 440/80R34 | 16.9R34         | 159A8 (155D) | SB              | TL    | DW14L | DW15L, DW16L                 | 17.4       | 61.8          | 28.3                      | 187.5                      | 750 | 46             | 46                            | 33                    | R-4        | Yes | 9820                                | 9570  | 9225  | 8975  | 8795  | 8545  |
| T445583      | 480/80R34 | 18.4R34         | 164A8 (159D) | SB              | TL    | DW15L | DW16L, DW18L                 | 19         | 64.2          | 29.3                      | 195.4                      | 775 | 46             | 46                            | 34                    | R-4        | Yes | 11090                               | 10805 | 10415 | 10130 | 9930  | 9645  |
| T445700      | 600/70R34 |                 | 172A8 (168D) | SB              | TL    | DW20B | DW18L                        | 23.3       | 66            | 29.7                      | 200.9                      | 800 | 46             | 46                            | 35                    | R-4        | Yes | 14200                               | 13825 | 13340 | 12965 | 12720 | 12345 |
| T445585      | 480/80R38 | 18.4R38         | 166A8 (161D) | SB              | TL    | DW15L | DW16L, DW18L                 | 18.8       | 68.2          | 31.2                      | 208                        | 825 | 46             | 46                            | 34                    | R-4        | Yes | 11730                               | 11420 | 11010 | 10705 | 10505 | 10195 |
| T445564      | 540/80R38 |                 | 172A8 (167D) | SB              | TL    | DW18L | DW16L                        | 21.9       | 72.2          | 32.8                      | 219.1                      | 875 | 46             | 46                            | 34                    | R-4        | Yes | 14200                               | 13825 | 13340 | 12965 | 12720 | 12345 |
| T445773      | 650/65R38 |                 | 175A8 (170D) | SB              | TL    | DW20B | DW21B, DW23B                 | 24.6       | 71.7          | 32.5                      | 218.7                      | 875 | 46             | 46                            | 39                    | R-4        | Yes | 15210                               | 14815 | 14285 | 13890 | 13625 | 13230 |
| T445595      | 650/65R42 |                 | 176A8 (171D) | SB              | TL    | DW20B | DW18L                        | 24.7       | 75.3          | 34.3                      | 229.8                      | 925 | 46             | 46                            | 39                    | R-4        | Yes | 15600                               | 15190 | 14640 | 14240 | 13965 | 13560 |
| T445847      | 710/70R42 |                 | 185A8 (180D) | SB              | TL    | DW23B | DW25B                        | 27.7       | 81.3          | 33.7                      | 246.1                      | 975 | 46             | 46                            | 44                    | R-4        | Yes | 20285                               | 19755 | 19050 | 18520 | 18165 | 17635 |

## ALL SIZES FOR WHEEL LOADER

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims        | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | M+S | Load capacity for constant load, lb |       |       |       |       |      |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|-----------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|-----|-------------------------------------|-------|-------|-------|-------|------|
|              |           |                 |              |                 |       |       |                       |            |               |                           |                            |     |                |                               |                       |            |                   |     | Speed (mph)                         |       |       |       |       |      |
|              |           |                 |              |                 |       |       |                       |            |               |                           |                            |     |                |                               |                       |            |                   |     | 25                                  | 27.5  | 30    | 35    | 37.5  | 40   |
| T445665      | 340/80R18 | 12.5R18         | 143A8 (138D) | SB              | TL    | 11    | W11, 10, W10, 12, W12 | 12.9       | 39.4          | 17.8                      | 119.3                      | 475 | 58             | 58                            | 30                    | R-4        |                   | Yes | 5985                                | 5830  | 5620  | 5465  | 5355  | 5205 |
| T445832      | 400/70R18 | 16.0/70R18      | 147A8 (143D) | SB              | TL    | 13    | W13, 12, W12          | 15.7       | 40.1          | 18                        | 120.8                      | 475 | 58             | 58                            | 33                    | R-4        |                   | Yes | 6910                                | 6725  | 6495  | 6305  | 6185  | 6010 |
| T445666      | 360/80R20 | 13.6R20         | 148A8 (143D) | SB              | TL    | 11    | W11, 10, W10, 12, W12 | 14.2       | 43            | 19.4                      | 130.4                      | 525 | 58             | 58                            | 30                    | R-4        |                   | Yes | 6910                                | 6725  | 6495  | 6305  | 6185  | 6010 |
| T445636      | 400/70R20 | 16.0/70R20      | 149A8 (144D) | SB              | TL    | 13    |                       | 15.5       | 42.2          | 19.1                      | 127.2                      | 500 | 58             | 58                            | 33                    | R-4        |                   | Yes | 7100                                | 6910  | 6670  | 6480  | 6360  | 6175 |
| T445586      | 420/65R24 |                 | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L, DW15L    | 15.8       | 45.6          | 20.5                      | 137.3                      | 550 | 58             | 58                            | 31                    | R-4        | T55112            | Yes | 7605                                | 7410  | 7145  | 6945  | 6810  | 6615 |
| T445669      | 460/70R24 | 17.5LR24        | 166A8 (161D) | SB              | TL    | DW14L | DW15L                 | 18.1       | 49.4          | 21.9                      | 149.3                      | 600 | 73             | 73                            | 38                    | R-4        | T55112            | Yes | 11730                               | 11420 | 11010 | 10705 | 10505 | 1019 |
| T445671      | 500/70R24 | 19.5LR24        | 171A8 (166D) | SB              | TL    | DW16L | DW15L, DW18L          | 19.7       | 51.7          | 22.8                      | 156.3                      | 625 | 73             | 73                            | 38                    | R-4        |                   | Yes | 13435                               | 13085 | 12620 | 12270 | 12035 | 1168 |
| T445672      | 540/70R24 | 21LR24          | 175A8 (170D) | SB              | TL    | DW18L | DW16L                 | 21.3       | 53.8          | 23.7                      | 163.1                      | 650 | 73             | 73                            | 38                    | R-4        |                   | Yes | 15210                               | 14815 | 14285 | 13890 | 13625 | 1323 |

# NOKIAN TYRES SOIL KING VF

## ADVANCED TRACTION TIRE WITH HIGHLY EFFICIENT GROUND CONTACT FOR HIGH-POWER TRACTORS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- Deep and extra wide pattern, provides big and powerful traction surface
- The center-zone pattern featuring extended and laterally supported lug tips balances behaviour and reduces loss of power on field and on road



### AVAILABLE SIZES

- VF540/65R28 - T445885
- VF600/65R28 - T445809
- VF600/70R28 - T445813
- VF540/65R30 - T445811
- VF600/60R30 - T445861
- VF600/70R30 - T445769
- VF600/70R34 - T445760
- VF650/60R34 - T445815
- VF650/65R34 - T445830
- VF710/60R34 - T445864
- VF650/65R38 - T445884
- VF650/85R38 - T445808
- VF710/70R38 - T445812
- VF650/65R42 - T445810
- VF710/60R42 - T445873
- VF710/70R42 - T445768
- VF710/75R42 - T445759

# NOKIAN TYRES SOIL KING VF


## ALL SIZES

| Product code | Size        | LI/SS       | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI  | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|-------------|-------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|-----------------------|------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |             |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                       |            |                        | Speed (mph)       |       |       |       |       |       |
|              |             |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                       |            |                        | 25                | 30    | 35    | 37.5  | 40    | 42.5  |
| T445885      | VF540/65R28 | 157D (154E) | SB              | TL    | DW20B | DW18L, DW16L   | 22         | 55.9          | 25                        | 166.7                      | 675  | 29             | 41                            | 69                    | R-1W       | 28.4                   | 9095              | 9095  | 9095  | 9095  | 9095  | 8280  |
| T445809      | VF600/65R28 | 163D (160E) | SB              | TL    | DW21B | DW20B, DW18L   | 23.8       | 59.6          | 26.5                      | 177.8                      | 700  | 29             | 41                            | 69                    | R-1W       | 30.6                   | 10750             | 10750 | 10750 | 10750 | 10750 | 9780  |
| T445813      | VF600/70R28 | 167D (164E) | SB              | TL    | DW21B | DW20B, DW18L   | 24.2       | 62.2          | 27                        | 185.2                      | 725  | 29             | 41                            | 69                    | R-1W       | 31                     | 12015             | 12015 | 12015 | 12015 | 12015 | 10935 |
| T445811      | VF540/65R30 | 158D (155E) | SB              | TL    | DW20B | DW18L, DW16L   | 22         | 58.6          | 26.2                      | 175                        | 700  | 29             | 41                            | 69                    | R-1W       | 28.4                   | 9370              | 9370  | 9370  | 9370  | 9370  | 8530  |
| T445861      | VF600/60R30 | 162D (158E) | SB              | TL    | DW20B | DW21B, DW18L   | 23.1       | 58.7          | 25.8                      | 174.9                      | 700  | 29             | 41                            | 69                    | R-1W       | 29.8                   | 10470             | 10470 | 10470 | 10470 | 10470 | 9535  |
| T445769      | VF600/70R30 | 168D (165E) | SB              | TL    | DW21B | DW18L, DW20B   | 24.2       | 62.9          | 27.4                      | 189.6                      | 750  | 29             | 41                            | 69                    | R-1W       | 31.1                   | 12345             | 12345 | 12345 | 12345 | 12345 | 11235 |
| T445760      | VF600/70R34 | 170D (167E) | SB              | TL    | DW21B | DW20B, DW18L   | 24.1       | 67.7          | 29.7                      | 202.4                      | 800  | 29             | 41                            | 73                    | R-1W       | 31                     | 13230             | 13230 | 13230 | 13230 | 13230 | 12035 |
| T445815      | VF650/60R34 | 168D (165E) | SB              | TL    | DW23B | DW21B, DW20B   | 25.9       | 65.6          | 28.9                      | 196                        | 775  | 29             | 41                            | 73                    | R-1W       | 33.1                   | 12345             | 12345 | 12345 | 12345 | 12345 | 11235 |
| T445830      | VF650/65R34 | 170D (167E) | SB              | TL    | DW23B | DW21B, DW20B   | 26         | 67.7          | 29.9                      | 203.1                      | 825  | 29             | 41                            | 73                    | R-1W       | 33.2                   | 13230             | 13230 | 13230 | 13230 | 13230 | 12035 |
| T445864      | VF710/60R34 | 173D (170E) | SB              | TL    | DW25B | DW24B          | 28         | 68            | 29.9                      | 203.5                      | 825  | 29             | 41                            | 73                    | R-1W       | 35.6                   | 14330             | 14330 | 14330 | 14330 | 14330 | 13040 |
| T445884      | VF650/65R38 | 172D (169E) | SB              | TL    | DW23B | DW21B, DW20B   | 25.9       | 72.2          | 32.4                      | 216.9                      | 875  | 29             | 41                            | 74                    | R-1W       | 33.1                   | 13890             | 13890 | 13890 | 13890 | 13890 | 12645 |
| T445808      | VF650/85R38 | 182D (179E) | SB              | TL    | DW23B | DW21B, DW20B   | 26.3       | 81.3          | 35.4                      | 243.7                      | 975  | 29             | 41                            | 79                    | R-1W       | 33.6                   | 18740             | 18740 | 18740 | 18740 | 18740 | 17055 |
| T445812      | VF710/70R38 | 181D (178E) | SB              | TL    | DW25B | DW24B, DW23B   | 28.4       | 77.1          | 33.9                      | 231.7                      | 925  | 29             | 41                            | 79                    | R-1W       | 36.1                   | 18190             | 18190 | 18190 | 18190 | 18190 | 16555 |
| T445810      | VF650/65R42 | 174D (170E) | SB              | TL    | DW23B | DW21B, DW20B   | 25.9       | 75.7          | 33.7                      | 227.2                      | 925  | 29             | 41                            | 74                    | R-1W       | 33.1                   | 14770             | 14770 | 14770 | 14770 | 14770 | 13435 |
| T445873      | VF710/60R42 | 176D (173E) | SB              | TL    | DW25B | DW24B, DW23B   | 28.2       | 76            | 33.9                      | 228.2                      | 925  | 29             | 41                            | 79                    | R-1W       | 35.9                   | 15655             | 15655 | 15655 | 15655 | 15655 | 14240 |
| T445768      | VF710/70R42 | 182D (179E) | SB              | TL    | DW25B | DW23B, DW24B   | 28.7       | 81.7          | 35.7                      | 247                        | 975  | 29             | 41                            | 79                    | R-1W       | 36.5                   | 18740             | 18740 | 18740 | 18740 | 18740 | 17055 |
| T445759      | VF710/75R42 | 184D (181E) | SB              | TL    | DW25B | DW23B, DW24B   | 28.6       | 84.6          | 37.1                      | 253.9                      | 1000 | 29             | 41                            | 83                    | R-1W       | 36.3                   | 19840             | 19840 | 19840 | 19840 | 19840 | 18055 |

# NOKIAN TYRES TRI 2

**A M+S BLOCK PATTERNED TIRE FOR  
WORK ON HARD GROUNDS AND ROADS  
IN ALL SEASONS**

- Use economy with durable long service life block pattern and energy efficiency.
- Reliable grip and comfortable handling also in varying weather conditions.
- Use of heavy implements enabled by high load capacity and strength of steel belted construction.



## AVAILABLE SIZES

- 250/75R16 - T845539
- 250/80R16 - T845495
- 340/80R18 - T445391
- 360/70R20 - T445569
- 360/80R20 - T445389
- 300/80R24 - T445419
- 340/80R24 - T445376
- 360/80R24 - T445378
- 400/80R24 - T445372
- 420/65R24 - T445392
- 440/80R24 - T445385
- 460/65R24 - T445393
- 500/70R24 - T445467
- 540/65R24 - T445420
- 320/85R28 - T445579
- 360/80R28 - T445550
- 400/80R28 - T445383
- 440/80R28 - T445337
- 480/65R28 - T445444
- 540/65R28 - T445442
- 440/80R30 - T445384
- 480/80R30 - T445386
- 540/65R30 - T445371
- 600/70R30 - T445657
- 440/80R34 - T445369
- 480/80R34 - T445370
- 600/65R34 - T445656
- 480/80R38 - T445377
- 540/80R38 - T445338
- 600/65R38 - T445445
- 650/65R38 - T445443
- 620/80R42 - T445518
- 650/65R42 - T445390
- 710/70R42 - T445655

# NOKIAN TYRES TRI 2

## ALL SIZES

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims               | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | M+S | Load capacity for constant load, lb |       |       |       |       |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|-----|-------------------------------------|-------|-------|-------|-------|
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                       |            |                   |     | Speed (mph)                         |       |       |       |       |
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                       |            |                   |     | 25                                  | 27.5  | 30    | 35    | 37.5  |
| T845539      | 250/75R16 |                 | 120G         | SB              | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 10.2       | 30.8          | 14.3                      | 94.1                       | 370 | 65             | 65                            | 20                    | R-4        |                   | Yes | 3680                                | 3585  | 3450  | 3360  | 3295  |
| T845495      | 250/80R16 | 7.5R16          | 119G         | SB              | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 10.8       | 32.2          | 14.8                      | 98.2                       | 390 | 65             | 65                            | 21                    | R-4        |                   | Yes | 3935                                | 3825  | 3695  | 3595  | 3515  |
| T445391      | 340/80R18 | 12.5R18         | 143A8 (138D) | SB              | TL    | 11    | W11, 10, W10, 12, W12        | 13.4       | 39.4          | 17.8                      | 118.5                      | 475 | 58             | 58                            | 31                    | R-4        |                   | Yes | 5985                                | 5830  | 5620  | 5465  | 5355  |
| T445569      | 360/70R20 |                 | 136A8 (131D) | SB              | TL    | 11    | W11, 10, W10, 12, W12        | 13.4       | 40.6          | 18.5                      | 122.2                      | 500 | 46             | 46                            | 33                    | R-4        |                   | Yes | 4950                                | 4815  | 4640  | 4520  | 4430  |
| T445389      | 360/80R20 | 13.6R20         | 147A8 (143D) | SB              | TL    | 11    | W11, 10, W11, 12, W12        | 14         | 43.1          | 19.5                      | 129.4                      | 500 | 58             | 58                            | 33                    | R-4        |                   | Yes | 6910                                | 6725  | 6495  | 6305  | 6185  |
| T445419      | 300/80R24 | 11.2R24         | 133A8 (128D) | SB              | TL    | DW10  | W9, W10, W11, DW11           | 11.6       | 42.9          | 19.8                      | 129.8                      | 525 | 46             | 46                            | 30                    | R-4        |                   | Yes | 4565                                | 4440  | 4290  | 4165  | 4090  |
| T445376      | 340/80R24 | 12.4R24         | 140A8 (135D) | SB              | TL    | DW11  | DW10, DW12                   | 13         | 45.4          | 20.5                      | 137.3                      | 550 | 46             | 46                            | 31                    | R-4        |                   | Yes | 5525                                | 5380  | 5190  | 5050  | 4950  |
| T445378      | 360/80R24 | 13.6R24         | 143A8 (138D) | SB              | TL    | DW11  | DW10, DW12                   | 13.7       | 46.6          | 21.2                      | 140.7                      | 575 | 46             | 46                            | 33                    | R-4        |                   | Yes | 6160                                | 5995  | 5785  | 5620  | 5525  |
| T445372      | 400/80R24 | 14.9R24         | 149A8 (144D) | SB              | TL    | DW13  | DW12, DW14L                  | 15.6       | 49.1          | 22                        | 148.1                      | 600 | 46             | 46                            | 34                    | R-4        | T55112            | Yes | 7100                                | 6910  | 6670  | 6480  | 6360  |
| T445392      | 420/65R24 |                 | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14, DW15L            | 15.8       | 45.5          | 20.7                      | 137.5                      | 550 | 58             | 58                            | 33                    | R-4        | T55112            | Yes | 7605                                | 7410  | 7145  | 6945  | 6810  |
| T445385      | 440/80R24 | 16.9R24         | 154A8 (149D) | SB              | TL    | DW14L | DW15L                        | 16.9       | 51.7          | 23                        | 155.8                      | 625 | 46             | 46                            | 35                    | R-4        | T55112            | Yes | 8245                                | 8025  | 7740  | 7530  | 7385  |
| T445393      | 460/65R24 |                 | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 17.3       | 47.4          | 21.3                      | 143.5                      | 575 | 58             | 58                            | 35                    | R-4        | T55112            | Yes | 8750                                | 8520  | 8210  | 7990  | 7835  |
| T445467      | 500/70R24 | 19.5LR24        | 164A8 (159D) | SB              | TL    | DW16L | DW15L, DW18L                 | 20.3       | 51.5          | 23                        | 155.8                      | 625 | 58             | 58                            | 35                    | R-4        |                   | Yes | 11090                               | 10805 | 10415 | 10130 | 9930  |
| T445420      | 540/65R24 |                 | 158A8 (154D) | SB              | TL    | DW18L | DW16L                        | 21.1       | 51.5          | 22.9                      | 156.1                      | 625 | 46             | 46                            | 35                    | R-4        |                   | Yes | 9260                                | 9015  | 8685  | 8455  | 8290  |
| T445579      | 320/85R28 | 12.4R28         | 141A8 (136D) | SB              | TL    | DW10  | W9, DW11, W10                | 12.3       | 49.2          | 22.6                      | 149.1                      | 600 | 46             | 46                            | 30                    | R-4        |                   | Yes | 5830                                | 5675  | 5480  | 5325  | 5225  |
| T445550      | 360/80R28 | 13.6R28         | 146A8 (142D) | SB              | TL    | DW11  | DW12, DW13                   | 13.9       | 51.3          | 23.4                      | 155.4                      | 625 | 46             | 46                            | 33                    | R-4        |                   | Yes | 6525                                | 6360  | 6130  | 5965  | 5840  |
| T445383      | 400/80R28 | 14.9R28         | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L                  | 15.6       | 53.2          | 24.4                      | 160.6                      | 650 | 46             | 46                            | 34                    | R-4        |                   | Yes | 7795                                | 7595  | 7320  | 7120  | 6980  |
| T445337      | 440/80R28 | 16.9R28         | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 17         | 55.6          | 25.4                      | 168                        | 675 | 46             | 46                            | 35                    | R-4        |                   | Yes | 9005                                | 8765  | 8455  | 8225  | 8060  |
| T445444      | 480/65R28 |                 | 154A8 (149D) | SB              | TL    | DW15L | DW14L, DW16L                 | 18.3       | 52.6          | 23.8                      | 158.5                      | 650 | 46             | 46                            | 35                    | R-4        | T55097            | Yes | 8245                                | 8025  | 7740  | 7530  | 7385  |
| T445442      | 540/65R28 |                 | 160A8 (155D) | SB              | TL    | DW18L | DW16L                        | 20.9       | 55.6          | 25.2                      | 167.2                      | 675 | 46             | 46                            | 35                    | R-4        | T545229           | Yes | 9820                                | 9570  | 9225  | 8975  | 8795  |
| T445384      | 440/80R30 | 16.9R30         | 157A8 (153D) | SB              | TL    | DW14L | DW15L, DW16L                 | 16.9       | 57.6          | 26                        | 175.1                      | 700 | 46             | 46                            | 35                    | R-4        | T55371            | Yes | 9260                                | 9015  | 8685  | 8455  | 8290  |
| T445386      | 480/80R30 | 18.4R30         | 162A8 (157D) | SB              | TL    | DW15L | DW16L, DW18L                 | 18.6       | 60.1          | 26.9                      | 182.5                      | 725 | 46             | 46                            | 37                    | R-4        | T55371            | Yes | 10460                               | 10185 | 9820  | 9545  | 9370  |
| T445371      | 540/65R30 |                 | 161A8 (156D) | SB              | TL    | DW18L | DW16L                        | 20.9       | 57.5          | 25.4                      | 173.3                      | 700 | 46             | 46                            | 38                    | R-4        | T55371            | Yes | 10140                               | 9875  | 9525  | 9260  | 9085  |
| T445657      | 600/70R30 |                 | 171A8 (166D) | SB              | TL    | DW20B | DW18L                        | 23.8       | 61.6          | 27.6                      | 187.2                      | 750 | 46             | 46                            | 40                    | R-4        |                   | Yes | 13435                               | 13085 | 12620 | 12270 | 12035 |
| T445369      | 440/80R34 | 16.9R34         | 159A8 (155D) | SB              | TL    | DW14L | DW15L, DW16L                 | 16.8       | 61.7          | 28.2                      | 187                        | 750 | 46             | 46                            | 35                    | R-4        | T55391            | Yes | 9820                                | 9570  | 9225  | 8975  | 8795  |
| T445370      | 480/80R34 | 18.4R34         | 164A8 (159D) | SB              | TL    | DW15L | DW16L, DW18L                 | 18.6       | 64.2          | 28.9                      | 194.9                      | 775 | 46             | 46                            | 37                    | R-4        | T55391            | Yes | 11090                               | 10805 | 10415 | 10130 | 9930  |
| T445656      | 600/65R34 |                 | 169A8 (164D) | SB              | TL    | DW20B | DW18L                        | 23.4       | 63.7          | 29                        | 194.3                      | 775 | 46             | 46                            | 40                    | R-4        |                   | Yes | 12675                               | 12345 | 11905 | 11575 | 11355 |
| T445377      | 480/80R38 | 18.4R38         | 166A8 (161D) | SB              | TL    | DW15L | DW16L, DW18L                 | 18.3       | 68.2          | 31.2                      | 206.9                      | 825 | 46             | 46                            | 37                    | R-4        |                   | Yes | 11730                               | 11420 | 11010 | 10705 | 10505 |
| T445338      | 540/80R38 | 20.8R28         | 172A8 (167D) | SB              | TL    | DW18L | DW16L                        | 21.8       | 71.9          | 32.8                      | 217.4                      | 875 | 46             | 46                            | 38                    | R-4        |                   | Yes | 14200                               | 13825 | 13340 | 12965 | 12720 |

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | M+S | Load capacity for constant load, lb |       |       |       |       |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------|-----|-------------------------------------|-------|-------|-------|-------|
|              |           |                 |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                       |            |                   |     | Speed (mph)                         |       |       |       |       |
|              |           |                 |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                       |            |                   |     | 25                                  | 27.5  | 30    | 35    | 37.5  |
| T445445      | 600/65R38 |                 | 170A8 (166D) | SB              | TL    | DW18L | DW20B          | 23         | 68.5          | 31.1                      | 208.3                      | 825 | 46             | 46                            | 38                    | R-4        |                   | Yes | 13435                               | 13085 | 12620 | 12270 | 12035 |
| T445443      | 650/65R38 |                 | 175A8 (170D) | SB              | TL    | DW20B | DW18L, DW23B   | 25         | 71.3          | 32.2                      | 216.9                      | 875 | 46             | 46                            | 42                    | R-4        |                   | Yes | 15210                               | 14815 | 14285 | 13890 | 13625 |
| T445518      | 620/80R42 |                 | 181A8 (177D) | SB              | TL    | DW20B | DW23B          | 24.6       | 81.1          | 36.4                      | 247.6                      | 975 | 46             | 46                            | 44                    | R-4        |                   | Yes | 18510                               | 18025 | 17385 | 16900 | 16580 |
| T445390      | 650/65R42 |                 | 176A8 (171D) | SB              | TL    | DW20B | DW18L, DW23B   | 24.3       | 75.3          | 33.4                      | 228                        | 925 | 46             | 46                            | 42                    | R-4        |                   | Yes | 15600                               | 15190 | 14640 | 14240 | 13965 |
| T445655      | 710/70R42 |                 | 185A8 (180D) | SB              | TL    | DW23B |                | 28.2       | 80.5          | 36.3                      | 246.3                      | 975 | 46             | 46                            | 47                    | R-4        |                   | Yes | 20285                               | 19755 | 19050 | 18520 | 18165 |

# NOKIAN TYRES TRI STEEL

## PUNCTURE PROTECTION FOR SPECIAL APPLICATIONS

- A special loader tire with a puncture-resisting block pattern.
- Steel fortification for extra durability.
- Suitable for waste treatment, recycling plants and for industrial use.



2026-05-24



### AVAILABLE SIZES

- 460/65R24 - T445245
- 480/65R24 - T445222

# NOKIAN TYRES TRI STEEL


## ALL SIZES

| Product code | Size      | LI/SS        | TL/TT | Rim   | Permitted rims                       | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Load capacity for constant load, lb |      |      |      |      |      |
|--------------|-----------|--------------|-------|-------|--------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|------------|-------------------------------------|------|------|------|------|------|
|              |           |              |       |       |                                      |            |               |                           |                            |     |                |                               |                       |            | Speed (mph)                         |      |      |      |      |      |
|              |           |              |       |       |                                      |            |               |                           |                            |     |                |                               |                       |            | 25                                  | 27.5 | 30   | 35   | 37.5 | 40   |
| T445245      | 460/65R24 | 156A8 (151D) | TL    | DW13  | W13, DW13L, W14L, DW14L, W15L, DW15L | 16.8       | 46.6          | 21.5                      | 141                        | 575 | 58             | 58                            | 34                    | R-4        | 8750                                | 8520 | 8210 | 7990 | 7835 | 7605 |
| T445222      | 480/65R24 | 151A8 (146D) | TL    | DW14L | W14L, W15L, DW15L, W16L, DW16L       | 18.4       | 48.7          | 22.2                      | 147.2                      | 600 | 46             | 46                            | 35                    | R-4        | 7605                                | 7410 | 7145 | 6945 | 6810 | 6615 |

# NOKIAN TYRES COUNTRY KING

## EFFICIENT RADIAL FLOTATION TIRE FOR AGRICULTURAL TRANSPORTATIONS ON ROAD AND FIELD

- Durability and low rolling resistance due to high positive pattern ratio and special tread compound.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.



### AVAILABLE SIZES

- 500/60R22.5 - T445453
- 560/45R22.5 - T445402
- 560/60R22.5 - T445401
- 580/65R22.5 - T445405
- 600/50R22.5 - T445441
- 650/50R22.5 - T445407
- 710/35R22.5 - T445542
- 710/45R22.5 - T445496
- 600/55R26.5 - T445653
- 620/60R26.5 - T445404
- 650/65R26.5 - T445440
- 710/50R26.5 - T445406
- 800/45R26.5 - T445600
- 650/65R30.5 - T445611
- 750/60R30.5 - T445610

# NOKIAN TYRES COUNTRY KING


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims   | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Load capacity for mixed, lb |       |       |       |       |       |
|--------------|-------------|-------|-----------------|-------|---------|------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |             |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                       |                   | Speed (mph)                 |       |       |       |       |       |
|              |             |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                       |                   | 25                          | 27.5  | 30    | 35    | 37.5  | 40    |
| T445453      | 500/60R22.5 | 155D  | SB              | TL    | AG16.00 |                  | 20.1       | 46.1          | 20.5                      | 141                        | 550 | 58             | 58                            | 21                    | T55096            | 11620                       | 11025 | 10340 | 9745  | 9140  | 8545  |
| T445402      | 560/45R22.5 | 152D  | SB              | TL    | AG16.00 |                  | 21.2       | 42.4          | 18.7                      | 129.1                      | 525 | 58             | 58                            | 20                    | T56435            | 10650                       | 10095 | 9470  | 8920  | 8380  | 7825  |
| T445401      | 560/60R22.5 | 161D  | SB              | TL    | AG16.00 | AG18.00, AG20.00 | 22.3       | 48.7          | 21.9                      | 148.2                      | 600 | 58             | 58                            | 23                    | T55089            | 13865                       | 13150 | 12335 | 11630 | 10915 | 10195 |
| T445405      | 580/65R22.5 | 166D  | SB              | TL    | AG16.00 | AG18.00          | 23         | 51.1          | 23.1                      | 156.6                      | 625 | 58             | 58                            | 24                    | T55089            | 15895                       | 15070 | 14145 | 13315 | 12500 | 11685 |
| T445441      | 600/50R22.5 | 159D  | SB              | TL    | AG20.00 |                  | 23.4       | 46.1          | 21                        | 140.7                      | 550 | 58             | 58                            | 23                    | T55089            | 13120                       | 12445 | 11675 | 11000 | 10320 | 9645  |
| T445407      | 650/50R22.5 | 163D  | SB              | TL    | AG20.00 |                  | 25.4       | 48.6          | 22.2                      | 149.2                      | 575 | 58             | 58                            | 23                    | T55089            | 14615                       | 13865 | 13005 | 12260 | 11495 | 10750 |
| T445542      | 710/35R22.5 | 157D  | SB              | TL    | AG24.00 |                  | 27.4       | 42.1          | 19.1                      | 127.9                      | 525 | 58             | 58                            | 28                    |                   | 12370                       | 11730 | 11000 | 10375 | 9735  | 9095  |
| T445496      | 710/45R22.5 | 165D  | SB              | TL    | AG24.00 |                  | 27.4       | 47.8          | 21.5                      | 145.5                      | 575 | 58             | 58                            | 24                    | T55092            | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445653      | 600/55R26.5 | 165D  | SB              | TL    | AG20.00 |                  | 23.7       | 52.6          | 23.8                      | 160.3                      | 625 | 58             | 58                            | 28                    | T55098            | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445404      | 620/60R26.5 | 169D  | SB              | TL    | AG20.00 |                  | 24.9       | 55.2          | 25.2                      | 168.9                      | 675 | 58             | 58                            | 25                    | T55098            | 17395                       | 16490 | 15475 | 14575 | 13680 | 12785 |
| T445440      | 650/65R26.5 | 174D  | SB              | TL    | AG20.00 |                  | 25.8       | 59.8          | 27.1                      | 183.3                      | 725 | 58             | 58                            | 25                    | T55102            | 20085                       | 19060 | 17870 | 16845 | 15805 | 14770 |
| T445406      | 710/50R26.5 | 170D  | SB              | TL    | AG24.00 |                  | 29.1       | 55.3          | 25.4                      | 169.4                      | 650 | 58             | 58                            | 26                    | T55102            | 18440                       | 17495 | 16400 | 15455 | 14505 | 13560 |
| T445600      | 800/45R26.5 | 174D  | SB              | TL    | AG28.00 | AG24.00          | 30.3       | 54.9          | 24.5                      | 166.9                      | 675 | 58             | 58                            | 33                    | T55102            | 20085                       | 19060 | 17870 | 16845 | 15805 | 14770 |
| T445611      | 650/65R30.5 | 176D  | SB              | TL    | AG20.00 |                  | 25.5       | 63.9          | 29                        | 195.6                      | 775 | 58             | 58                            | 33                    |                   | 21285                       | 20195 | 18940 | 17845 | 16745 | 15655 |
| T445610      | 750/60R30.5 | 181D  | SB              | TL    | AG24.00 |                  | 29.9       | 66.1          | 29.8                      | 202.5                      | 800 | 58             | 58                            | 33                    |                   | 24735                       | 23470 | 22015 | 20735 | 19465 | 18190 |

# NOKIAN TYRES COUNTRY KING G2

## PREMIUM FLOTATION TIRE FOR HIGH-PERFORMANCE AGRICULTURAL TRANSPORT

- Deep tread offers long-lasting performance and excellent value in transport use
- Dual-purpose tread pattern design delivers performance and reduces loss of power on both on-road transport and field conditions
- Large pattern contact and rounded shoulder design for advanced soil and crop damage prevention



### AVAILABLE SIZES

- 560/60R22.5 - T445876
- 600/50R22.5 - T445877
- 650/50R22.5 - T445878
- 710/45R22.5 - T445879
- VF600/55R26.5 - T445880
- VF620/60R26.5 - T445888
- VF650/55R26.5 - T445881



# NOKIAN TYRES COUNTRY KING G2

## ALL SIZES

| Product code | Size          | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims   | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Load capacity for mixed, lb |       |       |       |       |       |
|--------------|---------------|-------|-----------------|-------|---------|------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |               |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                       | Speed (mph)                 |       |       |       |       |       |
|              |               |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                       | 25                          | 27.5  | 30    | 35    | 37.5  | 40    |
| T445876      | 560/60R22.5   | 161D  | SB              | TL    | AG18.00 | AG16.00, AG20.00 | 22         | 49.4          | 22.4                      | 150.2                      | 600 | 58             | 58                            | 28                    | 13865                       | 13150 | 12335 | 11630 | 10915 | 10195 |
| T445877      | 600/50R22.5   | 159D  | SB              | TL    | AG20.00 |                  | 24.1       | 46.1          | 21                        | 140.4                      | 550 | 58             | 58                            | 28                    | 13120                       | 12445 | 11675 | 11000 | 10320 | 9645  |
| T445878      | 650/50R22.5   | 163D  | SB              | TL    | AG20.00 |                  | 25.4       | 48.5          | 21.9                      | 147.4                      | 575 | 58             | 58                            | 28                    | 14615                       | 13865 | 13005 | 12260 | 11495 | 10750 |
| T445879      | 710/45R22.5   | 165D  | SB              | TL    | AG24.00 |                  | 28.9       | 48.1          | 21.7                      | 146.6                      | 575 | 58             | 58                            | 28                    | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445880      | VF600/55R26.5 | 167D  | SB              | TL    | AG20.00 |                  | 24.4       | 53.3          | 23.5                      | 161.6                      | 625 | 41             | 58                            | 30                    | 15500                       | 14780 | 14055 | 13340 | 12730 | 12015 |
| T445888      | VF620/60R26.5 | 171D  | SB              | TL    | AG20.00 |                  | 24.4       | 56.7          | 24.8                      | 171.9                      | 650 | 41             | 58                            | 30                    | 17495                       | 16680 | 15860 | 15045 | 14375 | 13560 |
| T445881      | VF650/55R26.5 | 171D  | SB              | TL    | AG20.00 |                  | 25.7       | 55.6          | 24.2                      | 168.5                      | 650 | 41             | 58                            | 30                    | 17495                       | 16680 | 15860 | 15045 | 14375 | 13560 |

# NOKIAN TYRES CT

## EARTHMOVING GRADE RADIAL FLOTATION TIRE FOR HEAVY TRANSPORTATIONS

- Exceptional mileage provided by dense and thick heavy-duty block pattern.
- Special puncture damage resistance with three layers of steel reinforcements in the tread area.
- Stable load-bearing provided by the extra-strength multilayer construction.



### AVAILABLE SIZES

- 560/60R22.5 - T445626
- 600/50R22.5 - T445627
- 600/55R26.5 - T445782
- 650/55R26.5 - T445556
- 600/60R30.5 - T445629

# NOKIAN TYRES CT


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Load capacity for mixed, lb |       |       |       |       |       |
|--------------|-------------|-------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |             |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   | Speed (mph)                 |       |       |       |       |       |
|              |             |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   | 25                          | 27.5  | 30    | 35    | 37.5  | 40    |
| T445626      | 560/60R22.5 | 165D  | SB              | TL    | AG18.00 | AG16.00        | 22         | 49            | 21.9                      | 150                        | 600 | 73             | 73                            | 28                    | T55098            | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445627      | 600/50R22.5 | 163D  | SB              | TL    | AG20.00 |                | 23.5       | 46.2          | 20.8                      | 140.7                      | 550 | 73             | 73                            | 28                    | T55089            | 14615                       | 13865 | 13005 | 12260 | 11495 | 10750 |
| T445782      | 600/55R26.5 | 173D  | SB              | TL    | AG20.00 |                | 23.7       | 52.6          | 24.1                      | 161.3                      | 625 | 87             | 87                            | 30                    | T55098            | 19490                       | 18485 | 17340 | 16335 | 15335 | 14330 |
| T445556      | 650/55R26.5 | 177D  | SB              | TL    | AG20.00 | AG22.00        | 24.9       | 54.7          | 25                        | 167.9                      | 725 | 87             | 87                            | 34                    | T55098            | 21890                       | 20755 | 19480 | 18340 | 17220 | 16095 |
| T445629      | 600/60R30.5 | 173D  | SB              | TL    | AG20.00 |                | 23.9       | 58.9          | 26.8                      | 179.9                      | 725 | 73             | 73                            | 33                    | T55098            | 19490                       | 18485 | 17340 | 16335 | 15335 | 14330 |

# NOKIAN TYRES ELS

## RADIAL TRACTION FLOTATION TIRE FOR AGRICULTURAL OPERATIONS IN CHALLENGING SOIL CONDITIONS

- Reliable grip due to open, well cleaning traction pattern.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.



### AVAILABLE SIZES

- 600/50R22.5 - T445292
- 600/50R22.5 - T445708
- 710/45R22.5 - T445659
- 600/55R26.5 - T445654
- 650/65R26.5 - T445465
- 700/50R26.5 - T445641
- 750/55R26.5 - T445601
- 850/50R30.5 - T445499
- 710/55R34 - T445470
- 800/50R34 - T445469
- 800/60R34 - T445500

# NOKIAN TYRES ELS


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims      | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Load capacity for mixed, lb |       |       |       |       |       |
|--------------|-------------|-------|-----------------|-------|---------|---------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |             |       |                 |       |         |                     |            |               |                           |                            |     |                |                               |                       |                   | Speed (mph)                 |       |       |       |       |       |
|              |             |       |                 |       |         |                     |            |               |                           |                            |     |                |                               |                       |                   | 25                          | 27.5  | 30    | 35    | 37.5  | 40    |
| T445292      | 600/50R22.5 | 156D  |                 | TL    | AG20.00 | 20.00               | 24.6       | 46.1          | 20.9                      | 140.3                      | 550 | 52             | 52                            | 24                    |                   | 11995                       | 11375 | 10670 | 10055 | 9435  | 8820  |
| T445708      | 600/50R22.5 | 159D  | SB              | TL    | AG20.00 |                     | 23.6       | 45.8          | 20.6                      | 140                        | 550 | 58             | 58                            | 24                    | T55089            | 13120                       | 12445 | 11675 | 11000 | 10320 | 9645  |
| T445659      | 710/45R22.5 | 165D  | SB              | TL    | AG24.00 |                     | 27.2       | 47.4          | 21.2                      | 144.8                      | 575 | 58             | 58                            | 25                    | T55092            | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445654      | 600/55R26.5 | 165D  | SB              | TL    | AG20.00 |                     | 23.4       | 52.3          | 23.5                      | 160.3                      | 625 | 58             | 58                            | 28                    | T55098            | 15445                       | 14650 | 13735 | 12940 | 12145 | 11355 |
| T445465      | 650/65R26.5 | 174D  | SB              | TL    | AG20.00 |                     | 25.4       | 59.6          | 26.8                      | 181.8                      | 725 | 58             | 58                            | 30                    | T55102            | 20085                       | 19060 | 17870 | 16845 | 15805 | 14770 |
| T445641      | 700/50R26.5 | 170D  | SB              | TL    | AG24.00 | AG20.00             | 27         | 53.9          | 24.2                      | 165.3                      | 650 | 58             | 58                            | 28                    | T55099            | 17990                       | 17065 | 16005 | 15080 | 14155 | 13230 |
| T445601      | 750/55R26.5 | 177D  | SB              | TL    | AG24.00 |                     | 29.1       | 58.8          | 26.4                      | 179.3                      | 700 | 58             | 58                            | 30                    | T55102            | 21890                       | 20755 | 19480 | 18340 | 17220 | 16095 |
| T445499      | 850/50R30.5 | 182D  | SB              | TL    | AG28.00 | AG27.00, AG30.00    | 34.7       | 64            | 28.9                      | 194.3                      | 775 | 58             | 58                            | 34                    |                   | 25485                       | 24175 | 22675 | 21365 | 20050 | 18740 |
| T445470      | 710/55R34   | 177D  | SB              | TL    | DW24B   | DW20B, DW23B        | 27.8       | 64.6          | 29.4                      | 196.7                      | 775 | 58             | 58                            | 33                    | T55394            | 21890                       | 20755 | 19480 | 18340 | 17220 | 16095 |
| T445469      | 800/50R34   | 181D  | SB              | TL    | DW25B   | DW23B, DW24B, DW28B | 31.1       | 64.5          | 29.2                      | 196.4                      | 800 | 58             | 58                            | 33                    | T55394            | 24735                       | 23470 | 22015 | 20735 | 19465 | 18190 |
| T445500      | 800/60R34   | 186D  | SB              | TL    | DW25B   | DW23B, DW24B, DW28B | 31.5       | 71.4          | 32                        | 218.2                      | 875 | 58             | 58                            | 38                    |                   | 28485                       | 27020 | 25340 | 23875 | 22410 | 20945 |

# NOKIAN TYRES FLOAT KING VF

## NEXT-LEVEL FLOTATION FOR HIGH-CAPACITY AGRICULTURAL TRAILERS AND TANKERS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- The grip pattern works great in challenging soil conditions and on road
- The center-zone pattern with continuous contact balances behaviour and reduces loss of power on field and on road



### AVAILABLE SIZES

- VF600/55R26.5 - T445824
- VF620/60R26.5 - T445825
- VF650/55R26.5 - T445823
- VF650/65R26.5 - T445826
- VF710/50R26.5 - T445822
- VF750/60R30.5 - T445739
- VF850/50R30.5 - T445821
- VF800/60R32 - T445819
- VF710/55R34 - T445818
- VF800/50R34 - T445820

# NOKIAN TYRES FLOAT KING VF

## ALL SIZES

| Product code | Size          | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Load capacity for mixed, lb |       |       |       |       |       |
|--------------|---------------|-------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |               |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                       | Speed (mph)                 |       |       |       |       |       |
|              |               |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                       | 25                          | 27.5  | 30    | 35    | 37.5  | 40    |
| T445824      | VF600/55R26.5 | 167D  | SB              | TL    | AG20.00 |                | 24.1       | 53.3          | 23.4                      | 161.6                      | 625 | 41             | 41                            | 33                    | 15500                       | 14780 | 14055 | 13340 | 12730 | 12015 |
| T445825      | VF620/60R26.5 | 171D  | SB              | TL    | AG20.00 |                | 24.7       | 56.7          | 24.8                      | 172.2                      | 675 | 41             | 41                            | 33                    | 17495                       | 16680 | 15860 | 15045 | 14375 | 13560 |
| T445823      | VF650/55R26.5 | 171D  | SB              | TL    | AG20.00 |                | 25.6       | 55.7          | 24.1                      | 168.6                      | 650 | 41             | 41                            | 33                    | 17495                       | 16680 | 15860 | 15045 | 14375 | 13560 |
| T445826      | VF650/65R26.5 | 176D  | SB              | TL    | AG20.00 |                | 25.3       | 60.9          | 26.5                      | 185                        | 725 | 41             | 41                            | 33                    | 20195                       | 19255 | 18310 | 17370 | 16590 | 15655 |
| T445822      | VF710/50R26.5 | 173D  | SB              | TL    | AG24.00 |                | 29.2       | 55.4          | 24                        | 167.8                      | 650 | 41             | 41                            | 33                    | 18485                       | 17625 | 16765 | 15905 | 15190 | 14330 |
| T445739      | VF750/60R30.5 | 183D  | SB              | TL    | AG24.00 |                | 30         | 66.4          | 28.3                      | 202.5                      | 800 | 41             | 41                            | 35                    | 24890                       | 23735 | 22575 | 21420 | 20450 | 19290 |
| T445821      | VF850/50R30.5 | 184D  | SB              | TL    | AG28.00 |                | 34.8       | 65.1          | 28                        | 197.4                      | 775 | 41             | 41                            | 35                    | 25595                       | 24405 | 23215 | 22025 | 21030 | 19840 |
| T445819      | VF800/60R32   | 188D  | SB              | TL    | DW27B   | DW25B          | 32.8       | 71            | 30.7                      | 216                        | 850 | 41             | 41                            | 35                    | 28440                       | 27115 | 25795 | 24470 | 23370 | 22045 |
| T445818      | VF710/55R34   | 179D  | SB              | TL    | DW23B   | DW24B          | 28.7       | 65.8          | 28.9                      | 200.7                      | 775 | 41             | 41                            | 35                    | 22045                       | 21020 | 19995 | 18970 | 18110 | 17085 |
| T445820      | VF800/50R34   | 183D  | SB              | TL    | DW25B   | DW24B, DW28B   | 31.7       | 66.5          | 28.8                      | 202.3                      | 800 | 41             | 41                            | 35                    | 24890                       | 23735 | 22575 | 21420 | 20450 | 19290 |

# UNDERGROUND MINING TIRES

## DRILL RIGS AND OTHER MINING MACHINES



**59**  
**Nokian Tyres  
Armor Gard 2  
Mine**



**61**  
**Nokian Tyres  
MINE KING E-4**

## UNDERGROUND LOADER



**63**  
**Nokian Tyres  
MINE KING  
L-5S**



**65**  
**Nokian Tyres  
MINE L-3S**

## WHEEL LOADER




**67**  
**Nokian Tyres  
Nordman MINE  
E-4**

# NOKIAN TYRES ARMOR GARD 2 MINE

**STRONG TIRE FOR DRILL RIGS WITH MINING COMPOUND AND IMPROVED, WIDER TREAD**

- New, improved tread lowers the contact pressure and improves service life, providing excellent cut resistance.
- Stable, accurate driving response for predictable handling and a high load-bearing capacity.
- Groove depth indicator helps monitor your tire condition.



## AVAILABLE SIZES

- 9.00-20 - T445836
- 10.00-20 - T445770



# NOKIAN TYRES ARMOR GARD 2 MINE

## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |       |       |       |       |       |
|              |          |       |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                 | creep | 2.5   | 5     | 12    | 15    |
| T445836      | 9.00-20  | 162A5 | 16         | TT    | 7.0 | 7.5            | 10.6       | 40.9          | 18.9                      | 123.4                      | 145            | 145                           | 23                    | E-2        | T52520            | 12.2                   | 15820             | 13615 | 13615 | 13615 | 10470 | 10470 |
| T445770      | 10.00-20 | 164A5 | 16         | TT    | 7.5 | 8.0            | 11.2       | 42.1          | 19.1                      | 126.3                      | 131            | 131                           | 26                    | E-2        | T52620            | 13.1                   | 16645             | 14330 | 14330 | 14330 | 11025 | 11025 |

# NOKIAN TYRES MINE KING E-4

## PURPOSE DESIGNED AND BUILT SPECIAL TIRE FOR DRILL RIGS AND UTILITY VEHICLES

- Strong carcass with a maximum operating pressure of 10 bars, giving a solid foundation for your drill rig.
- Deep grooves with a solid middle section for good puncture resistance and a long tire service life.
- Sharp shoulders and large contact area for better grip.



### AVAILABLE SIZES

- 12.00-20 - T445712
- 14.00-20 - T445617
- 14.00-24 - T445709

# NOKIAN TYRES MINE KING E-4


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|----------|-------|------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |         |                |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |       |       |       |       |       |
|              |          |       |            |       |         |                |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                 | creep | 2.5   | 5     | 12    | 15    |
| T445712      | 12.00-20 | 176A5 | 20         | TT    | 8.5     | 9.0, 8.0       | 13         | 45.2          | 20.5                      | 135.8                      | 145            | 145                           | 44                    | E-4        | T52810            | 14.9                   | 23635             | 20350 | 20350 | 20350 | 15655 | 15655 |
| T445617      | 14.00-20 | 185A2 | 20         | TT    | 10.0    | 9.0            | 14.6       | 48.2          | 22                        | 144.4                      | 145            | 145                           | 50                    | E-4        | T52920            | 17.7                   | 26510             | 23250 | 20395 | 17745 | 17130 | 16315 |
| T445709      | 14.00-24 | 188A2 | 28         | TL    | 10.00WA | 10.00VA        | 15.1       | 54.8          | 24.8                      | 163.5                      | 134            | 145                           | 58                    | E-4        | T55767            | 17.7                   | 28660             | 25135 | 22045 | 19180 | 18520 | 17635 |

# NOKIAN TYRES MINE KING L-5S

## FOR EXTREME UNDERGROUND LOADING APPLICATIONS

- More strengthening layers to ensure tire safety in demanding applications.
- High load capacity, enabling use in heavier, more effective machines.
- Cut and crack resistant tread provides a long service life.



## AVAILABLE SIZES

- 12.00-20 - T445544
- 17.5-25 - T445540
- 17.5-25 - T445580
- 18.00-25 - T445545
- 26.5-25 - T445546
- 29.5-29 - T445547

# NOKIAN TYRES MINE KING L-5S


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                 | creep | 2.5   | 5     |
| T445544      | 12.00-20 | 173A2 | 20         | TT    | 8.5       | 9.0                     | 13.5       | 46.4          | 21.7                      | 141                        | 123            | 145                           | 45                    | L-5S       | T52810            | 14.9                   | 22930             | 18630 | 16335 | 14330 |
| T445540      | 17.5-25  | 184A2 | 24         | TL    | 14.00/1.5 | 14.00/1.3               | 17.5       | 55.1          | 26                        | 168.9                      | 98             | 116                           | 83                    | L-5S       | T55867            | 21                     | 31745             | 25795 | 22620 | 19840 |
| T445580      | 17.5-25  | 188A2 | 34         | TL    | 14.00/1.5 | 14.00/1.3               | 17.9       | 55.7          | 26.1                      | 169.6                      | 116            | 145                           | 83                    | L-5S       | T55867            | 21                     | 35275             | 28660 | 25135 | 22045 |
| T445545      | 18.00-25 | 202A2 | 32         | TL    | 13.00/2.5 | 15.00/2.5, 13.00/2.5 IF | 20.7       | 65.9          | 30.4                      | 201.6                      | 109            | 116                           | 100                   | L-5S       | T55831            | 23.5                   | 52910             | 42990 | 37700 | 33070 |
| T445546      | 26.5-25  | 209A2 | 36         | TL    | 22.00/3.0 | 22.00/3.0IF             | 26.9       | 70.5          | 32.6                      | 216.7                      | 91             | 116                           | 113                   | L-5S       |                   | 31.8                   | 65255             | 53020 | 46495 | 40785 |
| T445547      | 29.5-29  | 218A2 | 40         | TL    | 25.00/3.5 | 24.00/3.5               | 30.2       | 79.5          | 36.4                      | 241.9                      | 91             | 116                           | 123                   | L-5S       |                   | 35.4                   | 83245             | 67640 | 59315 | 52030 |

# NOKIAN TYRES MINE L-3S

THE FIRST UNDERGROUND LOADER TIRE THAT IS READY FOR PROTECTIVE CHAINS

- Strong, stable tire for extreme conditions.
- Supports the chains in an optimal way and can be set instantly – no modification is needed.
- With chains compatible with the chainless L-5S tires.



## AVAILABLE SIZES

- 26.5-25 - T445522

# NOKIAN TYRES MINE L-3S

## ALL SIZES

| Product code | Size    | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | Load capacity, lb |       |       |       |
|--------------|---------|-------|------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|------------------------|-------------------|-------|-------|-------|
|              |         |       |            |       |           |                |            |               |                           |                            |                |                               |                       |            |                        | Speed (mph)       |       |       |       |
|              |         |       |            |       |           |                |            |               |                           |                            |                |                               |                       |            |                        | 0                 | creep | 2.5   | 5     |
| T445522      | 26.5-25 | 209A2 | 36         | TL    | 22.00/3.0 | 22.00/3.0IF    | 26         | 67.2          | 30.5                      | 202.2                      | 91             | 116                           | 53                    | L-3S       | 31.8                   | 65255             | 53020 | 46495 | 40785 |

# NOKIAN TYRES NORDMAN MINE E-4

## DURABILITY FOR ARTICULATED DUMP TRUCKS

- Durable radial all-steel structure
- Excellent choice for rough conditions in quarries
- Cost effective mine tire - EUR/h



## AVAILABLE SIZES

- 26.5R25 - T845483
- 29.5R25 - T845482

# NOKIAN TYRES NORDMAN MINE E-4

## ALL SIZES

| Product code | Size    | LI/SS        | TL/TT | Rim       | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|---------|--------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |         |              |       |           |                |            |               |                           |                            |                |                               |                       |            |                        | Speed (mph)       |       |       |       |       |       |
|              |         |              |       |           |                |            |               |                           |                            |                |                               |                       |            |                        | 12                | 15    | 17.5  | 22.5  | 25    | 30    |
| T845483      | 26.5R25 | 209A2 (193B) | TL    | 22.00/3.0 | 22.00/3.0IF    | 26.9       | 70.8          | 30.3                      | 210.7                      | 83             | 102                           | 69                    | E-4        | 31.8                   | 34260             | 32630 | 31405 | 30180 | 28550 | 25695 |
| T845482      | 29.5R25 | 216A2 (200B) | TL    | 25.00/3.5 | 25.00/3.5IF    | 30.2       | 75.6          | 32.2                      | 226.3                      | 83             | 102                           | 76                    | E-4        | 35.4                   | 41480             | 39505 | 38030 | 36540 | 34570 | 31105 |

# PORTS AND TERMINALS TIRES

## REACH STACKER



70  
Nokian Tyres  
HTS G2 E-4



72  
Nokian Tyres  
HTS G2 L-4S

## WHEELED EXCAVATOR



82  
Nokian Tyres  
Armor Gard 2

## REACH STACKER LOAD AXLE USE



74  
Nokian Tyres  
HTS G2 L-5S

## FORK LIFT



76  
Nokian Tyres  
Armor Gard

## RTG



78  
Nokian Tyres  
RTG

## TERMINAL TRACTOR




80  
Nokian Tyres  
HTS Tugger

# NOKIAN TYRES HTS G2 E-4

## KEEP THE GOODS MOVING – EFFICIENTLY AND ECONOMICALLY

- Supported blocks with chamfered edges improve tire cooling and turning properties.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



### AVAILABLE SIZES

- 14.00-24 - T445710
- 16.00-25 - T445711
- 18.00-25 - T445637
- 18.00-33 - T445662

# NOKIAN TYRES HTS G2 E-4

## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity for load wheel, lb |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)                      |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                                | creep | 2.5   | 5     | 12    | 15    |
| T445710      | 14.00-24 | 188A5 | 28         | TL    | 10.00WA   | 10.00VA                 | 15.4       | 55            | 25.2                      | 165.2                      | 145            | 145                           | 60                    | E-4        | T55767            | 17.7                   | 33070                            | 28660 | 28660 | 28660 | 28660 | 28660 |
| T445711      | 16.00-25 | 199A5 | 36         | TL    | 11.25/2.0 | 11.25/2.0 IF, 13.00/2.0 | 17.8       | 60.5          | 27.3                      | 181.3                      | 145            | 145                           | 72                    | E-4        | T55810            | 20.4                   | 44975                            | 38980 | 38980 | 38980 | 38980 | 38980 |
| T445637      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 21.2       | 65.6          | 30.1                      | 200.8                      | 145            | 145                           | 73                    | E-4        | T55831            | 23.5                   | 57870                            | 50155 | 50155 | 50155 | 50155 | 50155 |
| T445662      | 18.00-33 | 214A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF            | 20.2       | 73.5          | 33.4                      | 222.4                      | 145            | 145                           | 88                    | E-4        |                   | 23.5                   | 70105                            | 60760 | 60760 | 60760 | 60760 | 60760 |

# NOKIAN TYRES HTS G2 L-4S

## HARD-WEARING REACH STACKER TIRE WITH SLICK, SMOOTH TREAD

- Deep, long-lasting smooth tread for extensive tire service life and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 18.00-25 - T445638
- 18.00-33 - T445663

# NOKIAN TYRES HTS G2 L-4S

## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity for load wheel, lb |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)                      |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                                | creep | 2.5   | 5     | 12    | 15    |
| T445638      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 21.2       | 65.6          | 30.3                      | 196.9                      | 145            | 145                           | 74                    | L-4S       | T55831            | 23.5                   | 57870                            | 50155 | 50155 | 50155 | 50155 | 50155 |
| T445663      | 18.00-33 | 214A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF            | 20.4       | 73.2          | 33.4                      | 223.1                      | 145            | 145                           | 76                    | L-4S       |                   | 23.5                   | 70105                            | 60760 | 60760 | 60760 | 60760 | 60760 |

# NOKIAN TYRES HTS G2 L-5S

**LONG-LASTING FRONT TIRE FOR REACH STACKERS – THE SMOOTH, EXTRA-DEEP TREAD OFFERS MORE WORKING HOURS**

- Extra-deep, long-lasting smooth tread increases tread durability and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 18.00-25 - T445805



# NOKIAN TYRES HTS G2 L-5S

## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity for load wheel, lb |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)                      |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                                | creep | 2.5   | 5     | 12    | 15    |
| T445805      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 20.6       | 65.7          | 29.3                      | 198.1                      | 145            | 145                           | 100                   | L-5S       | T55831            | 23.5                   | 57870                            | 50155 | 50155 | 50155 | 50155 | 50155 |

# NOKIAN TYRES ARMOR GARD

## LONG SERVICE LIFE FOR MATERIAL HANDLING MACHINES AND LOADERS

- Strong tire carcass enables precise steering and stability.
- Special rubber compound optimized for harbor use gives an excellent service life.
- Sturdy structure enables long service life as well as great retreading properties.



2026-05-24



## AVAILABLE SIZES

- 12.00-20 - T445459

# NOKIAN TYRES ARMOR GARD


## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | TL/TT | Rim | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity for load wheel, lb |       |       |       |       |       |
|--------------|----------|---------------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |               |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)                      |       |       |       |       |       |
|              |          |               |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                                | creep | 2.5   | 5     | 12    | 15    |
| T445459      | 12.00-20 | 176A5 (176A5) | 20         | TT    | 8.5 | 9.0            | 13         | 45.2          | 20.5                      | 135.1                      | 145            | 145                           | 32                    | E-2        | T52810            | 14.9                   | 23635                            | 20350 | 20350 | 20350 | 20350 | 20350 |

# NOKIAN TYRES RTG

## MORE AGILITY AND DURABILITY FOR THE RTG CRANES

- Tread pattern and tire shape that allow the wheel to turn more easily.
- Low heat build-up slows down tire wear and gives it more operating hours.
- Special rubber compound optimized for harbour use.



### AVAILABLE SIZES

- 14.00-24 - T445471

# NOKIAN TYRES RTG


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim    | Permitted rims   | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |
|--------------|----------|-------|------------|-------|--------|------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|-------|
|              |          |       |            |       |        |                  |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |       |       |       |       |
|              |          |       |            |       |        |                  |            |               |                           |                            |                |                               |                       |            |                   |                        | 0                 | 2.5   | 5     | 12    | 15    |
| T445471      | 14.00-24 | 188A5 | 28         | TL    | 10.00W | 10.00WA, 10.00VA | 15.4       | 53.7          | 24.8                      | 163.3                      | 145            | 145                           | 29                    | E-2        | T55767            | 17.7                   | 33070             | 28660 | 28660 | 28660 | 28660 |

# NOKIAN TYRES HTS TUGGER

## MASSIVE LOAD CAPACITY FOR TERMINAL TRACTORS

- Sturdy multi-layer structure enables exceptional load-bearing capacity.
- Optimized for predictable handling.
- Designed to be as low as possible without compromising other qualities, making it ideal for terminal tractor use.



## AVAILABLE SIZES

- 315/60R22.5 - T445221

# NOKIAN TYRES HTS TUGGER


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|-------------|-------|-----------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |             |       |                 |       |      |                |            |               |                           |                            |                |                               |                       |            |                        | Speed (mph)       |       |       |       |       |       |
|              |             |       |                 |       |      |                |            |               |                           |                            |                |                               |                       |            |                        | creep             | 2.5   | 5     | 12    | 15    | 22.5  |
| T445221      | 315/60R22.5 | 174A5 | SB              | TL    | 9.00 | 9.75           | 11.9       | 37.3          | 16.7                      | 113.8                      | 145            | 145                           | 26                    | IND-3      | 14.8                   | 19200             | 19200 | 19200 | 16625 | 16625 | 14770 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size     | LI/SS        | Ply rating | TL/TT | Rim | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |      |      |      |      |      |
|--------------|----------|--------------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|------|------|------|------|------|
|              |          |              |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |      |      |      |      |      |
|              |          |              |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | 15                | 17.5 | 22.5 | 25   | 27.5 | 30   |
| T445649      | 10.00-20 | 148B (164A5) | 16         | TT    | 7.5 | 8.0            | 11.1       | 42            | 19.7                      | 124.9                      | 109            | 131                           | 26                    | E-2        | T52620            | 13.1                   | 8820              | 8475 | 8125 | 7705 | 7365 | 6945 |
| T445650      | 11.00-20 | 151B (170A5) | 16         | TT    | 8.0 | 8.5            | 12         | 43.5          | 20.4                      | 132.3                      | 109            | 131                           | 29                    | E-2        | T52720            | 13.9                   | 9655              | 9280 | 8895 | 8445 | 8060 | 7605 |

# EARTHMOVING AND ROAD MAINTENANCE TIRES

## WHEEL LOADER



85  
Nokian Tyres  
Ground King  
Loader



87  
Nokian Tyres  
Hakkapeliitta  
Loader



89  
Nokian Tyres  
Loader Grip



91  
Nokian Tyres  
Loader Grip 2

## BACKHOE LOADER



93  
Nokian Tyres  
Ground Kare



95  
Nokian Tyres  
Ground Kare  
Semi-Slick

## ROAD GRADER



87  
Nokian Tyres  
Hakkapeliitta  
Loader

## WHEELED EXCAVATOR



97  
Nokian Tyres  
Armor Gard 2



99  
Nokian Tyres  
Excavator




93  
Nokian Tyres  
Ground Kare

# NOKIAN TYRES GROUND KING LOADER

## STABLE AND VERSATILE LOADER TIRE WITH EXCELLENT SOFT SOIL GRIP AND ROAD HANDLING

- The Hybrilug™ technology combines the advantages of block and lug pattern, enabling smooth and silent ride on various terrains.
- Excellent self-cleaning properties improve grip for increased productivity on soft soil.
- Accurate, stable and comfortable working is ensured by the strong radial carcass with tough shoulders.



### AVAILABLE SIZES

- 20.5R25 - T445796

# NOKIAN TYRES GROUND KING LOADER


## ALL SIZES

| Product code | Size    | LI/SS | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims         | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | Load capacity, lb |       |       |       |       |       |
|--------------|---------|-------|------------|-----------------|-------|-----------|------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |         |       |            |                 |       |           |                        |            |               |                           |                            |                |                               |                       |            |                        | Speed (mph)       |       |       |       |       |       |
|              |         |       |            |                 |       |           |                        |            |               |                           |                            |                |                               |                       |            |                        | 12                | 15    | 17.5  | 22.5  | 25    | 30    |
| T445796      | 20.5R25 | 186A2 | ★          | SB              | TL    | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7 | 20.3       | 58.6          | 25.4                      | 177.4                      | 65             | 65                            | 60                    | L-3        | 24.6                   | 17595             | 16755 | 16125 | 15500 | 14660 | 13195 |

# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL-SEASON WHEEL LOADER TIRE WITH GREAT WINTER GRIP

- Aggressive tread design with dense siping gives you the best possible grip on snow and ice.
- All-new rubber compound and non-directional tire tread design ensure long service life and even wear.
- Re-designed carcass structure gives more lifetime and better stability.



### AVAILABLE SIZES

- 14.00R24 - T445691
- 17.5R25 - T445590
- 20.5R25 - T445591
- 23.5R25 - T445592



# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL SIZES FOR ROAD GRADER

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim    | Permitted rims           | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | M+S | Load capacity, lb |      |      |      |      |
|--------------|----------|---------------|------------|-----------------|-------|--------|--------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-----|-------------------|------|------|------|------|
|              |          |               |            |                 |       |        |                          |            |               |                           |                            |                |                               |                       |            |                   |                        |     | Speed (mph)       |      |      |      |      |
|              |          |               |            |                 |       |        |                          |            |               |                           |                            |                |                               |                       |            |                   |                        |     | 0                 | 5    | 12   | 17.5 | 25   |
| T445691      | 14.00R24 | 153A8 (176A2) | ★          | SB              | TL    | 8.00TG | 10.00VA, 10.00WA, 10.00W | 15         | 53.7          | 24.6                      | 163.7                      | 54             | 80                            | 30                    | L-2        | T55767            | 17.1                   | Yes | 8045              | 8045 | 8045 | 8045 | 8045 |

## ALL SIZES FOR WHEEL LOADER

| Product code | Size    | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims             | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | M+S | Load capacity, lb |       |       |       |       |
|--------------|---------|---------------|------------|-----------------|-------|-----------|----------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-----|-------------------|-------|-------|-------|-------|
|              |         |               |            |                 |       |           |                            |            |               |                           |                            |                |                               |                       |            |                   |                        |     | Speed (mph)       |       |       |       |       |
|              |         |               |            |                 |       |           |                            |            |               |                           |                            |                |                               |                       |            |                   |                        |     | 12                | 15    | 17.5  | 22.5  | 25    |
| T445590      | 17.5R25 | 176A2 (153A8) | ★          | SB              | TL    | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 17.3       | 52.9          | 23.3                      | 160.6                      | 65             | 65                            | 35                    | L-2        | T55867            | 21                     | Yes | 13150             | 12520 | 12050 | 11585 | 10955 |
| T445591      | 20.5R25 | 186A2 (168B)  | ★          | SB              | TL    | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7     | 21.2       | 58.5          | 25.6                      | 177.5                      | 65             | 65                            | 40                    | L-2        |                   | 24.6                   | Yes | 17595             | 16755 | 16125 | 15500 | 14660 |
| T445592      | 23.5R25 | 195A2 (176B)  | ★          | SB              | TL    | 19.50/2.5 | 19.50/2.5IF                | 24.2       | 63.4          | 27.4                      | 190.9                      | 65             | 65                            | 44                    | L-2        |                   | 28.2                   | Yes | 22500             | 21430 | 20625 | 19820 | 18750 |

# NOKIAN TYRES LOADER GRIP

## STURDY GRIP FOR WHEEL LOADERS AND EARTHMOVING MACHINES

- Sturdy, hard-wearing structure for excellent mileage.
- Comfortable driving response for efficient working.
- Good winter grip makes the tire highly suitable for year-round use.



### AVAILABLE SIZES

- 17.5R25 - T445255
- 20.5R25 - T445171
- 23.5R25 - T445223



# NOKIAN TYRES LOADER GRIP

## ALL SIZES

| Product code | Size    | LI/SS        | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims             | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | M+S | Load capacity, lb |       |       |       |       |       |
|--------------|---------|--------------|------------|-----------------|-------|-----------|----------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-----|-------------------|-------|-------|-------|-------|-------|
|              |         |              |            |                 |       |           |                            |            |               |                           |                            |                |                               |                       |            |                   |                        |     | Speed (mph)       |       |       |       |       |       |
|              |         |              |            |                 |       |           |                            |            |               |                           |                            |                |                               |                       |            |                   |                        |     | 12                | 15    | 17.5  | 22.5  | 25    | 30    |
| T445255      | 17.5R25 | 176A2 (157B) | ★          | SB              | TL    | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 17.7       | 52.8          | 23.4                      | 159.8                      | 65             | 65                            | 35                    | L-3        | T55867            | 21                     | Yes | 13150             | 12520 | 12050 | 11585 | 10955 | 9800  |
| T445171      | 20.5R25 | 186A2 (168B) | ★          | SB              | TL    | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7     | 20.9       | 58.8          | 25.5                      | 177.2                      | 65             | 65                            | 39                    | L-3        |                   | 24.6                   | Yes | 17595             | 16755 | 16125 | 15500 | 14660 | 13100 |
| T445223      | 23.5R25 | 195A2 (176B) | ★          | SB              | TL    | 19.50/2.5 | 19.50/2.5IF                | 24.8       | 63.3          | 27.6                      | 192.1                      | 65             | 65                            | 43                    | L-3        |                   | 28.2                   | Yes | 22500             | 21430 | 20625 | 19820 | 18750 | 16600 |

# NOKIAN TYRES LOADER GRIP 2

## ABSOLUTE GRIP AND DURABILITY FOR WHEEL LOADERS AND ADT MACHINES

- Specially for wheel loaders designed tread blocks create traction on soft gravel and on icy, slippery roads.
- Excellent mileage and sidewall protection against sidewall slashes and abrasions.
- Stability on every terrain due to wide tire contact area and the block-patterned tread.



### AVAILABLE SIZES

- 15.5R25 - T445463



# NOKIAN TYRES LOADER GRIP 2

## ALL SIZES

| Product code | Size    | LI/SS        | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Min. dual spacing (in) | M+S | Load capacity, lb |       |      |      |      |      |
|--------------|---------|--------------|------------|-----------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|------------------------|-----|-------------------|-------|------|------|------|------|
|              |         |              |            |                 |       |           |                |            |               |                           |                            |                |                               |                       |            |                        |     | Speed (mph)       |       |      |      |      |      |
|              |         |              |            |                 |       |           |                |            |               |                           |                            |                |                               |                       |            |                        |     | 12                | 15    | 17.5 | 22.5 | 25   | 30   |
| T445463      | 15.5R25 | 169A2 (152B) | ★          | SB              | TL    | 12.00/1.3 | 13.00/1.4 (DC) | 15.2       | 50.4          | 22.4                      | 153                        | 65             | 65                            | 29                    | L-3        | 18.6                   | Yes | 10735             | 10230 | 9845 | 9460 | 8950 | 8060 |

# NOKIAN TYRES GROUND KARE

## EXCAVATOR AND BACKHOE LOADER TIRE FOR VERSATILE CONTRACTING WORK

- The tread design enables low surface pressure, great traction and smooth, comfortable driving on road.
- The high load-bearing capacity enables the use of heavy auxiliary equipment.
- The special design adds stability by absorbing swings and shocks.



### AVAILABLE SIZES

- 500/45-22.5 - T445868
- 600/40-22.5 - T445828
- 600/50-22.5 - T445798
- 650/45-22.5 - T445664
- 710/40-22.5 - T445799
- 620/60B30 - T445802
- 620/60B34 - T445668



# NOKIAN TYRES GROUND KARE

## ALL SIZES FOR WHEELED EXCAVATOR

| Product code | Size        | LI/SS | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Min. dual spacing (in) | Load capacity for constant load, lb |       |       |       |       |       |
|--------------|-------------|-------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-------------------|------------------------|-------------------------------------|-------|-------|-------|-------|-------|
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   |                        | Speed (mph)                         |       |       |       |       |       |
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   |                        | 15                                  | 17.5  | 22.5  | 25    | 27.5  | 30    |
| T445868      | 500/45-22.5 | 160A8 | 24         | SF              | TL    | AG16.00 | AG18.00        | 19.6       | 40.8          | 18.6                      | 123.1                      | 500 | 87             | 87                            | 30                    | T56435            | 22.3                   | 10515                               | 10320 | 10120 | 9920  | 9525  | 9030  |
| T445828      | 600/40-22.5 | 167A8 | 24         | SF              | TL    | AG20.00 |                | 23         | 41.9          | 19.1                      | 126.2                      | 500 | 87             | 87                            | 31                    | T55089            | 28.4                   | 12730                               | 12500 | 12260 | 12015 | 11530 | 10935 |
| T445798      | 600/50-22.5 | 173A8 | 24         | SF              | TL    | AG20.00 |                | 23.7       | 45.5          | 20.1                      | 137.6                      | 550 | 87             | 87                            | 33                    | T55089            | 28.4                   | 15190                               | 14905 | 14615 | 14330 | 13755 | 13040 |
| T445664      | 650/45-22.5 | 175A8 | 24         | SF              | TL    | AG22.00 | AG20.00        | 26.1       | 45.1          | 20.6                      | 137.5                      | 550 | 87             | 87                            | 33                    | T55092            | 30.5                   | 16125                               | 15820 | 15520 | 15210 | 14605 | 13845 |
| T445799      | 710/40-22.5 | 173A8 | 24         | SF              | TL    | AG24.00 |                | 27.5       | 45.1          | 19.9                      | 136.9                      | 550 | 80             | 80                            | 33                    | T55092            | 34.3                   | 15190                               | 14905 | 14615 | 14330 | 13755 | 13040 |

## ALL SIZES FOR BACKHOE LOADER

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Load capacity for constant load, lb |       |       |       |       |       |
|--------------|-----------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|-------------------|-------------------------------------|-------|-------|-------|-------|-------|
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                       |                   | Speed (mph)                         |       |       |       |       |       |
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                       |                   | 15                                  | 17.5  | 22.5  | 25    | 27.5  | 30    |
| T445802      | 620/60B30 | 176A8 (173B) | SB              | TL    | DW20B | DW18L          | 24.5       | 59.1          | 26.3                      | 179.5                      | 65             | 65                            | 31                    | T55371            | 16590                               | 16280 | 15960 | 15655 | 15025 | 14240 |
| T445668      | 620/60B34 | 178A8 (175B) | SB              | TL    | DW20B | DW18L          | 24.8       | 63.3          | 29.5                      | 193.2                      | 65             | 65                            | 31                    | T55395            | 17525                               | 17195 | 16865 | 16535 | 15875 | 15045 |

# NOKIAN TYRES GROUND KARE SEMI-SLICK

## EXTENDED SERVICE LIFE AND STABILITY FOR RAILWAY USE

- The unique structure of the Nokian Tyres Ground Kare Semi-Slick tire has been optimized to offer a much longer service life than regular backhoe loader tires.
- With stable, shock absorbing structure and high load-bearing capacity, Nokian Tyres Ground Kare Semi-Slick tire gives digging work a stable foundation and enables the use of heavy work attachments.
- Its tread pattern with larger blocks in the center makes driving more comfortable, and the stable structure improves the overall handling of the backhoe loader.



## AVAILABLE SIZES

- 620/60B34 - T445688



# NOKIAN TYRES GROUND KARE SEMI-SLICK


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Load capacity for constant load, lb |       |       |       |       |       |
|--------------|-----------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|-------------------|-------------------------------------|-------|-------|-------|-------|-------|
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                       |                   | Speed (mph)                         |       |       |       |       |       |
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                       |                   | 15                                  | 17.5  | 22.5  | 25    | 27.5  | 30    |
| T445688      | 620/60B34 | 178A8 (175B) | SB              | TL    | DW20B | DW18L          | 24.8       | 63.3          | 29.5                      | 193                        | 65             | 65                            | 31                    | T55395            | 17525                               | 17195 | 16865 | 16535 | 15875 | 15045 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size     | LI/SS        | Ply rating | TL/TT | Rim | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tread code | Tube product code | Min. dual spacing (in) | Load capacity, lb |      |      |      |      |      |
|--------------|----------|--------------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|------------|-------------------|------------------------|-------------------|------|------|------|------|------|
|              |          |              |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | Speed (mph)       |      |      |      |      |      |
|              |          |              |            |       |     |                |            |               |                           |                            |                |                               |                       |            |                   |                        | 15                | 17.5 | 22.5 | 25   | 27.5 | 30   |
| T445649      | 10.00-20 | 148B (164A5) | 16         | TT    | 7.5 | 8.0            | 11.1       | 42            | 19.7                      | 124.9                      | 109            | 131                           | 26                    | E-2        | T52620            | 13.1                   | 8820              | 8475 | 8125 | 7705 | 7365 | 6945 |
| T445650      | 11.00-20 | 151B (170A5) | 16         | TT    | 8.0 | 8.5            | 12         | 43.5          | 20.4                      | 132.3                      | 109            | 131                           | 29                    | E-2        | T52720            | 13.9                   | 9655              | 9280 | 8895 | 8445 | 8060 | 7605 |

# NOKIAN TYRES EXCAVATOR

## EXCAVATOR TIRE FOR SOFT SURFACES

- Excellent self-cleaning properties with curvy lug design improve traction on soft surfaces.
- High load-bearing capacity and improved stability.
- Steel fortified against punctures with a reinforced shoulder for a long service life.



## AVAILABLE SIZES

- 600/50-22.5 - T445604
- 710/40-22.5 - T445606
- 650/45-22.5 - T445605

# NOKIAN TYRES EXCAVATOR

## ALL SIZES

| Product code | Size        | LI/SS | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | SRI | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | Min. dual spacing (in) | Load capacity for constant load, lb |       |       |       |       |       |
|--------------|-------------|-------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|-----------------------|-------------------|------------------------|-------------------------------------|-------|-------|-------|-------|-------|
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   |                        | Speed (mph)                         |       |       |       |       |       |
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                       |                   |                        | 15                                  | 17.5  | 22.5  | 25    | 27.5  | 30    |
| T445604      | 600/50-22.5 | 173A8 | 24         | SF              | TL    | AG20.00 |                | 23         | 45.2          | 20.4                      | 139                        | 550 | 87             | 87                            | 50                    | T55089            | 28.4                   | 15190                               | 14905 | 14615 | 14330 | 13755 | 13040 |
| T445605      | 650/45-22.5 | 175A8 | 24         | SF              | TL    | AG22.00 | AG20.00        | 25.3       | 45.2          | 20.3                      | 138.8                      | 550 | 87             | 87                            | 50                    | T55092            | 30.5                   | 16125                               | 15820 | 15520 | 15210 | 14605 | 13845 |
| T445606      | 710/40-22.5 | 173A8 | 24         | SF              | TL    | AG24.00 |                | 27         | 45.4          | 20.4                      | 138.8                      | 550 | 80             | 80                            | 50                    | T55092            | 34.3                   | 15190                               | 14905 | 14615 | 14330 | 13755 | 13040 |

# ALL TERRAIN TRUCKS AND MILITARY VEHICLES TIRES

## ALL-TERRAIN TRUCK, MILITARY VEHICLE



102

**Nokian Tyres  
MPT Agile**




104

**Nokian Tyres  
MPT Agile 2**

# NOKIAN TYRES MPT AGILE

## ON AND OFF ROAD AGILITY

- The open arrow-shaped tread pattern ensures good self-cleaning, ensuring grip under demanding circumstances.
- Improved grip on soft surfaces such as mud and snow.
- Exceptional mobility.



## AVAILABLE SIZES

- 365/80R20 - T445431

# NOKIAN TYRES MPT AGILE


## ALL SIZES

| Product code | Size      | LI/SS | Reinforced code | TL/TT | Rim | Permitted rims     | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | M+S | Load capacity for highway service, lb |      |      |      |      |      |
|--------------|-----------|-------|-----------------|-------|-----|--------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|-----|---------------------------------------|------|------|------|------|------|
|              |           |       |                 |       |     |                    |            |               |                           |                            |                |                               |                       |     | Speed (mph)                           |      |      |      |      |      |
|              |           |       |                 |       |     |                    |            |               |                           |                            |                |                               |                       |     | 25                                    | 30   | 37.5 | 42.5 | 50   | 55   |
| T445431      | 365/80R20 | 152G  | SB              | TL    | 11  | 11 SDC, 12, 12 SDC | 14.2       | 43            | 19.9                      | 131.6                      | 91             | 91                            | 25                    | Yes | 8380                                  | 8225 | 8225 | 8225 | 8135 | 7825 |

# NOKIAN TYRES MPT AGILE 2

## NEW GENERATION TIRE FOR SPECIAL ON AND OFF ROAD VEHICLES

- Improved grip on soft surfaces such as mud and snow.
- Good steering response and stable handling on different terrains and speeds.
- Symmetrical tread pattern is designed to perform equally well regardless of the tires' rotational direction.



### AVAILABLE SIZES

- 14.00R20 - T445651

# NOKIAN TYRES MPT AGILE 2

## ALL SIZES

| Product code | Size     | LI/SS | Reinforced code | TL/TT | Rim    | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Max. inflation pressure (psi) | Tread depth (1/32 in) | Tube product code | M+S | Load capacity for highway service, lb |       |       |       |       |       |
|--------------|----------|-------|-----------------|-------|--------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|-----------------------|-------------------|-----|---------------------------------------|-------|-------|-------|-------|-------|
|              |          |       |                 |       |        |                |            |               |                           |                            |                |                               |                       |                   |     | Speed (mph)                           |       |       |       |       |       |
|              |          |       |                 |       |        |                |            |               |                           |                            |                |                               |                       |                   |     | 25                                    | 30    | 37.5  | 42.5  | 50    | 55    |
| T445651      | 14.00R20 | 164G  | SB              | TL    | 10.00V | 10.00W         | 15.7       | 49.8          | 23.1                      | 157                        | 110            | 110                           | 31                    | T52920            | Yes | 11795                                 | 11575 | 11575 | 11575 | 11465 | 11025 |

# TRUCKS AND BUSES TIRES

## STEER



**107**  
Nokian Tyres  
Hakkapeliitta  
City Bus



**110**  
Nokian Tyres  
Hakkapeliitta  
Truck F2



**113**  
Nokian Tyres  
Hakka City Bus



**115**  
Nokian Tyres  
Hakka Truck  
Coach



**117**  
Nokian Tyres  
Hakka Truck  
Steer



**120**  
Nokian Tyres  
Hakka Truck  
Steer 2



**122**  
Nokian Tyres  
E-Truck Steer



**125**  
Nokian Tyres  
E-Truck Steer  
17.5



**127**  
Nokian Tyres  
E-Truck Steer  
19.5



**129**  
Nokian Tyres  
R-Truck Steer

## DRIVE



**131**  
Nokian Tyres  
Hakkapeliitta  
Truck D



**133**  
Nokian Tyres  
Hakkapeliitta  
Truck D2



**135**  
Nokian Tyres  
Hakkapeliitta  
Truck E2



**138**  
Nokian Tyres  
Hakka Truck  
Drive



**141**  
Nokian Tyres  
Hakka Truck  
Drive 2



**143**  
Nokian Tyres  
E-Truck Drive



**146**  
Nokian Tyres  
E-Truck Drive  
17.5



**148**  
Nokian Tyres  
E-Truck Drive  
19.5



**150**  
Nokian Tyres  
R-Truck Drive

## TRAILER



**152**  
Nokian Tyres  
Hakkapeliitta  
Truck T



**154**  
Nokian Tyres  
Hakka Truck  
844+



**156**  
Nokian Tyres  
Hakka Truck  
Trailer



**158**  
Nokian Tyres  
Hakka Truck  
Trailer 2



**160**  
Nokian Tyres  
E-Truck  
Trailer




**164**  
Nokian Tyres  
R-Truck  
Trailer

# NOKIAN TYRES HAKKAPELIITTA CITY BUS

## WINTER TIRE FOR CITY BUSES – DURABILITY AND EXCELLENT GRIP IN URBAN WINTER CONDITIONS

- Excellent winter grip in urban conditions.
- Reinforced sidewalls protect the tire against curbs.
- Siping designed for minimal heel/toe wear.



### AVAILABLE SIZES

- 275/70R22.5 - T675218
- 275/70R22.5 - T675330
- 295/80R22.5 - T675240
- 295/80R22.5 - T675356

# NOKIAN TYRES HAKKAPELIITTA CITY BUS

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675218      | 275/70R22.5 | 150/148J (152/148E) | TL    | 8.25 | 7.50           | 10.8       | 38.1          | 17.9                      | 115.9                      | 131            | 26                    | 12.2                   | D                  | B        | B           | 72         | Yes | Yes                       |
| T675330      | 275/70R22.5 | 152/149J (150/148K) | TL    | 8.25 | 7.50           | 11.1       | 38.2          | 17.7                      | 115                        | 131            | 26                    | 12.2                   | D                  | B        | A           | 70         | Yes | Yes                       |
| T675240      | 295/80R22.5 | 152/148J (154/150E) | TL    | 9.00 | 8.25           | 11.7       | 41.1          | 19.3                      | 126.1                      | 123            | 21                    | 13.2                   | D                  | B        | B           | 75         | Yes | Yes                       |
| T675356      | 295/80R22.5 | 154/149J            | TL    | 9.00 | 8.25           | 11.9       | 41.6          | 19.3                      | 125.4                      | 123            | 23                    | 13.2                   | C                  | B        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675218      | 275/70R22.5 | Single  | 42.5                   | 12060   | 12435 | 12810 | 13160 | 13535 | 13890 | 14240 | 14595 | 14945 | 15300 | 15655 |
|              |             | Dual    | 42.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
|              |             | Single  | 62.5                   | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 62.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675330      | 275/70R22.5 | Single  | 62.5                   | 12060   | 12435 | 12810 | 13160 | 13535 | 13890 | 14240 | 14595 | 14945 | 15300 | 15655 |
|              |             | Dual    | 62.5                   | 22090   | 22775 | 23435 | 24120 | 24780 | 25420 | 26080 | 26740 | 27380 | 28020 | 28660 |
|              |             | Single  | 67.5                   | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 67.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675240      | 295/80R22.5 | Single  | 42.5                   | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 42.5                   | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
|              |             | Single  | 62.5                   | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 62.5                   | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675356      | 295/80R22.5 | Single  | 62.5                   | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |     |     |
|--------------|------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
|              |      |         |                 | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127 | 131 |
|              |      | Dual    | 62.5<br>mph     | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |     |     |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.


# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## WINTER STEER AXLE TIRE - GRIP FOR DEMANDING WINTER CONDITIONS IN REGIONAL AND LONG-DISTANCE TRANSPORT

- Aggressive pattern, deep grooves and a new shoulder design enable reference-level grip and good self-cleaning.
- Improved Spiral Sipe System keeps the siping effective even when the tire wears down.
- New, large stone ejectors protect the tire from stone trapping.



2026-05-24



## AVAILABLE SIZES

- 295/80R22.5 - T675041
- 295/80R22.5 - T675310
- 315/70R22.5 - T675040
- 315/70R22.5 - T675300
- 315/80R22.5 - T675039
- 315/80R22.5 - T675319
- 385/55R22.5 - T675276
- 385/55R22.5 - T675311
- 385/65R22.5 - T675038
- 385/65R22.5 - T675237
- 385/65R22.5 - T675291

# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675041      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 11.7       | 41.5          | 19.3                      | 126.1                      | 123            | 19                    | 13.2                   | D                  | B        | A           | 71         | Yes | Yes                       |
| T675310      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 12         | 41.5          | 19.2                      | 125.4                      | 123            | 19                    | 13.2                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675040      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.3       | 40.2          | 18.5                      | 122.2                      | 131            | 18                    | 13.8                   | D                  | C        | A           | 71         | Yes | Yes                       |
| T675300      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.2       | 39.8          | 18.3                      | 121.8                      | 131            | 18                    | 13.8                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675039      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.3       | 42.4          | 19.7                      | 129                        | 123            | 20                    | 13.8                   | D                  | B        | B           | 73         | Yes | Yes                       |
| T675319      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.2       | 42.8          | 19.8                      | 129.2                      | 123            | 20                    | 13.8                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675276      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 15         | 39.5          | 18.4                      | 120                        | 131            | 17                    |                        | C                  | B        | B           | 73         | Yes | Yes                       |
| T675311      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 14.9       | 39.1          | 18                        | 118.8                      | 131            | 20                    |                        | C                  | A        | A           | 71         | Yes | Yes                       |
| T675038      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 14.8       | 42.8          | 19.8                      | 130                        | 131            | 20                    |                        | E                  | B        | B           | 73         | Yes | Yes                       |
| T675237      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 15         | 42.7          | 19.7                      | 129.7                      | 131            | 20                    |                        | C                  | B        | B           | 75         | Yes | Yes                       |
| T675291      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 15.2       | 42.3          | 19.4                      | 127.9                      | 131            | 20                    |                        | C                  | A        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | mph   | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   |
| T675041      | 295/80R22.5 | Single  | 80              | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80              | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |       |       |
| T675310      | 295/80R22.5 | Single  | 80              | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80              | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |       |       |
| T675040      | 315/70R22.5 | Single  | 75              | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |
|              |             | Dual    | 75              | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80              | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 80              | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675300      | 315/70R22.5 | Single  | 75              | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | mph   | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   |
|              |             | Dual    | 75              | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80              | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80              | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
| T675039      | 315/80R22.5 | Single  | 75              | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75              | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80              | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80              | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
| T675319      | 315/80R22.5 | Single  | 75              | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75              | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
|              |             | Single  | 80              | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80              | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
| T675276      | 385/55R22.5 | Single  | 67.5            | 16005   | 16490 | 17000 | 17460 | 17945 | 18430 | 18895 | 19380 | 19840 |       |       |
|              |             | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675311      | 385/55R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675038      | 385/65R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75              | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |
| T675237      | 385/65R22.5 | Single  | 67.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |
| T675291      | 385/65R22.5 | Single  | 67.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA CITY BUS

## ALL-WEATHER TIRE FOR ALL AXLES – DURABILITY AND ALL-WEATHER PERFORMANCE FOR CITY BUSES

- Specifically designed for the modern urban needs. Increased load capacity.
- Reinforced sidewalls protect the tire against curb.
- Tread pattern for minimal heel/toe wear.



### AVAILABLE SIZES

- 275/70R22.5 - T675318

# NOKIAN TYRES HAKKA CITY BUS

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675318      | 275/70R22.5 | 152/149J (150/148K) | TL    | 8.25 | 7.50           | 11         | 38.1          | 17.6                      | 115                        | 131            | 23                    | 12.2                   | D                  | B        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675318      | 275/70R22.5 | Single  | 62.5                   | 12060   | 12435 | 12810 | 13160 | 13535 | 13890 | 14240 | 14595 | 14945 | 15300 | 15655 |
|              |             | Dual    | 62.5                   | 22090   | 22775 | 23435 | 24120 | 24780 | 25420 | 26080 | 26740 | 27380 | 28020 | 28660 |
|              |             | Single  | 67.5                   | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 67.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |

# NOKIAN TYRES HAKKA TRUCK COACH

## ALL-WEATHER TIRE FOR ALL AXLES – CONFIDENT GRIP AND COMFORT FOR LONG-DISTANCE BUSES

- Grip-improving siping with unique activators and optimized open pattern design.
- Rubber compound and tread pattern optimized for smooth, quiet rides.
- Long service life and even wear pattern. Rock Resistor grooves prevent stone trapping.



### AVAILABLE SIZES

- 295/80R22.5 - T675271
- 315/80R22.5 - T675272
- 295/80R22.5 - T675355



# NOKIAN TYRES HAKKA TRUCK COACH

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675271      | 295/80R22.5 | 154/149M | TL    | 9.00 | 8.25           | 11.7       | 41.5          | 19.3                      | 126.3                      | 123            | 20                    | 13.2                   | D                  | C        | A           | 70         | Yes | Yes                       |
| T675355      | 295/80R22.5 | 154/150M | TL    | 9.00 | 8.25           | 11.9       | 41.5          | 19.3                      | 125.4                      | 123            | 20                    | 13.2                   | C                  | A        | A           | 71         | Yes | Yes                       |
| T675272      | 315/80R22.5 | 156/150L | TL    | 9.00 | 9.75           | 12.4       | 42.4          | 19.7                      | 129                        | 123            | 20                    | 13.8                   | C                  | C        | A           | 69         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   |
| T675271      | 295/80R22.5 | Single  | 80                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |
|              |             | Dual    | 80                     | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |
| T675355      | 295/80R22.5 | Single  | 80                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |
|              |             | Dual    | 80                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |
| T675272      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL-WEATHER STEER AXLE TIRE - EXCELLENT MILEAGE FOR REGIONAL TRANSPORT

- Wide, slow-wearing tread for excellent mileage.
- New kind of sipe activators improve grip on snowy and wet surfaces.
- Stone ejectors protect the tire from stone trapping.



### AVAILABLE SIZES

- 295/80R22.5 - T675221
- 315/60R22.5 - T675249
- 315/70R22.5 - T675220
- 315/70R22.5 - T675302
- 315/80R22.5 - T675214
- 385/55R22.5 - T675241
- 385/65R22.5 - T675222

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675221      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 11.7       | 41.2          | 19.2                      | 125.3                      | 123            | 20                    | 13.2                   | D                  | B        | A           | 70         | Yes | Yes                       |
| T675249      | 315/60R22.5 | 154/148L            | TL    | 9.00  | 9.75           | 12.4       | 37.8          | 17.7                      | 114.8                      | 131            | 16                    | 13.5                   | C                  | B        | B           | 72         | Yes | Yes                       |
| T675220      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.3       | 40.2          | 18.5                      | 122.2                      | 131            | 18                    | 13.8                   | C                  | B        | A           | 70         | Yes | Yes                       |
| T675302      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.3       | 39.8          | 18.3                      | 121.8                      | 131            | 18                    | 13.8                   | C                  | B        | A           | 70         | Yes | Yes                       |
| T675214      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.4       | 42.5          | 19.7                      | 129.1                      | 123            | 20                    | 13.8                   | D                  | B        | A           | 70         | Yes | Yes                       |
| T675241      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 15.1       | 39.6          | 18.4                      | 120.3                      | 131            | 20                    |                        | D                  | C        | A           | 70         | Yes | Yes                       |
| T675222      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 14.8       | 42.6          | 19.7                      | 129.6                      | 131            | 20                    |                        | C                  | B        | A           | 70         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675221      | 295/80R22.5 | Single  | 80                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80                     | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |       |       |
| T675249      | 315/60R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675220      | 315/70R22.5 | Single  | 75                     | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 80                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675302      | 315/70R22.5 | Single  | 75                     | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
|              |             | Dual    | 80                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675214      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
| T675241      | 385/55R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675222      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75                     | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK STEER 2

**ALL-WEATHER STEER AXLE TIRE –  
EXCELLENT HANDLING AND MILEAGE  
FOR LONG DISTANCE AND REGIONAL  
TRANSPORT**

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance
- Unique center tread design with siping in two directions, even wear shape and excellent handling properties
- Deep siping in the center tread maintains grip when the tire wears down



## AVAILABLE SIZES

- 315/60R22.5 - T675325
- 315/70R22.5 - T675316
- 315/80R22.5 - T675348
- 385/55R22.5 - T675349
- 385/65R22.5 - T675354



# NOKIAN TYRES HAKKA TRUCK STEER 2

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675325      | 315/60R22.5 | 154/148L | TL    | 9.00  | 9.75           | 12.5       | 37.5          | 17.4                      | 113.3                      | 131            | 18                    | 13.5                   | C                  | B        | A           | 70         | Yes | Yes                       |
| T675316      | 315/70R22.5 | 156/150L | TL    | 9.00  | 9.75           | 12.3       | 39.8          | 18.4                      | 121.8                      | 131            | 18                    | 13.8                   | C                  | A        | A           | 71         | Yes | Yes                       |
| T675348      | 315/80R22.5 | 156/150L | TL    | 9.00  | 9.75           | 12.4       | 42.7          | 19.8                      | 129.2                      | 123            | 20                    | 13.8                   | C                  | A        | A           | 71         | Yes | Yes                       |
| T675349      | 385/55R22.5 | 160K     | TL    | 11.75 | 12.25          | 14.9       | 39            | 18                        | 118.8                      | 131            | 18                    |                        | C                  | A        | B           | 72         | Yes | Yes                       |
| T675354      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 15.2       | 42.2          | 19.4                      | 127.9                      | 131            | 19                    |                        | B                  | A        | A           | 71         | Yes | Yes                       |


## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | mph   | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   |
| T675325      | 315/60R22.5 | Single  | 75              | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75              | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675316      | 315/70R22.5 | Single  | 75              | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |
|              |             | Dual    | 75              | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675348      | 315/80R22.5 | Single  | 75              | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75              | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
| T675349      | 385/55R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675354      | 385/65R22.5 | Single  | 67.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

# NOKIAN TYRES E-TRUCK STEER

## ALL-SEASON STEER AXLE TIRE – GOOD GRIP AND MILEAGE FOR REGIONAL TRANSPORTS

- New type of zigzag-shaped grooves prevent stone trapping.
- Even wear pattern for good mileage.
- Spiral Sipe System adds grip on all roads.



### AVAILABLE SIZES

- 295/80R22.5 - T675226
- 295/80R22.5 - T675336
- 315/70R22.5 - T675223
- 315/70R22.5 - T675297
- 315/80R22.5 - T675219
- 315/80R22.5 - T675308
- 385/55R22.5 - T675248
- 385/55R22.5 - T675333
- 385/65R22.5 - T675247
- 385/65R22.5 - T675332

# NOKIAN TYRES E-TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675226      | 295/80R22.5 | 152/148M            | TL    | 9.00  | 8.25           | 11.7       | 41.1          | 19.2                      | 124.9                      | 123            | 17                    | 13.2                   | C                  | B        | A           | 70         | Yes | Yes                       |
| T675336      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 11.9       | 41.3          | 18                        | 126.5                      | 123            | 18                    | 13.2                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675223      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00  | 9.75           | 12.5       | 40.1          | 18.6                      | 121.9                      | 131            | 17                    | 13.8                   | C                  | A        | A           | 70         | Yes | Yes                       |
| T675297      | 315/70R22.5 | 156/150L            | TL    | 9.00  | 9.75           | 12.2       | 40            | 18.5                      | 121.9                      | 131            | 20                    | 13.8                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675219      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 12.4       | 42.2          | 19.6                      | 128.1                      | 123            | 18                    | 13.8                   | C                  | A        | A           | 69         | Yes | Yes                       |
| T675308      | 315/80R22.5 | 156/150L            | TL    | 9.00  | 9.75           | 12.4       | 42.4          | 19.7                      | 129.8                      | 123            | 19                    | 13.8                   | B                  | B        | A           | 71         | Yes | Yes                       |
| T675248      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 15         | 39.3          | 18.3                      | 119.6                      | 131            | 16                    |                        | B                  | B        | A           | 68         | Yes | Yes                       |
| T675333      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 14.8       | 39.1          | 18                        | 119.7                      | 131            | 18                    |                        | B                  | B        | A           | 70         | Yes | Yes                       |
| T675247      | 385/65R22.5 | 160K                | TL    | 11.75 | 12.25          | 14.9       | 42.4          | 19.6                      | 129                        | 131            | 17                    |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675332      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 14.8       | 42.2          | 19.4                      | 129.2                      | 131            | 18                    |                        | C                  | B        | A           | 70         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675226      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675336      | 295/80R22.5 | Single  | 80                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80                     | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |       |       |
| T675223      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675297      | 315/70R22.5 | Single  | 75                     | 13605   | 14020 | 14420 | 14835 | 15235 | 15655 | 16050 | 16445 | 16845 | 17240 | 17635 |


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675219      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
| T675308      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
| T675248      | 385/55R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675333      | 385/55R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675247      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675332      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL-SEASON STEER AXLE TIRE - STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



### AVAILABLE SIZES

- 215/75R17.5 - T675252
- 235/75R17.5 - T675253
- 215/75R17.5 - T675338
- 235/75R17.5 - T675342

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675252      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 8.4        | 30            | 14.1                      | 91.1                       | 102            | 15                    | 9.4                    | C                  | C        | A           | 70         | Yes | Yes                       |
| T675338      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 8.3        | 30.4          | 14.1                      | 93                         | 102            | 16                    | 9.4                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675253      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 9.4        | 31.1          | 14.6                      | 94.6                       | 112            | 15                    | 10.3                   | C                  | B        | A           | 67         | Yes | Yes                       |
| T675342      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 8.9        | 31.3          | 14.5                      | 95.7                       | 112            | 16                    | 10.3                   | C                  | B        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |       |  |  |  |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|--|
|              |             |         |                        | 73  | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   | 105   | 109   | 112   |  |  |  |
| T675252      | 215/75R17.5 | Single  | 80                     | 5730  | 5950  | 6175  | 6395  | 6635  | 6855  | 7055  | 7275  | 7495  |       |       |       |  |  |  |
|              |             | Dual    | 80                     | 10780   | 11200 | 11640 | 12060 | 12480 | 12895 | 13295 | 13715 | 14110 |       |       |       |  |  |  |
| T675338      | 215/75R17.5 | Single  | 80                     | 5730  | 5950  | 6175  | 6395  | 6635  | 6855  | 7055  | 7275  | 7495  |       |       |       |  |  |  |
|              |             | Dual    | 80                     | 10780   | 11200 | 11640 | 12060 | 12480 | 12895 | 13295 | 13715 | 14110 |       |       |       |  |  |  |
| T675253      | 235/75R17.5 | Single  | 80                     |   |       | 6700  | 6945  | 7185  | 7430  | 7650  | 7895  | 8135  | 8355  | 8600  | 8820  |  |  |  |
|              |             | Dual    | 80                     |   |       | 12745 | 13205 | 13645 | 14110 | 14550 | 14990 | 15455 | 15895 | 16315 | 16755 |  |  |  |
| T675342      | 235/75R17.5 | Single  | 80                     |   |       | 6700  | 6945  | 7185  | 7430  | 7650  | 7895  | 8135  | 8355  | 8600  | 8820  |  |  |  |
|              |             | Dual    | 80                     |   |       | 12745 | 13205 | 13645 | 14110 | 14550 | 14990 | 15455 | 15895 | 16315 | 16755 |  |  |  |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL-SEASON STEER AXLE TIRE – STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



### AVAILABLE SIZES

- 265/70R19.5 - T675263
- 285/70R19.5 - T675262
- 265/70R19.5 - T675343
- 285/70R19.5 - T675344

# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675263      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 9.9        | 33.8          | 15.7                      | 102.8                      | 112            | 16                    | 11.6                   | C                  | B        | A           | 68         | Yes | Yes                       |
| T675343      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 10.2       | 33.9          | 15.7                      | 103.9                      | 112            | 16                    | 11.6                   | C                  | B        | A           | 71         | Yes | Yes                       |
| T675262      | 285/70R19.5 | 145/143M | TL    | 8.25 | 9.00           | 10.6       | 34.9          | 16.1                      | 106.1                      | 123            | 17                    | 12.5                   | C                  | C        | A           | 67         | Yes | Yes                       |
| T675344      | 285/70R19.5 | 146/144L | TL    | 8.25 | 9.00           | 10.9       | 35.2          | 16.3                      | 107.8                      | 131            | 17                    | 12.5                   | C                  | B        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 80  | 83    | 87    | 91    | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675263      | 265/70R19.5 | Single  | 80                     | 8380  | 8685  | 8975  | 9280  | 9570  | 9875  | 10165 | 10450 | 10735 | 11025 |       |       |       |       |       |
|              |             | Dual    | 80                     | 15805   | 16380 | 16955 | 17525 | 18080 | 18630 | 19180 | 19730 | 20285 | 20810 |       |       |       |       |       |
| T675343      | 265/70R19.5 | Single  | 80                     | 8380  | 8685  | 8975  | 9280  | 9570  | 9875  | 10165 | 10450 | 10735 | 11025 |       |       |       |       |       |
|              |             | Dual    | 80                     | 15805   | 16380 | 16955 | 17525 | 18080 | 18630 | 19180 | 19730 | 20285 | 20810 |       |       |       |       |       |
| T675262      | 285/70R19.5 | Single  | 80                     |   |       | 9680  | 10010 | 10320 | 10625 | 10955 | 11265 | 11575 | 11885 | 12190 | 12480 | 12785 |       |       |
|              |             | Dual    | 80                     |   |       | 18190 | 18785 | 19380 | 19975 | 20570 | 21165 | 21740 | 22310 | 22885 | 23455 | 24030 |       |       |
| T675344      | 285/70R19.5 | Single  | 75                     |   |       | 9570  | 9875  | 10185 | 10515 | 10825 | 11135 | 11440 | 11730 | 12035 | 12345 | 12630 | 12940 | 13230 |
|              |             | Dual    | 75                     |   |       | 17855 | 18455 | 19025 | 19620 | 20195 | 20770 | 21340 | 21915 | 22465 | 23040 | 23590 | 24140 | 24690 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK STEER

## STEER AXLE TIRE – CONTROLLED STEERING FOR ON/OFF-ROAD USE

- Stone ejectors in the main grooves prolong operating life especially on rough surfaces.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.



## AVAILABLE SIZES

- 315/80R22.5 - T675238
- 315/80R22.5 - T675331
- 385/65R22.5 - T675239
- 385/65R22.5 - T675260
- 385/65R22.5 - T675313

# NOKIAN TYRES R-TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675238      | 315/80R22.5 | 156/150K | TL    | 9.00  | 9.75           | 12.2       | 42.6          | 19.8                      | 129.5                      | 120            | 20                    | 13.8                   | C                  | B        | A           | 70         | Yes | Yes                       |
| T675331      | 315/80R22.5 | 156/150K | TL    | 9.00  | 9.75           | 12.2       | 43.1          | 20                        | 129.2                      | 123            | 20                    | 13.8                   | C                  | A        | A           | 71         | Yes | Yes                       |
| T675239      | 385/65R22.5 | 160K     | TL    | 11.75 | 12.25          | 14.9       | 42.8          | 19.8                      | 130                        | 131            | 20                    |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675260      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 15         | 42.8          | 19.8                      | 130                        | 131            | 20                    |                        | C                  | C        | A           | 70         | Yes | Yes                       |
| T675313      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 15.2       | 42.2          | 19.4                      | 127.9                      | 131            | 20                    |                        | C                  | A        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |  |  |  |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|--|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |  |  |  |
| T675238      | 315/80R22.5 | Single  | 67.5                   | 14575   | 15015 | 15455 | 15895 | 16335 | 16775 | 17220 | 17635 |       |       |       |  |  |  |
|              |             | Dual    | 67.5                   | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |  |  |  |
| T675331      | 315/80R22.5 | Single  | 67.5                   | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |  |  |  |
|              |             | Dual    | 67.5                   | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |  |  |  |
| T675239      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |  |  |  |
| T675260      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |  |  |  |
| T675313      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |  |  |  |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK D

## SUPERIOR GRIP AND STABILITY IN THE LONG HAUL

- The deep 3D siping maintains grip even when the tire wears down.
- The patented Twin-Block pattern design ensures superior traction especially on packed snow and icy roads.
- New design with a lower rolling resistance saves fuel and the environment.



### AVAILABLE SIZES

- 275/70R22.5 - T675233
- 295/80R22.5 - T675031
- 315/70R22.5 - T675032
- 315/80R22.5 - T675030



# NOKIAN TYRES HAKKAPELIITTA TRUCK D

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675233      | 275/70R22.5 | 148/145M            | TL    | 8.25 | 7.50           | 10.9       | 37.7          | 17.5                      | 114.6                      | 131            | 20                    | 12.2                   | D                  | B        | B           | 75         | Yes | Yes                       |
| T675031      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 8.25           | 11.7       | 41.9          | 19.5                      | 127.2                      | 123            | 25                    | 13.2                   | D                  | C        | B           | 74         | Yes | Yes                       |
| T675032      | 315/70R22.5 | 152/148M (154/150L) | TL    | 9.00 | 9.75           | 12.4       | 40.6          | 18.7                      | 123.5                      | 123            | 25                    | 13.8                   | D                  | C        | A           | 73         | Yes | Yes                       |
| T675030      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 12.3       | 42.8          | 19.8                      | 130.1                      | 120            | 25                    | 13.8                   | D                  | D        | B           | 76         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675233      | 275/70R22.5 | Single  | 80                     | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 80                     | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675031      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675032      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675030      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK D2

## WINTER DRIVE AXLE TIRE – ENHANCED WEAR RESISTANCE AND GRIP ON WINTER ROADS

- Deeper reach, better worn grip and improved stability due to peg siping and open center tread design.
- Patented Twin-Block pattern design to achieve superior stability and traction especially on packed snow and icy roads.
- New generation of Hakkapeliitta Truck D family with better mileage performance.



## AVAILABLE SIZES

- 295/80R22.5 - T675320
- 315/80R22.5 - T675321
- 315/70R22.5 - T675301

# NOKIAN TYRES HAKKAPELIITTA TRUCK D2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675320      | 295/80R22.5 | 152/148M (154/150L) | TL    | 9.00 | 8.25           | 12         | 41.7          | 19.4                      | 127.2                      | 123            | 25                    | 13.2                   | D                  | B        | A           | 73         | Yes | Yes                       |
| T675301      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 12.3       | 40.2          | 18.6                      | 121.8                      | 131            | 24                    | 13.8                   | D                  | B        | A           | 73         | Yes | Yes                       |
| T675321      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           | 12.2       | 43            | 19.8                      | 129.2                      | 123            | 25                    | 13.8                   | D                  | B        | B           | 75         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675320      | 295/80R22.5 | Single  | 75                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675301      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675321      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
|              |             | Single  | 80                     | 13340   | 13755 | 14155 | 14550 | 14970 | 15365 | 15740 | 16140 | 16535 |       |       |
|              |             | Dual    | 80                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |

# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## WINTER DRIVE AXLE TIRE – SUPERIOR TRACTION AND OPTIMIZED PERFORMANCE ON SEVERE WINTER CONDITIONS

- Deeper reach, better grip when worn and improved stability due to peg siping.
- Consistent rigidity and even wear pattern brought by connected block system.
- Increased tire service life enabled by the open center tread design and extra deep-reaching center sipes.



### AVAILABLE SIZES

- 275/70R22.5 - T675274
- 275/70R22.5 - T675357
- 295/80R22.5 - T675259
- 295/80R22.5 - T675290
- 295/80R22.5 - T675368
- 315/70R22.5 - T675258
- 315/70R22.5 - T675309
- 315/80R22.5 - T675257
- 315/80R22.5 - T675289



# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675274      | 275/70R22.5 | 148/145M            | TL    | 8.25 | 7.50           | 10.5       | 38.1          | 17.7                      | 115.9                      | 131            | 22                    | 12.2                   | E                  | C        | B           | 74         | Yes | Yes                       |
| T675357      | 275/70R22.5 | 148/145M            | TL    | 8.25 | 7.50           | 10.8       | 38.2          | 17.7                      | 115                        | 131            | 22                    | 12.2                   | D                  | A        | B           | 74         | Yes | Yes                       |
| T675259      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 9.75           | 11.7       | 41.9          | 19.5                      | 126.9                      | 123            | 25                    | 13.2                   | D                  | D        | B           | 74         | Yes | Yes                       |
| T675290      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 9.75           | 11.9       | 41.5          | 19.4                      | 125.4                      | 123            | 25                    | 13.2                   | D                  | C        | A           | 73         | Yes | Yes                       |
| T675368      | 295/80R22.5 | 152/149M            | TL    | 9.00 | 9.75           | 11.9       | 41.5          | 19.4                      | 125.4                      | 123            | 25                    | 13.2                   | D                  | C        | A           | 73         | Yes | Yes                       |
| T675258      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 12.4       | 40.4          | 18.7                      | 122.9                      | 131            | 23                    | 13.8                   | D                  | D        | B           | 74         | Yes | Yes                       |
| T675309      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 12.2       | 40.1          | 18.5                      | 121.8                      | 131            | 23                    | 13.8                   | D                  | A        | A           | 73         | Yes | Yes                       |
| T675257      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           | 12.4       | 42.9          | 19.9                      | 130.3                      | 123            | 25                    | 13.8                   | D                  | D        | A           | 73         | Yes | Yes                       |
| T675289      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           | 12.3       | 43.1          | 19.8                      | 129.2                      | 123            | 25                    | 13.8                   | D                  | A        | A           | 73         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675274      | 275/70R22.5 | Single  | 80                     | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 80                     | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675357      | 275/70R22.5 | Single  | 80                     | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 80                     | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675259      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675290      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675368      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 23125   | 23830 | 24535 | 25245 | 25925 | 26610 | 27295 | 27975 | 28660 |       |       |

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675258      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675309      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675257      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
| T675289      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL-WEATHER DRIVE AXLE TIRE - GRIP FOR REGIONAL TRANSPORT

- Open V-shaped tread design with good self-cleaning.
- Optimized tread pattern staggering ensures even wear pattern.
- Effective siping improves grip in both acceleration and braking.



### AVAILABLE SIZES

- 295/60R22.5 - T675250
- 295/80R22.5 - T675034
- 315/60R22.5 - T675251
- 315/70R22.5 - T675036
- 315/70R22.5 - T675303
- 315/80R22.5 - T675035



# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675250      | 295/60R22.5 | 150/147L            | TL    | 9.00 | 9.75           | 11.8       | 36.7          | 17.2                      | 111.4                      | 131            | 19                    | 13                     | D                  | C        | B           | 76         | Yes | Yes                       |
| T675034      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 8.25           | 11.7       | 41.7          | 19.2                      | 126.9                      | 123            | 23                    | 13.2                   | E                  | C        | B           | 75         | Yes | Yes                       |
| T675251      | 315/60R22.5 | 152/148L            | TL    | 9.00 | 9.75           | 12.2       | 37.9          | 17.7                      | 115.2                      | 131            | 20                    | 13.5                   | C                  | C        | B           | 76         | Yes | Yes                       |
| T675036      | 315/70R22.5 | 152/148M (154/150L) | TL    | 9.00 | 9.75           | 12.4       | 40.5          | 18.7                      | 123.1                      | 123            | 23                    | 13.8                   | D                  | C        | B           | 75         | Yes | Yes                       |
| T675303      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 12.3       | 40            | 18.6                      | 121.8                      | 131            | 23                    | 13.8                   | D                  | B        | A           | 72         | Yes | Yes                       |
| T675035      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 12.3       | 42.7          | 19.8                      | 129.8                      | 120            | 23                    | 13.8                   | D                  | C        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675250      | 295/60R22.5 | Single  | 75                     | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 75                     | 20900   | 21540 | 22180 | 22820 | 23435 | 24050 | 24670 | 25285 | 25905 | 26520 | 27115 |
| T675034      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675251      | 315/60R22.5 | Single  | 75                     | 12060   | 12435 | 12810 | 13160 | 13535 | 13890 | 14240 | 14595 | 14945 | 15300 | 15655 |
|              |             | Dual    | 75                     | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675036      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675303      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |     |     |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127 | 131 |
|              |             | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |     |     |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |     |     |
| T675035      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |     |     |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |     |     |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |     |     |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |     |     |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK DRIVE 2

**ALL-WEATHER DRIVE AXLE TIRE –  
ENHANCED GRIP AND EVEN WEAR FOR  
LONG DISTANCE AND REGIONAL  
TRANSPORT**

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance
- Effective deep self-generating siping improves grip in both acceleration and braking
- Optimized tread pattern staggering ensures even wear pattern



## AVAILABLE SIZES

- 295/60R22.5 - T675324
- 315/80R22.5 - T675350
- 315/70R22.5 - T675315



# NOKIAN TYRES HAKKA TRUCK DRIVE 2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675324      | 295/60R22.5 | 150/147L            | TL    | 9.00 | 9.75           | 11.3       | 36.5          | 16.9                      | 110.5                      | 131            | 21                    | 13                     | D                  | A        | A           | 73         | Yes | Yes                       |
| T675315      | 315/70R22.5 | 154/150L            | TL    | 9.00 | 9.75           | 12.2       | 40.1          | 18.6                      | 121.8                      | 131            | 23                    | 13.8                   | D                  | A        | A           | 73         | Yes | Yes                       |
| T675350      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           | 12.4       | 43            | 19.9                      | 129.2                      | 123            | 23                    | 13.8                   | D                  | B        | A           | 73         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675324      | 295/60R22.5 | Single  | 75                     | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 75                     | 20900   | 21540 | 22180 | 22820 | 23435 | 24050 | 24670 | 25285 | 25905 | 26520 | 27115 |
| T675315      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675350      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |

# NOKIAN TYRES E-TRUCK DRIVE

## ALL-SEASON DRIVE AXLE TIRE -RELIABLE TRACTION AND EVEN WEAR FOR REGIONAL TRANSPORT

- Effective block pattern and open center tread design ensure good traction.
- Even wear pattern for a long, trouble-free service life.
- Low rolling resistance and tire noise for fuel economy and comfort.



### AVAILABLE SIZES

- 295/80R22.5 - T675282
- 295/80R22.5 - T675335
- 315/70R22.5 - T675296
- 315/70R22.5 - T675367
- 315/80R22.5 - T675280
- 315/80R22.5 - T675307

# NOKIAN TYRES E-TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675282      | 295/80R22.5 | 152/148M            | TL    | 8.25 |                | 11.7       | 41.5          | 19.3                      | 126.1                      | 123            | 22                    | 13.2                   | D                  | C        | B           | 75         | Yes | Yes                       |
| T675335      | 295/80R22.5 | 152/148M            | TL    | 8.25 |                | 11.9       | 41.7          | 19.4                      | 127.5                      | 123            | 25                    | 13.2                   | D                  | B        | B           | 74         | Yes | Yes                       |
| T675296      | 315/70R22.5 | 154/150L            | TL    | 9.00 | 9.75           | 12.1       | 40.2          | 18.7                      | 122.7                      | 131            | 25                    | 13.8                   | D                  | B        | B           | 74         | Yes | Yes                       |
| T675367      | 315/70R22.5 | 154/150L            | TL    | 9.00 | 9.75           | 12.1       | 40.2          | 18.7                      | 122.7                      | 131            | 25                    | 13.8                   | C                  | B        | B           | 74         | Yes | Yes                       |
| T675280      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 12.4       | 42.4          | 19.8                      | 129.4                      | 120            | 22                    | 13.8                   | D                  | C        | B           | 76         | Yes | Yes                       |
| T675307      | 315/80R22.5 | 156/150L            | TL    | 9.00 | 9.75           | 12.4       | 42.9          | 19.9                      | 131.2                      | 123            | 25                    | 13.8                   | C                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675282      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675335      | 295/80R22.5 | Single  | 80                     | 12630   | 13005 | 13405 | 13780 | 14155 | 14530 | 14905 | 15280 | 15655 |       |       |
|              |             | Dual    | 80                     | 22420   | 23105 | 23790 | 24450 | 25135 | 25795 | 26455 | 27115 | 27780 |       |       |
| T675296      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675367      | 315/70R22.5 | Single  | 75                     | 12745   | 13140 | 13515 | 13910 | 14285 | 14660 | 15060 | 15430 | 15785 | 16160 | 16535 |
|              |             | Dual    | 75                     | 22775   | 23480 | 24165 | 24845 | 25530 | 26215 | 26895 | 27560 | 28220 | 28880 | 29540 |
| T675280      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |       |       |
|              |             | Dual    | 75                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |
|              |             | Single  | 80                     | 13670   | 14090 | 14505 | 14905 | 15320 | 15720 | 16140 | 16535 |       |       |       |
|              |             | Dual    | 80                     | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |       |       |


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |     |     |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127 | 131 |
| T675307      | 315/80R22.5 | Single  | 75                     | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |     |     |
|              |             | Dual    | 75                     | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |     |     |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL-SEASON DRIVE AXLE TIRE - DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and a long tire life.
- Abrasion-resistant rubber compound provides good mileage.



### AVAILABLE SIZES

- 215/75R17.5 - T675255
- 235/75R17.5 - T675256
- 215/75R17.5 - T675337
- 235/75R17.5 - T675339

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675255      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 8.4        | 30            | 14.1                      | 91.3                       | 102            | 17                    | 9.4                    | D                  | D        | A           | 72         | Yes | Yes                       |
| T675337      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 8.2        | 30.5          | 14.2                      | 93.2                       | 102            | 18                    | 9.4                    | D                  | B        | B           | 74         | Yes | Yes                       |
| T675256      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 9.4        | 31.1          | 14.6                      | 94.6                       | 112            | 17                    | 10.3                   | D                  | C        | A           | 72         | Yes | Yes                       |
| T675339      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 9          | 31.5          | 14.6                      | 96.3                       | 112            | 18                    | 10.3                   | D                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |       |  |  |  |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|--|
|              |             |         |                        | 73  | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   | 105   | 109   | 112   |  |  |  |
| T675255      | 215/75R17.5 | Single  | 80                     | 5730  | 5950  | 6175  | 6395  | 6635  | 6855  | 7055  | 7275  | 7495  |       |       |       |  |  |  |
|              |             | Dual    | 80                     | 10780   | 11200 | 11640 | 12060 | 12480 | 12895 | 13295 | 13715 | 14110 |       |       |       |  |  |  |
| T675337      | 215/75R17.5 | Single  | 80                     | 5730  | 5950  | 6175  | 6395  | 6635  | 6855  | 7055  | 7275  | 7495  |       |       |       |  |  |  |
|              |             | Dual    | 80                     | 10780   | 11200 | 11640 | 12060 | 12480 | 12895 | 13295 | 13715 | 14110 |       |       |       |  |  |  |
| T675256      | 235/75R17.5 | Single  | 80                     |   |       | 6700  | 6945  | 7185  | 7430  | 7650  | 7895  | 8135  | 8355  | 8600  | 8820  |  |  |  |
|              |             | Dual    | 80                     |   |       | 12745 | 13205 | 13645 | 14110 | 14550 | 14990 | 15455 | 15895 | 16315 | 16755 |  |  |  |
| T675339      | 235/75R17.5 | Single  | 80                     |   |       | 6700  | 6945  | 7185  | 7430  | 7650  | 7895  | 8135  | 8355  | 8600  | 8820  |  |  |  |
|              |             | Dual    | 80                     |   |       | 12745 | 13205 | 13645 | 14110 | 14550 | 14990 | 15455 | 15895 | 16315 | 16755 |  |  |  |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL-SEASON DRIVE AXLE TIRE - DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and long tire life.
- Abrasion-resistant rubber compound provides good mileage.



### AVAILABLE SIZES

- 265/70R19.5 - T675265
- 285/70R19.5 - T675264
- 265/70R19.5 - T675340
- 285/70R19.5 - T675341

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675265      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 9.9        | 34.1          | 15.7                      | 103.5                      | 112            | 19                    | 11.6                   | D                  | C        | A           | 72         | Yes | Yes                       |
| T675340      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 10.2       | 34.1          | 15.8                      | 104.4                      | 112            | 19                    | 11.6                   | C                  | B        | B           | 74         | Yes | Yes                       |
| T675264      | 285/70R19.5 | 145/143M | TL    | 8.25 | 9.00           | 10.6       | 35            | 16.1                      | 106.4                      | 123            | 18                    | 12.5                   | C                  | C        | A           | 73         | Yes | Yes                       |
| T675341      | 285/70R19.5 | 146/144L | TL    | 8.25 | 9.00           | 11         | 35.4          | 16.4                      | 108.2                      | 131            | 19                    | 12.5                   | C                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 80  | 83    | 87    | 91    | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675265      | 265/70R19.5 | Single  | 80                     | 8380  | 8685  | 8975  | 9280  | 9570  | 9875  | 10165 | 10450 | 10735 | 11025 |       |       |       |       |       |
|              |             | Dual    | 80                     | 15805   | 16380 | 16955 | 17525 | 18080 | 18630 | 19180 | 19730 | 20285 | 20810 |       |       |       |       |       |
| T675340      | 265/70R19.5 | Single  | 80                     | 8380  | 8685  | 8975  | 9280  | 9570  | 9875  | 10165 | 10450 | 10735 | 11025 |       |       |       |       |       |
|              |             | Dual    | 80                     | 15805   | 16380 | 16955 | 17525 | 18080 | 18630 | 19180 | 19730 | 20285 | 20810 |       |       |       |       |       |
| T675264      | 285/70R19.5 | Single  | 80                     |   |       | 9680  | 10010 | 10320 | 10625 | 10955 | 11265 | 11575 | 11885 | 12190 | 12480 | 12785 |       |       |
|              |             | Dual    | 80                     |   |       | 18190 | 18785 | 19380 | 19975 | 20570 | 21165 | 21740 | 22310 | 22885 | 23455 | 24030 |       |       |
| T675341      | 285/70R19.5 | Single  | 75                     |   |       | 9570  | 9875  | 10185 | 10515 | 10825 | 11135 | 11440 | 11730 | 12035 | 12345 | 12630 | 12940 | 13230 |
|              |             | Dual    | 75                     |   |       | 17855 | 18455 | 19025 | 19620 | 20195 | 20770 | 21340 | 21915 | 22465 | 23040 | 23590 | 24140 | 24690 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK DRIVE

## DRIVE AXLE TIRE – DURABILITY FOR DEMANDING ON/OFF-ROAD USE

- Open tread pattern ensures good self-cleaning and grip in changing driving conditions.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.



## AVAILABLE SIZES

- 315/80R22.5 - T675235
- 315/80R22.5 - T675312

# NOKIAN TYRES R-TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675235      | 315/80R22.5 | 156/150K | TL    | 9.00 | 9.75           | 12.3       | 42.4          | 19.7                      | 128.8                      | 120            | 26                    | 13.8                   | D                  | C        | B           | 75         | Yes | Yes                       |
| T675312      | 315/80R22.5 | 156/150K | TL    | 9.00 | 9.75           | 12.2       | 43.1          | 20                        | 129.2                      | 123            | 27                    | 13.8                   | D                  | B        | B           | 75         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   |
| T675235      | 315/80R22.5 | Single  | 67.5                   | 14575   | 15015 | 15455 | 15895 | 16335 | 16775 | 17220 | 17635 |       |
|              |             | Dual    | 67.5                   | 24405   | 25155 | 25905 | 26630 | 27380 | 28110 | 28815 | 29540 |       |
| T675312      | 315/80R22.5 | Single  | 67.5                   | 14220   | 14660 | 15100 | 15520 | 15960 | 16380 | 16800 | 17220 | 17635 |
|              |             | Dual    | 67.5                   | 23830   | 24560 | 25285 | 26015 | 26720 | 27450 | 28155 | 28835 | 29540 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK T

**WINTER TRAILER TIRE - STABLE  
PERFORMANCE AND SECURE TRACTION  
ON SNOW AND ICE**

- Wide zigzag-shape grooves improve self-cleaning and grip on snow.
- Strong shoulders resist wear even in tight cornering.
- Marked stud locations for effective studding.



## AVAILABLE SIZES

- 265/70R19.5 - T675232
- 265/70R19.5 - T675358

# NOKIAN TYRES HAKKAPELIITTA TRUCK T

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675232      | 265/70R19.5 | 143/141J | TL    | 7.50 | 6.75, 8.25     | 10.3       | 34.1          | 16                        | 103.7                      | 123            | 18                    | 11.6                   | D                  | C        | B           | 72         | Yes | Yes                       |
| T675358      | 265/70R19.5 | 143/141J | TL    | 7.50 | 6.75, 8.25     | 10.2       | 34.3          | 15.9                      | 102.4                      | 131            | 18                    | 11.6                   | D                  | C        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675232      | 265/70R19.5 | Single  | 62.5                   | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5                   | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675358      | 265/70R19.5 | Single  | 62.5                   | 9260  | 9545  | 9835  | 10095 | 10385 | 10670 | 10935 | 11200 | 11485 | 11750 | 12015 |
|              |             | Dual    | 62.5                   | 17505   | 18035 | 18565 | 19090 | 19620 | 20150 | 20655 | 21185 | 21695 | 22200 | 22710 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK 844+

## STURDY TIRE FOR ALL SEASONS

- Belt structure ensures even wear and excellent mileage.
- The Spiral Sipe System maintains tire properties even when worn.
- Stone ejectors in the main grooves reduce stone trapping.



## AVAILABLE SIZES

- 275/70R22.5 - T675215

# NOKIAN TYRES HAKKA TRUCK 844+

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675215      | 275/70R22.5 | 148/145L | TL    | 8.25 | 7.50           | 10.7       | 38            | 17.6                      | 115.4                      | 131            | 18                    | 12.2                   | C                  | B        | A           | 67         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675215      | 275/70R22.5 | Single  | 75                     | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 75                     | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL-WEATHER TRAILER TIRE – MILEAGE AND STABILITY FOR REGIONAL TRANSPORT

- New tread compound and tire construction for higher mileage and lower rolling resistance.
- Sturdy 5-rib open groove tread pattern with its dense, deep interlocking sipes ensures better grip.
- The wide shoulder design for improved stability and lateral grip as well as protection against lateral scrubbing.



### AVAILABLE SIZES

- 265/70R19.5 - T675268
- 275/70R22.5 - T675273
- 385/55R22.5 - T675267
- 385/55R22.5 - T675304
- 385/65R22.5 - T675266



# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS       | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|-------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675268      | 265/70R19.5 | 143/141J    | TL    | 7.50  | 6.75, 8.25     | 9.9        | 34.3          | 15.9                      | 104.3                      | 123            | 18                    | 11.6                   | C                  | C        | A           | 71         | Yes | Yes                       |
| T675273      | 275/70R22.5 | 148/145L    | TL    | 8.25  | 7.50           | 10.7       | 38.1          | 17.7                      | 115.9                      | 131            | 18                    | 12.2                   | D                  | C        | A           | 68         | Yes | Yes                       |
| T675267      | 385/55R22.5 | 160K (158L) | TL    | 11.75 | 12.25          | 15         | 39.5          | 18.4                      | 120                        | 131            | 19                    |                        | B                  | C        | A           | 69         | Yes | Yes                       |
| T675304      | 385/55R22.5 | 160K        | TL    | 11.75 | 12.25          | 14.9       | 39.1          | 18                        | 118.8                      | 131            | 19                    |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675266      | 385/65R22.5 | 160K (158L) | TL    | 11.75 | 12.25          | 15         | 42.7          | 19.7                      | 129.7                      | 131            | 20                    |                        | B                  | C        | A           | 67         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | mph   | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   |
| T675268      | 265/70R19.5 | Single  | 62.5            | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5            | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675273      | 275/70R22.5 | Single  | 75              | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 75              | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675267      | 385/55R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75              | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |
| T675304      | 385/55R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675266      | 385/65R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75              | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK TRAILER 2

## ALL-WEATHER TRAILER TIRE – IMPROVED MILEAGE AND STABILITY FOR LONG DISTANCE AND REGIONAL TRANSPORT

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance
- Sturdy tread pattern and deep tread with effective transverse sipes for better grip
- Wide shoulder design for improved stability and lateral grip as well as protection against lateral scrubbing



### AVAILABLE SIZES

- 265/70R19.5 - T675352
- 275/70R22.5 - T675353
- 435/50R19.5 - T675326
- 385/55R22.5 - T675317
- 445/45R19.5 - T675359
- 385/65R22.5 - T675351



2026-05-24

# NOKAIN TYRES HAKKA TRUCK TRAILER 2

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675352      | 265/70R19.5 | 143/141J | TL    | 7.50  | 6.75, 8.25     | 10.2       | 34.3          | 15.9                      | 102.4                      | 123            | 18                    | 11.6                   | C                  | A        | A           | 71         | Yes | Yes                       |
| T675326      | 435/50R19.5 | 164J     | TL    | 14.00 | 15.00          | 16.9       | 36.4          | 16.5                      | 111.1                      | 131            | 16                    |                        | C                  | A        | A           | 71         | Yes | Yes                       |
| T675359      | 445/45R19.5 | 164J     | TL    | 14.00 | 15.00          | 17.2       | 35.4          | 16                        | 106.8                      | 131            | 16                    |                        | C                  | A        | B           | 72         | Yes | Yes                       |
| T675353      | 275/70R22.5 | 148/145L | TL    | 8.25  | 7.50           | 10.8       | 38            | 17.6                      | 115                        | 131            | 18                    | 12.2                   | C                  | A        | A           | 70         | Yes | Yes                       |
| T675317      | 385/55R22.5 | 160K     | TL    | 11.75 | 12.25          | 14.9       | 39.1          | 18                        | 118.8                      | 131            | 19                    |                        | B                  | A        | A           | 70         | Yes | Yes                       |
| T675351      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 15.2       | 42.2          | 19.5                      | 127.9                      | 131            | 20                    |                        | B                  | A        | A           | 71         | Yes | Yes                       |


## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | mph   | 94    | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   |
| T675352      | 265/70R19.5 | Single  | 62.5            | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5            | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675326      | 435/50R19.5 | Single  | 62.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |
| T675359      | 445/45R19.5 | Single  | 62.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |
| T675353      | 275/70R22.5 | Single  | 75              | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 75              | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675317      | 385/55R22.5 | Single  | 67.5            | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675351      | 385/65R22.5 | Single  | 67.5            | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

# NOKIAN TYRES E-TRUCK TRAILER

## ALL-SEASON TRAILER TIRE – STABILITY AND GRIP FOR REGIONAL TRANSPORT

- New zigzag-shaped grooves improve stability.
- Groove design reduces stone trapping, resulting in longer tire life.
- Good grip on main road use.



### AVAILABLE SIZES

- 215/75R17.5 - T675254
- 215/75R17.5 - T675334
- 235/75R17.5 - T675245
- 235/75R17.5 - T675327
- 245/70R17.5 - T675246
- 245/70R17.5 - T675328
- 265/70R19.5 - T675244
- 265/70R19.5 - T675329
- 385/55R22.5 - T675270
- 385/55R22.5 - T675306
- 385/65R22.5 - T675217
- 385/65R22.5 - T675275
- 385/65R22.5 - T675283
- 385/65R22.5 - T675305

# NOKIAN TYRES E-TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675254      | 215/75R17.5 | 135/133J            | TL    | 6.00  | 6.75           | 8.3        | 30.6          | 14.3                      | 92.9                       | 123            | 15                    | 9.4                    | D                  | B        | A           | 69         | Yes | Yes                       |
| T675334      | 215/75R17.5 | 135/133J            | TL    | 6.00  | 6.75           | 8.3        | 30.4          | 14                        | 93                         | 123            | 15                    | 9.4                    | C                  | B        | A           | 69         | Yes | Yes                       |
| T675245      | 235/75R17.5 | 143/141J            | TL    | 6.75  | 7.50           | 9.4        | 31.7          | 14.8                      | 96.3                       | 127            | 16                    | 10.3                   | C                  | A        | A           | 69         | Yes | Yes                       |
| T675327      | 235/75R17.5 | 143/141J            | TL    | 6.75  | 7.50           | 9          | 31.3          | 14.3                      | 95.8                       | 131            | 16                    | 10.3                   | C                  | B        | A           | 69         | Yes | Yes                       |
| T675246      | 245/70R17.5 | 143/141J (146/146F) | TL    | 7.50  | 6.75           | 9.6        | 31.4          | 14.5                      | 95.4                       | 127            | 16                    | 11                     | D                  | A        | A           | 71         | Yes | Yes                       |
| T675328      | 245/70R17.5 | 143/141J (146/146F) | TL    | 7.50  | 6.75           | 9.6        | 31.2          | 14.3                      | 95.4                       | 131            | 16                    | 11                     | C                  | B        | A           | 69         | Yes | Yes                       |
| T675244      | 265/70R19.5 | 143/141J            | TL    | 7.50  | 6.75, 8.25     | 9.8        | 34.3          | 15.9                      | 104.3                      | 123            | 17                    | 11.6                   | D                  | A        | A           | 71         | Yes | Yes                       |
| T675329      | 265/70R19.5 | 143/141J            | TL    | 7.50  | 6.75, 8.25     | 10.3       | 34.1          | 15.7                      | 104.2                      | 123            | 18                    | 11.6                   | C                  | B        | A           | 69         | Yes | Yes                       |
| T675270      | 385/55R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 15         | 39.5          | 18.4                      | 120                        | 131            | 18                    |                        | C                  | B        | A           | 69         | Yes | Yes                       |
| T675306      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 14.8       | 39.1          | 18                        | 119.7                      | 131            | 18                    |                        | B                  | B        | A           | 70         | Yes | Yes                       |
| T675217      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 14.9       | 42.5          | 19.6                      | 129.3                      | 131            | 20                    |                        | C                  | B        | A           | 70         | Yes | Yes                       |
| T675275      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 15         | 42.5          | 19.6                      | 129.3                      | 131            | 20                    |                        | C                  | B        | A           | 68         | Yes | Yes                       |
| T675283      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 14.9       | 42.5          | 19.6                      | 129.3                      | 131            | 20                    |                        | C                  | B        | A           | 68         | Yes | Yes                       |
| T675305      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 14.9       | 42.2          | 19.4                      | 129.2                      | 131            | 19                    |                        | B                  | B        | A           | 69         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |     |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131 |
| T675254      | 215/75R17.5 | Single  | 62.5                   | 7760  | 8005  | 8225  | 8465  | 8685  | 8930  | 9150  | 9390  | 9610  |       |     |
|              |             | Dual    | 62.5                   | 14660   | 15100 | 15545 | 16005 | 16425 | 16865 | 17305 | 17745 | 18165 |       |     |
| T675334      | 215/75R17.5 | Single  | 62.5                   | 7760  | 8005  | 8225  | 8465  | 8685  | 8930  | 9150  | 9390  | 9610  |       |     |
|              |             | Dual    | 62.5                   | 14660   | 15100 | 15545 | 16005 | 16425 | 16865 | 17305 | 17745 | 18165 |       |     |
| T675245      | 235/75R17.5 | Single  | 62.5                   | 9480  | 9765  | 10055 | 10340 | 10625 | 10915 | 11175 | 11465 | 11750 | 12015 |     |
|              |             | Dual    | 62.5                   | 17900   | 18455 | 19005 | 19535 | 20060 | 20615 | 21140 | 21670 | 22180 | 22710 |     |

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675327      | 235/75R17.5 | Single  | 62.5                   | 9260  | 9545  | 9835  | 10095 | 10385 | 10670 | 10935 | 11200 | 11485 | 11750 | 12015 |
|              |             | Dual    | 62.5                   | 17505   | 18035 | 18565 | 19090 | 19620 | 20150 | 20655 | 21185 | 21695 | 22200 | 22710 |
| T675246      | 245/70R17.5 | Single  | 50                     | 10185   | 10515 | 10825 | 11135 | 11440 | 11730 | 12035 | 12345 | 12630 | 12940 | 13230 |
|              |             | Dual    | 50                     | 20395   | 21010 | 21625 | 22245 | 22860 | 23480 | 24075 | 24670 | 25265 | 25860 | 26455 |
|              |             | Single  | 62.5                   | 9480  | 9765  | 10055 | 10340 | 10625 | 10915 | 11175 | 11465 | 11750 | 12015 |       |
|              |             | Dual    | 62.5                   | 17900   | 18455 | 19005 | 19535 | 20060 | 20615 | 21140 | 21670 | 22180 | 22710 |       |
| T675328      | 245/70R17.5 | Single  | 50                     | 10185   | 10515 | 10825 | 11135 | 11440 | 11730 | 12035 | 12345 | 12630 | 12940 | 13230 |
|              |             | Dual    | 50                     | 20395   | 21010 | 21625 | 22245 | 22860 | 23480 | 24075 | 24670 | 25265 | 25860 | 26455 |
|              |             | Single  | 62.5                   | 9260  | 9545  | 9835  | 10095 | 10385 | 10670 | 10935 | 11200 | 11485 | 11750 | 12015 |
|              |             | Dual    | 62.5                   | 17505   | 18035 | 18565 | 19090 | 19620 | 20150 | 20655 | 21185 | 21695 | 22200 | 22710 |
| T675244      | 265/70R19.5 | Single  | 62.5                   | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5                   | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675329      | 265/70R19.5 | Single  | 62.5                   | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5                   | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675270      | 385/55R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75                     | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |
| T675306      | 385/55R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675217      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75                     | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |
| T675275      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |
| T675283      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
|              |             | Single  | 75                     | 15125   | 15585 | 16050 | 16490 | 16955 | 17395 | 17855 | 18300 | 18740 |       |       |
| T675305      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.


# NOKIAN TYRES R-TRUCK TRAILER

## TRAILER TIRE – RELIABLE PERFORMANCE ON VARIABLE SURFACES FOR ON/OFF-ROAD USE

- Robust design ensures excellent mileage in addition to resistance to damage.
- Special rubber compound and low heat build-up means that tire wears evenly and retains its good properties throughout its lifetime.
- Strong shoulders withstand tight cornering and the staggered tread pattern wears evenly.



2026-05-24



## AVAILABLE SIZES

- 265/70R19.5 - T675242
- 265/70R19.5 - T675295
- 285/70R19.5 - T675269
- 285/70R19.5 - T675360
- 275/70R22.5 - T675243
- 275/70R22.5 - T675345
- 385/65R22.5 - T675234
- 385/65R22.5 - T675314

# NOKIAN TYRES R-TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (in) | Diameter (in) | Loaded static radius (in) | Rolling circumference (in) | Pressure (psi) | Tread depth (1/32 in) | Min. dual spacing (in) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-----------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675242      | 265/70R19.5 | 143/141J | TL    | 7.50  | 6.75, 8.25     | 9.9        | 34.5          | 15.9                      | 105                        | 123            | 19                    | 11.6                   | E                  | B        | B           | 73         | Yes | Yes                       |
| T675295      | 265/70R19.5 | 143/141J | TL    | 7.50  | 6.75, 8.25     | 10.2       | 34.3          | 15.9                      | 102.4                      | 131            | 19                    | 11.6                   | D                  | A        | A           | 71         | Yes | Yes                       |
| T675269      | 285/70R19.5 | 150/148J | TL    | 8.25  | 9.00           | 10.5       | 35.2          | 16.3                      | 107.1                      | 131            | 18                    | 12.5                   | D                  | B        | B           | 72         | Yes | Yes                       |
| T675360      | 285/70R19.5 | 150/148J | TL    | 8.25  | 9.00           | 11         | 35.2          | 16.1                      | 106.4                      | 131            | 18                    | 12.5                   | D                  | A        | B           | 72         | Yes | Yes                       |
| T675243      | 275/70R22.5 | 148/145K | TL    | 8.25  | 7.50           | 10.7       | 38.3          | 17.8                      | 116.3                      | 131            | 20                    | 12.2                   | D                  | B        | B           | 74         | Yes | Yes                       |
| T675345      | 275/70R22.5 | 148/145K | TL    | 8.25  | 7.50           | 10.8       | 38.4          | 17.6                      | 115                        | 131            | 20                    | 12.2                   | D                  | A        | A           | 71         | Yes | Yes                       |
| T675234      | 385/65R22.5 | 160K     | TL    | 11.75 | 12.25          | 15.3       | 42.2          | 19.5                      | 128.3                      | 131            | 19                    |                        | C                  | B        | B           | 74         | Yes | Yes                       |
| T675314      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 15.2       | 42.2          | 19.3                      | 127.9                      | 131            | 19                    |                        | C                  | A        | B           | 73         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
| T675242      | 265/70R19.5 | Single  | 62.5                   | 9700  | 9985  | 10295 | 10580 | 10870 | 11155 | 11440 | 11730 | 12015 |       |       |
|              |             | Dual    | 62.5                   | 18320   | 18895 | 19445 | 19995 | 20545 | 21100 | 21625 | 22180 | 22710 |       |       |
| T675295      | 265/70R19.5 | Single  | 62.5                   | 9260  | 9545  | 9835  | 10095 | 10385 | 10670 | 10935 | 11200 | 11485 | 11750 | 12015 |
|              |             | Dual    | 62.5                   | 17505   | 18035 | 18565 | 19090 | 19620 | 20150 | 20655 | 21185 | 21695 | 22200 | 22710 |
| T675269      | 285/70R19.5 | Single  | 62.5                   | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 62.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675360      | 285/70R19.5 | Single  | 62.5                   | 11375   | 11730 | 12080 | 12435 | 12765 | 13095 | 13450 | 13780 | 14110 | 14440 | 14770 |
|              |             | Dual    | 62.5                   | 21405   | 22070 | 22730 | 23370 | 24010 | 24650 | 25285 | 25905 | 26545 | 27160 | 27780 |
| T675243      | 275/70R22.5 | Single  | 67.5                   | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |
|              |             | Dual    | 67.5                   | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675345      | 275/70R22.5 | Single  | 67.5                   | 10715   | 11025 | 11355 | 11685 | 11995 | 12325 | 12630 | 12965 | 13270 | 13580 | 13890 |

| Product code | Size        | Fitting | Reference speed<br>mph | Maximum load capacity per axle (lb) at various cold inflation pressures (psi) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|------------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                        | 94  | 98    | 102   | 105   | 109   | 112   | 116   | 120   | 123   | 127   | 131   |
|              |             | Dual    | 67.5                   | 19710   | 20325 | 20920 | 21515 | 22110 | 22685 | 23280 | 23855 | 24425 | 25000 | 25575 |
| T675234      | 385/65R22.5 | Single  | 67.5                   | 15300   | 15765 | 16225 | 16690 | 17150 | 17615 | 18055 | 18495 | 18960 | 19400 | 19840 |
| T675314      | 385/65R22.5 | Single  | 67.5                   | 17000   | 17505 | 18035 | 18540 | 19050 | 19555 | 20060 | 20570 | 21055 | 21560 | 22045 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.