

# TECHNICAL MANUAL

UPDATED: 2026-11-28

NOKIAN HEAVY TYRES

nokian® TYRES

# TABLE OF CONTENTS


FORESTRY 4
FOREST KING F2 5
FOREST KING TRS 2 7
FOREST KING TRS 2+ 9
FOREST KING TRS 3 11
FOREST KING TRS L-2 13
NORDMAN FOREST ELS L-2 15
NORDMAN FOREST F 17
NORDMAN FOREST TRS L-2 19
FOREST KING TRS LS-2 21
LOGGER KING LS-2 23
LOGGER KING LS-2 EXTREME 25
FOREST KING T 27
TR FOREST 2 29
TR MULTIPLUS 31
TRACTOR KING 33

AGRICULTURAL AND CONTRACTING 35
TR MULTIPLUS 36
GROUND KING 38
HAKKAPELIITTA TRI 40
SOIL KING VF 43
TRI 2 45
TRI STEEL 48
COUNTRY KING 50
COUNTRY KING G2 52
CT 54
ELS 56
FLOAT KING VF 58

UNDERGROUND MINING 60
ARMOR GARD 2 MINE 61
MINE KING E-4 63
MINE KING L-5S 65
MINE L-3S 67
NORDMAN MINE E-4 69

PORTS AND TERMINALS 71
HTS G2 E-4 72
HTS G2 L-4S 74
HTS G2 L-5S 76
ARMOR GARD 78
RTG 80
HTS TUGGER 82
ARMOR GARD 2 84

EARTHMOVING AND ROAD MAINTENANCE 86
GROUND KING LOADER 87




nokian® TYRES

HAKKAPELIITTA LOADER 89
LOADER GRIP 91
LOADER GRIP 2 93
GROUND KARE 95
GROUND KARE SEMI-SLICK 97
ARMOR GARD 2 99
EXCAVATOR 101

ALL TERRAIN TRUCKS AND MILITARY VEHICLES 103
MPT AGILE 104
MPT AGILE 2 106

TRUCKS AND BUSES 108
HAKKAPELIITTA CITY BUS 109
HAKKAPELIITTA TRUCK F2 111
HAKKA CITY BUS 114
HAKKA TRUCK COACH 116
HAKKA TRUCK STEER 118
HAKKA TRUCK STEER 2 120
E-TRUCK STEER 122
E-TRUCK STEER 17.5 124
E-TRUCK STEER 19.5 126
R-TRUCK STEER 128
HAKKAPELIITTA TRUCK D2 130
HAKKAPELIITTA TRUCK E2 132
HAKKA TRUCK DRIVE 135
HAKKA TRUCK DRIVE 2 137
E-TRUCK DRIVE 139
E-TRUCK DRIVE 17.5 141
E-TRUCK DRIVE 19.5 143
R-TRUCK DRIVE 145
HAKKAPELIITTA TRUCK T 147
HAKKA TRUCK TRAILER 149
HAKKA TRUCK TRAILER 2 151
E-TRUCK TRAILER 153
R-TRUCK TRAILER 156

# FORESTRY TIRES

## FORWARDER AND HARVESTER



5
Nokian Tyres
Forest King F2



7
Nokian Tyres
Forest King
TRS 2



9
Nokian Tyres
Forest King
TRS 2+



11
Nokian Tyres
Forest King
TRS 3



13
Nokian Tyres
Forest King
TRS L-2



15
Nokian Tyres
Nordman
Forest ELS L-2



17
Nokian Tyres
Nordman
Forest F



19
Nokian Tyres
Nordman
Forest TRS L-2

## SKIDDER AND FELLER BUNCHER



21
Nokian Tyres
Forest King
TRS LS-2



23
Nokian Tyres
Logger King
LS-2



25
Nokian Tyres
Logger King
LS-2 Extreme

## TRACTOR



27
Nokian Tyres
Forest King T



29
Nokian Tyres
TR Forest 2



31
Nokian Tyres
TR Multiplus



33
Nokian Tyres
Tractor King

# NOKIAN TYRES FOREST KING F2

## TRACK TIRE FOR HARVESTERS AND FORWARDERS

- Protective tread design with strong shoulders gives excellent functionality in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound in tread and especially in shoulder.
- High load-bearing capacity and comprehensive selection of sizes fills the needs of existing forest machinery – from smallest to heaviest.




## AVAILABLE SIZES

- 600/50-22.5 - T445619
- 710/40-22.5 - T445608
- 710/40-24.5 - T445572
- 800/40-24.5 - T445717
- 600/55-26.5 - T445573
- 710/45-26.5 - T445589
- 710/45-26.5 - T445571
- 710/55-26.5 - T445800
- 750/55-26.5 - T445574
- 800/40-26.5 - T445603
- 710/55-28.5 - T445570
- 780/50-28.5 - T445537
- 780/55-30.5 - T445846

# NOKIAN TYRES FOREST KING F2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445619 | 600/50-22.5 | 159A8 (167A2) | 20 | SF | TT | AG20.00 | | 605 | 1167 | 539 | 3544 | 500 | 550 | 30 | LS-2 | T55089 | 5450 | 5380 | 4680 | 4375 |
| T445608 | 710/40-22.5 | 161A8 (168A2) | 20 | SF | TT | AG24.00 | | 709 | 1167 | 537 | 3550 | 500 | 550 | 30 | LS-2 | T55092 | 5600 | 5690 | 4950 | 4625 |
| T445572 | 710/40-24.5 | 163A8 (170A2) | 20 | SF | TT | AG24.00 | | 699 | 1230 | 570 | 3738 | 500 | 550 | 35 | LS-2 | T545448 | 6000 | 5995 | 5215 | 4875 |
| T445717 | 800/40-24.5 | 169A8 (176A2) | 20 | SF | TT | AG28.00 | | 786 | 1250 | 569 | 3795 | 500 | 550 | 35 | LS-2 | T545448 | 7100 | 7135 | 6205 | 5800 |
| T445573 | 600/55-26.5 | 165A8 (172A2) | 20 | SF | TT | AG20.00 | | 602 | 1342 | 618 | 4071 | 500 | 550 | 35 | LS-2 | T55098 | 6300 | 6335 | 5510 | 5150 |
| T445589 | 710/45-26.5 | 173A8 (180A2) | 24 | SF | TT | AG24.00 | | 708 | 1345 | 621 | 4084 | 600 | 600 | 35 | LS-2 | T55099 | 8000 | 7995 | 6955 | 6500 |
| T445571 | 710/45-26.5 | 168A8 (175A2) | 20 | SF | TT | AG24.00 | | 705 | 1345 | 622 | 4084 | 500 | 550 | 35 | LS-2 | T55099 | 6900 | 6890 | 5990 | 5600 |
| T445800 | 710/55-26.5 | 179A8 (186A2) | 24 | SF | TT | AG24.00 | AG22.00 | 697 | 1505 | 686 | 4559 | 600 | 600 | 35 | LS-2 | T55102 | 9500 | 9535 | 8295 | 7750 |
| T445574 | 750/55-26.5 | 182A8 (189A2) | 24 | SF | TT | AG24.00 | | 769 | 1473 | 674 | 4486 | 600 | 600 | 35 | LS-2 | T55102 | 10600 | 10455 | 9095 | 8500 |
| T445603 | 800/40-26.5 | 170A8 (177A2) | 20 | SF | TT | AG28.00 | | 807 | 1339 | 620 | 4084 | 500 | 550 | 35 | LS-2 | T545312 | 7300 | 7380 | 6420 | 6000 |
| T445570 | 710/55-28.5 | 180A8 (187A2) | 24 | SF | TT | AG24.00 | | 719 | 1515 | 696 | 4618 | 600 | 600 | 35 | LS-2 | T545543 | 9750 | 9840 | 8560 | 8000 |
| T445537 | 780/50-28.5 | 182A8 (190A2) | 24 | SF | TT | AG26.00 | | 783 | 1515 | 697 | 4618 | 600 | 600 | 35 | LS-2 | T545543 | 10600 | 10455 | 9095 | 8500 |
| T445846 | 780/55-30.5 | 187A8 (195A2) | 24 | SF | TT | AG26.00 | | 780 | 1631 | 745 | 4974 | 600 | 600 | 35 | | T55891 | 12150 | 11995 | 10435 | 9750 |

# NOKIAN TYRES FOREST KING TRS 2

## TRACTION TIRE FOR HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip.
- Wide lug ends, lifted groove bottom in shoulder and considered pitch length give good performance in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound on shoulders.




## AVAILABLE SIZES

- 600/50-22.5 - T445618
- 710/40-22.5 - T445607
- 600/50-24.5 - T445639
- 710/40-24.5 - T445568
- 800/40-24.5 - T445718
- 600/55-26.5 - T445567
- 710/45-26.5 - T445566
- 710/45-26.5 - T445640
- 710/55-26.5 - T445801
- 750/55-26.5 - T445602
- 800/40-26.5 - T445594
- 710/55-28.5 - T445612
- 780/50-28.5 - T445581

# NOKIAN TYRES FOREST KING TRS 2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445618 | 600/50-22.5 | 159A8 (167A2) | 20 | SF | TT | AG20.00 | | 597 | 1168 | 533 | 3550 | 500 | 550 | 42 | LS-2 | T55089 | 5450 | 5380 | 4680 | 4375 |
| T445607 | 710/40-22.5 | 161A8 (168A2) | 20 | SF | TT | AG24.00 | | 705 | 1171 | 535 | 3569 | 500 | 550 | 42 | LS-2 | T55092 | 5600 | 5690 | 4950 | 4625 |
| T445639 | 600/50-24.5 | 164A8 (171A2) | 20 | SF | TT | AG20.00 | AG22.00 | 603 | 1230 | 566 | 3738 | 550 | 550 | 48 | LS-2 | T545447 | 5600 | 5535 | 4815 | 4500 |
| T445568 | 710/40-24.5 | 163A8 (170A2) | 20 | SF | TT | AG24.00 | | 694 | 1233 | 570 | 3757 | 500 | 550 | 48 | LS-2 | T545448 | 6000 | 5995 | 5215 | 4875 |
| T445718 | 800/40-24.5 | 169A8 (176A2) | 20 | SF | TT | AG28.00 | | 784 | 1251 | 566 | 3808 | 500 | 550 | 48 | LS-2 | T545448 | 7100 | 7135 | 6205 | 5800 |
| T445567 | 600/55-26.5 | 165A8 (172A2) | 20 | SF | TT | AG20.00 | | 598 | 1347 | 619 | 4096 | 500 | 550 | 48 | LS-2 | T55098 | 6300 | 6335 | 5510 | 5150 |
| T445566 | 710/45-26.5 | 168A8 (175A2) | 20 | SF | TT | AG24.00 | | 703 | 1344 | 618 | 4103 | 500 | 550 | 48 | LS-2 | T55099 | 6900 | 6890 | 5990 | 5600 |
| T445640 | 710/45-26.5 | 173A8 (180A2) | 24 | SF | TT | AG24.00 | | 702 | 1345 | 617 | 4115 | 600 | 600 | 48 | LS-2 | T55099 | 8000 | 7995 | 6955 | 6500 |
| T445801 | 710/55-26.5 | 179A8 (186A2) | 24 | SF | TT | AG24.00 | AG22.00 | 697 | 1503 | 688 | 4546 | 600 | 600 | 49 | LS-2 | T55102 | 9500 | 9535 | 8295 | 7750 |
| T445602 | 750/55-26.5 | 182A8 (189A2) | 24 | SF | TT | AG24.00 | | 755 | 1477 | 674 | 4499 | 600 | 600 | 49 | LS-2 | T55102 | 10600 | 10455 | 9095 | 8500 |
| T445594 | 800/40-26.5 | 170A8 (177A2) | 20 | SF | TT | AG28.00 | | 798 | 1343 | 619 | 4096 | 500 | 550 | 48 | LS-2 | T545312 | 7300 | 7380 | 6420 | 6000 |
| T445612 | 710/55-28.5 | 180A8 (187A2) | 24 | SF | TT | AG24.00 | | 711 | 1513 | 693 | 4618 | 600 | 600 | 49 | LS-2 | T545543 | 9750 | 9840 | 8560 | 8000 |
| T445581 | 780/50-28.5 | 182A8 (190A2) | 24 | SF | TT | AG26.00 | | 782 | 1513 | 691 | 4611 | 600 | 600 | 49 | LS-2 | T545543 | 10600 | 10455 | 9095 | 8500 |

# NOKIAN TYRES FOREST KING TRS 2+

## TRACTION TIRE FOR 6WD HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip
- Special tread design with extra wing bars give excellent support, traction and protection in chain and wheel track use
- Strong 24PR diagonal structure with steel fortification gives excellent puncture protection and impressive stability



## AVAILABLE SIZES

- 600/65-34 - T445714
- 710/55-34 - T445715
- 710/70-34 - T445716

# NOKIAN TYRES FOREST KING TRS 2+

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | | | |
| | | | | | | | | | | | | | | | | | 10 | 10 | 20 | 30 | 40 | 50 |
| T445714 | 600/65-34 | 169A8 (176A2) | 24 | SF | TT | DW20B | | 615 | 1638 | 743 | 4964 | 400 | 400 | 50 | LS-2 | T55394 | 7100 | 8700 | 7135 | 6205 | 5800 | 5280 |
| T445715 | 710/55-34 | 173A8 (180A2) | 24 | SF | TT | DW24B | DW23B | 715 | 1634 | 740 | 4957 | 400 | 400 | 50 | LS-2 | T55394 | 8000 | 9750 | 7995 | 6955 | 6500 | 5915 |
| T445716 | 710/70-34 | 181A8 (188A2) | 24 | SF | TT | DW23B | DW24B, DW25B | 744 | 1833 | 821 | 5554 | 400 | 400 | 53 | LS-2 | T55892 | 10000 | 12375 | 10150 | 8830 | 8250 | 7510 |

# NOKIAN TYRES FOREST KING TRS 3

## TRACTION TIRE FOR HARVESTERS AND FORWARDERS

- A strong and reliable traction tire. The tractive tread design with high tread depth delivers excellent traction and lateral grip.
- Wide lugs, extra shoulder lift and optimized shoulder roundness give good performance with tracks and chains.
- The strong diagonal structure with steel fortification, offers excellent puncture protection, while enhanced tread compound increases durability.






## AVAILABLE SIZES

- 600/50-22.5 - T445889
- 710/40-22.5 - T445890
- 600/50-24.5 - T445891
- 710/45-24.5 - T445892
- 800/40-24.5 - T445893
- 600/55-26.5 - T445894
- 650/60-26.5 - T445904
- 710/45-26.5 - T445896
- 710/45-26.5 - T445895
- 710/55-26.5 - T445902
- 750/55-26.5 - T445898
- 800/40-26.5 - T445897
- 710/55-28.5 - T445899
- 780/50-28.5 - T445900
- 780/55-30.5 - T445901

# NOKIAN TYRES FOREST KING TRS 3

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445889 | 600/50-22.5 | 159A8 (167A2) | 20 | SF | TT | AG20.00 | | 604 | 1172 | 531 | 3554 | 500 | 550 | 42 | LS-2 | T55089 | 5450 | 5380 | 4680 | 4375 |
| T445890 | 710/40-22.5 | 161A8 (168A2) | 20 | SF | TT | AG24.00 | | 698 | 1175 | 536 | 3570 | 500 | 550 | 42 | LS-2 | T55092 | 5600 | 5690 | 4950 | 4625 |
| T445891 | 600/50-24.5 | 166A8 (173A2) | 24 | SF | TT | AG20.00 | AG22.00 | 609 | 1247 | 566 | 3790 | 600 | 600 | 48 | LS-2 | T545447 | 6500 | 6520 | 5670 | 5300 |
| T445892 | 710/45-24.5 | 166A8 (173A2) | 20 | SF | TT | AG24.00 | | 702 | 1247 | 568 | 3788 | 500 | 550 | 48 | LS-2 | T545448 | 6500 | 6520 | 5670 | 5300 |
| T445893 | 800/40-24.5 | 169A8 (176A2) | 20 | SF | TT | AG28.00 | | 795 | 1250 | 571 | 3805 | 500 | 550 | 48 | LS-2 | T545448 | 7100 | 7135 | 6205 | 5800 |
| T445894 | 600/55-26.5 | 165A8 (172A2) | 20 | SF | TT | AG20.00 | | 597 | 1347 | 615 | 4088 | 500 | 550 | 48 | LS-2 | T55098 | 6300 | 6335 | 5510 | 5150 |
| T445904 | 650/60-26.5 | 177A8 (184A2) | 24 | SF | TT | AG20.00 | AG22.00 | 638 | 1496 | 676 | 4559 | 600 | 600 | 49 | LS-2 | T55897 | 9000 | 8980 | 7810 | 7300 |
| T445896 | 710/45-26.5 | 173A8 (180A2) | 24 | SF | TT | AG24.00 | | 701 | 1342 | 614 | 4090 | 600 | 600 | 48 | LS-2 | T55099 | 8000 | 7995 | 6955 | 6500 |
| T445895 | 710/45-26.5 | 168A8 (175A2) | 20 | SF | TT | AG24.00 | | 698 | 1344 | 616 | 4090 | 500 | 550 | 48 | LS-2 | T55099 | 6900 | 6890 | 5990 | 5600 |
| T445902 | 710/55-26.5 | 179A8 (186A2) | 24 | SF | TT | AG24.00 | | 717 | 1487 | 675 | 4543 | 600 | 600 | 49 | LS-2 | T55102 | 9500 | 9535 | 8295 | 7750 |
| T445898 | 750/55-26.5 | 182A8 (189A2) | 24 | SF | TT | AG24.00 | | 736 | 1487 | 674 | 4542 | 600 | 600 | 49 | LS-2 | T55102 | 10600 | 10455 | 9095 | 8500 |
| T445897 | 800/40-26.5 | 170A8 (177A2) | 20 | SF | TT | AG28.00 | | 789 | 1344 | 617 | 4091 | 500 | 550 | 48 | LS-2 | T545312 | 7300 | 7380 | 6420 | 6000 |
| T445899 | 710/55-28.5 | 180A8 (187A2) | 24 | SF | TT | AG24.00 | | 710 | 1527 | 694 | 4648 | 600 | 600 | 49 | LS-2 | T545543 | 9750 | 9840 | 8560 | 8000 |
| T445900 | 780/50-28.5 | 182A8 (190A2) | 24 | SF | TT | AG26.00 | | 771 | 1529 | 694 | 4666 | 600 | 600 | 49 | LS-2 | T545543 | 10600 | 10455 | 9095 | 8500 |
| T445901 | 780/55-30.5 | 187A8 (195A2) | 24 | SF | TT | AG26.00 | | 776 | 1630 | 741 | 4990 | 600 | 600 | 49 | LS-2 | T55891 | 12150 | 11995 | 10435 | 9750 |

# NOKIAN TYRES FOREST KING TRS L-2

## RELIABLE GRIP AND TRACTION

- Wide and high pattern lugs for good mobility and operating comfort
- Optimised lug angle and sharp tire shoulders providing excellent lateral grip
- Steel protection against punctures




## AVAILABLE SIZES

- 650/60-26.5 - T445395

# NOKIAN TYRES FOREST KING TRS L-2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445395 | 650/60-26.5 | 172A8 (179A2) | 20 | SF | TT | AG20.00 | 655 | 1479 | 676 | 4467 | 500 | 550 | 50 | L-2 | T55897 | 7750 | 7750 | 6740 | 6300 |

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King ELS L-2 are applicable to Nordman Forest ELS L-2, making it a perfect option as a replacement tire.
- The design of the tire provides good performance in track and chain use.




## AVAILABLE SIZES

- 600/50-22.5 - T445623

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445623 | 600/50-22.5 | 149A8 (156A2) | 16 | SF | TT | AG20.00 | 606 | 1164 | 543 | 3544 | 320 | 400 | 32 | LS-2 | T55089 | 4000 | 4000 | 3480 | 3250 |

# NOKIAN TYRES NORDMAN FOREST F

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The design of the tire provides good performance in track and chain use.




## AVAILABLE SIZES

- 710/40-22.5 - T445625
- 710/40-24.5 - T445599
- 600/55-26.5 - T445598
- 710/45-26.5 - T445565
- 750/55-26.5 - T445597

# NOKIAN TYRES NORDMAN FOREST F

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445625 | 710/40-22.5 | 151A8 (158A2) | 16 | SF | TT | AG24.00 | 701 | 1164 | 538 | 3544 | 320 | 400 | 28 | LS-2 | T55092 | 4250 | 4245 | 3690 | 3450 |
| T445599 | 710/40-24.5 | 163A8 (170A2) | 20 | SF | TT | AG24.00 | 706 | 1223 | 573 | 3729 | 500 | 550 | 29 | LS-2 | T545448 | 6000 | 5995 | 5215 | 4875 |
| T445598 | 600/55-26.5 | 165A8 (172A2) | 20 | SF | TT | AG20.00 | 615 | 1339 | 624 | 4065 | 500 | 550 | 32 | LS-2 | T55098 | 6300 | 6335 | 5510 | 5150 |
| T445565 | 710/45-26.5 | 168A8 (175A2) | 20 | SF | TT | AG24.00 | 711 | 1345 | 622 | 4046 | 500 | 550 | 30 | LS-2 | T55099 | 6900 | 6890 | 5990 | 5600 |
| T445597 | 750/55-26.5 | 177A8 (184A2) | 20 | SF | TT | AG24.00 | 762 | 1476 | 680 | 4467 | 500 | 550 | 32 | LS-2 | T55102 | 9000 | 8980 | 7810 | 7300 |

# NOKIAN TYRES NORDMAN FOREST TRS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King TRS L-2 are applicable to Nordman Forest TRS L-2, making it a perfect option as a replacement tire.
- Good terrain mobility due to aggressive tread design with high tread depth.






## AVAILABLE SIZES

- 600/50-22.5 - T445622
- 710/40-22.5 - T445624
- 600/55-26.5 - T445527
- 710/45-26.5 - T445541
- 750/55-26.5 - T445528
- 600/65-34 - T445475
- 700/55-34 - T445476
- 700/70-34 - T445596

# NOKIAN TYRES NORDMAN FOREST TRS L-2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | |
| | | | | | | | | | | | | | | | | | 10 | 20 | 30 | 40 |
| T445622 | 600/50-22.5 | 149A8 (156A2) | 16 | SF | TT | AG20.00 | | 605 | 1168 | 545 | 3544 | 320 | 400 | 42 | LS-2 | T55089 | 4000 | 4000 | 3480 | 3250 |
| T445624 | 710/40-22.5 | 151A8 (158A2) | 16 | SF | TT | AG24.00 | | 706 | 1169 | 539 | 3537 | 320 | 400 | 42 | LS-2 | T55092 | 4250 | 4245 | 3690 | 3450 |
| T445527 | 600/55-26.5 | 165A8 (172A2) | 20 | SF | TT | AG20.00 | | 613 | 1345 | 616 | 4065 | 500 | 550 | 48 | LS-2 | T55098 | 6300 | 6335 | 5510 | 5150 |
| T445541 | 710/45-26.5 | 168A8 (175A2) | 20 | SF | TT | AG24.00 | | 711 | 1345 | 608 | 4077 | 500 | 550 | 48 | LS-2 | T55099 | 6900 | 6890 | 5990 | 5600 |
| T445528 | 750/55-26.5 | 177A8 (184A2) | 20 | SF | TT | AG24.00 | | 752 | 1480 | 672 | 4461 | 500 | 550 | 50 | LS-2 | T55102 | 9000 | 8980 | 7810 | 7300 |
| T445475 | 600/65-34 | 163A8 (170A2) | 20 | SF | TT | DW20B | | 615 | 1644 | 755 | 4964 | 320 | 360 | 51 | LS-2 | T55394 | 6000 | 5995 | 5215 | 4875 |
| T445476 | 700/55-34 | 166A8 (173A2) | 20 | SF | TT | DW24B | DW23B | 708 | 1634 | 751 | 4938 | 320 | 360 | 51 | LS-2 | T55394 | 6500 | 6520 | 5670 | 5300 |
| T445596 | 700/70-34 | 173A8 (180A2) | 20 | SF | TT | DW20B | DW23B, DW24B | 723 | 1848 | 840 | 5542 | 320 | 360 | 53 | LS-2 | T55892 | 8000 | 7995 | 6955 | 6500 |

# NOKIAN TYRES FOREST KING TRS LS-2

## A FORESTRY AND EARTHMOVING MACHINE TRACTION TIRE WITH A STRONG TRACTION BAR AND EXCELLENT GRIP. WELLCLEANING, OPEN-CENTRE TREAD DESIGN. DURABLE SPECIAL RUBBER COMPOUND AND EFFICIENT STEEL FORTIFICATION

- Tires for log skidders, wide tread with high traction lugs
- Special cut and crack resistant compound
- Steel fortification against punctures




## AVAILABLE SIZES

- 28L-26 - T445516

# NOKIAN TYRES FOREST KING TRS LS-2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | | |
| | | | | | | | | | | | | | | | | 10 | 15 | 25 | 30 | 40 |
| T445516 | 28L-26 | 173A6 (185A2) | 26 | SF | TL | DW25B | 741 | 1641 | 748 | 4945 | 340 | 400 | 53 | LS-2 | T55101 | 9200 | 7800 | 7150 | 6500 | 5850 |

# NOKIAN TYRES LOGGER KING LS-2

## FORESTRY TIRE FOR FULL-TREE MACHINES, SUCH AS SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.




## AVAILABLE SIZES

- 23.1-26 - T445616
- 28L-26 - T445615
- 24.5-32 - T445614
- 30.5L-32 - T445621

# NOKIAN TYRES LOGGER KING LS-2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | | |
| | | | | | | | | | | | | | | | | 10 | 15 | 25 | 30 | 40 |
| T445616 | 23.1-26 | 160A6 (156A8) | 16 | SF | TL | DW20B | 604 | 1623 | 749 | 4882 | 280 | 280 | 54 | LS-2 | T55897 | 6300 | 5400 | 4950 | 4500 | 4050 |
| T445615 | 28L-26 | 165A6 (161A8) | 20 | SF | TL | DW25B | 720 | 1647 | 754 | 4945 | 280 | 280 | 58 | LS-2 | T55101 | 7250 | 6200 | 5700 | 5150 | 4650 |
| T445614 | 24.5-32 | 169A6 (167A8) | 20 | SF | TL | DH21 | 637 | 1829 | 846 | 5517 | 280 | 310 | 58 | LS-2 | T55393 | 8200 | 7000 | 6450 | 5850 | 5250 |
| T445621 | 30.5L-32 | 170A6 (167A8) | 20 | SF | TL | DH27 | 773 | 1843 | 853 | 5542 | 240 | 240 | 67 | LS-2 | T55388 | 8400 | 7200 | 6600 | 6000 | 5400 |

# NOKIAN TYRES LOGGER KING LS-2 EXTREME

## TIRE FOR FULL-TREE MACHINES, I. A. SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.




## AVAILABLE SIZES

- 30.5L-32 - T445613
- 35.5L-32 - T445620

# NOKIAN TYRES LOGGER KING LS-2 EXTREME

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | | | |
| | | | | | | | | | | | | | | | | 10 | 10 | 15 | 25 | 30 | 40 |
| T445613 | 30.5L-32 | 176A6 (172A8) | 26 | SF | TL | DH27 | 778 | 1842 | 849 | 5548 | 310 | 310 | 67 | LS-2 | T55388 | 10000 | 8550 | | 7850 | 7100 | 6400 |
| T445620 | 35.5L-32 | 183A6 (180A8) | 26 | SF | TL | DH31 | 915 | 2009 | 920 | 6063 | 280 | 280 | 67 | LS-2 | T55879 | 12250 | 10500 | 9650 | 8750 | 7850 | |

# NOKIAN TYRES FOREST KING T

## FOR TRACTORS AND SKIDDERS USED IN FORESTRY, FOREST CLEARANCE OR ROAD CONSTRUCTION

- Strong and wide lugs enable good traction and tolerate high tractive forces.
- Steel fortifications together with strong diagonal construction give excellent puncture resistance.
- Stiff diagonal construction enables better stability.




## AVAILABLE SIZES

- 500/70-28 - T445335
- 540/70-30 - T445314
- 650/75-38 - T445313

# NOKIAN TYRES FOREST KING T

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | Speed (km/h) | | | | |
| | | | | | | | | | | | | | | | | | 10 | 10 | 20 | 30 | 40 | 50 |
| T445335 | 500/70-28 | 146A8 | SF | TT | DW16L | | 510 | 1401 | 650 | 4241 | 675 | 240 | 280 | 49 | LS-2 | T545229 | 3650 | 4500 | 3690 | 3210 | 3000 | 2730 |
| T445314 | 540/70-30 | 152A8 (149B) | SF | TT | DW16L | DW18B | 534 | 1518 | 705 | 4505 | 725 | 240 | 280 | 50 | LS-2 | T55371 | 4375 | 5325 | 4365 | 3800 | 3550 | 3230 |
| T445313 | 650/75-38 | 168A8 (165B) | SF | TT | DW20B | DW23B | 647 | 1956 | 900 | 5890 | 925 | 240 | 280 | 53 | LS-2 | T55893 | 6900 | 8400 | 6890 | 5990 | 5600 | 5095 |

# NOKIAN TYRES TR FOREST 2

## FOR SMALL AND MEDIUM SIZE TRACTORS USED IN VERSATILE TASKS F.EX IN FORESTRY

- Cut and crack resistant compound together with strong cross-ply construction to tolerate rough conditions.
- Stiff diagonal construction enables great stability.
- Tractive tread design with good self-cleaning properties.




## AVAILABLE SIZES

- 320/85-24 - T445784
- 340/85-24 - T445780
- 380/85-24 - T445778
- 340/85-28 - T445785
- 380/85-28 - T445790
- 420/85-28 - T445789
- 420/85-30 - T445786
- 420/85-34 - T445779
- 460/85-34 - T445777
- 420/85-38 - T445793
- 460/85-38 - T445788
- 520/85-38 - T445787

# NOKIAN TYRES TR FOREST 2

## ALL SIZES

| Product code | Size | Equivalent size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for tractor, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445784 | 320/85-24 | 12.4-24 | 130A8 (127B) | 16 | TL | DW11 | DW10 | 326 | 1174 | 529 | 3534 | 550 | 280 | 280 | 36 | R-1 | 2110 | 2035 | 1955 | 1900 | 1825 | 1730 |
| T445780 | 340/85-24 | 13.6-24 | 134A8 (131B) | 16 | TL | DW12 | DW11 | 348 | 1223 | 552 | 3682 | 575 | 280 | 280 | 38 | R-1 | 2355 | 2270 | 2185 | 2120 | 2035 | 1930 |
| T445778 | 380/85-24 | 14.9-24 | 140A8 (137B) | 16 | TL | DW13 | DW13L, DW11, DW12 | 390 | 1266 | 566 | 3813 | 600 | 280 | 280 | 42 | R-1 | 2775 | 2675 | 2575 | 2500 | 2400 | 2275 |
| T445785 | 340/85-28 | 13.6-28 | 136A8 (133B) | 16 | TL | DW12 | DW11 | 352 | 1308 | 591 | 3947 | 625 | 280 | 280 | 42 | R-1 | 2485 | 2395 | 2305 | 2240 | 2150 | 2040 |
| T445790 | 380/85-28 | 14.9-28 | 142A8 (139B) | 16 | TL | DW13 | DW13L, DW11, DW12 | 392 | 1359 | 613 | 4107 | 650 | 280 | 280 | 42 | R-1 | 2940 | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445789 | 420/85-28 | 16.9-28 | 148A8 (145B) | 16 | TL | DW15L | DW14L, DW13L, DW13 | 435 | 1423 | 639 | 4310 | 675 | 280 | 280 | 46 | R-1 | 3495 | 3370 | 3245 | 3150 | 3025 | 2865 |
| T445786 | 420/85-30 | 16.9-30 | 149A8 (146B) | 16 | TL | DW15L | DW14L, DW13L, DW13 | 430 | 1490 | 668 | 4482 | 700 | 280 | 280 | 47 | R-1 | 3610 | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445779 | 420/85-34 | 16.9-34 | 151A8 (148B) | 16 | TL | DW15L | DW14L, DW13L, DW13 | 429 | 1577 | 707 | 4744 | 750 | 280 | 280 | 47 | R-1 | 3830 | 3690 | 3555 | 3450 | 3310 | 3140 |
| T445777 | 460/85-34 | 18.4-34 | 155A8 (152B) | 16 | TL | DW16L | DW15L | 465 | 1638 | 756 | 4951 | 775 | 280 | 280 | 50 | R-1 | 4300 | 4145 | 3990 | 3875 | 3720 | 3525 |
| T445793 | 420/85-38 | 16.9-38 | 152A8 (149B) | 16 | TL | DW15L | DW14L, DW13L, DW13 | 431 | 1673 | 759 | 5081 | 800 | 280 | 280 | 50 | R-1 | 3940 | 3800 | 3655 | 3550 | 3410 | 3230 |
| T445788 | 460/85-38 | 18.4-38 | 157A8 (154B) | 16 | TL | DW16L | DW15L | 471 | 1740 | 785 | 5267 | 825 | 280 | 280 | 53 | R-1 | 4580 | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445787 | 520/85-38 | 20.8-38 | 164A8 (160B) | 16 | TL | DW18L | DW16L | 536 | 1832 | 817 | 5524 | 875 | 280 | 280 | 54 | R-1 | 5550 | 5350 | 5150 | 5000 | 4800 | 4550 |

# NOKIAN TYRES TR MULTIPLUS

## FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.




## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415

# NOKIAN TYRES TR MULTIPLUS

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for tractor, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445410 | 500/65R24 | 142A8 (139B) | SB | TL | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 489 | 1242 | 575 | 3735 | 600 | 240 | 320 | 48 | R-1 | | 2940 | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445411 | 500/65R28 | 144A8 (141B) | SB | TL | DW15L | DW16L, W16L, W15L, W14L, W13 | 491 | 1341 | 622 | 4055 | 650 | 240 | 320 | 48 | R-1 | T55097 | 3110 | 2995 | 2885 | 2800 | 2690 | 2550 |
| T445412 | 540/65R28 | 149A8 (146B) | SB | TL | DW16 | W15L, W16L, DW18L, W18L, DW16L | 522 | 1409 | 653 | 4254 | 675 | 240 | 320 | 51 | R-1 | T545229 | 3610 | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445413 | 600/65R34 | 157A8 (154B) | SB | TL | DW18L | W16L, W18L, DW20B, DW16L | 585 | 1640 | 750 | 4930 | 775 | 240 | 320 | 52 | R-1 | T55395 | 4580 | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445414 | 600/65R38 | 159A8 (156B) | SB | TL | DW18L | W16L, W18L, DW20B, DW16L | 584 | 1743 | 809 | 5290 | 825 | 240 | 320 | 52 | R-1 | | 4855 | 4680 | 4505 | 4375 | 4200 | 3980 |
| T445415 | 650/65R38 | 164A8 (160B) | SB | TL | DW20B | DW18 | 641 | 1808 | 838 | 5485 | 875 | 240 | 320 | 53 | R-1 | T545322 | 5410 | 5215 | 5020 | 4875 | 4680 | 4435 |

# NOKIAN TYRES TRACTOR KING

## VERSATILE HEAVY-DUTY RADIAL TRACTION TIRE FOR DEMANDING OFF-ROAD APPLICATIONS AND HIGH-SPEED ROAD TRANSITS

- Strong steel belted radial carcass strengthened with forest tread compound. 400 kPa max pressure enabling high load carrying capacity and stability.
- Wide tread and radically increased amount of tractive edges for supreme traction.
- Innovative tread design with even ground contact resulting in comfortable drive. Durability up to 65 km/h speeds.



## AVAILABLE SIZES

- 480/65R28 - T445806
- 500/65R28 - T445673
- 540/65R28 - T445674
- 600/60R28 - T445675
- 600/65R28 - T445851
- 540/65R30 - T445676
- 540/70R30 - T445677
- 600/70R30 - T445678
- 620/75R30 - T445679
- 600/65R34 - T445680
- 600/70R34 - T445681
- 600/65R38 - T445682
- 650/65R38 - T445683
- 650/75R38 - T445684
- 650/85R38 - T445685
- 710/70R38 - T445741
- 800/70R38 - T445852
- 650/65R42 - T445740
- 710/70R42 - T445686
- 710/75R42 - T445687

# NOKIAN TYRES TRACTOR KING

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for tractor, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445806 | 480/65R28 | 148D | SB | TL | DW15L | DW16L, DW14L, DW18L | 487 | 1359 | 629 | 4103 | 650 | 320 | 400 | 48 | R-1W | 3450 | 3370 | 3310 | 3245 | 3195 | 3150 |
| T445673 | 500/65R28 | 150D | SB | TL | DW16L | DW15L, DW18L | 494 | 1358 | 629 | 4103 | 650 | 320 | 400 | 48 | R-1W | 3670 | 3585 | 3520 | 3450 | 3400 | 3350 |
| T445674 | 540/65R28 | 154D | SB | TL | DW18L | DW16L | 542 | 1409 | 650 | 4248 | 675 | 320 | 400 | 48 | R-1W | 4105 | 4015 | 3940 | 3865 | 3805 | 3750 |
| T445675 | 600/60R28 | 157D | SB | TL | DW18L | DW20B | 584 | 1423 | 617 | 4255 | 675 | 320 | 400 | 49 | R-1W | 4515 | 4415 | 4330 | 4250 | 4185 | 4125 |
| T445851 | 600/65R28 | 160D | SB | TL | DW20B | DW18L | 606 | 1502 | 692 | 4530 | 700 | 320 | 400 | 50 | R-1W | 4930 | 4815 | 4725 | 4635 | 4570 | 4500 |
| T445676 | 540/65R30 | 155D | SB | TL | DW18L | DW16L | 537 | 1463 | 677 | 4427 | 700 | 320 | 400 | 49 | R-1W | 4245 | 4145 | 4070 | 3990 | 3935 | 3875 |
| T445677 | 540/70R30 | 159D | SB | TL | DW18L | DW16L | 543 | 1506 | 693 | 4539 | 725 | 320 | 400 | 50 | R-1W | 4790 | 4680 | 4595 | 4505 | 4440 | 4375 |
| T445678 | 600/70R30 | 165D | SB | TL | DW18L | DW20B | 579 | 1602 | 730 | 4826 | 750 | 320 | 400 | 51 | R-1W | 5640 | 5510 | 5410 | 5305 | 5225 | 5150 |
| T445679 | 620/75R30 | 169D | SB | TL | DW20B | | 624 | 1688 | 770 | 5097 | 800 | 320 | 400 | 52 | R-1 | 6350 | 6205 | 6090 | 5975 | 5885 | 5800 |
| T445680 | 600/65R34 | 163D | SB | TL | DW18L | DW20B | 581 | 1641 | 754 | 4960 | 775 | 320 | 400 | 52 | R-1W | 5340 | 5215 | 5120 | 5020 | 4950 | 4875 |
| T445681 | 600/70R34 | 167D | SB | TL | DW18L | DW20B | 585 | 1703 | 775 | 5138 | 800 | 320 | 400 | 52 | R-1W | 5970 | 5830 | 5725 | 5615 | 5530 | 5450 |
| T445682 | 600/65R38 | 165D | SB | TL | DW18L | DW20B | 579 | 1744 | 805 | 5282 | 825 | 320 | 400 | 53 | R-1W | 5640 | 5510 | 5410 | 5305 | 5225 | 5150 |
| T445683 | 650/65R38 | 169D | SB | TL | DW20B | | 632 | 1811 | 830 | 5479 | 875 | 320 | 400 | 53 | R-1W | 6350 | 6205 | 6090 | 5975 | 5885 | 5800 |
| T445684 | 650/75R38 | 175D | SB | TL | DW20B | DW23B, DW21B | 644 | 1943 | 880 | 5894 | 925 | 320 | 400 | 55 | R-1W | 7555 | 7385 | 7245 | 7105 | 7005 | 6900 |
| T445685 | 650/85R38 | 178D | SB | TL | DW20B | DW23B, DW21B | 641 | 2068 | 941 | 6272 | 975 | 320 | 400 | 55 | R-1 | 8215 | 8025 | 7875 | 7725 | 7615 | 7500 |
| T445741 | 710/70R38 | 177D | SB | TL | DW23B | DW25B | 716 | 1955 | 890 | 5921 | 925 | 320 | 400 | 55 | R-1W | 7995 | 7810 | 7665 | 7520 | 7410 | 7300 |
| T445852 | 800/70R38 | 183D | SB | TL | DW27B | DW25B | 825 | 2083 | 951 | 6300 | 975 | 320 | 400 | 56 | R-1 | 9580 | 9365 | 9190 | 9015 | 8880 | 8750 |
| T445740 | 650/65R42 | 170D | SB | TL | DW20B | DW21B, DW23B | 633 | 1913 | 881 | 5799 | 925 | 320 | 400 | 55 | R-1W | 6570 | 6420 | 6300 | 6180 | 6090 | 6000 |
| T445686 | 710/70R42 | 179D | SB | TL | DW23B | DW25B | 716 | 2061 | 943 | 6235 | 975 | 320 | 400 | 56 | R-1W | 8485 | 8295 | 8140 | 7985 | 7865 | 7750 |
| T445687 | 710/75R42 | 181D | SB | TL | DW23B | DW25B | 716 | 2131 | 972 | 6458 | 1000 | 320 | 400 | 57 | R-1W | 9035 | 8830 | 8665 | 8500 | 8375 | 8250 |

# AGRICULTURAL AND CONTRACTING TIRES

## TRACTOR



36
**Nokian Tyres TR Multiplus**



38
**Nokian Tyres Ground King**



40
**Nokian Tyres Hakkapeliitta TRI**



43
**Nokian Tyres Soil King VF**



45
**Nokian Tyres TRI 2**



48
**Nokian Tyres TRI Steel**

## TRAILER



50
**Nokian Tyres Country King**



52
**Nokian Tyres Country King G2**



54
**Nokian Tyres CT**



56
**Nokian Tyres ELS**



58
**Nokian Tyres Float King VF**

## WHEEL LOADER



40
**Nokian Tyres Hakkapeliitta TRI**

# NOKIAN TYRES TR MULTIPLUS

## FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.




## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415

# NOKIAN TYRES TR MULTIPLUS

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for tractor, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445410 | 500/65R24 | 142A8 (139B) | SB | TL | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 489 | 1242 | 575 | 3735 | 600 | 240 | 320 | 48 | R-1 | | 2940 | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445411 | 500/65R28 | 144A8 (141B) | SB | TL | DW15L | DW16L, W16L, W15L, W14L, W13 | 491 | 1341 | 622 | 4055 | 650 | 240 | 320 | 48 | R-1 | T55097 | 3110 | 2995 | 2885 | 2800 | 2690 | 2550 |
| T445412 | 540/65R28 | 149A8 (146B) | SB | TL | DW16 | W15L, W16L, DW18L, W18L, DW16L | 522 | 1409 | 653 | 4254 | 675 | 240 | 320 | 51 | R-1 | T545229 | 3610 | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445413 | 600/65R34 | 157A8 (154B) | SB | TL | DW18L | W16L, W18L, DW20B, DW16L | 585 | 1640 | 750 | 4930 | 775 | 240 | 320 | 52 | R-1 | T55395 | 4580 | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445414 | 600/65R38 | 159A8 (156B) | SB | TL | DW18L | W16L, W18L, DW20B, DW16L | 584 | 1743 | 809 | 5290 | 825 | 240 | 320 | 52 | R-1 | | 4855 | 4680 | 4505 | 4375 | 4200 | 3980 |
| T445415 | 650/65R38 | 164A8 (160B) | SB | TL | DW20B | DW18 | 641 | 1808 | 838 | 5485 | 875 | 240 | 320 | 53 | R-1 | T545322 | 5410 | 5215 | 5020 | 4875 | 4680 | 4435 |

# NOKIAN TYRES GROUND KING

## CROSSOVER TIRE FOR MIXED AGRICULTURAL WORK

- Advanced alternative for the lug pattern traction tire that combines the features and benefits of two pattern types.
- Solid performance on fields and roads with traction, multi-directional grip and continuous contact.
- Supports the versatile use of implements with stability, high strength and load capacity.





## AVAILABLE SIZES

- 420/70R28 - T445733
- 480/65R28 - T445764
- 480/70R28 - T445735
- 540/65R28 - T445737
- 600/65R28 - T445762
- 600/70R28 - T445763
- 540/65R30 - T445728
- 600/70R30 - T445726
- 600/65R34 - T445729
- 600/70R34 - T445730
- 650/65R34 - T445731
- 520/70R38 - T445732
- 580/70R38 - T445734
- 600/65R38 - T445765
- 650/65R38 - T445738
- 650/85R38 - T445743
- 710/70R38 - T445744
- 650/65R42 - T445727
- 710/70R42 - T445725
- 710/75R42 - T445722

# NOKIAN TYRES GROUND KING

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | M+S | Load capacity for tractor, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 45 | 50 | 55 | 60 | 65 | 70 |
| T445733 | 420/70R28 | 144D (141E) | SB | TL | DW13 | DW14L, DW12 | 408 | 1352 | 620 | 4102 | 650 | 320 | 320 | 46 | R-1W | Yes | 2995 | 2940 | 2885 | 2840 | 2800 | 2550 |
| T445764 | 480/65R28 | 148D (145E) | SB | TL | DW15L | DW14L | 475 | 1348 | 617 | 4091 | 650 | 320 | 320 | 45 | R-1W | Yes | 3370 | 3310 | 3245 | 3195 | 3150 | 2865 |
| T445735 | 480/70R28 | 151D (148E) | SB | TL | DW15L | DW16L, DW14L | 471 | 1409 | 642 | 4270 | 675 | 320 | 320 | 48 | R-1W | Yes | 3690 | 3625 | 3555 | 3500 | 3450 | 3140 |
| T445737 | 540/65R28 | 154D (151E) | SB | TL | DW18L | DW16L | 536 | 1403 | 637 | 4244 | 675 | 320 | 320 | 50 | R-1W | Yes | 4015 | 3940 | 3865 | 3805 | 3750 | 3415 |
| T445762 | 600/65R28 | 160D (156E) | SB | TL | DW20B | DW18L | 600 | 1507 | 682 | 4564 | 700 | 320 | 320 | 55 | R-1W | Yes | 4815 | 4725 | 4635 | 4570 | 4500 | 4095 |
| T445763 | 600/70R28 | 164D (160E) | SB | TL | DW20B | DW18L | 601 | 1563 | 708 | 4756 | 725 | 320 | 320 | 55 | R-1W | Yes | 5350 | 5250 | 5150 | 5075 | 5000 | 4550 |
| T445728 | 540/65R30 | 155D (152E) | SB | TL | DW18L | DW16L | 535 | 1475 | 679 | 4451 | 700 | 320 | 320 | 50 | R-1W | Yes | 4145 | 4070 | 3990 | 3935 | 3875 | 3525 |
| T445726 | 600/70R30 | 165D (161E) | SB | TL | DW20B | DW18L | 600 | 1588 | 714 | 4820 | 750 | 320 | 320 | 55 | R-1W | Yes | 5510 | 5410 | 5305 | 5225 | 5150 | 4685 |
| T445729 | 600/65R34 | 163D (159E) | SB | TL | DW20B | DW18L | 600 | 1644 | 751 | 5016 | 775 | 320 | 320 | 55 | R-1W | Yes | 5215 | 5120 | 5020 | 4950 | 4875 | 4435 |
| T445730 | 600/70R34 | 167D (163E) | SB | TL | DW20B | DW18L | 594 | 1701 | 771 | 5170 | 800 | 320 | 320 | 55 | R-1W | Yes | 5830 | 5725 | 5615 | 5530 | 5450 | 4960 |
| T445731 | 650/65R34 | 167D (164E) | SB | TL | DW20B | | 632 | 1700 | 769 | 5173 | 825 | 320 | 320 | 55 | R-1W | Yes | 5830 | 5725 | 5615 | 5530 | 5450 | 4960 |
| T445732 | 520/70R38 | 160D (157E) | SB | TL | DW16L | DW18L, DW15L | 516 | 1752 | 803 | 5342 | 825 | 320 | 320 | 55 | R-1W | Yes | 4815 | 4725 | 4635 | 4570 | 4500 | 4095 |
| T445734 | 580/70R38 | 166D (163E) | SB | TL | DW18L | | 577 | 1829 | 835 | 5574 | 875 | 320 | 320 | 56 | R-1W | Yes | 5670 | 5565 | 5460 | 5380 | 5300 | 4825 |
| T445765 | 600/65R38 | 165D (161E) | SB | TL | DW20B | DW18L | 601 | 1745 | 798 | 5321 | 825 | 320 | 320 | 55 | R-1W | Yes | 5510 | 5410 | 5305 | 5225 | 5150 | 4685 |
| T445738 | 650/65R38 | 169D (166E) | SB | TL | DW20B | | 635 | 1820 | 827 | 5540 | 875 | 320 | 320 | 59 | R-1W | Yes | 6205 | 6090 | 5975 | 5885 | 5800 | 5280 |
| T445743 | 650/85R38 | 178D (175E) | SB | TL | DW20B | DW21B, DW23B | 645 | 2071 | 933 | 6272 | 975 | 320 | 320 | 63 | R-1W | Yes | 8025 | 7875 | 7725 | 7615 | 7500 | 6825 |
| T445744 | 710/70R38 | 177D (174E) | SB | TL | DW23B | DW25B | 705 | 1953 | 884 | 5934 | 925 | 320 | 320 | 62 | R-1W | Yes | 7810 | 7665 | 7520 | 7410 | 7300 | 6645 |
| T445727 | 650/65R42 | 170D (167E) | SB | TL | DW20B | | 634 | 1913 | 872 | 5811 | 925 | 320 | 320 | 59 | R-1W | Yes | 6420 | 6300 | 6180 | 6090 | 6000 | 5460 |
| T445725 | 710/70R42 | 179D (175E) | SB | TL | DW23B | | 706 | 2059 | 933 | 6245 | 975 | 320 | 320 | 62 | R-1W | Yes | 8295 | 8140 | 7985 | 7865 | 7750 | 7055 |
| T445722 | 710/75R42 | 181D (178E) | SB | TL | DW23B | | 703 | 2132 | 964 | 6476 | 1000 | 320 | 320 | 62 | R-1W | Yes | 8830 | 8665 | 8500 | 8375 | 8250 | 7510 |

# NOKIAN TYRES HAKKAPELIITTA TRI

## A M+S BLOCK PATTERNED TIRE WITH SUPERIOR WINTER GRIP FOR YEAR-ROUND WORK IN BUILT ENVIRONMENTS

- Safety and effectivity with siped M+S block pattern and all-season grip compound.
- High level comfort due to low noise and vibration design.
- Use economy in year round use with long service life tread compound and energy efficiency.






## AVAILABLE SIZES

- 250/75R16 - T845540
- 250/80R16 - T845541
- 340/80R18 - T445665
- 400/60R18 - T445667
- 400/70R18 - T445832
- 360/70R20 - T445756
- 360/80R20 - T445666
- 400/70R20 - T445636
- 300/80R24 - T445757
- 340/80R24 - T445753
- 360/80R24 - T445587
- 400/80R24 - T445582
- 420/65R24 - T445586
- 440/80R24 - T445634
- 460/70R24 - T445669
- 500/70R24 - T445671
- 540/70R24 - T445672
- 360/80R28 - T445752
- 400/80R28 - T445584
- 440/80R28 - T445563
- 540/65R28 - T445772
- 440/80R30 - T445758
- 480/80R30 - T445754
- 540/65R30 - T445736
- 540/65R30 - T445609
- 600/70R30 - T445848
- 440/80R34 - T445588
- 480/80R34 - T445583
- 600/70R34 - T445700
- 480/80R38 - T445585
- 540/80R38 - T445564
- 650/65R38 - T445773
- 650/65R42 - T445595
- 710/70R42 - T445847

nokian® TYRES

# NOKIAN TYRES HAKKAPELIITTA TRI

## ALL SIZES FOR TRACTOR

| Product code | Size | Equivalent size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | M+S | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T845540 | 250/75R16 | | 120G | | TL | 8 | W7, 7, 7J, W8, 8J, W9, 9, 9J | 258 | 783 | 363 | 2390 | 370 | 450 | 450 | 16 | R-4 | Yes | 1670 | 1625 | 1565 | 1525 | 1495 | 1450 |
| T845541 | 250/80R16 | 7.5R16 | 119G | | TL | 8 | W7, 7, 7J, W8, 8J, W9, 9, 9J | 275 | 818 | 377 | 2494 | 390 | 450 | 450 | 17 | R-4 | Yes | 1785 | 1735 | 1675 | 1630 | 1595 | 1550 |
| T445667 | 400/60R18 | | 148A8 (143D) | SB | TL | 13 | | 400 | 950 | 427 | 2870 | 450 | 500 | 500 | 26 | R-4 | Yes | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445756 | 360/70R20 | | 136A8 (131D) | SB | TL | W11 | 10, W10, 12, W12 | 343 | 1029 | 466 | 3111 | 475 | 320 | 320 | 24 | R-4 | Yes | 2245 | 2185 | 2105 | 2050 | 2010 | 1950 |
| T445757 | 300/80R24 | 11.2R24 | 133A8 (128D) | SB | TL | DW10 | W9, W10, W11, DW11 | 301 | 1077 | 492 | 3260 | 525 | 320 | 320 | 24 | R-4 | Yes | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| T445753 | 340/80R24 | 12.4R24 | 140A8 (135D) | SB | TL | DW11 | DW10, DW12 | 333 | 1138 | 517 | 3445 | 550 | 320 | 320 | 24 | R-4 | Yes | 2505 | 2440 | 2355 | 2290 | 2245 | 2180 |
| T445587 | 360/80R24 | 13.6R24 | 143A8 (138D) | SB | TL | DW11 | DW10, DW12, DW13 | 357 | 1185 | 543 | 3600 | 575 | 320 | 320 | 24 | R-4 | Yes | 2795 | 2720 | 2625 | 2550 | 2505 | 2430 |
| T445582 | 400/80R24 | 14.9R24 | 149A8 (144D) | SB | TL | DW13 | DW12, DW14L | 399 | 1248 | 567 | 3770 | 600 | 320 | 320 | 25 | R-4 | Yes | 3220 | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445634 | 440/80R24 | 16.9R24 | 154A8 (149D) | SB | TL | DW14L | DW15L | 435 | 1294 | 585 | 3921 | 625 | 320 | 320 | 26 | R-4 | Yes | 3740 | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445752 | 360/80R28 | 13.6R28 | 146A8 (142D) | SB | TL | DW11 | DW12, DW13 | 349 | 1311 | 595 | 3998 | 625 | 320 | 320 | 24 | R-4 | Yes | 2960 | 2885 | 2780 | 2705 | 2650 | 2575 |
| T445584 | 400/80R28 | 14.9R28 | 151A8 (146D) | SB | TL | DW13 | DW12, DW14L | 400 | 1351 | 617 | 4103 | 650 | 320 | 320 | 25 | R-4 | Yes | 3535 | 3445 | 3320 | 3230 | 3165 | 3075 |
| T445563 | 440/80R28 | 16.9R28 | 156A8 (151D) | SB | TL | DW14L | DW15L, DW16L | 440 | 1414 | 640 | 4285 | 675 | 320 | 320 | 26 | R-4 | Yes | 4085 | 3975 | 3835 | 3730 | 3655 | 3550 |
| T445772 | 540/65R28 | | 160A8 (155D) | SB | TL | DW18L | DW16L | 535 | 1398 | 634 | 4243 | 675 | 320 | 320 | 28 | R-4 | Yes | 4455 | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445758 | 440/80R30 | 16.9R30 | 157A8 (153D) | SB | TL | DW14L | DW15L, W16L | 435 | 1455 | 657 | 4426 | 700 | 320 | 320 | 26 | R-4 | Yes | 4200 | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445754 | 480/80R30 | 18.4R30 | 162A8 (157D) | SB | TL | DW15L | DW16L, DW18L | 466 | 1536 | 692 | 4671 | 725 | 320 | 320 | 27 | R-4 | Yes | 4745 | 4620 | 4455 | 4330 | 4250 | 4125 |
| T445736 | 540/65R30 | | 171A8 (166D) | SB | TL | DW18L | DW16L | 534 | 1460 | 667 | 4442 | 700 | 450 | 450 | 28 | R-4 | Yes | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445609 | 540/65R30 | | 161A8 (156D) | SB | TL | DW18L | DW16L | 530 | 1463 | 665 | 4430 | 700 | 320 | 320 | 28 | R-4 | Yes | 4600 | 4480 | 4320 | 4200 | 4120 | 4000 |
| T445848 | 600/70R30 | | 171A8 (166D) | SB | TL | DW20B | DW18L | 602 | 1581 | 709 | 4772 | 750 | 320 | 320 | 30 | R-4 | Yes | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445588 | 440/80R34 | 16.9R34 | 159A8 (155D) | SB | TL | DW14L | DW15L, DW16L | 442 | 1570 | 718 | 4763 | 750 | 320 | 320 | 26 | R-4 | Yes | 4455 | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445583 | 480/80R34 | 18.4R34 | 164A8 (159D) | SB | TL | DW15L | DW16L, DW18L | 482 | 1631 | 744 | 4964 | 775 | 320 | 320 | 27 | R-4 | Yes | 5030 | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445700 | 600/70R34 | | 172A8 (168D) | SB | TL | DW20B | DW18L | 593 | 1676 | 755 | 5102 | 800 | 320 | 320 | 28 | R-4 | Yes | 6440 | 6270 | 6050 | 5880 | 5770 | 5600 |
| T445585 | 480/80R38 | 18.4R38 | 166A8 (161D) | SB | TL | DW15L | DW16L, DW18L | 477 | 1733 | 792 | 5284 | 825 | 320 | 320 | 27 | R-4 | Yes | 5320 | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445564 | 540/80R38 | | 172A8 (167D) | SB | TL | DW18L | DW16L | 556 | 1833 | 832 | 5566 | 875 | 320 | 320 | 27 | R-4 | Yes | 6440 | 6270 | 6050 | 5880 | 5770 | 5600 |
| T445773 | 650/65R38 | | 175A8 (170D) | SB | TL | DW20B | DW21B, DW23B | 625 | 1821 | 825 | 5555 | 875 | 320 | 320 | 31 | R-4 | Yes | 6900 | 6720 | 6480 | 6300 | 6180 | 6000 |
| T445595 | 650/65R42 | | 176A8 (171D) | SB | TL | DW20B | DW18L | 627 | 1912 | 871 | 5836 | 925 | 320 | 320 | 31 | R-4 | Yes | 7075 | 6890 | 6640 | 6460 | 6335 | 6150 |
| T445847 | 710/70R42 | | 185A8 (180D) | SB | TL | DW23B | DW25B | 704 | 2065 | 857 | 6251 | 975 | 320 | 320 | 35 | R-4 | Yes | 9200 | 8960 | 8640 | 8400 | 8240 | 8000 |

# ALL SIZES FOR WHEEL LOADER

| Product code | Size | Equivalent size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445665 | 340/80R18 | 12.5R18 | 143A8 (138D) | SB | TL | 11 | W11, 10, W10, 12, W12 | 328 | 1001 | 452 | 3031 | 475 | 400 | 400 | 24 | R-4 | | Yes | 2715 | 2645 | 2550 | 2480 | 2430 | 2360 |
| T445832 | 400/70R18 | 16.0/ 70R18 | 147A8 (143D) | SB | TL | 13 | W13, 12, W12 | 400 | 1018 | 458 | 3068 | 475 | 400 | 400 | 26 | R-4 | | Yes | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445666 | 360/80R20 | 13.6R20 | 148A8 (143D) | SB | TL | 11 | W11, 10, W10, 12, W12 | 360 | 1093 | 493 | 3311 | 525 | 400 | 400 | 24 | R-4 | | Yes | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445636 | 400/70R20 | 16.0/ 70R20 | 149A8 (144D) | SB | TL | 13 | | 394 | 1071 | 485 | 3231 | 500 | 400 | 400 | 26 | R-4 | | Yes | 3220 | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445586 | 420/65R24 | | 151A8 (146D) | SB | TL | DW13 | DW12, DW14L, DW15L | 402 | 1157 | 520 | 3487 | 550 | 400 | 400 | 25 | R-4 | T55112 | Yes | 3450 | 3360 | 3240 | 3150 | 3090 | 3000 |
| T445669 | 460/70R24 | 17.5LR24 | 166A8 (161D) | SB | TL | DW14L | DW15L | 460 | 1255 | 557 | 3792 | 600 | 500 | 500 | 30 | R-4 | T55112 | Yes | 5320 | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445671 | 500/70R24 | 19.5LR24 | 171A8 (166D) | SB | TL | DW16L | DW15L, DW18L | 500 | 1314 | 580 | 3971 | 625 | 500 | 500 | 30 | R-4 | | Yes | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445672 | 540/70R24 | 21LR24 | 175A8 (170D) | SB | TL | DW18L | DW16L | 540 | 1367 | 603 | 4143 | 650 | 500 | 500 | 30 | R-4 | | Yes | 6900 | 6720 | 6480 | 6300 | 6180 | 6000 |

# NOKIAN TYRES SOIL KING VF

## ADVANCED TRACTION TIRE WITH HIGHLY EFFICIENT GROUND CONTACT FOR HIGH-POWER TRACTORS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- Deep and extra wide pattern, provides big and powerful traction surface
- The center-zone pattern featuring extended and laterally supported lug tips balances behaviour and reduces loss of power on field and on road




## AVAILABLE SIZES

- VF540/65R28 - T445885
- VF600/65R28 - T445809
- VF600/70R28 - T445813
- VF540/65R30 - T445811
- VF600/60R30 - T445861
- VF600/70R30 - T445769
- VF600/70R34 - T445760
- VF650/60R34 - T445815
- VF650/65R34 - T445830
- VF710/60R34 - T445864
- VF650/65R38 - T445884
- VF650/85R38 - T445808
- VF710/70R38 - T445812
- VF650/65R42 - T445810
- VF710/60R42 - T445873
- VF710/70R42 - T445768
- VF710/75R42 - T445759

# NOKIAN TYRES SOIL KING VF

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 40 | 50 | 55 | 60 | 65 | 70 |
| T445885 | VF540/65R28 | 157D (154E) | SB | TL | DW20B | DW18L, DW16L | 558 | 1421 | 636 | 4234 | 675 | 200 | 280 | 55 | R-1W | 721 | 4125 | 4125 | 4125 | 4125 | 4125 | 3755 |
| T445809 | VF600/65R28 | 163D (160E) | SB | TL | DW21B | DW20B, DW18L | 604 | 1514 | 672 | 4516 | 700 | 200 | 280 | 55 | R-1W | 776 | 4875 | 4875 | 4875 | 4875 | 4875 | 4435 |
| T445813 | VF600/70R28 | 167D (164E) | SB | TL | DW21B | DW20B, DW18L | 614 | 1580 | 685 | 4703 | 725 | 200 | 280 | 55 | R-1W | 788 | 5450 | 5450 | 5450 | 5450 | 5450 | 4960 |
| T445811 | VF540/65R30 | 158D (155E) | SB | TL | DW20B | DW18L, DW16L | 558 | 1488 | 665 | 4444 | 700 | 200 | 280 | 55 | R-1W | 721 | 4250 | 4250 | 4250 | 4250 | 4250 | 3870 |
| T445861 | VF600/60R30 | 162D (158E) | SB | TL | DW20B | DW21B, DW18L | 588 | 1492 | 655 | 4442 | 700 | 200 | 280 | 55 | R-1W | 757 | 4750 | 4750 | 4750 | 4750 | 4750 | 4325 |
| T445769 | VF600/70R30 | 168D (165E) | SB | TL | DW21B | DW18L, DW20B | 615 | 1598 | 697 | 4817 | 750 | 200 | 280 | 55 | R-1W | 789 | 5600 | 5600 | 5600 | 5600 | 5600 | 5095 |
| T445760 | VF600/70R34 | 170D (167E) | SB | TL | DW21B | DW20B, DW18L | 613 | 1720 | 755 | 5142 | 800 | 200 | 280 | 58 | R-1W | 787 | 6000 | 6000 | 6000 | 6000 | 6000 | 5460 |
| T445815 | VF650/60R34 | 168D (165E) | SB | TL | DW23B | DW21B, DW20B | 658 | 1667 | 735 | 4979 | 775 | 200 | 280 | 58 | R-1W | 841 | 5600 | 5600 | 5600 | 5600 | 5600 | 5095 |
| T445830 | VF650/65R34 | 170D (167E) | SB | TL | DW23B | DW21B, DW20B | 660 | 1720 | 759 | 5159 | 825 | 200 | 280 | 58 | R-1W | 843 | 6000 | 6000 | 6000 | 6000 | 6000 | 5460 |
| T445864 | VF710/60R34 | 173D (170E) | SB | TL | DW25B | DW24B | 712 | 1728 | 760 | 5169 | 825 | 200 | 280 | 58 | R-1W | 905 | 6500 | 6500 | 6500 | 6500 | 6500 | 5915 |
| T445884 | VF650/65R38 | 172D (169E) | SB | TL | DW23B | DW21B, DW20B | 658 | 1835 | 823 | 5509 | 875 | 200 | 280 | 59 | R-1W | 841 | 6300 | 6300 | 6300 | 6300 | 6300 | 5735 |
| T445808 | VF650/85R38 | 182D (179E) | SB | TL | DW23B | DW21B, DW20B | 668 | 2064 | 900 | 6190 | 975 | 200 | 280 | 63 | R-1W | 853 | 8500 | 8500 | 8500 | 8500 | 8500 | 7735 |
| T445812 | VF710/70R38 | 181D (178E) | SB | TL | DW25B | DW24B, DW23B | 721 | 1959 | 862 | 5885 | 925 | 200 | 280 | 63 | R-1W | 916 | 8250 | 8250 | 8250 | 8250 | 8250 | 7510 |
| T445810 | VF650/65R42 | 174D (170E) | SB | TL | DW23B | DW21B, DW20B | 658 | 1923 | 855 | 5770 | 925 | 200 | 280 | 59 | R-1W | 841 | 6700 | 6700 | 6700 | 6700 | 6700 | 6095 |
| T445873 | VF710/60R42 | 176D (173E) | SB | TL | DW25B | DW24B, DW23B | 717 | 1930 | 861 | 5796 | 925 | 200 | 280 | 63 | R-1W | 911 | 7100 | 7100 | 7100 | 7100 | 7100 | 6460 |
| T445768 | VF710/70R42 | 182D (179E) | SB | TL | DW25B | DW23B, DW24B | 730 | 2075 | 906 | 6274 | 975 | 200 | 280 | 63 | R-1W | 927 | 8500 | 8500 | 8500 | 8500 | 8500 | 7735 |
| T445759 | VF710/75R42 | 184D (181E) | SB | TL | DW25B | DW23B, DW24B | 727 | 2150 | 943 | 6448 | 1000 | 200 | 280 | 66 | R-1W | 923 | 9000 | 9000 | 9000 | 9000 | 9000 | 8190 |

# NOKIAN TYRES TRI 2

## A M+S BLOCK PATTERNED TIRE FOR WORK ON HARD GROUNDS AND ROADS IN ALL SEASONS

- Use economy with durable long service life block pattern and energy efficiency.
- Reliable grip and comfortable handling also in varying weather conditions.
- Use of heavy implements enabled by high load capacity and strength of steel belted construction.




## AVAILABLE SIZES

- 250/75R16 - T845539
- 250/80R16 - T845495
- 340/80R18 - T445391
- 360/70R20 - T445569
- 360/80R20 - T445389
- 300/80R24 - T445419
- 340/80R24 - T445376
- 360/80R24 - T445378
- 400/80R24 - T445372
- 420/65R24 - T445392
- 440/80R24 - T445385
- 460/65R24 - T445393
- 500/70R24 - T445467
- 540/65R24 - T445420
- 320/85R28 - T445579
- 360/80R28 - T445550
- 400/80R28 - T445383
- 440/80R28 - T445337
- 480/65R28 - T445444
- 540/65R28 - T445442
- 440/80R30 - T445384
- 480/80R30 - T445386
- 540/65R30 - T445371
- 600/70R30 - T445657
- 440/80R34 - T445369
- 480/80R34 - T445370
- 600/65R34 - T445656
- 480/80R38 - T445377
- 540/80R38 - T445338
- 600/65R38 - T445445
- 650/65R38 - T445443
- 620/80R42 - T445518
- 650/65R42 - T445390
- 710/70R42 - T445655

# NOKIAN TYRES TRI 2

## ALL SIZES

| Product code | Size | Equivalent size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T845539 | 250/75R16 | | 120G | SB | TL | 8 | W7, 7, 7J, W8, 8J, W9, 9, 9J | 258 | 783 | 363 | 2390 | 370 | 450 | 450 | 16 | R-4 | | Yes | 1670 | 1625 | 1565 | 1525 | 1495 | 1450 |
| T845495 | 250/80R16 | 7.5R16 | 119G | SB | TL | 8 | W7, 7, 7J, W8, 8J, W9, 9, 9J | 274 | 818 | 377 | 2494 | 390 | 450 | 450 | 17 | R-4 | | Yes | 1785 | 1735 | 1675 | 1630 | 1595 | 1550 |
| T445391 | 340/80R18 | 12.5R18 | 143A8 (138D) | SB | TL | 11 | W11, 10, W10, 12, W12 | 341 | 1002 | 453 | 3010 | 475 | 400 | 400 | 25 | R-4 | | Yes | 2715 | 2645 | 2550 | 2480 | 2430 | 2360 |
| T445569 | 360/70R20 | | 136A8 (131D) | SB | TL | 11 | W11, 10, W10, 12, W12 | 341 | 1030 | 470 | 3104 | 500 | 320 | 320 | 26 | R-4 | | Yes | 2245 | 2185 | 2105 | 2050 | 2010 | 1950 |
| T445389 | 360/80R20 | 13.6R20 | 147A8 (143D) | SB | TL | 11 | W11, 10, W11, 12, W12 | 355 | 1095 | 495 | 3286 | 500 | 400 | 400 | 26 | R-4 | | Yes | 3135 | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445419 | 300/80R24 | 11.2R24 | 133A8 (128D) | SB | TL | DW10 | W9, W10, W11, DW11 | 295 | 1090 | 502 | 3297 | 525 | 320 | 320 | 24 | R-4 | | Yes | 2070 | 2015 | 1945 | 1890 | 1855 | 1800 |
| T445376 | 340/80R24 | 12.4R24 | 140A8 (135D) | SB | TL | DW11 | DW10, DW12 | 330 | 1154 | 521 | 3487 | 550 | 320 | 320 | 25 | R-4 | | Yes | 2505 | 2440 | 2355 | 2290 | 2245 | 2180 |
| T445378 | 360/80R24 | 13.6R24 | 143A8 (138D) | SB | TL | DW11 | DW10, DW12 | 347 | 1184 | 539 | 3574 | 575 | 320 | 320 | 26 | R-4 | | Yes | 2795 | 2720 | 2625 | 2550 | 2505 | 2430 |
| T445372 | 400/80R24 | 14.9R24 | 149A8 (144D) | SB | TL | DW13 | DW12, DW14L | 395 | 1248 | 560 | 3763 | 600 | 320 | 320 | 27 | R-4 | T55112 | Yes | 3220 | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445392 | 420/65R24 | | 151A8 (146D) | SB | TL | DW13 | DW12, DW14, DW15L | 402 | 1155 | 525 | 3493 | 550 | 400 | 400 | 26 | R-4 | T55112 | Yes | 3450 | 3360 | 3240 | 3150 | 3090 | 3000 |
| T445385 | 440/80R24 | 16.9R24 | 154A8 (149D) | SB | TL | DW14L | DW15L | 430 | 1312 | 585 | 3958 | 625 | 320 | 320 | 28 | R-4 | T55112 | Yes | 3740 | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445393 | 460/65R24 | | 156A8 (151D) | SB | TL | DW14L | DW15L, DW16L | 439 | 1204 | 540 | 3644 | 575 | 400 | 400 | 28 | R-4 | T55112 | Yes | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| T445467 | 500/70R24 | 19.5LR24 | 164A8 (159D) | SB | TL | DW16L | DW15L, DW18L | 515 | 1307 | 585 | 3958 | 625 | 400 | 400 | 28 | R-4 | | Yes | 5030 | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445420 | 540/65R24 | | 158A8 (154D) | SB | TL | DW18L | DW16L | 535 | 1307 | 582 | 3965 | 625 | 320 | 320 | 28 | R-4 | | Yes | 4200 | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445579 | 320/85R28 | 12.4R28 | 141A8 (136D) | SB | TL | DW10 | W9, DW11, W10 | 312 | 1250 | 575 | 3788 | 600 | 320 | 320 | 24 | R-4 | | Yes | 2645 | 2575 | 2485 | 2415 | 2370 | 2300 |
| T445550 | 360/80R28 | 13.6R28 | 146A8 (142D) | SB | TL | DW11 | DW12, DW13 | 353 | 1302 | 595 | 3946 | 625 | 320 | 320 | 26 | R-4 | | Yes | 2960 | 2885 | 2780 | 2705 | 2650 | 2575 |
| T445383 | 400/80R28 | 14.9R28 | 151A8 (146D) | SB | TL | DW13 | DW12, DW14L | 397 | 1351 | 620 | 4078 | 650 | 320 | 320 | 27 | R-4 | | Yes | 3535 | 3445 | 3320 | 3230 | 3165 | 3075 |
| T445337 | 440/80R28 | 16.9R28 | 156A8 (151D) | SB | TL | DW14L | DW15L, DW16L | 433 | 1413 | 644 | 4266 | 675 | 320 | 320 | 28 | R-4 | | Yes | 4085 | 3975 | 3835 | 3730 | 3655 | 3550 |
| T445444 | 480/65R28 | | 154A8 (149D) | SB | TL | DW15L | DW14L, DW16L | 464 | 1336 | 604 | 4025 | 650 | 320 | 320 | 28 | R-4 | T55097 | Yes | 3740 | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445442 | 540/65R28 | | 160A8 (155D) | SB | TL | DW18L | DW16L | 531 | 1411 | 641 | 4247 | 675 | 320 | 320 | 28 | R-4 | T545229 | Yes | 4455 | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445384 | 440/80R30 | 16.9R30 | 157A8 (153D) | SB | TL | DW14L | DW15L, DW16L | 430 | 1464 | 660 | 4448 | 700 | 320 | 320 | 28 | R-4 | T55371 | Yes | 4200 | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445386 | 480/80R30 | 18.4R30 | 162A8 (157D) | SB | TL | DW15L | DW16L, DW18L | 472 | 1526 | 683 | 4636 | 725 | 320 | 320 | 29 | R-4 | T55371 | Yes | 4745 | 4620 | 4455 | 4330 | 4250 | 4125 |
| T445371 | 540/65R30 | | 161A8 (156D) | SB | TL | DW18L | DW16L | 530 | 1460 | 644 | 4401 | 700 | 320 | 320 | 30 | R-4 | T55371 | Yes | 4600 | 4480 | 4320 | 4200 | 4120 | 4000 |
| T445657 | 600/70R30 | | 171A8 (166D) | SB | TL | DW20B | DW18L | 604 | 1564 | 702 | 4756 | 750 | 320 | 320 | 32 | R-4 | | Yes | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445369 | 440/80R34 | 16.9R34 | 159A8 (155D) | SB | TL | DW14L | DW15L, DW16L | 427 | 1567 | 717 | 4751 | 750 | 320 | 320 | 28 | R-4 | T55391 | Yes | 4455 | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445370 | 480/80R34 | 18.4R34 | 164A8 (159D) | SB | TL | DW15L | DW16L, DW18L | 472 | 1630 | 734 | 4951 | 775 | 320 | 320 | 29 | R-4 | T55391 | Yes | 5030 | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445656 | 600/65R34 | | 169A8 (164D) | SB | TL | DW20B | DW18L | 595 | 1619 | 736 | 4935 | 775 | 320 | 320 | 32 | R-4 | | Yes | 5750 | 5600 | 5400 | 5250 | 5150 | 5000 |
| T445377 | 480/80R38 | 18.4R38 | 166A8 (161D) | SB | TL | DW15L | DW16L, DW18L | 466 | 1733 | 793 | 5256 | 825 | 320 | 320 | 29 | R-4 | | Yes | 5320 | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445338 | 540/80R38 | 20.8R28 | 172A8 (167D) | SB | TL | DW18L | DW16L | 553 | 1825 | 834 | 5523 | 875 | 320 | 320 | 30 | R-4 | | Yes | 6440 | 6270 | 6050 | 5880 | 5770 | 5600 |

| Product code | Size | Equivalent size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445445 | 600/65R38 | | 170A8 (166D) | SB | TL | DW18L | DW20B | 583 | 1740 | 790 | 5290 | 825 | 320 | 320 | 30 | R-4 | | Yes | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445443 | 650/65R38 | | 175A8 (170D) | SB | TL | DW20B | DW18L, DW23B | 620 | 1810 | 819 | 5510 | 875 | 320 | 320 | 33 | R-4 | | Yes | 6900 | 6720 | 6480 | 6300 | 6180 | 6000 |
| T445518 | 620/80R42 | | 181A8 (177D) | SB | TL | DW20B | DW23B | 626 | 2059 | 925 | 6289 | 975 | 320 | 320 | 35 | R-4 | | Yes | 8395 | 8175 | 7885 | 7665 | 7520 | 7300 |
| T445390 | 650/65R42 | | 176A8 (171D) | SB | TL | DW20B | DW18L, DW23B | 617 | 1913 | 848 | 5791 | 925 | 320 | 320 | 33 | R-4 | | Yes | 7075 | 6890 | 6640 | 6460 | 6335 | 6150 |
| T445655 | 710/70R42 | | 185A8 (180D) | SB | TL | DW23B | | 717 | 2045 | 923 | 6255 | 975 | 320 | 320 | 37 | R-4 | | Yes | 9200 | 8960 | 8640 | 8400 | 8240 | 8000 |

# NOKIAN TYRES TRI STEEL

## PUNCTURE PROTECTION FOR SPECIAL APPLICATIONS

- A special loader tire with a puncture-resisting block pattern.
- Steel fortification for extra durability.
- Suitable for waste treatment, recycling plants and for industial use.




## AVAILABLE SIZES

- 460/65R24 - T445245
- 480/65R24 - T445222

# NOKIAN TYRES TRI STEEL

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445245 | 460/65R24 | 156A8 (151D) | TL | DW13 | W13, DW13L, W14L, DW14L, W15L, DW15L | 426 | 1184 | 545 | 3581 | 575 | 400 | 400 | 27 | R-4 | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| T445222 | 480/65R24 | 151A8 (146D) | TL | DW14L | W14L, W15L, DW15L, W16L, DW16L | 468 | 1237 | 565 | 3740 | 600 | 320 | 320 | 28 | R-4 | 3450 | 3360 | 3240 | 3150 | 3090 | 3000 |

# NOKIAN TYRES COUNTRY KING

## EFFICIENT RADIAL FLOTATION TIRE FOR AGRICULTURAL TRANSPORTATIONS ON ROAD AND FIELD

- Durability and low rolling resistance due to high positive pattern ratio and special tread compound.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.





## AVAILABLE SIZES

- 500/60R22.5 - T445453
- 560/45R22.5 - T445402
- 560/60R22.5 - T445401
- 580/65R22.5 - T445405
- 600/50R22.5 - T445441
- 650/50R22.5 - T445407
- 710/35R22.5 - T445542
- 710/45R22.5 - T445496
- 600/55R26.5 - T445653
- 620/60R26.5 - T445404
- 650/65R26.5 - T445440
- 710/50R26.5 - T445406
- 800/45R26.5 - T445600
- 650/65R30.5 - T445611
- 750/60R30.5 - T445610

# NOKIAN TYRES COUNTRY KING

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445453 | 500/60R22.5 | 155D | SB | TL | AG16.00 | | 510 | 1172 | 521 | 3581 | 550 | 400 | 400 | 17 | T55096 | 5270 | 5000 | 4690 | 4420 | 4145 | 3875 |
| T445402 | 560/45R22.5 | 152D | SB | TL | AG16.00 | | 538 | 1078 | 474 | 3280 | 525 | 400 | 400 | 16 | T56435 | 4830 | 4580 | 4295 | 4045 | 3800 | 3550 |
| T445401 | 560/60R22.5 | 161D | SB | TL | AG16.00 | AG18.00, AG20.00 | 567 | 1237 | 557 | 3764 | 600 | 400 | 400 | 18 | T55089 | 6290 | 5965 | 5595 | 5275 | 4950 | 4625 |
| T445405 | 580/65R22.5 | 166D | SB | TL | AG16.00 | AG18.00 | 584 | 1299 | 586 | 3977 | 625 | 400 | 400 | 19 | T55089 | 7210 | 6835 | 6415 | 6040 | 5670 | 5300 |
| T445441 | 600/50R22.5 | 159D | SB | TL | AG20.00 | | 594 | 1170 | 533 | 3575 | 550 | 400 | 400 | 18 | T55089 | 5950 | 5645 | 5295 | 4990 | 4680 | 4375 |
| T445407 | 650/50R22.5 | 163D | SB | TL | AG20.00 | | 644 | 1235 | 564 | 3789 | 575 | 400 | 400 | 18 | T55089 | 6630 | 6290 | 5900 | 5560 | 5215 | 4875 |
| T445542 | 710/35R22.5 | 157D | SB | TL | AG24.00 | | 696 | 1070 | 484 | 3248 | 525 | 400 | 400 | 22 | | 5610 | 5320 | 4990 | 4705 | 4415 | 4125 |
| T445496 | 710/45R22.5 | 165D | SB | TL | AG24.00 | | 697 | 1213 | 545 | 3695 | 575 | 400 | 400 | 19 | T55092 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445653 | 600/55R26.5 | 165D | SB | TL | AG20.00 | | 603 | 1335 | 604 | 4072 | 625 | 400 | 400 | 22 | T55098 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445404 | 620/60R26.5 | 169D | SB | TL | AG20.00 | | 632 | 1403 | 639 | 4291 | 675 | 400 | 400 | 20 | T55098 | 7890 | 7480 | 7020 | 6610 | 6205 | 5800 |
| T445440 | 650/65R26.5 | 174D | SB | TL | AG20.00 | | 656 | 1519 | 689 | 4656 | 725 | 400 | 400 | 20 | T55897 | 9110 | 8645 | 8105 | 7640 | 7170 | 6700 |
| T445406 | 710/50R26.5 | 170D | SB | TL | AG24.00 | | 740 | 1405 | 646 | 4304 | 650 | 400 | 400 | 21 | T55102 | 8365 | 7935 | 7440 | 7010 | 6580 | 6150 |
| T445600 | 800/45R26.5 | 174D | SB | TL | AG28.00 | AG24.00 | 769 | 1394 | 622 | 4240 | 675 | 400 | 400 | 26 | T55102 | 9110 | 8645 | 8105 | 7640 | 7170 | 6700 |
| T445611 | 650/65R30.5 | 176D | SB | TL | AG20.00 | | 647 | 1623 | 737 | 4969 | 775 | 400 | 400 | 26 | | 9655 | 9160 | 8590 | 8095 | 7595 | 7100 |
| T445610 | 750/60R30.5 | 181D | SB | TL | AG24.00 | | 760 | 1679 | 757 | 5144 | 800 | 400 | 400 | 26 | | 11220 | 10645 | 9985 | 9405 | 8830 | 8250 |

# NOKIAN TYRES COUNTRY KING G2

## PREMIUM FLOTATION TIRE FOR HIGH-PERFORMANCE AGRICULTURAL TRANSPORT

- Deep tread offers long-lasting performance and excellent value in transport use
- Dual-purpose tread pattern design delivers performance and reduces loss of power on both on-road transport and field conditions
- Large pattern contact and rounded shoulder design for advanced soil and crop damage prevention






## AVAILABLE SIZES

- 560/60R22.5 - T445876
- VF560/60R22.5 - T445919
- 600/50R22.5 - T445877
- 650/50R22.5 - T445878
- 710/45R22.5 - T445879
- VF600/55R26.5 - T445880
- VF620/60R26.5 - T445888
- VF650/55R26.5 - T445881
- VF710/50R26.5 - T445882
- VF800/45R26.5 - T445883

# NOKIAN TYRES COUNTRY KING G2

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Load capacity for mixed, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445876 | 560/60R22.5 | 161D | SB | TL | AG18.00 | AG16.00, AG20.00 | 560 | 1254 | 570 | 3814 | 600 | 400 | 400 | 22 | 6290 | 5965 | 5595 | 5275 | 4950 | 4625 |
| T445919 | VF560/60R22.5 | 166D | SB | TL | AG18.00 | AG16.00, AG20.00 | | | 552 | 3797 | 600 | 320 | 400 | 22 | 6835 | 6520 | 6200 | 5885 | 5620 | 5300 |
| T445877 | 600/50R22.5 | 159D | SB | TL | AG20.00 | | 613 | 1171 | 533 | 3567 | 550 | 400 | 400 | 22 | 5950 | 5645 | 5295 | 4990 | 4680 | 4375 |
| T445878 | 650/50R22.5 | 163D | SB | TL | AG20.00 | | 644 | 1231 | 557 | 3744 | 575 | 400 | 400 | 22 | 6630 | 6290 | 5900 | 5560 | 5215 | 4875 |
| T445879 | 710/45R22.5 | 165D | SB | TL | AG24.00 | | 733 | 1221 | 551 | 3723 | 575 | 400 | 400 | 22 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445880 | VF600/55R26.5 | 167D | SB | TL | AG20.00 | | 620 | 1353 | 596 | 4104 | 625 | 280 | 400 | 24 | 7030 | 6705 | 6375 | 6050 | 5775 | 5450 |
| T445888 | VF620/60R26.5 | 171D | SB | TL | AG20.00 | | 621 | 1439 | 631 | 4366 | 650 | 280 | 400 | 24 | 7935 | 7565 | 7195 | 6825 | 6520 | 6150 |
| T445881 | VF650/55R26.5 | 171D | SB | TL | AG20.00 | | 653 | 1411 | 615 | 4281 | 650 | 280 | 400 | 24 | 7935 | 7565 | 7195 | 6825 | 6520 | 6150 |
| T445882 | VF710/50R26.5 | 173D | SB | TL | AG24.00 | | 740 | 1404 | 611 | 4254 | 650 | 280 | 400 | 24 | 8385 | 7995 | 7605 | 7215 | 6890 | 6500 |
| T445883 | VF800/45R26.5 | 176D | SB | TL | AG28.00 | AG26.00 | 826 | 1415 | 615 | 4298 | 675 | 280 | 400 | 24 | 9160 | 8735 | 8305 | 7880 | 7525 | 7100 |

# NOKIAN TYRES CT

## EARTHMOVING GRADE RADIAL FLOTATION TIRE FOR HEAVY TRANSPORTATIONS

- Exceptional mileage provided by dense and thick heavy-duty block pattern.
- Special punture damage resistance with three layers of steel reinforcements in the tread area.
- Stable load-bearing provided by the extra-strength multilayer construction.



## AVAILABLE SIZES

- 560/60R22.5 - T445626
- 600/50R22.5 - T445627
- 600/55R26.5 - T445782
- 650/55R26.5 - T445556
- 600/60R30.5 - T445629

# NOKIAN TYRES CT

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445626 | 560/60R22.5 | 165D | SB | TL | AG18.00 | AG16.00 | 560 | 1245 | 555 | 3811 | 600 | 500 | 500 | 22 | T55098 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445627 | 600/50R22.5 | 163D | SB | TL | AG20.00 | | 597 | 1173 | 528 | 3574 | 550 | 500 | 500 | 22 | T55089 | 6630 | 6290 | 5900 | 5560 | 5215 | 4875 |
| T445782 | 600/55R26.5 | 173D | SB | TL | AG20.00 | | 603 | 1335 | 612 | 4098 | 625 | 600 | 600 | 24 | T55098 | 8840 | 8385 | 7865 | 7410 | 6955 | 6500 |
| T445556 | 650/55R26.5 | 177D | SB | TL | AG20.00 | AG22.00 | 632 | 1389 | 635 | 4265 | 725 | 600 | 600 | 27 | T55098 | 9930 | 9415 | 8835 | 8320 | 7810 | 7300 |
| T445629 | 600/60R30.5 | 173D | SB | TL | AG20.00 | | 606 | 1497 | 681 | 4570 | 725 | 500 | 500 | 26 | T55098 | 8840 | 8385 | 7865 | 7410 | 6955 | 6500 |

# NOKIAN TYRES ELS

## RADIAL TRACTION FLOTATION TIRE FOR AGRICULTURAL OPERATIONS IN CHALLENGING SOIL CONDITIONS

- Reliable grip due to open, well cleaning traction pattern.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.



## AVAILABLE SIZES

- 600/50R22.5 - T445708
- 600/50R22.5 - T445292
- 710/45R22.5 - T445659
- 600/55R26.5 - T445654
- 650/65R26.5 - T445465
- 700/50R26.5 - T445641
- 750/55R26.5 - T445601
- 850/50R30.5 - T445499
- 710/55R34 - T445470
- 800/50R34 - T445469
- 800/60R34 - T445500

# NOKIAN TYRES ELS

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg Speed (km/h) | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445708 | 600/50R22.5 | 159D | SB | TL | AG20.00 | | 600 | 1164 | 523 | 3555 | 550 | 400 | 400 | 19 | T55089 | 5950 | 5645 | 5295 | 4990 | 4680 | 4375 |
| T445292 | 600/50R22.5 | 156D | | TL | AG20.00 | 20.00 | 625 | 1172 | 531 | 3563 | 550 | 360 | 360 | 19 | | 5440 | 5160 | 4840 | 4560 | 4280 | 4000 |
| T445659 | 710/45R22.5 | 165D | SB | TL | AG24.00 | | 691 | 1204 | 538 | 3678 | 575 | 400 | 400 | 20 | T55092 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445654 | 600/55R26.5 | 165D | SB | TL | AG20.00 | | 594 | 1329 | 596 | 4072 | 625 | 400 | 400 | 22 | T55098 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445465 | 650/65R26.5 | 174D | SB | TL | AG20.00 | | 646 | 1514 | 680 | 4618 | 725 | 400 | 400 | 24 | T55897 | 9110 | 8645 | 8105 | 7640 | 7170 | 6700 |
| T445641 | 700/50R26.5 | 170D | SB | TL | AG24.00 | AG20.00 | 685 | 1369 | 615 | 4198 | 650 | 400 | 400 | 22 | T55099 | 8160 | 7740 | 7260 | 6840 | 6420 | 6000 |
| T445601 | 750/55R26.5 | 177D | SB | TL | AG24.00 | | 738 | 1493 | 670 | 4555 | 700 | 400 | 400 | 24 | T55102 | 9930 | 9415 | 8835 | 8320 | 7810 | 7300 |
| T445499 | 850/50R30.5 | 182D | SB | TL | AG28.00 | AG27.00, AG30.00 | 881 | 1625 | 734 | 4936 | 775 | 400 | 400 | 27 | | 11560 | 10965 | 10285 | 9690 | 9095 | 8500 |
| T445470 | 710/55R34 | 177D | SB | TL | DW24B | DW20B, DW23B | 707 | 1641 | 748 | 4995 | 775 | 400 | 400 | 26 | T55394 | 9930 | 9415 | 8835 | 8320 | 7810 | 7300 |
| T445469 | 800/50R34 | 181D | SB | TL | DW25B | DW23B, DW24B, DW28B | 791 | 1639 | 741 | 4988 | 800 | 400 | 400 | 26 | T55394 | 11220 | 10645 | 9985 | 9405 | 8830 | 8250 |
| T445500 | 800/60R34 | 186D | SB | TL | DW25B | DW23B, DW24B, DW28B | 799 | 1813 | 813 | 5542 | 875 | 400 | 400 | 30 | | 12920 | 12255 | 11495 | 10830 | 10165 | 9500 |

# NOKIAN TYRES FLOAT KING VF

## NEXT-LEVEL FLOTATION FOR HIGH-CAPACITY AGRICULTURAL TRAILERS AND TANKERS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- The grip pattern works great in challenging soil conditions and on road
- The center-zone pattern with continuous contact balances behaviour and reduces loss of power on field and on road



## AVAILABLE SIZES

- VF600/55R26.5 - T445824
- VF620/60R26.5 - T445825
- VF650/55R26.5 - T445823
- VF650/65R26.5 - T445826
- VF710/50R26.5 - T445822
- VF750/60R30.5 - T445739
- VF850/50R30.5 - T445821
- VF800/60R32 - T445819
- VF710/55R34 - T445818
- VF800/50R34 - T445820

# NOKIAN TYRES FLOAT KING VF

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Load capacity for mixed, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 40 | 45 | 50 | 55 | 60 | 65 |
| T445824 | VF600/55R26.5 | 167D | SB | TL | AG20.00 | | 613 | 1355 | 595 | 4104 | 625 | 280 | 280 | 26 | 7030 | 6705 | 6375 | 6050 | 5775 | 5450 |
| T445825 | VF620/60R26.5 | 171D | SB | TL | AG20.00 | | 628 | 1440 | 629 | 4374 | 675 | 280 | 280 | 26 | 7935 | 7565 | 7195 | 6825 | 6520 | 6150 |
| T445823 | VF650/55R26.5 | 171D | SB | TL | AG20.00 | | 649 | 1414 | 612 | 4283 | 650 | 280 | 280 | 26 | 7935 | 7565 | 7195 | 6825 | 6520 | 6150 |
| T445826 | VF650/65R26.5 | 176D | SB | TL | AG20.00 | | 643 | 1548 | 672 | 4699 | 725 | 280 | 280 | 26 | 9160 | 8735 | 8305 | 7880 | 7525 | 7100 |
| T445822 | VF710/50R26.5 | 173D | SB | TL | AG24.00 | | 741 | 1406 | 609 | 4263 | 650 | 280 | 280 | 26 | 8385 | 7995 | 7605 | 7215 | 6890 | 6500 |
| T445739 | VF750/60R30.5 | 183D | SB | TL | AG24.00 | | 762 | 1686 | 719 | 5143 | 800 | 280 | 280 | 28 | 11290 | 10765 | 10240 | 9715 | 9275 | 8750 |
| T445821 | VF850/50R30.5 | 184D | SB | TL | AG28.00 | | 884 | 1653 | 710 | 5015 | 775 | 280 | 280 | 28 | 11610 | 11070 | 10530 | 9990 | 9540 | 9000 |
| T445819 | VF800/60R32 | 188D | SB | TL | DW27B | DW25B | 834 | 1804 | 779 | 5487 | 850 | 280 | 280 | 28 | 12900 | 12300 | 11700 | 11100 | 10600 | 10000 |
| T445818 | VF710/55R34 | 179D | SB | TL | DW23B | DW24B | 728 | 1672 | 734 | 5097 | 775 | 280 | 280 | 28 | 10000 | 9535 | 9070 | 8605 | 8215 | 7750 |
| T445820 | VF800/50R34 | 183D | SB | TL | DW25B | DW24B, DW28B | 806 | 1690 | 732 | 5138 | 800 | 280 | 280 | 28 | 11290 | 10765 | 10240 | 9715 | 9275 | 8750 |

# UNDERGROUND MINING TIRES

## DRILL RIGS AND OTHER MINING MACHINES



61

**Nokian Tyres Armor Gard 2 Mine**



63

**Nokian Tyres MINE KING E-4**

## UNDERGROUND LOADER



65

**Nokian Tyres MINE KING L-5S**



67

**Nokian Tyres MINE L-3S**

## WHEEL LOADER



69

**Nokian Tyres Nordman MINE E-4**

# NOKIAN TYRES ARMOR GARD 2 MINE

## STRONG TIRE FOR DRILL RIGS WITH MINING COMPOUND AND IMPROVED, WIDER TREAD

- New, improved tread lowers the contact pressure and improves service life, providing excellent cut resistance.
- Stable, accurate driving response for predictable handling and a high load-bearing capacity.
- Groove depth indicator helps monitor your tire condition.





## AVAILABLE SIZES

- 9.00-20 - T445836
- 10.00-20 - T445770

# NOKIAN TYRES ARMOR GARD 2 MINE

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445836 | 9.00-20 | 162A5 | 16 | TT | 7.0 | 7.5 | 270 | 1040 | 479 | 3135 | 1000 | 1000 | 18.5 | E-2 | T52520 | 311 | 7175 | 6175 | 6175 | 6175 | 4750 | 4750 |
| T445770 | 10.00-20 | 164A5 | 16 | TT | 7.5 | 8.0 | 285 | 1069 | 484 | 3209 | 900 | 900 | 21 | E-2 | T52620 | 334 | 7550 | 6500 | 6500 | 6500 | 5000 | 5000 |

# NOKIAN TYRES MINE KING E-4

## PURPOSE DESIGNED AND BUILT SPECIAL TIRE FOR DRILL RIGS AND UTILITY VEHICLES

- Strong carcass with a maximum operating pressure of 10 bars, giving a solid foundation for your drill rig.
- Deep grooves with a solid middle section for good puncture resistance and a long tire service life.
- Sharp shoulders and large contact area for better grip.




## AVAILABLE SIZES

- 12.00-20 - T445712
- 14.00-20 - T445617
- 14.00-24 - T445709

# NOKIAN TYRES MINE KING E-4

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445712 | 12.00-20 | 176A5 | 20 | TT | 8.5 | 9.0, 8.0 | 330 | 1147 | 520 | 3449 | 1000 | 1000 | 35 | E-4 | T52810 | 378 | 10720 | 9230 | 9230 | 9230 | 7100 | 7100 |
| T445617 | 14.00-20 | 185A2 | 20 | TT | 10.0 | 9.0 | 372 | 1225 | 560 | 3669 | 1000 | 1000 | 40 | E-4 | T52920 | 450 | 12025 | 10545 | 9250 | 8050 | 7770 | 7400 |
| T445709 | 14.00-24 | 188A2 | 28 | TL | 10.00WA | 10.00VA | 383 | 1391 | 631 | 4153 | 925 | 1000 | 46 | E-4 | T55767 | 450 | 13000 | 11400 | 10000 | 8700 | 8400 | 8000 |

# NOKIAN TYRES MINE KING L-5S

## FOR EXTREME UNDERGROUND LOADING APPLICATIONS

- More strengthening layers to ensure tire safety in demanding applications.
- High load capacity, enabling use in heavier, more effective machines.
- Cut and crack resistant tread provides a long service life.




## AVAILABLE SIZES

- 12.00-20 - T445544
- 17.5-25 - T445540
- 17.5-25 - T445580
- 18.00-25 - T445545
- 26.5-25 - T445546
- 29.5-29 - T445547

# NOKIAN TYRES MINE KING L-5S

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 |
| T445544 | 12.00-20 | 173A2 | 20 | TT | 8.5 | 9.0 | 342 | 1179 | 550 | 3582 | 850 | 1000 | 36 | L-5S | T52810 | 378 | 10400 | 8450 | 7410 | 6500 |
| T445540 | 17.5-25 | 184A2 | 24 | TL | 14.00/1.5 | 14.00/1.3 | 445 | 1400 | 661 | 4291 | 675 | 800 | 66 | L-5S | T55867 | 534 | 14400 | 11700 | 10260 | 9000 |
| T445580 | 17.5-25 | 188A2 | 34 | TL | 14.00/1.5 | 14.00/1.3 | 454 | 1416 | 663 | 4307 | 800 | 1000 | 66 | L-5S | T55867 | 534 | 16000 | 13000 | 11400 | 10000 |
| T445545 | 18.00-25 | 202A2 | 32 | TL | 13.00/2.5 | 15.00/2.5, 13.00/2.5 IF | 526 | 1675 | 772 | 5120 | 750 | 800 | 79 | L-5S | T55831 | 598 | 24000 | 19500 | 17100 | 15000 |
| T445546 | 26.5-25 | 209A2 | 36 | TL | 22.00/3.0 | 22.00/3.0IF | 683 | 1791 | 829 | 5504 | 625 | 800 | 90 | L-5S | | 808 | 29600 | 24050 | 21090 | 18500 |
| T445547 | 29.5-29 | 218A2 | 40 | TL | 25.00/3.5 | 24.00/3.5 | 767 | 2020 | 925 | 6145 | 625 | 800 | 98 | L-5S | | 900 | 37760 | 30680 | 26905 | 23600 |

# NOKIAN TYRES MINE L-3S

## THE FIRST UNDERGROUND LOADER TIRE THAT IS READY FOR PROTECTIVE CHAINS

- Strong, stable tire for extreme conditions.
- Supports the chains in an optimal way and can be set instantly – no modification is needed.
- With chains compatible with the chainless L-5S tires.




## AVAILABLE SIZES

- 26.5-25 - T445522

# NOKIAN TYRES MINE L-3S

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | |
| | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 |
| T445522 | 26.5-25 | 209A2 | 36 | TL | 22.00/3.0 | 22.00/3.0IF | 660 | 1706 | 775 | 5136 | 625 | 800 | 42 | L-3S | 808 | 29600 | 24050 | 21090 | 18500 |

# NOKIAN TYRES NORDMAN MINE E-4

## DURABILITY FOR ARTICULATED DUMP TRUCKS

- Durable radial all-steel structure
- Excellent choice for rough conditions in quarries
- Cost effective mine tire - EUR/h




## AVAILABLE SIZES

- 26.5R25 - T845483

# NOKIAN TYRES NORDMAN MINE E-4

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 20 | 25 | 30 | 35 | 40 | 50 |
| T845483 | 26.5R25 | 209A2 (193B) | TL | 22.00/3.0 | 22.00/3.0IF | 682 | 1798 | 769 | 5353 | 575 | 700 | 55 | E-4 | 808 | 15540 | 14800 | 14245 | 13690 | 12950 | 11655 |

# PORTS AND TERMINALS TIRES

## REACH STACKER



72
Nokian Tyres HTS G2 E-4



74
Nokian Tyres HTS G2 L-4S

## WHEELED EXCAVATOR



84
Nokian Tyres Armor Gard 2

## REACH STACKER LOAD AXLE USE



76
Nokian Tyres HTS G2 L-5S

## FORK LIFT



78
Nokian Tyres Armor Gard

## RTG



80
Nokian Tyres RTG

## TERMINAL TRACTOR



82
Nokian Tyres HTS Tugger

# NOKIAN TYRES HTS G2 E-4

## KEEP THE GOODS MOVING – EFFICIENTLY AND ECONOMICALLY

- Supported blocks with chamfered edges improve tire cooling and turning properties.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 14.00-24 - T445710
- 16.00-25 - T445711
- 18.00-25 - T445637
- 18.00-33 - T445662

# NOKIAN TYRES HTS G2 E-4

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445710 | 14.00-24 | 188A5 | 28 | TL | 10.00WA | 10.00VA | 390 | 1397 | 640 | 4197 | 1000 | 1000 | 48 | E-4 | T55767 | 450 | 15000 | 13000 | 13000 | 13000 | 13000 | 13000 |
| T445711 | 16.00-25 | 199A5 | 36 | TL | 11.25/2.0 | 11.25/2.0 IF, 13.00/2.0 | 453 | 1537 | 694 | 4606 | 1000 | 1000 | 57 | E-4 | T55810 | 518 | 20400 | 17680 | 17680 | 17680 | 17680 | 17680 |
| T445637 | 18.00-25 | 207A5 | 40 | TL | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 538 | 1667 | 765 | 5100 | 1000 | 1000 | 58 | E-4 | T55831 | 598 | 26250 | 22750 | 22750 | 22750 | 22750 | 22750 |
| T445662 | 18.00-33 | 214A5 | 40 | TL | 13.00/2.5 | 13.00/2.5 IF | 512 | 1866 | 849 | 5649 | 1000 | 1000 | 70 | E-4 | | 598 | 31800 | 27560 | 27560 | 27560 | 27560 | 27560 |

# NOKIAN TYRES HTS G2 L-4S

## HARD-WEARING REACH STACKER TIRE WITH SLICK, SMOOTH TREAD

- Deep, long-lasting smooth tread for extensive tire service life and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.




## AVAILABLE SIZES

- 18.00-25 - T445638
- 18.00-33 - T445663

# NOKIAN TYRES HTS G2 L-4S

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445638 | 18.00-25 | 207A5 | 40 | TL | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 538 | 1667 | 770 | 5000 | 1000 | 1000 | 59 | L-4S | T55831 | 598 | 26250 | 22750 | 22750 | 22750 | 22750 | 22750 |
| T445663 | 18.00-33 | 214A5 | 40 | TL | 13.00/2.5 | 13.00/2.5 IF | 519 | 1860 | 849 | 5667 | 1000 | 1000 | 60 | L-4S | | 598 | 31800 | 27560 | 27560 | 27560 | 27560 | 27560 |

# NOKIAN TYRES HTS G2 L-5S

## LONG-LASTING FRONT TIRE FOR REACH STACKERS – THE SMOOTH, EXTRA-DEEP TREAD OFFERS MORE WORKING HOURS

- Extra-deep, long-lasting smooth tread increases tread durability and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.




## AVAILABLE SIZES

- 18.00-25 - T445805

# NOKIAN TYRES HTS G2 L-5S

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445805 | 18.00-25 | 207A5 | 40 | TL | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 524 | 1669 | 745 | 5032 | 1000 | 1000 | 79 | L-5S | T55831 | 598 | 26250 | 22750 | 22750 | 22750 | 22750 | 22750 |

# NOKIAN TYRES ARMOR GARD

## LONG SERVICE LIFE FOR MATERIAL HANDLING MACHINES AND LOADERS

- Strong tire carcass enables precise steering and stability.
- Special rubber compound optimized for harbor use gives an excellent service life.
- Sturdy structure enables long service life as well as great retreading properties.




## AVAILABLE SIZES

- 12.00-20 - T445459

# NOKIAN TYRES ARMOR GARD

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 0 | 1 | 5 | 10 | 20 | 25 |
| T445459 | 12.00-20 | 176A5 (176A5) | 20 | TT | 8.5 | 9.0 | 329 | 1149 | 521 | 3431 | 1000 | 1000 | 25.5 | E-2 | T52810 | 378 | 10720 | 9230 | 9230 | 9230 | 9230 | 9230 |

# NOKIAN TYRES RTG

## MORE AGILITY AND DURABILITY FOR THE RTG CRANES

- Tread pattern and tire shape that allow the wheel to turn more easily.
- Low heat build-up slows down tire wear and gives it more operating hours.
- Special rubber compound optimized for harbour use.




## AVAILABLE SIZES

- 14.00-24 - T445471

# NOKIAN TYRES RTG

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | |
| | | | | | | | | | | | | | | | | | 0 | 5 | 10 | 20 | 25 |
| T445471 | 14.00-24 | 188A5 | 28 | TL | 10.00W | 10.00WA, 10.00VA | 392 | 1363 | 629 | 4147 | 1000 | 1000 | 23 | E-2 | T55767 | 450 | 15000 | 13000 | 13000 | 13000 | 13000 |

# NOKIAN TYRES HTS TUGGER

## MASSIVE LOAD CAPACITY FOR TERMINAL TRACTORS

- Sturdy multi-layer structure enables exceptional load-bearing capacity.
- Optimized for predictable handling.
- Designed to be as low as possible without compromising other qualities, making it ideal for terminal tractor use.




## AVAILABLE SIZES

- 315/60R22.5 - T445221

# NOKIAN TYRES HTS TUGGER

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | 1 | 5 | 10 | 20 | 25 | 35 |
| T445221 | 315/60R22.5 | 174A5 | SB | TL | 9.00 | 9.75 | 302 | 948 | 425 | 2890 | 1000 | 1000 | 21 | IND-3 | 376 | 8710 | 8710 | 8710 | 7540 | 7540 | 6700 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445649 | 10.00-20 | 148B (164A5) | 16 | TT | 7.5 | 8.0 | 283 | 1066 | 500 | 3173 | 750 | 900 | 21 | E-2 | T52620 | 334 | 4000 | 3845 | 3685 | 3495 | 3340 | 3150 |
| T445650 | 11.00-20 | 151B (170A5) | 16 | TT | 8.0 | 8.5 | 306 | 1106 | 518 | 3361 | 750 | 900 | 23 | E-2 | T52720 | 352 | 4380 | 4210 | 4035 | 3830 | 3655 | 3450 |

# EARTHMOVING AND ROAD MAINTENANCE TIRES

## WHEEL LOADER



87
**Nokian Tyres Ground King Loader**



89
**Nokian Tyres Hakkapeliitta Loader**



91
**Nokian Tyres Loader Grip**



93
**Nokian Tyres Loader Grip 2**

## BACKHOE LOADER



95
**Nokian Tyres Ground Kare**



97
**Nokian Tyres Ground Kare Semi-Slick**

## ROAD GRADER



89
**Nokian Tyres Hakkapeliitta Loader**

## WHEELED EXCAVATOR



99
**Nokian Tyres Armor Gard 2**



101
**Nokian Tyres Excavator**



95
**Nokian Tyres Ground Kare**

# NOKIAN TYRES GROUND KING LOADER

## STABLE AND VERSATILE LOADER TIRE WITH EXCELLENT SOFT SOIL GRIP AND ROAD HANDLING

- The Hybrilug™ technology combines the advantages of block and lug pattern, enabling smooth and silent ride on various terrains.
- Excellent self-cleaning properties improve grip for increased productivity on soft soil.
- Accurate, stable and comfortable working is ensured by the strong radial carcass with tough shoulders.




## AVAILABLE SIZES

- 17.5R25 - T445874
- 20.5R25 - T445796
- 20.5R25 - T445796

# NOKIAN TYRES GROUND KING LOADER

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 20 | 25 | 30 | 35 | 40 | 50 |
| T445874 | 17.5R25 | 176A2 | ★ | SB | TL | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 432 | 1351 | 532 | 4065 | 450 | 450 | 46 | L-3 | 534 | 5965 | 5680 | 5465 | 5255 | 4970 | 4475 |
| T445796 | 20.5R25 | 186A2 | ★ | SB | TL | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7 | 516 | 1488 | 645 | 4506 | 450 | 450 | 48 | L-3 | 624 | 7980 | 7600 | 7315 | 7030 | 6650 | 5985 |

# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL-SEASON WHEEL LOADER TIRE WITH GREAT WINTER GRIP

- Aggressive tread design with dense siping gives you the best possible grip on snow and ice.
- All-new rubber compound and non-directional tire tread design ensure long service life and even wear.
- Re-designed carcass structure gives more lifetime and better stability.




## AVAILABLE SIZES

- 14.00R24 - T445691
- 17.5R25 - T445590
- 20.5R25 - T445591
- 23.5R25 - T445592

# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL SIZES FOR ROAD GRADER

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg Speed (km/h) 0 | 10 | 20 | 30 | 40 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T445691 | 14.00R24 | 153A8 (176A2) | ★ | SB | TL | 8.00TG | 10.00VA, 10.00WA, 10.00W | 380 | 1363 | 624 | 4159 | 375 | 550 | 24 | L-2 | T55767 | 434 | Yes | 3650 | 3650 | 3650 | 3650 | 3650 |

## ALL SIZES FOR WHEEL LOADER

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg Speed (km/h) 20 | 25 | 30 | 35 | 40 | 50 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T445590 | 17.5R25 | 176A2 (153A8) | ★ | SB | TL | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 440 | 1344 | 593 | 4078 | 450 | 450 | 28 | L-2 | T55867 | 534 | Yes | 5965 | 5680 | 5465 | 5255 | 4970 | 4475 |
| T445591 | 20.5R25 | 186A2 (168B) | ★ | SB | TL | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7 | 538 | 1487 | 650 | 4509 | 450 | 450 | 32 | L-2 | | 624 | Yes | 7980 | 7600 | 7315 | 7030 | 6650 | 5985 |
| T445592 | 23.5R25 | 195A2 (176B) | ★ | SB | TL | 19.50/2.5 | 19.50/2.5IF | 615 | 1611 | 695 | 4850 | 450 | 450 | 35 | L-2 | | 716 | Yes | 10205 | 9720 | 9355 | 8990 | 8505 | 7655 |

# NOKIAN TYRES LOADER GRIP

## STURDY GRIP FOR WHEEL LOADERS AND EARTHMOVING MACHINES

- Sturdy, hard-wearing structure for excellent mileage.
- Comfortable driving response for efficient working.
- Good winter grip makes the tire highly suitable for year-round use.






## AVAILABLE SIZES

- 17.5R25 - T445255
- 20.5R25 - T445171
- 23.5R25 - T445223

# NOKIAN TYRES LOADER GRIP

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | | 20 | 25 | 30 | 35 | 40 | 50 |
| T445255 | 17.5R25 | 176A2 (157B) | ★ | SB | TL | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 450 | 1340 | 594 | 4059 | 450 | 450 | 28 | L-3 | T55867 | 534 | Yes | 5965 | 5680 | 5465 | 5255 | 4970 | 4475 |
| T445171 | 20.5R25 | 186A2 (168B) | ★ | SB | TL | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7 | 532 | 1493 | 648 | 4500 | 450 | 450 | 31 | L-3 | | 624 | Yes | 7980 | 7600 | 7315 | 7030 | 6650 | 5985 |
| T445223 | 23.5R25 | 195A2 (176B) | ★ | SB | TL | 19.50/2.5 | 19.50/2.5IF | 630 | 1607 | 700 | 4880 | 450 | 450 | 34 | L-3 | | 716 | Yes | 10205 | 9720 | 9355 | 8990 | 8505 | 7655 |

# NOKIAN TYRES LOADER GRIP 2

## ABSOLUTE GRIP AND DURABILITY FOR WHEEL LOADERS AND ADT MACHINES

- Specially for wheel loaders designed tread blocks create traction on soft gravel and on icy, slippery roads.
- Excellent mileage and sidewall protection against sidewall slashes and abrasions.
- Stability on every terrain due to wide tire contact area and the block-patterned tread.




## AVAILABLE SIZES

- 15.5R25 - T445463

# NOKIAN TYRES LOADER GRIP 2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | M+S | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | 20 | 25 | 30 | 35 | 40 | 50 |
| T445463 | 15.5R25 | 169A2 (152B) | ★ | SB | TL | 12.00/1.3 | 13.00/1.4 (DC) | 387 | 1280 | 569 | 3885 | 450 | 450 | 23 | L-3 | 473 | Yes | 4870 | 4640 | 4465 | 4290 | 4060 | 3655 |

# NOKIAN TYRES GROUND KARE

## EXCAVATOR AND BACKHOE LOADER TIRE FOR VERSATILE CONTRACTING WORK

- The tread design enables low surface pressure, great traction and smooth, comfortable driving on road.
- The high load-bearing capacity enables the use of heavy auxiliary equipment.
- The special design adds stability by absorbing swings and shocks.



## AVAILABLE SIZES

- 500/45-22.5 - T445868
- 600/40-22.5 - T445828
- 600/50-22.5 - T445798
- 650/45-22.5 - T445664
- 710/40-22.5 - T445799
- 620/60B30 - T445802
- 620/60B34 - T445668

# NOKIAN TYRES GROUND KARE

## ALL SIZES FOR WHEELED EXCAVATOR

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Min. dual spacing (mm) | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445868 | 500/45-22.5 | 160A8 | 24 | SF | TL | AG16.00 | AG18.00 | 499 | 1036 | 472 | 3126 | 500 | 600 | 600 | 24 | T56435 | 566 | 4770 | 4680 | 4590 | 4500 | 4320 | 4095 |
| T445828 | 600/40-22.5 | 167A8 | 24 | SF | TL | AG20.00 | | 585 | 1063 | 484 | 3206 | 500 | 600 | 600 | 25 | T55089 | 721 | 5775 | 5670 | 5560 | 5450 | 5230 | 4960 |
| T445798 | 600/50-22.5 | 173A8 | 24 | SF | TL | AG20.00 | | 603 | 1156 | 511 | 3495 | 550 | 600 | 600 | 26 | T55089 | 721 | 6890 | 6760 | 6630 | 6500 | 6240 | 5915 |
| T445664 | 650/45-22.5 | 175A8 | 24 | SF | TL | AG22.00 | AG20.00 | 661 | 1146 | 524 | 3493 | 550 | 600 | 600 | 26 | T55092 | 774 | 7315 | 7175 | 7040 | 6900 | 6625 | 6280 |
| T445799 | 710/40-22.5 | 173A8 | 24 | SF | TL | AG24.00 | | 698 | 1145 | 505 | 3478 | 550 | 550 | 550 | 26 | T55092 | 872 | 6890 | 6760 | 6630 | 6500 | 6240 | 5915 |

## ALL SIZES FOR BACKHOE LOADER

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445802 | 620/60B30 | 176A8 (173B) | SB | TL | DW20B | DW18L | 623 | 1500 | 667 | 4560 | 450 | 450 | 25 | T55371 | 7525 | 7385 | 7240 | 7100 | 6815 | 6460 |
| T445668 | 620/60B34 | 178A8 (175B) | SB | TL | DW20B | DW18L | 630 | 1607 | 750 | 4907 | 450 | 450 | 25 | T55395 | 7950 | 7800 | 7650 | 7500 | 7200 | 6825 |

# NOKIAN TYRES GROUND KARE SEMI-SLICK

## EXTENDED SERVICE LIFE AND STABILITY FOR RAILWAY USE

- The unique structure of the Nokian Tyres Ground Kare Semi-Slick tire has been optimized to offer a much longer service life than regular backhoe loader tires.
- With stable, shock absorbing structure and high load-bearing capacity, Nokian Tyres Ground Kare Semi-Slick tire gives digging work a stable foundation and enables the use of heavy work attachments.
- Its tread pattern with larger blocks in the center makes driving more comfortable, and the stable structure improves the overall handling of the backhoe loader.



## AVAILABLE SIZES

- 620/60B34 - T445688

# NOKIAN TYRES GROUND KARE SEMI-SLICK

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445688 | 620/60B34 | 178A8 (175B) | SB | TL | DW20B | DW18L | 631 | 1609 | 749 | 4901 | 450 | 450 | 25 | T55395 | 7950 | 7800 | 7650 | 7500 | 7200 | 6825 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445649 | 10.00-20 | 148B (164A5) | 16 | TT | 7.5 | 8.0 | 283 | 1066 | 500 | 3173 | 750 | 900 | 21 | E-2 | T52620 | 334 | 4000 | 3845 | 3685 | 3495 | 3340 | 3150 |
| T445650 | 11.00-20 | 151B (170A5) | 16 | TT | 8.0 | 8.5 | 306 | 1106 | 518 | 3361 | 750 | 900 | 23 | E-2 | T52720 | 352 | 4380 | 4210 | 4035 | 3830 | 3655 | 3450 |

# NOKIAN TYRES EXCAVATOR

## EXCAVATOR TIRE FOR SOFT SURFACES

- Excellent self-cleaning properties with curvy lug design improve traction on soft surfaces.
- High load-bearing capacity and improved stability.
- Steel fortified against punctures with a reinforced shoulder for a long service life.




## AVAILABLE SIZES

- 600/50-22.5 - T445604
- 650/45-22.5 - T445605
- 710/40-22.5 - T445606

# NOKIAN TYRES EXCAVATOR

## ALL SIZES

| Product code | Size | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Min. dual spacing (mm) | Load capacity for constant load, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | | | 25 | 30 | 35 | 40 | 45 | 50 |
| T445604 | 600/50-22.5 | 173A8 | 24 | SF | TL | AG20.00 | | 583 | 1149 | 517 | 3531 | 550 | 600 | 600 | 40 | T55089 | 721 | 6890 | 6760 | 6630 | 6500 | 6240 | 5915 |
| T445605 | 650/45-22.5 | 175A8 | 24 | SF | TL | AG22.00 | AG20.00 | 643 | 1148 | 515 | 3525 | 550 | 600 | 600 | 40 | T55092 | 774 | 7315 | 7175 | 7040 | 6900 | 6625 | 6280 |
| T445606 | 710/40-22.5 | 173A8 | 24 | SF | TL | AG24.00 | | 685 | 1153 | 518 | 3525 | 550 | 550 | 550 | 40 | T55092 | 872 | 6890 | 6760 | 6630 | 6500 | 6240 | 5915 |

# ALL TERRAIN TRUCKS AND MILITARY VEHICLES TIRES

## ALL-TERRAIN TRUCK, MILITARY VEHICLE



104
**Nokian Tyres MPT Agile**



106
**Nokian Tyres MPT Agile 2**

# NOKIAN TYRES MPT AGILE

## ON AND OFF ROAD AGILITY

- The open arrow-shaped tread pattern ensures good self-cleaning, ensuring grip under demanding circumstances.
- Improved grip on soft surfaces such as mud and snow.
- Exceptional mobility.




## AVAILABLE SIZES

- 365/80R20 - T445431

# NOKIAN TYRES MPT AGILE

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | M+S | Load capacity for highway service, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | 40 | 50 | 60 | 70 | 80 | 90 |
| T445431 | 365/80R20 | 152G | SB | TL | 11 | 11 SDC, 12, 12 SDC | 360 | 1092 | 505 | 3343 | 625 | 625 | 20 | Yes | 3800 | 3730 | 3730 | 3730 | 3690 | 3550 |

# NOKIAN TYRES MPT AGILE 2

## NEW GENERATION TIRE FOR SPECIAL ON AND OFF ROAD VEHICLES

- Improved grip on soft surfaces such as mud and snow.
- Good steering response and stable handling on different terrains and speeds.
- Symmetrical tread pattern is designed to perform equally well regardless of the tires' rotational direction.



## AVAILABLE SIZES

- 14.00R20 - T445651

# NOKIAN TYRES MPT AGILE 2

## ALL SIZES

| Product code | Size | LI/SS | Reinforced code | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | M+S | Load capacity for highway service, kg | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | Speed (km/h) | | | | | |
| | | | | | | | | | | | | | | | | 40 | 50 | 60 | 70 | 80 | 90 |
| T445651 | 14.00R20 | 164G | SB | TL | 10.00V | 10.00W | 400 | 1265 | 588 | 3989 | 760 | 760 | 25 | T52920 | Yes | 5350 | 5250 | 5250 | 5250 | 5200 | 5000 |

# TRUCKS AND BUSES TIRES

## STEER


109 Nokian Tyres Hakkapeliitta City Bus


111 Nokian Tyres Hakkapeliitta Truck F2


114 Nokian Tyres Hakka City Bus


116 Nokian Tyres Hakka Truck Coach


118 Nokian Tyres Hakka Truck Steer


120 Nokian Tyres Hakka Truck Steer 2


122 Nokian Tyres E-Truck Steer


124 Nokian Tyres E-Truck Steer 17.5


126 Nokian Tyres E-Truck Steer 19.5


128 Nokian Tyres R-Truck Steer

## DRIVE


130 Nokian Tyres Hakkapeliitta Truck D2


132 Nokian Tyres Hakkapeliitta Truck E2


135 Nokian Tyres Hakka Truck Drive


137 Nokian Tyres Hakka Truck Drive 2


139 Nokian Tyres E-Truck Drive


141 Nokian Tyres E-Truck Drive 17.5


143 Nokian Tyres E-Truck Drive 19.5


145 Nokian Tyres R-Truck Drive

## TRAILER


147 Nokian Tyres Hakkapeliitta Truck T


149 Nokian Tyres Hakka Truck Trailer


151 Nokian Tyres Hakka Truck Trailer 2


153 Nokian Tyres E-Truck Trailer


156 Nokian Tyres R-Truck Trailer

# NOKIAN TYRES HAKKAPELIITTA CITY BUS

## WINTER TIRE FOR ALL AXLES – DURABILITY AND EXCELLENT GRIP FOR CITY BUSES

- Excellent winter grip in urban conditions.
- Reinforced sidewalls protect the tire against curbs.
- Siping designed for minimal heel/toe wear.




## AVAILABLE SIZES

- 275/70R22.5 - T675330
- 295/80R22.5 - T675356

# NOKIAN TYRES HAKKAPELIITTA CITY BUS

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675330 | 275/70R22.5 | 152/149J (150/148K) | TL | 8.25 | 7.50 | 281 | 971 | 450 | 2922 | 900 | 20.5 | 311 | D | B | A | 70 | Yes | Yes |
| T675356 | 295/80R22.5 | 154/149J | TL | 9.00 | 8.25 | 303 | 1056 | 489 | 3184 | 850 | 18.5 | 335 | C | B | B | 72 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675330 | 275/70R22.5 | Single | 100 | 5470 | 5640 | 5810 | 5970 | 6140 | 6300 | 6460 | 6620 | 6780 | 6940 | 7100 |
| | | Dual | 100 | 10020 | 10330 | 10630 | 10940 | 11240 | 11530 | 11830 | 12130 | 12420 | 12710 | 13000 |
| | | Single | 110 | 5160 | 5320 | 5480 | 5640 | 5790 | 5940 | 6100 | 6250 | 6400 | 6550 | 6700 |
| | | Dual | 110 | 9710 | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675356 | 295/80R22.5 | Single | 100 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 100 | 10490 | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## WINTER STEER AXLE TIRE FOR REGIONAL AND LONG-DISTANCE TRANSPORT – GRIP FOR DEMANDING WINTER CONDITIONS IN REGIONAL AND LONG-DISTANCE TRANSPORT

- Aggressive pattern, deep grooves and a new shoulder design enable reference-level grip and good self-cleaning.
- Improved Spiral Sipe System keeps the siping effective even when the tire wears down.
- New, large stone ejectors protect the tire from stone trapping.




## AVAILABLE SIZES

- 295/80R22.5 - T675310
- 315/70R22.5 - T675300
- 315/80R22.5 - T675319
- 385/55R22.5 - T675311
- 385/55R22.5 - T675372
- 385/65R22.5 - T675291

# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675310 | 295/80R22.5 | 154/149M | TL | 9.00 | 8.25 | 304 | 1053 | 487 | 3184 | 850 | 15 | 335 | C | B | A | 71 | Yes | Yes |
| T675300 | 315/70R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 311 | 1011 | 466 | 3093 | 900 | 14.5 | 351 | C | B | A | 71 | Yes | Yes |
| T675319 | 315/80R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 311 | 1086 | 504 | 3282 | 850 | 16 | 351 | C | B | A | 71 | Yes | Yes |
| T675311 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 378 | 992 | 456 | 3018 | 900 | 15.5 | | C | A | A | 71 | Yes | Yes |
| T675372 | 385/55R22.5 | 164K | TL | 11.75 | 12.25 | 378 | 992 | 452 | 3018 | 900 | 15.5 | | C | A | A | 71 | Yes | Yes |
| T675291 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 386 | 1074 | 493 | 3248 | 900 | 16 | | C | A | B | 72 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675310 | 295/80R22.5 | Single | 130 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 130 | 10490 | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 | | |
| T675300 | 315/70R22.5 | Single | 120 | 6170 | 6360 | 6540 | 6730 | 6910 | 7100 | 7280 | 7460 | 7640 | 7820 | 8000 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| | | Single | 130 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 130 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| T675319 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| | | Single | 130 | 6200 | 6390 | 6580 | 6760 | 6950 | 7130 | 7320 | 7500 | | | |
| | | Dual | 130 | 11070 | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 | | | |
| T675311 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| T675372 | 385/55R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675291 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA CITY BUS

## ALL-WEATHER TIRE FOR ALL AXLES – DURABILITY AND ALL-WEATHER PERFORMANCE FOR CITY BUSES

- Especially designed for the modern urban needs, increased load capacity.
- Reinforced sidewalls protect the tire against curbs.
- Tread pattern for minimal heel/toe wear.



## AVAILABLE SIZES

- 275/70R22.5 - T675318

# NOKIAN TYRES HAKKA CITY BUS

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675318 | 275/70R22.5 | 152/149J (150/148K) | TL | 8.25 | 7.50 | 280 | 967 | 448 | 2922 | 900 | 18.5 | 311 | D | B | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675318 | 275/70R22.5 | Single | 100 | 5470 | 5640 | 5810 | 5970 | 6140 | 6300 | 6460 | 6620 | 6780 | 6940 | 7100 |
| | | Dual | 100 | 10020 | 10330 | 10630 | 10940 | 11240 | 11530 | 11830 | 12130 | 12420 | 12710 | 13000 |
| | | Single | 110 | 5160 | 5320 | 5480 | 5640 | 5790 | 5940 | 6100 | 6250 | 6400 | 6550 | 6700 |
| | | Dual | 110 | 9710 | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK COACH

## ALL-WEATHER TIRE FOR ALL AXLES – CONFIDENT GRIP AND COMFORT FOR LONG-DISTANCE BUSES

- Grip-improving siping with unique activators and optimized open pattern design.
- Rubber compound and tread pattern optimized for smooth, quiet rides.
- Long service life and even wear pattern. Rock Resistor grooves prevent stone trapping.



## AVAILABLE SIZES

- 295/80R22.5 - T675355

# NOKIAN TYRES HAKKA TRUCK COACH

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675355 | 295/80R22.5 | 154/150M | TL | 9.00 | 8.25 | 303 | 1055 | 490 | 3184 | 850 | 15.5 | 335 | C | A | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 |
| T675355 | 295/80R22.5 | Single | 130 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 |
| | | Dual | 130 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL-WEATHER STEER AXLE TIRE – EXCELLENT MILEAGE FOR REGIONAL TRANSPORT

- Wide, slow-wearing tread for excellent mileage.
- New kind of sipe activators improve grip on snowy and wet surfaces.
- Stone ejectors protect the tire from stone trapping.




## AVAILABLE SIZES

- 315/70R22.5 - T675302

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675302 | 315/70R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 312 | 1010 | 466 | 3093 | 900 | 14.5 | 351 | C | B | A | 70 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675302 | 315/70R22.5 | Single | 120 | 6170 | 6360 | 6540 | 6730 | 6910 | 7100 | 7280 | 7460 | 7640 | 7820 | 8000 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| | | Single | 130 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 130 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK STEER 2

## ALL-WEATHER STEER AXLE TIRE – EXCELLENT HANDLING AND MILEAGE FOR LONG DISTANCE AND REGIONAL TRANSPORT

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance.
- Unique center tread design with siping in two directions, even wear shape and excellent handling properties.
- Deep siping in the center tread maintains grip when the tire wears down.




## AVAILABLE SIZES

- 315/60R22.5 - T675325
- 315/70R22.5 - T675316
- 315/80R22.5 - T675348
- 385/55R22.5 - T675349
- 385/55R22.5 - T675369
- 385/65R22.5 - T675354

# NOKIAN TYRES HAKKA TRUCK STEER 2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675325 | 315/60R22.5 | 154/148L | TL | 9.00 | 9.75 | 317 | 952 | 441 | 2879 | 900 | 14 | 344 | C | B | A | 70 | Yes | Yes |
| T675316 | 315/70R22.5 | 156/150L | TL | 9.00 | 9.75 | 312 | 1011 | 467 | 3093 | 900 | 14.5 | 351 | C | A | A | 71 | Yes | Yes |
| T675348 | 315/80R22.5 | 156/150L | TL | 9.00 | 9.75 | 314 | 1084 | 502 | 3282 | 850 | 15.5 | 351 | C | A | A | 71 | Yes | Yes |
| T675349 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 379 | 990 | 456 | 3018 | 900 | 14.5 | | C | A | B | 72 | Yes | Yes |
| T675369 | 385/55R22.5 | 164K | TL | 11.75 | 12.25 | | | 452 | 3018 | 900 | 14.5 | | B | A | B | 72 | Yes | Yes |
| T675354 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 385 | 1071 | 492 | 3248 | 900 | 15 | | B | A | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675325 | 315/60R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 9710 | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675316 | 315/70R22.5 | Single | 120 | 6170 | 6360 | 6540 | 6730 | 6910 | 7100 | 7280 | 7460 | 7640 | 7820 | 8000 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675348 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| T675349 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| T675369 | 385/55R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |
| T675354 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER

## ALL-SEASON STEER AXLE TIRE – GOOD GRIP AND MILEAGE FOR REGIONAL TRANSPORTS

- New type of zigzag-shaped grooves prevent stone trapping.
- Even wear pattern for good mileage.
- Spiral Sipe System adds grip on all roads.



## AVAILABLE SIZES

- 295/80R22.5 - T675336
- 315/70R22.5 - T675297
- 315/80R22.5 - T675308
- 385/55R22.5 - T675333
- 385/65R22.5 - T675332

# NOKIAN TYRES E-TRUCK STEER

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675336 | 295/80R22.5 | 154/149M | TL | 9.00 | 8.25 | 303 | 1050 | 458 | 3212 | 850 | 14.5 | 335 | C | B | A | 71 | Yes | Yes |
| T675297 | 315/70R22.5 | 156/150L | TL | 9.00 | 9.75 | 309 | 1015 | 469 | 3097 | 900 | 15.5 | 351 | C | B | A | 71 | Yes | Yes |
| T675308 | 315/80R22.5 | 156/150L | TL | 9.00 | 9.75 | 316 | 1077 | 501 | 3297 | 850 | 15 | 351 | B | B | A | 71 | Yes | Yes |
| T675333 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 376 | 994 | 457 | 3040 | 900 | 14.5 | | B | B | A | 70 | Yes | Yes |
| T675332 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 375 | 1073 | 493 | 3282 | 900 | 14.5 | | C | B | A | 70 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675336 | 295/80R22.5 | Single | 130 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 130 | 10490 | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 | | |
| T675297 | 315/70R22.5 | Single | 120 | 6170 | 6360 | 6540 | 6730 | 6910 | 7100 | 7280 | 7460 | 7640 | 7820 | 8000 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675308 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| T675333 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| T675332 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL-SEASON STEER AXLE TIRE – STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 215/75R17.5 - T675338
- 235/75R17.5 - T675342

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675338 | 215/75R17.5 | 126/124M | TL | 6.00 | 6.75 | 210 | 772 | 358 | 2363 | 700 | 12.5 | 239 | C | B | A | 71 | Yes | Yes |
| T675342 | 235/75R17.5 | 132/130M | TL | 6.75 | 7.50 | 226 | 795 | 369 | 2432 | 775 | 12.5 | 262 | C | B | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 500 | 525 | 550 | 575 | 600 | 625 | 650 | 675 | 700 | 725 | 750 | 775 |
| T675338 | 215/75R17.5 | Single | 130 | 2600 | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 | | | |
| | | Dual | 130 | 4890 | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 | | | |
| T675342 | 235/75R17.5 | Single | 130 | | | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
| | | Dual | 130 | | | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL-SEASON STEER AXLE TIRE – STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 265/70R19.5 - T675343
- 285/70R19.5 - T675344

# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675343 | 265/70R19.5 | 140/138M | TL | 7.50 | 6.75, 8.25 | 260 | 862 | 399 | 2638 | 775 | 13 | 295 | C | B | A | 71 | Yes | Yes |
| T675344 | 285/70R19.5 | 146/144L | TL | 8.25 | 9.00 | 278 | 895 | 415 | 2739 | 900 | 13.5 | 318 | C | B | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 550 | 575 | 600 | 625 | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675343 | 265/70R19.5 | Single | 130 | 3800 | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000 | | | | | |
| | | Dual | 130 | 7170 | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440 | | | | | |
| T675344 | 285/70R19.5 | Single | 120 | | | 4340 | 4480 | 4620 | 4770 | 4910 | 5050 | 5190 | 5320 | 5460 | 5600 | 5730 | 5870 | 6000 |
| | | Dual | 120 | | | 8100 | 8370 | 8630 | 8900 | 9160 | 9420 | 9680 | 9940 | 10190 | 10450 | 10700 | 10950 | 11200 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK STEER

## STEER AXLE TIRE – CONTROLLED STEERING FOR ON/OFF-ROAD USE

- Stone ejectors in the main grooves prolong operating life especially on rough surfaces.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.




## AVAILABLE SIZES

- 315/80R22.5 - T675331
- 385/65R22.5 - T675313

# NOKIAN TYRES R-TRUCK STEER

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675331 | 315/80R22.5 | 156/150K | TL | 9.00 | 9.75 | 311 | 1096 | 508 | 3282 | 850 | 16 | 351 | C | A | A | 71 | Yes | Yes |
| T675313 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 386 | 1073 | 492 | 3248 | 900 | 16 | | C | A | B | 72 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675331 | 315/80R22.5 | Single | 110 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 110 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| T675313 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK D2

## WINTER DRIVE AXLE TIRE – ENHANCED WEAR RESISTANCE AND GRIP ON WINTER ROADS

- Deeper reach, better worn grip and improved stability due to peg siping and open center tread design.
- Patented Twin-Block pattern design to achieve superior stability and traction especially on packed snow and icy roads.
- New generation of Hakkapeliitta Truck D family with better mileage performance.



## AVAILABLE SIZES

- 295/80R22.5 - T675320
- 315/80R22.5 - T675321
- 315/70R22.5 - T675301

# NOKIAN TYRES HAKKAPELIITTA TRUCK D2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675320 | 295/80R22.5 | 152/148M (154/150L) | TL | 9.00 | 8.25 | 305 | 1060 | 493 | 3232 | 850 | 19.5 | 335 | D | B | A | 73 | Yes | Yes |
| T675301 | 315/70R22.5 | 154/150L (152/148M) | TL | 9.00 | 9.75 | 312 | 1021 | 473 | 3093 | 900 | 19 | 351 | D | B | A | 73 | Yes | Yes |
| T675321 | 315/80R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 310 | 1092 | 502 | 3282 | 850 | 20 | 351 | D | B | B | 75 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675320 | 295/80R22.5 | Single | 120 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| | | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |
| T675301 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| | | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |
| T675321 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| | | Single | 130 | 6050 | 6240 | 6420 | 6600 | 6790 | 6970 | 7140 | 7320 | 7500 | | |
| | | Dual | 130 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## WINTER DRIVE AXLE TIRE – SUPERIOR TRACTION AND OPTIMIZED PERFORMANCE ON SEVERE WINTER CONDITIONS

- Deeper reach, better grip when worn and improved stability due to peg siping.
- Consistent rigidity and even wear pattern brought by connected block system.
- Increased tire service life enabled by the open center tread design and extra deep-reaching center sipes.



## AVAILABLE SIZES

- 275/70R22.5 - T675357
- 275/70R22.5 - T675366
- 295/80R22.5 - T675290
- 295/80R22.5 - T675368
- 315/70R22.5 - T675309
- 315/80R22.5 - T675289

# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675357 | 275/70R22.5 | 148/145M | TL | 8.25 | 7.50 | 275 | 970 | 450 | 2922 | 900 | 17.5 | 311 | D | A | B | 74 | Yes | Yes |
| T675366 | 275/70R22.5 | 152/149J (150/148K) | TL | 8.25 | 7.50 | | | 447 | 2922 | 900 | 17.5 | 311 | D | A | B | 74 | Yes | Yes |
| T675290 | 295/80R22.5 | 152/148M | TL | 9.00 | 9.75 | 302 | 1055 | 492 | 3184 | 850 | 19.5 | 335 | D | C | A | 73 | Yes | Yes |
| T675368 | 295/80R22.5 | 152/149M | TL | 9.00 | 9.75 | 302 | 1055 | 492 | 3184 | 850 | 19.5 | 335 | D | C | A | 73 | Yes | Yes |
| T675309 | 315/70R22.5 | 154/150L (152/148M) | TL | 9.00 | 9.75 | 311 | 1018 | 471 | 3093 | 900 | 18.5 | 351 | D | A | A | 73 | Yes | Yes |
| T675289 | 315/80R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 312 | 1094 | 502 | 3282 | 850 | 20 | 351 | D | A | A | 73 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675357 | 275/70R22.5 | Single | 130 | 4860 | 5000 | 5150 | 5300 | 5440 | 5590 | 5730 | 5880 | 6020 | 6160 | 6300 |
| | | Dual | 130 | 8940 | 9220 | 9490 | 9760 | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675366 | 275/70R22.5 | Single | 100 | 5470 | 5640 | 5810 | 5970 | 6140 | 6300 | 6460 | 6620 | 6780 | 6940 | 7100 |
| | | Dual | 100 | 10020 | 10330 | 10630 | 10940 | 11240 | 11530 | 11830 | 12130 | 12420 | 12710 | 13000 |
| T675290 | 295/80R22.5 | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |
| T675368 | 295/80R22.5 | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10490 | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 | | |
| T675309 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| | | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675289 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL-WEATHER DRIVE AXLE TIRE – GRIP FOR REGIONAL TRANSPORT

- Open V-shaped tread design with good self-cleaning.
- Optimized tread pattern staggering ensures even wear pattern.
- Effective siping improves grip in both acceleration and braking.




## AVAILABLE SIZES

- 315/70R22.5 - T675303

# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675303 | 315/70R22.5 | 154/150L (152/148M) | TL | 9.00 | 9.75 | 312 | 1017 | 472 | 3093 | 900 | 18 | 351 | D | B | A | 72 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675303 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| | | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK DRIVE 2

## ALL-WEATHER DRIVE AXLE TIRE – ENHANCED GRIP AND EVEN WEAR FOR LONG DISTANCE AND REGIONAL TRANSPORT

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance.
- Effective deep self generating siping improves grip in both acceleration and braking.
- Optimized tread pattern staggering ensures even wear pattern.






## AVAILABLE SIZES

- 295/60R22.5 - T675324
- 315/70R22.5 - T675315
- 315/80R22.5 - T675350

# NOKIAN TYRES HAKKA TRUCK DRIVE 2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675324 | 295/60R22.5 | 150/147L | TL | 9.00 | 9.75 | 288 | 926 | 429 | 2806 | 900 | 17 | 329 | D | A | A | 73 | Yes | Yes |
| T675315 | 315/70R22.5 | 154/150L | TL | 9.00 | 9.75 | 311 | 1018 | 472 | 3093 | 900 | 18 | 351 | D | A | A | 73 | Yes | Yes |
| T675350 | 315/80R22.5 | 156/150L (154/150M) | TL | 9.00 | 9.75 | 314 | 1092 | 506 | 3282 | 850 | 18.5 | 351 | D | B | A | 73 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675324 | 295/60R22.5 | Single | 120 | 5160 | 5320 | 5480 | 5640 | 5790 | 5940 | 6100 | 6250 | 6400 | 6550 | 6700 |
| | | Dual | 120 | 9480 | 9770 | 10060 | 10350 | 10630 | 10910 | 11190 | 11470 | 11750 | 12030 | 12300 |
| T675315 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675350 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |
| | | Single | 130 | 6200 | 6390 | 6580 | 6760 | 6950 | 7130 | 7320 | 7500 | | | |
| | | Dual | 130 | 11070 | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 | | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE

## ALL-SEASON DRIVE AXLE TIRE – RELIABLE TRACTION AND EVEN WEAR FOR REGIONAL TRANSPORT

- Effective block pattern and open center tread design ensure good traction.
- Even wear pattern for a long, trouble-free service life.
- Low rolling resistance and tire noise for fuel economy and comfort.



## AVAILABLE SIZES

- 295/80R22.5 - T675335
- 315/70R22.5 - T675367
- 315/70R22.5 - T675296
- 315/80R22.5 - T675307

# NOKIAN TYRES E-TRUCK DRIVE

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675335 | 295/80R22.5 | 152/148M | TL | 8.25 | | 301 | 1058 | 492 | 3238 | 850 | 19.5 | 335 | D | B | B | 74 | Yes | Yes |
| T675367 | 315/70R22.5 | 154/150L | TL | 9.00 | 9.75 | 308 | 1022 | 474 | 3117 | 900 | 19.5 | 351 | C | B | B | 74 | Yes | Yes |
| T675296 | 315/70R22.5 | 154/150L | TL | 9.00 | 9.75 | 308 | 1022 | 474 | 3117 | 900 | 19.5 | 351 | D | B | B | 74 | Yes | Yes |
| T675307 | 315/80R22.5 | 156/150L | TL | 9.00 | 9.75 | 314 | 1089 | 505 | 3333 | 850 | 19.5 | 351 | C | B | B | 74 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675335 | 295/80R22.5 | Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 | | |
| | | Dual | 130 | 10170 | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 | | |
| T675367 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675296 | 315/70R22.5 | Single | 120 | 5780 | 5960 | 6130 | 6310 | 6480 | 6650 | 6830 | 7000 | 7160 | 7330 | 7500 |
| | | Dual | 120 | 10330 | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675307 | 315/80R22.5 | Single | 120 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 | | |
| | | Dual | 120 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 | | |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL-SEASON DRIVE AXLE TIRE – DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and a long tire life.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 215/75R17.5 - T675337
- 235/75R17.5 - T675339

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675337 | 215/75R17.5 | 126/124M | TL | 6.00 | 6.75 | 208 | 774 | 360 | 2368 | 700 | 14.5 | 239 | D | B | B | 74 | Yes | Yes |
| T675339 | 235/75R17.5 | 132/130M | TL | 6.75 | 7.50 | 229 | 799 | 372 | 2446 | 775 | 14.5 | 262 | D | B | B | 74 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 500 | 525 | 550 | 575 | 600 | 625 | 650 | 675 | 700 | 725 | 750 | 775 |
| T675337 | 215/75R17.5 | Single | 130 | 2600 | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 | | | |
| | | Dual | 130 | 4890 | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 | | | |
| T675339 | 235/75R17.5 | Single | 130 | | | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
| | | Dual | 130 | | | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL-SEASON DRIVE AXLE TIRE – DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and long tire life.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 265/70R19.5 - T675340
- 285/70R19.5 - T675341

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675340 | 265/70R19.5 | 140/138M | TL | 7.50 | 6.75, 8.25 | 260 | 866 | 401 | 2651 | 775 | 15 | 295 | C | B | B | 74 | Yes | Yes |
| T675341 | 285/70R19.5 | 146/144L | TL | 8.25 | 9.00 | 279 | 898 | 416 | 2748 | 900 | 15 | 318 | C | B | B | 74 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 550 | 575 | 600 | 625 | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675340 | 265/70R19.5 | Single | 130 | 3800 | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000 | | | | | |
| | | Dual | 130 | 7170 | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440 | | | | | |
| T675341 | 285/70R19.5 | Single | 120 | | | 4340 | 4480 | 4620 | 4770 | 4910 | 5050 | 5190 | 5320 | 5460 | 5600 | 5730 | 5870 | 6000 |
| | | Dual | 120 | | | 8100 | 8370 | 8630 | 8900 | 9160 | 9420 | 9680 | 9940 | 10190 | 10450 | 10700 | 10950 | 11200 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK DRIVE

## DRIVE AXLE TIRE – DURABILITY FOR DEMANDING ON/OFF-ROAD USE

- Open tread pattern ensures good self-cleaning and grip in changing driving conditions.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.




## AVAILABLE SIZES

- 315/80R22.5 - T675312

# NOKIAN TYRES R-TRUCK DRIVE

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675312 | 315/80R22.5 | 156/150K | TL | 9.00 | 9.75 | 311 | 1096 | 508 | 3282 | 850 | 21.5 | 351 | D | B | B | 75 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 |
| T675312 | 315/80R22.5 | Single | 110 | 6450 | 6650 | 6850 | 7040 | 7240 | 7430 | 7620 | 7810 | 8000 |
| | | Dual | 110 | 10810 | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK T

## WINTER TRAILER TIRE – STABLE PERFORMANCE AND SECURE TRACTION ON SNOW AND ICE

- Wide zigzag-shape grooves improve self-cleaning and grip on snow.
- Strong shoulders resist wear even in tight cornering.
- Marked stud locations for effective studding.



## AVAILABLE SIZES

- 265/70R19.5 - T675358

# NOKIAN TYRES HAKKAPELIITTA TRUCK T

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675358 | 265/70R19.5 | 143/141J | TL | 7.50 | 6.75, 8.25 | 259 | 870 | 403 | 2601 | 900 | 14.5 | 295 | D | C | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675358 | 265/70R19.5 | Single | 100 | 4200 | 4330 | 4460 | 4580 | 4710 | 4840 | 4960 | 5080 | 5210 | 5330 | 5450 |
| | | Dual | 100 | 7940 | 8180 | 8420 | 8660 | 8900 | 9140 | 9370 | 9610 | 9840 | 10070 | 10300 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL-WEATHER TRAILER TIRE – MILEAGE AND STABILITY FOR REGIONAL TRANSPORT

- New tread compound and tire construction for higher mileage and lower rolling resistance.
- Sturdy 5-rib open groove tread pattern with its dense, deep interlocking sipes ensures better grip.
- The wide shoulder design for improved stability and lateral grip as well as protection against lateral scrubbing.



## AVAILABLE SIZES

- 385/55R22.5 - T675304
- 385/55R22.5 - T675370

# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675304 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 379 | 992 | 456 | 3018 | 900 | 15 | C | B | A | 71 | Yes | Yes |
| T675370 | 385/55R22.5 | 164K | TL | 11.75 | 12.25 | | | 452 | 3018 | 900 | 15 | B | B | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675304 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| T675370 | 385/55R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK TRAILER 2

## ALL-WEATHER TRAILER TIRE – IMPROVED MILEAGE AND STABILITY FOR LONG DISTANCE AND REGIONAL TRANSPORT

- New generation of the Hakka Truck range with improved mileage performance and low rolling resistance.
- Sturdy tread pattern and deep tread with effective transverse sipes for better grip.
- The wide shoulder design for improved stability and lateral grip as well as protection against lateral scrubbing.






## AVAILABLE SIZES

- 265/70R19.5 - T675352
- 435/50R19.5 - T675326
- 445/45R19.5 - T675359
- 275/70R22.5 - T675353
- 385/55R22.5 - T675317
- 385/55R22.5 - T675371
- 385/65R22.5 - T675351

# NOKIAN TYRES HAKKA TRUCK TRAILER 2

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675352 | 265/70R19.5 | 143/141J | TL | 7.50 | 6.75, 8.25 | 260 | 871 | 404 | 2601 | 850 | 14.5 | 295 | C | A | A | 71 | Yes | Yes |
| T675326 | 435/50R19.5 | 164J | TL | 14.00 | 15.00 | 429 | 925 | 419 | 2821 | 900 | 13 | | C | A | A | 71 | Yes | Yes |
| T675359 | 445/45R19.5 | 164J | TL | 14.00 | 15.00 | 438 | 898 | 407 | 2712 | 900 | 13 | | C | A | B | 72 | Yes | Yes |
| T675353 | 275/70R22.5 | 148/145L | TL | 8.25 | 7.50 | 274 | 964 | 448 | 2922 | 900 | 14.5 | 311 | C | A | A | 70 | Yes | Yes |
| T675317 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 379 | 992 | 456 | 3018 | 900 | 15 | | B | A | A | 70 | Yes | Yes |
| T675371 | 385/55R22.5 | 164K | TL | 11.75 | 12.25 | 379 | 992 | 452 | 3018 | 900 | 15 | | B | A | A | 70 | Yes | Yes |
| T675351 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 387 | 1073 | 495 | 3248 | 900 | 15.5 | | B | A | A | 71 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675352 | 265/70R19.5 | Single | 100 | 4400 | 4530 | 4670 | 4800 | 4930 | 5060 | 5190 | 5320 | 5450 | | |
| | | Dual | 100 | 8310 | 8570 | 8820 | 9070 | 9320 | 9570 | 9810 | 10060 | 10300 | | |
| T675326 | 435/50R19.5 | Single | 100 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |
| T675359 | 445/45R19.5 | Single | 100 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |
| T675353 | 275/70R22.5 | Single | 120 | 4860 | 5000 | 5150 | 5300 | 5440 | 5590 | 5730 | 5880 | 6020 | 6160 | 6300 |
| | | Dual | 120 | 8940 | 9220 | 9490 | 9760 | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675317 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| T675371 | 385/55R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |
| T675351 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK TRAILER

## ALL-SEASON TRAILER TIRE – STABILITY AND GRIP FOR REGIONAL TRANSPORT

- New zigzag-shaped grooves improve stability.
- Groove design reduces stone trapping, resulting in longer tire life.
- Good grip on main road use.



## AVAILABLE SIZES

- 215/75R17.5 - T675334
- 235/75R17.5 - T675327
- 245/70R17.5 - T675328
- 265/70R19.5 - T675329
- 385/55R22.5 - T675306
- 385/65R22.5 - T675217
- 385/65R22.5 - T675305

# NOKIAN TYRES E-TRUCK TRAILER

## ALL SIZES

| Product code | Size | LI/SS | TL/TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675334 | 215/75R17.5 | 135/133J | TL | 6.00 | 6.75 | 210 | 772 | 355 | 2361 | 850 | 12 | 239 | C | B | A | 69 | Yes | Yes |
| T675327 | 235/75R17.5 | 143/141J | TL | 6.75 | 7.50 | 228 | 795 | 363 | 2433 | 900 | 13 | 262 | C | B | A | 69 | Yes | Yes |
| T675328 | 245/70R17.5 | 143/141J (146/146F) | TL | 7.50 | 6.75 | 243 | 792 | 363 | 2424 | 900 | 13 | 279 | C | B | A | 69 | Yes | Yes |
| T675329 | 265/70R19.5 | 143/141J | TL | 7.50 | 6.75, 8.25 | 261 | 865 | 400 | 2646 | 850 | 14 | 295 | C | B | A | 69 | Yes | Yes |
| T675306 | 385/55R22.5 | 160K | TL | 11.75 | 12.25 | 377 | 994 | 457 | 3040 | 900 | 14.5 | | B | B | A | 70 | Yes | Yes |
| T675217 | 385/65R22.5 | 160K (158L) | TL | 11.75 | 12.25 | 378 | 1080 | 499 | 3283 | 900 | 15.5 | | C | B | A | 70 | Yes | Yes |
| T675305 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 378 | 1073 | 494 | 3282 | 900 | 15 | | B | B | A | 69 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675334 | 215/75R17.5 | Single | 100 | 3520 | 3630 | 3730 | 3840 | 3940 | 4050 | 4150 | 4260 | 4360 | | |
| | | Dual | 100 | 6650 | 6850 | 7050 | 7260 | 7450 | 7650 | 7850 | 8050 | 8240 | | |
| T675327 | 235/75R17.5 | Single | 100 | 4200 | 4330 | 4460 | 4580 | 4710 | 4840 | 4960 | 5080 | 5210 | 5330 | 5450 |
| | | Dual | 100 | 7940 | 8180 | 8420 | 8660 | 8900 | 9140 | 9370 | 9610 | 9840 | 10070 | 10300 |
| T675328 | 245/70R17.5 | Single | 80 | 4620 | 4770 | 4910 | 5050 | 5190 | 5320 | 5460 | 5600 | 5730 | 5870 | 6000 |
| | | Dual | 80 | 9250 | 9530 | 9810 | 10090 | 10370 | 10650 | 10920 | 11190 | 11460 | 11730 | 12000 |
| | | Single | 100 | 4200 | 4330 | 4460 | 4580 | 4710 | 4840 | 4960 | 5080 | 5210 | 5330 | 5450 |
| | | Dual | 100 | 7940 | 8180 | 8420 | 8660 | 8900 | 9140 | 9370 | 9610 | 9840 | 10070 | 10300 |
| T675329 | 265/70R19.5 | Single | 100 | 4400 | 4530 | 4670 | 4800 | 4930 | 5060 | 5190 | 5320 | 5450 | | |
| | | Dual | 100 | 8310 | 8570 | 8820 | 9070 | 9320 | 9570 | 9810 | 10060 | 10300 | | |
| T675306 | 385/55R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675217 | 385/65R22.5 | Single | 110 | 6940 | 7150 | 7360 | 7570 | 7780 | 7990 | 8190 | 8390 | 8600 | 8800 | 9000 |
| | | Single | 120 | 6860 | 7070 | 7280 | 7480 | 7690 | 7890 | 8100 | 8300 | 8500 | | |
| T675305 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK TRAILER

## TRAILER TIRE – RELIABLE PERFORMANCE ON VARIABLE SURFACES FOR ON/OFF-ROAD USE

- Robust design ensures excellent mileage in addition to resistance to damage.
- Special rubber compound and low heat build-up means that tire wears evenly and retains its good properties throughout its lifetime.
- Strong shoulders withstand tight cornering and the staggered tread pattern wears evenly.





## AVAILABLE SIZES

- 265/70R19.5 - T675295
- 285/70R19.5 - T675360
- 275/70R22.5 - T675345
- 385/65R22.5 - T675314

# NOKIAN TYRES R-TRUCK TRAILER

## ALL SIZES

| Product code | Size | LI/SS | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| T675295 | 265/70R19.5 | 143/141J | TL | 7.50 | 6.75, 8.25 | 259 | 872 | 403 | 2601 | 900 | 15 | 295 | D | A | A | 71 | Yes | Yes |
| T675360 | 285/70R19.5 | 150/148J | TL | 8.25 | 9.00 | 279 | 894 | 410 | 2703 | 900 | 14.5 | 318 | D | A | B | 72 | Yes | Yes |
| T675345 | 275/70R22.5 | 148/145K | TL | 8.25 | 7.50 | 275 | 975 | 448 | 2922 | 900 | 16 | 311 | D | A | A | 71 | Yes | Yes |
| T675314 | 385/65R22.5 | 164K | TL | 11.75 | 12.25 | 385 | 1071 | 491 | 3248 | 900 | 15 | | C | A | B | 73 | Yes | Yes |

## LOAD CAPACITIES

| Product code | Size | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | km/h | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 | 875 | 900 |
| T675295 | 265/70R19.5 | Single | 100 | 4200 | 4330 | 4460 | 4580 | 4710 | 4840 | 4960 | 5080 | 5210 | 5330 | 5450 |
| | | Dual | 100 | 7940 | 8180 | 8420 | 8660 | 8900 | 9140 | 9370 | 9610 | 9840 | 10070 | 10300 |
| T675360 | 285/70R19.5 | Single | 100 | 5160 | 5320 | 5480 | 5640 | 5790 | 5940 | 6100 | 6250 | 6400 | 6550 | 6700 |
| | | Dual | 100 | 9710 | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675345 | 275/70R22.5 | Single | 110 | 4860 | 5000 | 5150 | 5300 | 5440 | 5590 | 5730 | 5880 | 6020 | 6160 | 6300 |
| | | Dual | 110 | 8940 | 9220 | 9490 | 9760 | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675314 | 385/65R22.5 | Single | 110 | 7710 | 7940 | 8180 | 8410 | 8640 | 8870 | 9100 | 9330 | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.