

# TECHNICAL MANUAL

UPDATED: 2026-03-04

NOKIAN HEAVY TYRES

**nokian<sup>®</sup>**  
**TYRES**

# TABLE OF CONTENTS

|                                     |           |                                         |           |
|-------------------------------------|-----------|-----------------------------------------|-----------|
| <b>FORESTRY</b>                     | <b>4</b>  | <b>COUNTRY KING G2</b>                  | <b>50</b> |
| FOREST KING F2                      | 5         | CT                                      | 52        |
| FOREST KING TRS 2                   | 7         | ELS                                     | 54        |
| FOREST KING TRS 2+                  | 9         | FLOAT KING VF                           | 56        |
| FOREST KING TRS L-2                 | 11        | <b>UNDERGROUND MINING</b>               | <b>58</b> |
| NORDMAN FOREST ELS L-2              | 13        | ARMOR GARD 2 MINE                       | 59        |
| NORDMAN FOREST F                    | 15        | MINE KING E-4                           | 61        |
| NORDMAN FOREST TRS L-2              | 17        | MINE KING L-5S                          | 63        |
| FOREST KING TRS LS-2                | 19        | MINE L-3S                               | 65        |
| LOGGER KING LS-2                    | 21        | NORDMAN MINE E-4                        | 67        |
| LOGGER KING LS-2 EXTREME            | 23        | <b>PORTS AND TERMINALS</b>              | <b>69</b> |
| FOREST KING T                       | 25        | HTS G2 E-4                              | 70        |
| TR FOREST 2                         | 27        | HTS G2 L-4S                             | 72        |
| TR MULTIPLUS                        | 29        | HTS G2 L-5S                             | 74        |
| TRACTOR KING                        | 31        | ARMOR GARD                              | 76        |
| <b>AGRICULTURAL AND CONTRACTING</b> | <b>33</b> | RTG                                     | 78        |
| TR MULTIPLUS                        | 34        | HTS TUGGER                              | 80        |
| GROUND KING                         | 36        | ARMOR GARD 2                            | 82        |
| HAKKAPELIITTA TRI                   | 38        | <b>EARTHMOVING AND ROAD MAINTENANCE</b> | <b>84</b> |
| SOIL KING VF                        | 41        | GROUND KING LOADER                      | 85        |
| TRI 2                               | 43        | HAKKAPELIITTA LOADER                    | 87        |
| TRI STEEL                           | 46        |                                         |           |
| COUNTRY KING                        | 48        |                                         |           |

|                                                 |            |                        |     |
|-------------------------------------------------|------------|------------------------|-----|
| LOADER GRIP                                     | 89         | E-TRUCK STEER          | 119 |
| LOADER GRIP 2                                   | 91         | E-TRUCK STEER 17.5     | 122 |
| GROUND KARE                                     | 93         | E-TRUCK STEER 19.5     | 124 |
| GROUND KARE SEMI-SLICK                          | 95         | R-TRUCK STEER          | 126 |
| ARMOR GARD 2                                    | 97         | HAKKAPELIITTA TRUCK D  | 128 |
| EXCAVATOR                                       | 99         | HAKKAPELIITTA TRUCK E2 | 130 |
| <b>ALL TERRAIN TRUCKS AND MILITARY VEHICLES</b> | <b>101</b> | HAKKA TRUCK DRIVE      | 133 |
| MPT AGILE                                       | 102        | E-TRUCK DRIVE          | 136 |
| MPT AGILE 2                                     | 104        | E-TRUCK DRIVE 17.5     | 139 |
| <b>TRUCKS AND BUSES</b>                         | <b>106</b> | E-TRUCK DRIVE 19.5     | 141 |
| HAKKAPELIITTA CITY BUS                          | 107        | R-TRUCK DRIVE          | 143 |
| HAKKAPELIITTA TRUCK F2                          | 109        | HAKKAPELIITTA TRUCK T  | 145 |
| HAKKA CITY BUS                                  | 112        | HAKKA TRUCK 844+       | 147 |
| HAKKA TRUCK COACH                               | 114        | HAKKA TRUCK TRAILER    | 149 |
| HAKKA TRUCK STEER                               | 116        | E-TRUCK TRAILER        | 151 |
|                                                 |            | R-TRUCK TRAILER        | 155 |

# FORESTRY TIRES

## FORWARDER AND HARVESTER



5

**Nokian Tyres  
Forest King F2**



17

**Nokian Tyres  
Nordman  
Forest TRS L-2**



7

**Nokian Tyres  
Forest King  
TRS 2**



9

**Nokian Tyres  
Forest King  
TRS 2+**



11

**Nokian Tyres  
Forest King  
TRS L-2**



13

**Nokian Tyres  
Nordman  
Forest ELS L-2**



15

**Nokian Tyres  
Nordman  
Forest F**

## SKIDDER AND FELLER BUNCHER



19

**Nokian Tyres  
Forest King  
TRS LS-2**



21

**Nokian Tyres  
Logger King  
LS-2**



23

**Nokian Tyres  
Logger King  
LS-2 Extreme**

## TRACTOR



25

**Nokian Tyres  
Forest King T**



27

**Nokian Tyres  
TR Forest 2**



29

**Nokian Tyres  
TR Multiplus**



31

**Nokian Tyres  
Tractor King**


# NOKIAN TYRES FOREST KING F2

## TRACK TIRE FOR HARVESTERS AND FORWARDERS

- Protective tread design with strong shoulders gives excellent functionality in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound in tread and especially in shoulder.
- High load-bearing capacity and comprehensive selection of sizes fills the needs of existing forest machinery – from smallest to heaviest.



2026-03-04



## AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • 600/50-22.5 - T445619 | • 710/55-26.5 - T445800 |
| • 710/40-22.5 - T445608 | • 750/55-26.5 - T445574 |
| • 710/40-24.5 - T445572 | • 800/40-26.5 - T445603 |
| • 800/40-24.5 - T445717 | • 710/55-28.5 - T445570 |
| • 600/55-26.5 - T445573 | • 780/50-28.5 - T445537 |
| • 710/45-26.5 - T445589 | • 780/55-30.5 - T445846 |
| • 710/45-26.5 - T445571 |                         |

# NOKIAN TYRES FOREST KING F2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |       |      |
|--------------|-------------|---------------|------------|-----------------|--------|---------|----------------|------------|---------------|---------------------------|-----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|-------|------|
|              |             |               |            |                 |        |         |                |            |               |                           |                             |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |       |      |
|              |             |               |            |                 |        |         |                |            |               |                           |                             |                |                               |                  |            |                   | 10                                          | 20                         | 30    | 40   |
| T445619      | 600/50-22.5 | 159A8 (167A2) | 20         | SF              | TT     | AG20.00 |                | 605        | 1167          | 539                       | 3544                        | 500            | 550                           | 30               | LS-2       | T55089            | 5450                                        | 5380                       | 4680  | 4375 |
| T445608      | 710/40-22.5 | 161A8 (168A2) | 20         | SF              | TT     | AG24.00 |                | 709        | 1167          | 537                       | 3550                        | 500            | 550                           | 30               | LS-2       | T55092            | 5600                                        | 5690                       | 4950  | 4625 |
| T445572      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT     | AG24.00 |                | 699        | 1230          | 570                       | 3738                        | 500            | 550                           | 35               | LS-2       | T545448           | 6000                                        | 5995                       | 5215  | 4875 |
| T445717      | 800/40-24.5 | 169A8 (176A2) | 20         | SF              | TT     | AG28.00 |                | 786        | 1250          | 569                       | 3795                        | 500            | 550                           | 35               | LS-2       | T545448           | 7100                                        | 7135                       | 6205  | 5800 |
| T445573      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT     | AG20.00 |                | 602        | 1342          | 618                       | 4071                        | 500            | 550                           | 35               | LS-2       | T55098            | 6300                                        | 6335                       | 5510  | 5150 |
| T445589      | 710/45-26.5 | 173A8 (180A2) | 24         | SF              | TT     | AG24.00 |                | 708        | 1345          | 621                       | 4084                        | 600            | 600                           | 35               | LS-2       | T55099            | 8000                                        | 7995                       | 6955  | 6500 |
| T445571      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT     | AG24.00 |                | 705        | 1345          | 622                       | 4084                        | 500            | 550                           | 35               | LS-2       | T55099            | 6900                                        | 6890                       | 5990  | 5600 |
| T445800      | 710/55-26.5 | 179A8 (186A2) | 24         | SF              | TT     | AG24.00 | AG22.00        | 697        | 1505          | 686                       | 4559                        | 600            | 600                           | 35               | LS-2       | T55102            | 9500                                        | 9535                       | 8295  | 7750 |
| T445574      | 750/55-26.5 | 182A8 (189A2) | 24         | SF              | TT     | AG24.00 |                | 769        | 1473          | 674                       | 4486                        | 600            | 600                           | 35               | LS-2       | T55102            | 10600                                       | 10455                      | 9095  | 8500 |
| T445603      | 800/40-26.5 | 170A8 (177A2) | 20         | SF              | TT     | AG28.00 |                | 807        | 1339          | 620                       | 4084                        | 500            | 550                           | 35               | LS-2       | T545312           | 7300                                        | 7380                       | 6420  | 6000 |
| T445570      | 710/55-28.5 | 180A8 (187A2) | 24         | SF              | TT     | AG24.00 |                | 719        | 1515          | 696                       | 4618                        | 600            | 600                           | 35               | LS-2       | T545543           | 9750                                        | 9840                       | 8560  | 8000 |
| T445537      | 780/50-28.5 | 182A8 (190A2) | 24         | SF              | TT     | AG26.00 |                | 783        | 1515          | 697                       | 4618                        | 600            | 600                           | 35               | LS-2       | T545543           | 10600                                       | 10455                      | 9095  | 8500 |
| T445846      | 780/55-30.5 | 187A8 (195A2) | 24         | SF              | TT     | AG26.00 |                | 780        | 1631          | 745                       | 4974                        | 600            | 600                           | 35               |            | T55891            | 12150                                       | 11995                      | 10435 | 9750 |


# NOKIAN TYRES FOREST KING TRS 2

## TRACTION TIRE FOR HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip.
- Wide lug ends, lifted groove bottom in shoulder and considered pitch length give good performance in track and chain use.
- Strong diagonal structure with steel fortification gives excellent puncture protection. More protective compound on shoulders.



2026-03-04



## AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • 600/50-22.5 - T445618 | • 710/45-26.5 - T445640 |
| • 710/40-22.5 - T445607 | • 710/55-26.5 - T445801 |
| • 600/50-24.5 - T445639 | • 750/55-26.5 - T445602 |
| • 710/40-24.5 - T445568 | • 800/40-26.5 - T445594 |
| • 800/40-24.5 - T445718 | • 710/55-28.5 - T445612 |
| • 600/55-26.5 - T445567 | • 780/50-28.5 - T445581 |
| • 710/45-26.5 - T445566 |                         |

# NOKIAN TYRES FOREST KING TRS 2


## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |
|--------------|-------------|---------------|------------|-----------------|--------|---------|----------------|------------|---------------|---------------------------|-----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|
|              |             |               |            |                 |        |         |                |            |               |                           |                             |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |
|              |             |               |            |                 |        |         |                |            |               |                           |                             |                |                               |                  |            |                   | 10                                          | 20                         | 30   | 40   |
| T445618      | 600/50-22.5 | 159A8 (167A2) | 20         | SF              | TT     | AG20.00 |                | 597        | 1168          | 533                       | 3550                        | 500            | 550                           | 42               | LS-2       | T55089            | 5450                                        | 5380                       | 4680 | 4375 |
| T445607      | 710/40-22.5 | 161A8 (168A2) | 20         | SF              | TT     | AG24.00 |                | 705        | 1171          | 535                       | 3569                        | 500            | 550                           | 42               | LS-2       | T55092            | 5600                                        | 5690                       | 4950 | 4625 |
| T445639      | 600/50-24.5 | 164A8 (171A2) | 20         | SF              | TT     | AG20.00 | AG22.00        | 603        | 1230          | 566                       | 3738                        | 550            | 550                           | 48               | LS-2       | T545447           | 5600                                        | 5535                       | 4815 | 4500 |
| T445568      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT     | AG24.00 |                | 694        | 1233          | 570                       | 3757                        | 500            | 550                           | 48               | LS-2       | T545448           | 6000                                        | 5995                       | 5215 | 4875 |
| T445718      | 800/40-24.5 | 169A8 (176A2) | 20         | SF              | TT     | AG28.00 |                | 784        | 1251          | 566                       | 3808                        | 500            | 550                           | 48               | LS-2       | T545448           | 7100                                        | 7135                       | 6205 | 5800 |
| T445567      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT     | AG20.00 |                | 598        | 1347          | 619                       | 4096                        | 500            | 550                           | 48               | LS-2       | T55098            | 6300                                        | 6335                       | 5510 | 5150 |
| T445566      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT     | AG24.00 |                | 703        | 1344          | 618                       | 4103                        | 500            | 550                           | 48               | LS-2       | T55099            | 6900                                        | 6890                       | 5990 | 5600 |
| T445640      | 710/45-26.5 | 173A8 (180A2) | 24         | SF              | TT     | AG24.00 |                | 702        | 1345          | 617                       | 4115                        | 600            | 600                           | 48               | LS-2       | T55099            | 8000                                        | 7995                       | 6955 | 6500 |
| T445801      | 710/55-26.5 | 179A8 (186A2) | 24         | SF              | TT     | AG24.00 | AG22.00        | 697        | 1503          | 688                       | 4546                        | 600            | 600                           | 49               | LS-2       | T55102            | 9500                                        | 9535                       | 8295 | 7750 |
| T445602      | 750/55-26.5 | 182A8 (189A2) | 24         | SF              | TT     | AG24.00 |                | 755        | 1477          | 674                       | 4499                        | 600            | 600                           | 49               | LS-2       | T55102            | 10600                                       | 10455                      | 9095 | 8500 |
| T445594      | 800/40-26.5 | 170A8 (177A2) | 20         | SF              | TT     | AG28.00 |                | 798        | 1343          | 619                       | 4096                        | 500            | 550                           | 48               | LS-2       | T545312           | 7300                                        | 7380                       | 6420 | 6000 |
| T445612      | 710/55-28.5 | 180A8 (187A2) | 24         | SF              | TT     | AG24.00 |                | 711        | 1513          | 693                       | 4618                        | 600            | 600                           | 49               | LS-2       | T545543           | 9750                                        | 9840                       | 8560 | 8000 |
| T445581      | 780/50-28.5 | 182A8 (190A2) | 24         | SF              | TT     | AG26.00 |                | 782        | 1513          | 691                       | 4611                        | 600            | 600                           | 49               | LS-2       | T545543           | 10600                                       | 10455                      | 9095 | 8500 |

# NOKIAN TYRES FOREST KING TRS 2+

## TRACTION TIRE FOR 6WD HARVESTERS AND FORWARDERS

- Aggressive tread design, square shape, sharp shoulders and high tread depth provide superb traction and lateral grip
- Special tread design with extra wing bars give excellent support, traction and protection in chain and wheel track use
- Strong 24PR diagonal structure with steel fortification gives excellent puncture protection and impressive stability



## AVAILABLE SIZES

- 600/65-34 - T445714
- 710/70-34 - T445716
- 710/55-34 - T445715

# NOKIAN TYRES FOREST KING TRS 2+

## ALL SIZES

| Product code | Size      | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |       |      |      |      |
|--------------|-----------|---------------|------------|-----------------|--------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|-------|------|------|------|
|              |           |               |            |                 |        |       |                |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |       |      |      |      |
|              |           |               |            |                 |        |       |                |            |               |                           |                            |                |                               |                  |            |                   | 10                                          | 10                         | 20    | 30   | 40   | 50   |
| T445714      | 600/65-34 | 169A8 (176A2) | 24         | SF              | TT     | DW20B |                | 615        | 1638          | 743                       | 4964                       | 400            | 400                           | 50               | LS-2       | T55394            | 7100                                        | 8700                       | 7135  | 6205 | 5800 | 5280 |
| T445715      | 710/55-34 | 173A8 (180A2) | 24         | SF              | TT     | DW24B | DW23B          | 715        | 1634          | 740                       | 4957                       | 400            | 400                           | 50               | LS-2       | T55394            | 8000                                        | 9750                       | 7995  | 6955 | 6500 | 5915 |
| T445716      | 710/70-34 | 181A8 (188A2) | 24         | SF              | TT     | DW23B | DW24B, DW25B   | 744        | 1833          | 821                       | 5554                       | 400            | 400                           | 53               | LS-2       | T55388            | 10000                                       | 12375                      | 10150 | 8830 | 8250 | 7510 |


# NOKIAN TYRES FOREST KING TRS L-2

## RELIABLE GRIP AND TRACTION

- Wide and high pattern lugs for good mobility and operating comfort
- Optimised lug angle and sharp tire shoulders providing excellent lateral grip
- Steel protection against punctures



2026-03-04



## AVAILABLE SIZES

- 650/60-26.5 - T445395

# NOKIAN TYRES FOREST KING TRS L-2


## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |
|--------------|-------------|---------------|------------|-----------------|-------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                  |            |                   | 10                                          | 20                         | 30   | 40   |
| T445395      | 650/60-26.5 | 172A8 (179A2) | 20         | SF              | TT    | AG20.00 | 655        | 1479          | 676                       | 4467                       | 500            | 550                           | 50               | L-2        | T55102            | 7750                                        | 7750                       | 6740 | 6300 |

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King ELS L-2 are applicable to Nordman Forest ELS L-2, making it a perfect option as a replacement tire.
- The design of the tire provides good performance in track and chain use.



## AVAILABLE SIZES

- 600/50-22.5 - T445623

# NOKIAN TYRES NORDMAN FOREST ELS L-2

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim     | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |
|--------------|-------------|---------------|------------|-----------------|-------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |
|              |             |               |            |                 |       |         |            |               |                           |                            |                |                               |                  |            |                   | 10                                          | 20                         | 30   | 40   |
| T445623      | 600/50-22.5 | 149A8 (156A2) | 16         | SF              | TT    | AG20.00 | 606        | 1164          | 543                       | 3544                       | 320            | 400                           | 32               | LS-2       | T55089            | 4000                                        | 4000                       | 3480 | 3250 |


# NOKIAN TYRES NORDMAN FOREST F

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The design of the tire provides good performance in track and chain use.



2026-03-04



## AVAILABLE SIZES

- 710/40-22.5 - T445625
- 710/40-24.5 - T445599
- 600/55-26.5 - T445598
- 710/45-26.5 - T445565
- 750/55-26.5 - T445597

# NOKIAN TYRES NORDMAN FOREST F

## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim     | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |
|--------------|-------------|---------------|------------|-----------------|--------|---------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|
|              |             |               |            |                 |        |         |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |
|              |             |               |            |                 |        |         |            |               |                           |                            |                |                               |                  |            |                   | 10                                          | 20                         | 30   | 40   |
| T445625      | 710/40-22.5 | 151A8 (158A2) | 16         | SF              | TT     | AG24.00 | 701        | 1164          | 538                       | 3544                       | 320            | 400                           | 28               | LS-2       | T55092            | 4250                                        | 4245                       | 3690 | 3450 |
| T445599      | 710/40-24.5 | 163A8 (170A2) | 20         | SF              | TT     | AG24.00 | 706        | 1223          | 573                       | 3729                       | 500            | 550                           | 29               | LS-2       | T545448           | 6000                                        | 5995                       | 5215 | 4875 |
| T445598      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT     | AG20.00 | 615        | 1339          | 624                       | 4065                       | 500            | 550                           | 32               | LS-2       | T55098            | 6300                                        | 6335                       | 5510 | 5150 |
| T445565      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT     | AG24.00 | 711        | 1345          | 622                       | 4046                       | 500            | 550                           | 30               | LS-2       | T55099            | 6900                                        | 6890                       | 5990 | 5600 |
| T445597      | 750/55-26.5 | 177A8 (184A2) | 20         | SF              | TT     | AG24.00 | 762        | 1476          | 680                       | 4467                       | 500            | 550                           | 32               | LS-2       | T55102            | 9000                                        | 8980                       | 7810 | 7300 |


# NOKIAN TYRES NORDMAN FOREST TRS L-2

## COST-EFFICIENT REPLACEMENT TIRE FOR HARVESTERS AND FORWARDERS

- Strong and reliable diagonal structure with steel fortification gives excellent puncture protection in demanding forestry conditions.
- The existing tracks designed for Forest King TRS L-2 are applicable to Nordman Forest TRS L-2, making it a perfect option as a replacement tire.
- Good terrain mobility due to aggressive tread design with high tread depth.



2026-03-04



## AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • 600/50-22.5 - T445622 | • 750/55-26.5 - T445528 |
| • 710/40-22.5 - T445624 | • 600/65-34 - T445475   |
| • 600/55-26.5 - T445527 | • 700/55-34 - T445476   |
| • 710/45-26.5 - T445541 | • 700/70-34 - T445596   |

# NOKIAN TYRES NORDMAN FOREST TRS L-2


## ALL SIZES

| Product code | Size        | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |
|--------------|-------------|---------------|------------|-----------------|--------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|
|              |             |               |            |                 |        |         |                |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |
|              |             |               |            |                 |        |         |                |            |               |                           |                            |                |                               |                  |            |                   | 10                                          | 20                         | 30   | 40   |
| T445622      | 600/50-22.5 | 149A8 (156A2) | 16         | SF              | TT     | AG20.00 |                | 605        | 1168          | 545                       | 3544                       | 320            | 400                           | 42               | LS-2       | T55089            | 4000                                        | 4000                       | 3480 | 3250 |
| T445624      | 710/40-22.5 | 151A8 (158A2) | 16         | SF              | TT     | AG24.00 |                | 706        | 1169          | 539                       | 3537                       | 320            | 400                           | 42               | LS-2       | T55092            | 4250                                        | 4245                       | 3690 | 3450 |
| T445527      | 600/55-26.5 | 165A8 (172A2) | 20         | SF              | TT     | AG20.00 |                | 613        | 1345          | 616                       | 4065                       | 500            | 550                           | 48               | LS-2       | T55098            | 6300                                        | 6335                       | 5510 | 5150 |
| T445541      | 710/45-26.5 | 168A8 (175A2) | 20         | SF              | TT     | AG24.00 |                | 711        | 1345          | 608                       | 4077                       | 500            | 550                           | 48               | LS-2       | T55099            | 6900                                        | 6890                       | 5990 | 5600 |
| T445528      | 750/55-26.5 | 177A8 (184A2) | 20         | SF              | TT     | AG24.00 |                | 752        | 1480          | 672                       | 4461                       | 500            | 550                           | 50               | LS-2       | T55102            | 9000                                        | 8980                       | 7810 | 7300 |
| T445475      | 600/65-34   | 163A8 (170A2) | 20         | SF              | TT     | DW20B   |                | 615        | 1644          | 755                       | 4964                       | 320            | 360                           | 51               | LS-2       | T55394            | 6000                                        | 5995                       | 5215 | 4875 |
| T445476      | 700/55-34   | 166A8 (173A2) | 20         | SF              | TT     | DW24B   | DW23B          | 708        | 1634          | 751                       | 4938                       | 320            | 360                           | 51               | LS-2       | T55394            | 6500                                        | 6520                       | 5670 | 5300 |
| T445596      | 700/70-34   | 173A8 (180A2) | 20         | SF              | TT     | DW20B   | DW23B, DW24B   | 723        | 1848          | 840                       | 5542                       | 320            | 360                           | 53               | LS-2       | T55388            | 8000                                        | 7995                       | 6955 | 6500 |

# NOKIAN TYRES FOREST KING TRS LS-2

A FORESTRY AND EARTHMOVING MACHINE TRACTION TIRE WITH A STRONG TRACTION BAR AND EXCELLENT GRIP. WELLCLEANING, OPEN-CENTRE TREAD DESIGN. DURABLE SPECIAL RUBBER COMPOUND AND EFFICIENT STEEL FORTIFICATION

- Tires for log skidders, wide tread with high traction lugs
- Special cut and crack resistant compound
- Steel fortification against punctures



## AVAILABLE SIZES

- 28L-26 - T445516



# NOKIAN TYRES FOREST KING TRS LS-2


## ALL SIZES

| Product code | Size   | LI/SS         | Ply rating | Reinforced code | TL/ TT | Rim   | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg |      |      |      |
|--------------|--------|---------------|------------|-----------------|--------|-------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|------|------|------|
|              |        |               |            |                 |        |       |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                                                                  | Speed (km/h)                                                                                             |      |      |      |
|              |        |               |            |                 |        |       |            |               |                           |                            |                |                               |                  |            |                   | 10                                                                                            | 15                                                                                                       | 25   | 30   | 40   |
| T445516      | 28L-26 | 173A6 (185A2) | 26         | SF              | TL     | DW25B | 741        | 1641          | 748                       | 4945                       | 340            | 400                           | 53               | LS-2       | T55101            | 9200                                                                                          | 7800                                                                                                     | 7150 | 6500 | 5850 |

# NOKIAN TYRES LOGGER KING LS-2

## FORESTRY TIRE FOR FULL-TREE MACHINES, SUCH AS SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.



## AVAILABLE SIZES

- 23.1-26 - T445616
- 24.5-32 - T445614
- 28L-26 - T445615
- 30.5L-32 - T445621

# NOKIAN TYRES LOGGER KING LS-2


## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim   | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg |      |      |      |
|--------------|----------|---------------|------------|-----------------|-------|-------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|------|------|------|
|              |          |               |            |                 |       |       |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                                                                  | Speed (km/h)                                                                                             |      |      |      |
|              |          |               |            |                 |       |       |            |               |                           |                            |                |                               |                  |            |                   | 10                                                                                            | 15                                                                                                       | 25   | 30   | 40   |
| T445616      | 23.1-26  | 160A6 (156A8) | 16         | SF              | TL    | DW20B | 604        | 1623          | 749                       | 4882                       | 280            | 280                           | 54               | LS-2       | T55102            | 6300                                                                                          | 5400                                                                                                     | 4950 | 4500 | 4050 |
| T445615      | 28L-26   | 165A6 (161A8) | 20         | SF              | TL    | DW25B | 720        | 1647          | 754                       | 4945                       | 280            | 280                           | 58               | LS-2       | T55101            | 7250                                                                                          | 6200                                                                                                     | 5700 | 5150 | 4650 |
| T445614      | 24.5-32  | 169A6 (167A8) | 20         | SF              | TL    | DH21  | 637        | 1829          | 846                       | 5517                       | 280            | 310                           | 58               | LS-2       | T55393            | 8200                                                                                          | 7000                                                                                                     | 6450 | 5850 | 5250 |
| T445621      | 30.5L-32 | 170A6 (167A8) | 20         | SF              | TL    | DH27  | 773        | 1843          | 853                       | 5542                       | 240            | 240                           | 67               | LS-2       | T55388            | 8400                                                                                          | 7200                                                                                                     | 6600 | 6000 | 5400 |

# NOKIAN TYRES LOGGER KING LS-2 EXTREME

## TIRE FOR FULL-TREE MACHINES, I. A. SKIDDERS AND WHEELED FELLER BUNCHERS

- Strong diagonal carcass with steel fortification layers covering the whole tread area and shoulders. Very thick layer of CCR rubber on top of steel fortification.
- More straight tread profile enables very wide contact to surface. Wide, open and aggressive tread design with “shovel” lug shape gives great traction and self-cleaning.
- In extreme versions there are added layers of carcass material and extra layers of steel in tread that give more load-bearing capacity and ultimate puncture resistance.



## AVAILABLE SIZES

- 30.5L-32 - T445613
- 35.5L-32 - T445620

# NOKIAN TYRES LOGGER KING LS-2 EXTREME


## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim  | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for log skidder drive wheel for cable and grapple skidders forestry service, kg | Load capacity for log skidder drive wheel (other than on cable or grapple skidder) transport service, kg |      |      |      |      |
|--------------|----------|---------------|------------|-----------------|-------|------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|------|------|------|------|
|              |          |               |            |                 |       |      |            |               |                           |                            |                |                               |                  |            |                   | Speed (km/h)                                                                                  | Speed (km/h)                                                                                             |      |      |      |      |
|              |          |               |            |                 |       |      |            |               |                           |                            |                |                               |                  |            |                   | 10                                                                                            | 10                                                                                                       | 15   | 25   | 30   | 40   |
| T445613      | 30.5L-32 | 176A6 (172A8) | 26         | SF              | TL    | DH27 | 778        | 1842          | 849                       | 5548                       | 310            | 310                           | 67               | LS-2       | T55388            | 10000                                                                                         | 8550                                                                                                     |      | 7850 | 7100 | 6400 |
| T445620      | 35.5L-32 | 183A6 (180A8) | 26         | SF              | TL    | DH31 | 915        | 2009          | 920                       | 6063                       | 280            | 280                           | 67               | LS-2       | T55879            | 12250                                                                                         | 10500                                                                                                    | 9650 | 8750 | 7850 |      |

# NOKIAN TYRES FOREST KING T

**FOR TRACTORS AND SKIDDERS USED IN FORESTRY, FOREST CLEARANCE OR ROAD CONSTRUCTION**

- Strong and wide lugs enable good traction and tolerate high tractive forces.
- Steel fortifications together with strong diagonal construction give excellent puncture resistance.
- Stiff diagonal construction enables better stability.



## AVAILABLE SIZES

- 500/70-28 - T445335
- 650/75-38 - T445313
- 540/70-30 - T445314



# NOKIAN TYRES FOREST KING T


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for forestry service (lt), kg | Load capacity for road, kg |      |      |      |      |
|--------------|-----------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|---------------------------------------------|----------------------------|------|------|------|------|
|              |           |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                  |            |                   | Speed (km/h)                                | Speed (km/h)               |      |      |      |      |
|              |           |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                  |            |                   | 10                                          | 10                         | 20   | 30   | 40   | 50   |
| T445335      | 500/70-28 | 146A8        | SF              | TT    | DW16L |                | 510        | 1401          | 650                       | 4241                       | 675 | 240            | 280                           | 49               | LS-2       | T545229           | 3650                                        | 4500                       | 3690 | 3210 | 3000 | 2730 |
| T445314      | 540/70-30 | 152A8 (149B) | SF              | TT    | DW16L | DW18B          | 534        | 1518          | 705                       | 4505                       | 725 | 240            | 280                           | 50               | LS-2       | T55371            | 4375                                        | 5325                       | 4365 | 3800 | 3550 | 3230 |
| T445313      | 650/75-38 | 168A8 (165B) | SF              | TT    | DW20B | DW23B          | 647        | 1956          | 900                       | 5890                       | 925 | 240            | 280                           | 53               | LS-2       | T545322           | 6900                                        | 8400                       | 6890 | 5990 | 5600 | 5095 |

# NOKIAN TYRES TR FOREST 2

**FOR SMALL AND MEDIUM SIZE  
TRACTORS USED IN VERSATILE TASKS  
F.EX IN FORESTRY**

- Cut and crack resistant compound together with strong cross-ply construction to tolerate rough conditions.
- Stiff diagonal construction enables great stability.
- Tractive tread design with good self-cleaning properties.



## AVAILABLE SIZES

- |                       |                       |
|-----------------------|-----------------------|
| • 320/85-24 - T445784 | • 420/85-30 - T445786 |
| • 340/85-24 - T445780 | • 420/85-34 - T445779 |
| • 380/85-24 - T445778 | • 460/85-34 - T445777 |
| • 340/85-28 - T445785 | • 420/85-38 - T445793 |
| • 380/85-28 - T445790 | • 460/85-38 - T445788 |
| • 420/85-28 - T445789 | • 520/85-38 - T445787 |

# NOKIAN TYRES TR FOREST 2


## ALL SIZES

| Product code | Size      | Equivalent size | LI/SS        | Ply rating | TL/TT | Rim   | Permitted rims     | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for tractor, kg |      |      |      |      |      |
|--------------|-----------|-----------------|--------------|------------|-------|-------|--------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------------------|------|------|------|------|------|
|              |           |                 |              |            |       |       |                    |            |               |                           |                            |     |                |                               |                  |            | Speed (km/h)                  |      |      |      |      |      |
|              |           |                 |              |            |       |       |                    |            |               |                           |                            |     |                |                               |                  |            | 25                            | 30   | 35   | 40   | 45   | 50   |
| T445784      | 320/85-24 | 12.4-24         | 130A8 (127B) | 16         | TL    | DW11  | DW10               | 326        | 1174          | 529                       | 3534                       | 550 | 280            | 280                           | 36               | R-1        | 2110                          | 2035 | 1955 | 1900 | 1825 | 1730 |
| T445780      | 340/85-24 | 13.6-24         | 134A8 (131B) | 16         | TL    | DW12  | DW11               | 348        | 1223          | 552                       | 3682                       | 575 | 280            | 280                           | 38               | R-1        | 2355                          | 2270 | 2185 | 2120 | 2035 | 1930 |
| T445778      | 380/85-24 | 14.9-24         | 140A8 (137B) | 16         | TL    | DW13  | DW13L, DW11, DW12  | 390        | 1266          | 566                       | 3813                       | 600 | 280            | 280                           | 42               | R-1        | 2775                          | 2675 | 2575 | 2500 | 2400 | 2275 |
| T445785      | 340/85-28 | 13.6-28         | 136A8 (133B) | 16         | TL    | DW12  | DW11               | 352        | 1308          | 591                       | 3947                       | 625 | 280            | 280                           | 42               | R-1        | 2485                          | 2395 | 2305 | 2240 | 2150 | 2040 |
| T445790      | 380/85-28 | 14.9-28         | 142A8 (139B) | 16         | TL    | DW13  | DW13L, DW11, DW12  | 392        | 1359          | 613                       | 4107                       | 650 | 280            | 280                           | 42               | R-1        | 2940                          | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445789      | 420/85-28 | 16.9-28         | 148A8 (145B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 435        | 1423          | 639                       | 4310                       | 675 | 280            | 280                           | 46               | R-1        | 3495                          | 3370 | 3245 | 3150 | 3025 | 2865 |
| T445786      | 420/85-30 | 16.9-30         | 149A8 (146B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 430        | 1490          | 668                       | 4482                       | 700 | 280            | 280                           | 47               | R-1        | 3610                          | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445779      | 420/85-34 | 16.9-34         | 151A8 (148B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 429        | 1577          | 707                       | 4744                       | 750 | 280            | 280                           | 47               | R-1        | 3830                          | 3690 | 3555 | 3450 | 3310 | 3140 |
| T445777      | 460/85-34 | 18.4-34         | 155A8 (152B) | 16         | TL    | DW16L | DW15L              | 465        | 1638          | 756                       | 4951                       | 775 | 280            | 280                           | 50               | R-1        | 4300                          | 4145 | 3990 | 3875 | 3720 | 3525 |
| T445793      | 420/85-38 | 16.9-38         | 152A8 (149B) | 16         | TL    | DW15L | DW14L, DW13L, DW13 | 431        | 1673          | 759                       | 5081                       | 800 | 280            | 280                           | 50               | R-1        | 3940                          | 3800 | 3655 | 3550 | 3410 | 3230 |
| T445788      | 460/85-38 | 18.4-38         | 157A8 (154B) | 16         | TL    | DW16L | DW15L              | 471        | 1740          | 785                       | 5267                       | 825 | 280            | 280                           | 53               | R-1        | 4580                          | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445787      | 520/85-38 | 20.8-38         | 164A8 (160B) | 16         | TL    | DW18L | DW16L              | 536        | 1832          | 817                       | 5524                       | 875 | 280            | 280                           | 54               | R-1        | 5550                          | 5350 | 5150 | 5000 | 4800 | 4550 |

# NOKIAN TYRES TR MULTIPLUS

**FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS**

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.



## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415



# NOKIAN TYRES TR MULTIPLUS


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims                      | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for tractor, kg |      |      |      |      |      |
|--------------|-----------|--------------|-----------------|-------|-------|-------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|-------------------------------|------|------|------|------|------|
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                  |            |                   | Speed (km/h)                  |      |      |      |      |      |
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                  |            |                   | 25                            | 30   | 35   | 40   | 45   | 50   |
| T445410      | 500/65R24 | 142A8 (139B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 489        | 1242          | 575                       | 3735                       | 600 | 240            | 320                           | 48               | R-1        |                   | 2940                          | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445411      | 500/65R28 | 144A8 (141B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, W13        | 491        | 1341          | 622                       | 4055                       | 650 | 240            | 320                           | 48               | R-1        | T55097            | 3110                          | 2995 | 2885 | 2800 | 2690 | 2550 |
| T445412      | 540/65R28 | 149A8 (146B) | SB              | TL    | DW16  | W15L, W16L, DW18L, W18L, DW16L      | 522        | 1409          | 653                       | 4254                       | 675 | 240            | 320                           | 51               | R-1        | T545229           | 3610                          | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445413      | 600/65R34 | 157A8 (154B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 585        | 1640          | 750                       | 4930                       | 775 | 240            | 320                           | 52               | R-1        | T55395            | 4580                          | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445414      | 600/65R38 | 159A8 (156B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 584        | 1743          | 809                       | 5290                       | 825 | 240            | 320                           | 52               | R-1        |                   | 4855                          | 4680 | 4505 | 4375 | 4200 | 3980 |
| T445415      | 650/65R38 | 164A8 (160B) | SB              | TL    | DW20B | DW18                                | 641        | 1808          | 838                       | 5485                       | 875 | 240            | 320                           | 53               | R-1        | T545322           | 5410                          | 5215 | 5020 | 4875 | 4680 | 4435 |

# NOKIAN TYRES TRACTOR KING

## VERSATILE HEAVY-DUTY RADIAL TRACTION TIRE FOR DEMANDING OFF-ROAD APPLICATIONS AND HIGH-SPEED ROAD TRANSITS

- Strong steel belted radial carcass strengthened with forest tread compound. 400 kPa max pressure enabling high load carrying capacity and stability.
- Wide tread and radically increased amount of tractive edges for supreme traction.
- Innovative tread design with even ground contact resulting in comfortable drive. Durability up to 65 km/h speeds.



## AVAILABLE SIZES

- 480/65R28 - T445806
- 500/65R28 - T445673
- 540/65R28 - T445674
- 600/60R28 - T445675
- 600/65R28 - T445851
- 540/65R30 - T445676
- 540/70R30 - T445677
- 600/70R30 - T445678
- 620/75R30 - T445679
- 600/65R34 - T445680
- 600/70R34 - T445681
- 600/65R38 - T445682
- 650/65R38 - T445683
- 650/75R38 - T445684
- 650/85R38 - T445685
- 710/70R38 - T445741
- 800/70R38 - T445852
- 650/65R42 - T445740
- 710/70R42 - T445686
- 710/75R42 - T445687

# NOKIAN TYRES TRACTOR KING

## ALL SIZES

| Product code | Size      | LI/SS | Reinforced code | TL/TT | Rim   | Permitted rims      | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI  | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for tractor, kg |      |      |      |      |      |
|--------------|-----------|-------|-----------------|-------|-------|---------------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|------------------|------------|-------------------------------|------|------|------|------|------|
|              |           |       |                 |       |       |                     |            |               |                           |                            |      |                |                               |                  |            | Speed (km/h)                  |      |      |      |      |      |
|              |           |       |                 |       |       |                     |            |               |                           |                            |      |                |                               |                  |            | 40                            | 45   | 50   | 55   | 60   | 65   |
| T445806      | 480/65R28 | 148D  | SB              | TL    | DW15L | DW16L, DW14L, DW18L | 487        | 1359          | 629                       | 4103                       | 650  | 320            | 400                           | 48               | R-1W       | 3450                          | 3370 | 3310 | 3245 | 3195 | 3150 |
| T445673      | 500/65R28 | 150D  | SB              | TL    | DW16L | DW15L, DW18L        | 494        | 1358          | 629                       | 4103                       | 650  | 320            | 400                           | 48               | R-1W       | 3670                          | 3585 | 3520 | 3450 | 3400 | 3350 |
| T445674      | 540/65R28 | 154D  | SB              | TL    | DW18L | DW16L               | 542        | 1409          | 650                       | 4248                       | 675  | 320            | 400                           | 48               | R-1W       | 4105                          | 4015 | 3940 | 3865 | 3805 | 3750 |
| T445675      | 600/60R28 | 157D  | SB              | TL    | DW18L | DW20B               | 584        | 1423          | 617                       | 4255                       | 675  | 320            | 400                           | 49               | R-1W       | 4515                          | 4415 | 4330 | 4250 | 4185 | 4125 |
| T445851      | 600/65R28 | 160D  | SB              | TL    | DW20B | DW18L               | 606        | 1502          | 692                       | 4530                       | 700  | 320            | 400                           | 50               | R-1W       | 4930                          | 4815 | 4725 | 4635 | 4570 | 4500 |
| T445676      | 540/65R30 | 155D  | SB              | TL    | DW18L | DW16L               | 537        | 1463          | 677                       | 4427                       | 700  | 320            | 400                           | 49               | R-1W       | 4245                          | 4145 | 4070 | 3990 | 3935 | 3875 |
| T445677      | 540/70R30 | 159D  | SB              | TL    | DW18L | DW16L               | 543        | 1506          | 693                       | 4539                       | 725  | 320            | 400                           | 50               | R-1W       | 4790                          | 4680 | 4595 | 4505 | 4440 | 4375 |
| T445678      | 600/70R30 | 165D  | SB              | TL    | DW18L | DW20B               | 579        | 1602          | 730                       | 4826                       | 750  | 320            | 400                           | 51               | R-1W       | 5640                          | 5510 | 5410 | 5305 | 5225 | 5150 |
| T445679      | 620/75R30 | 169D  | SB              | TL    | DW20B |                     | 624        | 1688          | 770                       | 5097                       | 800  | 320            | 400                           | 52               | R-1        | 6350                          | 6205 | 6090 | 5975 | 5885 | 5800 |
| T445680      | 600/65R34 | 163D  | SB              | TL    | DW18L | DW20B               | 581        | 1641          | 754                       | 4960                       | 775  | 320            | 400                           | 52               | R-1W       | 5340                          | 5215 | 5120 | 5020 | 4950 | 4875 |
| T445681      | 600/70R34 | 167D  | SB              | TL    | DW18L | DW20B               | 585        | 1703          | 775                       | 5138                       | 800  | 320            | 400                           | 52               | R-1W       | 5970                          | 5830 | 5725 | 5615 | 5530 | 5450 |
| T445682      | 600/65R38 | 165D  | SB              | TL    | DW18L | DW20B               | 579        | 1744          | 805                       | 5282                       | 825  | 320            | 400                           | 53               | R-1W       | 5640                          | 5510 | 5410 | 5305 | 5225 | 5150 |
| T445683      | 650/65R38 | 169D  | SB              | TL    | DW20B |                     | 632        | 1811          | 830                       | 5479                       | 875  | 320            | 400                           | 53               | R-1W       | 6350                          | 6205 | 6090 | 5975 | 5885 | 5800 |
| T445684      | 650/75R38 | 175D  | SB              | TL    | DW20B | DW23B, DW21B        | 644        | 1943          | 880                       | 5894                       | 925  | 320            | 400                           | 55               | R-1W       | 7555                          | 7385 | 7245 | 7105 | 7005 | 6900 |
| T445685      | 650/85R38 | 178D  | SB              | TL    | DW20B | DW23B, DW21B        | 642        | 2066          | 941                       | 6272                       | 975  | 320            | 400                           | 55               | R-1        | 8215                          | 8025 | 7875 | 7725 | 7615 | 7500 |
| T445741      | 710/70R38 | 177D  | SB              | TL    | DW23B | DW25B               | 716        | 1955          | 890                       | 5921                       | 925  | 320            | 400                           | 55               | R-1W       | 7995                          | 7810 | 7665 | 7520 | 7410 | 7300 |
| T445852      | 800/70R38 | 183D  | SB              | TL    | DW27B | DW25B               | 825        | 2083          | 951                       | 6300                       | 975  | 320            | 400                           | 56               | R-1        | 9580                          | 9365 | 9190 | 9015 | 8880 | 8750 |
| T445740      | 650/65R42 | 170D  | SB              | TL    | DW20B | DW21B, DW23B        | 633        | 1913          | 881                       | 5799                       | 925  | 320            | 400                           | 55               | R-1W       | 6570                          | 6420 | 6300 | 6180 | 6090 | 6000 |
| T445686      | 710/70R42 | 179D  | SB              | TL    | DW23B | DW25B               | 716        | 2061          | 943                       | 6235                       | 975  | 320            | 400                           | 56               | R-1W       | 8485                          | 8295 | 8140 | 7985 | 7865 | 7750 |
| T445687      | 710/75R42 | 181D  | SB              | TL    | DW23B | DW25B               | 716        | 2131          | 972                       | 6458                       | 1000 | 320            | 400                           | 57               | R-1W       | 9035                          | 8830 | 8665 | 8500 | 8375 | 8250 |

# AGRICULTURAL AND CONTRACTING TIRES

## TRACTOR



34

**Nokian Tyres  
TR Multiplus**



36

**Nokian Tyres  
Ground King**



38

**Nokian Tyres  
Hakkapeliitta  
TRI**



41

**Nokian Tyres  
Soil King VF**



43

**Nokian Tyres  
TRI 2**



46

**Nokian Tyres  
TRI Steel**

## TRAILER



48

**Nokian Tyres  
Country King**



50

**Nokian Tyres  
Country King  
G2**



52

**Nokian Tyres  
CT**



54

**Nokian Tyres  
ELS**



56

**Nokian Tyres  
Float King VF**

## WHEEL LOADER




38

**Nokian Tyres  
Hakkapeliitta  
TRI**

# NOKIAN TYRES TR MULTIPLUS

FOR TRACTORS USED IN VERSATILE CONDITIONS LIKE FORESTRY, AGRICULTURAL WORK AND ROAD TRANSPORTS

- Radial construction forms wide footprint together with deep and open tread design, enabling excellent traction properties.
- Radial construction enables durability and good driving properties in road transports.
- Strengthened sidewalls enable use in conditions where punctures and cuts are possible, such as stony fields or forests.



## AVAILABLE SIZES

- 500/65R24 - T445410
- 500/65R28 - T445411
- 540/65R28 - T445412
- 600/65R34 - T445413
- 600/65R38 - T445414
- 650/65R38 - T445415



# NOKIAN TYRES TR MULTIPLUS


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims                      | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Load capacity for tractor, kg |      |      |      |      |      |
|--------------|-----------|--------------|-----------------|-------|-------|-------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|-------------------------------|------|------|------|------|------|
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                  |            |                   | Speed (km/h)                  |      |      |      |      |      |
|              |           |              |                 |       |       |                                     |            |               |                           |                            |     |                |                               |                  |            |                   | 25                            | 30   | 35   | 40   | 45   | 50   |
| T445410      | 500/65R24 | 142A8 (139B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, DW13L, W13 | 489        | 1242          | 575                       | 3735                       | 600 | 240            | 320                           | 48               | R-1        |                   | 2940                          | 2835 | 2730 | 2650 | 2545 | 2410 |
| T445411      | 500/65R28 | 144A8 (141B) | SB              | TL    | DW15L | DW16L, W16L, W15L, W14L, W13        | 491        | 1341          | 622                       | 4055                       | 650 | 240            | 320                           | 48               | R-1        | T55097            | 3110                          | 2995 | 2885 | 2800 | 2690 | 2550 |
| T445412      | 540/65R28 | 149A8 (146B) | SB              | TL    | DW16  | W15L, W16L, DW18L, W18L, DW16L      | 522        | 1409          | 653                       | 4254                       | 675 | 240            | 320                           | 51               | R-1        | T545229           | 3610                          | 3480 | 3350 | 3250 | 3120 | 2960 |
| T445413      | 600/65R34 | 157A8 (154B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 585        | 1640          | 750                       | 4930                       | 775 | 240            | 320                           | 52               | R-1        | T55395            | 4580                          | 4415 | 4250 | 4125 | 3960 | 3755 |
| T445414      | 600/65R38 | 159A8 (156B) | SB              | TL    | DW18L | W16L, W18L, DW20B, DW16L            | 584        | 1743          | 809                       | 5290                       | 825 | 240            | 320                           | 52               | R-1        |                   | 4855                          | 4680 | 4505 | 4375 | 4200 | 3980 |
| T445415      | 650/65R38 | 164A8 (160B) | SB              | TL    | DW20B | DW18                                | 641        | 1808          | 838                       | 5485                       | 875 | 240            | 320                           | 53               | R-1        | T545322           | 5410                          | 5215 | 5020 | 4875 | 4680 | 4435 |

# NOKIAN TYRES GROUND KING

## CROSSOVER TIRE FOR MIXED AGRICULTURAL WORK

- Advanced alternative for the lug pattern traction tire that combines the features and benefits of two pattern types.
- Solid performance on fields and roads with traction, multi-directional grip and continuous contact.
- Supports the versatile use of implements with stability, high strength and load capacity.



## AVAILABLE SIZES

- |                       |                       |
|-----------------------|-----------------------|
| • 420/70R28 - T445733 | • 650/65R34 - T445731 |
| • 480/65R28 - T445764 | • 520/70R38 - T445732 |
| • 480/70R28 - T445735 | • 580/70R38 - T445734 |
| • 540/65R28 - T445737 | • 600/65R38 - T445765 |
| • 600/65R28 - T445762 | • 650/65R38 - T445738 |
| • 600/70R28 - T445763 | • 650/85R38 - T445743 |
| • 540/65R30 - T445728 | • 710/70R38 - T445744 |
| • 600/70R30 - T445726 | • 650/65R42 - T445727 |
| • 600/65R34 - T445729 | • 710/70R42 - T445725 |
| • 600/70R34 - T445730 | • 710/75R42 - T445722 |

# NOKIAN TYRES GROUND KING


## ALL SIZES

| Product code | Size      | LI/SS       | Reinforced code | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI  | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | M+S | Load capacity for tractor, kg |      |      |      |      |      |
|--------------|-----------|-------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|------------------|------------|-----|-------------------------------|------|------|------|------|------|
|              |           |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                  |            |     | Speed (km/h)                  |      |      |      |      |      |
|              |           |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                  |            |     | 45                            | 50   | 55   | 60   | 65   | 70   |
| T445733      | 420/70R28 | 144D (141E) | SB              | TL    | DW13  | DW14L, DW12    | 408        | 1352          | 620                       | 4102                       | 650  | 320            | 320                           | 46               | R-1W       | Yes | 2995                          | 2940 | 2885 | 2840 | 2800 | 2550 |
| T445764      | 480/65R28 | 148D (145E) | SB              | TL    | DW15L | DW14L          | 475        | 1348          | 617                       | 4091                       | 650  | 320            | 320                           | 45               | R-1W       | Yes | 3370                          | 3310 | 3245 | 3195 | 3150 | 2865 |
| T445735      | 480/70R28 | 151D (148E) | SB              | TL    | DW15L | DW16L, DW14L   | 471        | 1409          | 642                       | 4270                       | 675  | 320            | 320                           | 48               | R-1W       | Yes | 3690                          | 3625 | 3555 | 3500 | 3450 | 3140 |
| T445737      | 540/65R28 | 154D (151E) | SB              | TL    | DW18L | DW16L          | 536        | 1403          | 637                       | 4244                       | 675  | 320            | 320                           | 50               | R-1W       | Yes | 4015                          | 3940 | 3865 | 3805 | 3750 | 3415 |
| T445762      | 600/65R28 | 160D (156E) | SB              | TL    | DW20B | DW18L          | 600        | 1507          | 682                       | 4564                       | 700  | 320            | 320                           | 55               | R-1W       | Yes | 4815                          | 4725 | 4635 | 4570 | 4500 | 4095 |
| T445763      | 600/70R28 | 164D (160E) | SB              | TL    | DW20B | DW18L          | 601        | 1563          | 708                       | 4756                       | 725  | 320            | 320                           | 55               | R-1W       | Yes | 5350                          | 5250 | 5150 | 5075 | 5000 | 4550 |
| T445728      | 540/65R30 | 155D (152E) | SB              | TL    | DW18L | DW16L          | 535        | 1475          | 679                       | 4451                       | 700  | 320            | 320                           | 50               | R-1W       | Yes | 4145                          | 4070 | 3990 | 3935 | 3875 | 3525 |
| T445726      | 600/70R30 | 165D (161E) | SB              | TL    | DW20B | DW18L          | 600        | 1588          | 714                       | 4820                       | 750  | 320            | 320                           | 55               | R-1W       | Yes | 5510                          | 5410 | 5305 | 5225 | 5150 | 4685 |
| T445729      | 600/65R34 | 163D (159E) | SB              | TL    | DW20B | DW18L          | 600        | 1644          | 751                       | 5016                       | 775  | 320            | 320                           | 55               | R-1W       | Yes | 5215                          | 5120 | 5020 | 4950 | 4875 | 4435 |
| T445730      | 600/70R34 | 167D (163E) | SB              | TL    | DW20B | DW18L          | 594        | 1701          | 771                       | 5170                       | 800  | 320            | 320                           | 55               | R-1W       | Yes | 5830                          | 5725 | 5615 | 5530 | 5450 | 4960 |
| T445731      | 650/65R34 | 167D (164E) | SB              | TL    | DW20B |                | 632        | 1700          | 769                       | 5173                       | 825  | 320            | 320                           | 55               | R-1W       | Yes | 5830                          | 5725 | 5615 | 5530 | 5450 | 4960 |
| T445732      | 520/70R38 | 160D (157E) | SB              | TL    | DW16L | DW18L, DW15L   | 516        | 1752          | 803                       | 5342                       | 825  | 320            | 320                           | 55               | R-1W       | Yes | 4815                          | 4725 | 4635 | 4570 | 4500 | 4095 |
| T445734      | 580/70R38 | 166D (163E) | SB              | TL    | DW18L |                | 577        | 1829          | 835                       | 5574                       | 875  | 320            | 320                           | 56               | R-1W       | Yes | 5670                          | 5565 | 5460 | 5380 | 5300 | 4825 |
| T445765      | 600/65R38 | 165D (161E) | SB              | TL    | DW20B | DW18L          | 601        | 1745          | 798                       | 5321                       | 825  | 320            | 320                           | 55               | R-1W       | Yes | 5510                          | 5410 | 5305 | 5225 | 5150 | 4685 |
| T445738      | 650/65R38 | 169D (166E) | SB              | TL    | DW20B |                | 635        | 1820          | 827                       | 5540                       | 875  | 320            | 320                           | 59               | R-1W       | Yes | 6205                          | 6090 | 5975 | 5885 | 5800 | 5280 |
| T445743      | 650/85R38 | 178D (175E) | SB              | TL    | DW20B | DW21B, DW23B   | 645        | 2071          | 933                       | 6272                       | 975  | 320            | 320                           | 63               | R-1W       | Yes | 8025                          | 7875 | 7725 | 7615 | 7500 | 6825 |
| T445744      | 710/70R38 | 177D (174E) | SB              | TL    | DW23B | DW25B          | 705        | 1953          | 884                       | 5934                       | 925  | 320            | 320                           | 62               | R-1W       | Yes | 7810                          | 7665 | 7520 | 7410 | 7300 | 6645 |
| T445727      | 650/65R42 | 170D (167E) | SB              | TL    | DW20B |                | 634        | 1913          | 872                       | 5811                       | 925  | 320            | 320                           | 59               | R-1W       | Yes | 6420                          | 6300 | 6180 | 6090 | 6000 | 5460 |
| T445725      | 710/70R42 | 179D (175E) | SB              | TL    | DW23B |                | 706        | 2059          | 933                       | 6245                       | 975  | 320            | 320                           | 62               | R-1W       | Yes | 8295                          | 8140 | 7985 | 7865 | 7750 | 7055 |
| T445722      | 710/75R42 | 181D (178E) | SB              | TL    | DW23B |                | 703        | 2132          | 964                       | 6476                       | 1000 | 320            | 320                           | 62               | R-1W       | Yes | 8830                          | 8665 | 8500 | 8375 | 8250 | 7510 |

# NOKIAN TYRES HAKKAPELIITTA TRI

**A M+S BLOCK PATTERNED TIRE WITH  
SUPERIOR WINTER GRIP FOR YEAR-  
ROUND WORK IN BUILT ENVIRONMENTS**

- Safety and effectivity with siped M+S block pattern and all-season grip compound.
- High level comfort due to low noise and vibration design.
- Use economy in year round use with long service life tread compound and energy efficiency.



## AVAILABLE SIZES

- 250/75R16 - T845540
- 250/80R16 - T845541
- 340/80R18 - T445665
- 400/60R18 - T445667
- 400/70R18 - T445832
- 360/70R20 - T445756
- 360/80R20 - T445666
- 400/70R20 - T445636
- 300/80R24 - T445757
- 340/80R24 - T445753
- 360/80R24 - T445587
- 400/80R24 - T445582
- 420/65R24 - T445586
- 440/80R24 - T445634
- 460/70R24 - T445669
- 500/70R24 - T445671
- 540/70R24 - T445672
- 360/80R28 - T445752
- 400/80R28 - T445584
- 440/80R28 - T445563
- 540/65R28 - T445772
- 440/80R30 - T445758
- 480/80R30 - T445754
- 540/65R30 - T445609
- 540/65R30 - T445736
- 600/70R30 - T445848
- 440/80R34 - T445588
- 480/80R34 - T445583
- 600/70R34 - T445700
- 480/80R38 - T445585
- 540/80R38 - T445564
- 650/65R38 - T445773
- 650/65R42 - T445595
- 710/70R42 - T445847

# NOKIAN TYRES HAKKAPELIITTA TRI

## ALL SIZES FOR TRACTOR

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims               | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | M+S | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-----|-------------------------------------|------|------|------|------|------|
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                  |            |     | Speed (km/h)                        |      |      |      |      |      |
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                  |            |     | 40                                  | 45   | 50   | 55   | 60   | 65   |
| T845540      | 250/75R16 |                 | 120G         |                 | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 258        | 783           | 363                       | 2390                       | 370 | 450            | 450                           | 16               | R-4        | Yes | 1670                                | 1625 | 1565 | 1525 | 1495 | 1450 |
| T845541      | 250/80R16 | 7.5R16          | 119G         |                 | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 275        | 818           | 377                       | 2494                       | 390 | 450            | 450                           | 17               | R-4        | Yes | 1785                                | 1735 | 1675 | 1630 | 1595 | 1550 |
| T445667      | 400/60R18 |                 | 148A8 (143D) | SB              | TL    | 13    |                              | 400        | 950           | 427                       | 2870                       | 450 | 500            | 500                           | 26               | R-4        | Yes | 3135                                | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445756      | 360/70R20 |                 | 136A8 (131D) | SB              | TL    | W11   | 10, W10, 12, W12             | 343        | 1029          | 466                       | 3111                       | 475 | 320            | 320                           | 24               | R-4        | Yes | 2245                                | 2185 | 2105 | 2050 | 2010 | 1950 |
| T445757      | 300/80R24 | 11.2R24         | 133A8 (128D) | SB              | TL    | DW10  | W9, W10, W11, DW11           | 301        | 1077          | 492                       | 3260                       | 525 | 320            | 320                           | 24               | R-4        | Yes | 2070                                | 2015 | 1945 | 1890 | 1855 | 1800 |
| T445753      | 340/80R24 | 12.4R24         | 140A8 (135D) | SB              | TL    | DW11  | DW10, DW12                   | 333        | 1138          | 517                       | 3445                       | 550 | 320            | 320                           | 24               | R-4        | Yes | 2505                                | 2440 | 2355 | 2290 | 2245 | 2180 |
| T445587      | 360/80R24 | 13.6R24         | 143A8 (138D) | SB              | TL    | DW11  | DW10, DW12, DW13             | 357        | 1185          | 543                       | 3600                       | 575 | 320            | 320                           | 24               | R-4        | Yes | 2795                                | 2720 | 2625 | 2550 | 2505 | 2430 |
| T445582      | 400/80R24 | 14.9R24         | 149A8 (144D) | SB              | TL    | DW13  | DW12, DW14L                  | 399        | 1248          | 567                       | 3770                       | 600 | 320            | 320                           | 25               | R-4        | Yes | 3220                                | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445634      | 440/80R24 | 16.9R24         | 154A8 (149D) | SB              | TL    | DW14L | DW15L                        | 435        | 1294          | 585                       | 3921                       | 625 | 320            | 320                           | 26               | R-4        | Yes | 3740                                | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445752      | 360/80R28 | 13.6R28         | 146A8 (142D) | SB              | TL    | DW11  | DW12, DW13                   | 349        | 1311          | 595                       | 3998                       | 625 | 320            | 320                           | 24               | R-4        | Yes | 2960                                | 2885 | 2780 | 2705 | 2650 | 2575 |
| T445584      | 400/80R28 | 14.9R28         | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L                  | 400        | 1351          | 617                       | 4103                       | 650 | 320            | 320                           | 25               | R-4        | Yes | 3535                                | 3445 | 3320 | 3230 | 3165 | 3075 |
| T445563      | 440/80R28 | 16.9R28         | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 440        | 1414          | 640                       | 4285                       | 675 | 320            | 320                           | 26               | R-4        | Yes | 4085                                | 3975 | 3835 | 3730 | 3655 | 3550 |
| T445772      | 540/65R28 |                 | 160A8 (155D) | SB              | TL    | DW18L | DW16L                        | 535        | 1398          | 634                       | 4243                       | 675 | 320            | 320                           | 28               | R-4        | Yes | 4455                                | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445758      | 440/80R30 | 16.9R30         | 157A8 (153D) | SB              | TL    | DW14L | DW15L, W16L                  | 435        | 1455          | 657                       | 4426                       | 700 | 320            | 320                           | 26               | R-4        | Yes | 4200                                | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445754      | 480/80R30 | 18.4R30         | 162A8 (157D) | SB              | TL    | DW15L | DW16L, DW18L                 | 466        | 1536          | 692                       | 4671                       | 725 | 320            | 320                           | 27               | R-4        | Yes | 4745                                | 4620 | 4455 | 4330 | 4250 | 4125 |
| T445609      | 540/65R30 |                 | 161A8 (156D) | SB              | TL    | DW18L | DW16L                        | 530        | 1463          | 665                       | 4430                       | 700 | 320            | 320                           | 28               | R-4        | Yes | 4600                                | 4480 | 4320 | 4200 | 4120 | 4000 |
| T445736      | 540/65R30 |                 | 171A8 (166D) | SB              | TL    | DW18L | DW16L                        | 534        | 1460          | 667                       | 4442                       | 700 | 450            | 450                           | 28               | R-4        | Yes | 6095                                | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445848      | 600/70R30 |                 | 171A8 (166D) | SB              | TL    | DW20B | DW18L                        | 602        | 1581          | 709                       | 4772                       | 750 | 320            | 320                           | 30               | R-4        | Yes | 6095                                | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445588      | 440/80R34 | 16.9R34         | 159A8 (155D) | SB              | TL    | DW14L | DW15L, DW16L                 | 442        | 1570          | 718                       | 4763                       | 750 | 320            | 320                           | 26               | R-4        | Yes | 4455                                | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445583      | 480/80R34 | 18.4R34         | 164A8 (159D) | SB              | TL    | DW15L | DW16L, DW18L                 | 482        | 1631          | 744                       | 4964                       | 775 | 320            | 320                           | 27               | R-4        | Yes | 5030                                | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445700      | 600/70R34 |                 | 172A8 (168D) | SB              | TL    | DW20B | DW18L                        | 593        | 1676          | 755                       | 5102                       | 800 | 320            | 320                           | 28               | R-4        | Yes | 6440                                | 6270 | 6050 | 5880 | 5770 | 5600 |
| T445585      | 480/80R38 | 18.4R38         | 166A8 (161D) | SB              | TL    | DW15L | DW16L, DW18L                 | 477        | 1733          | 792                       | 5284                       | 825 | 320            | 320                           | 27               | R-4        | Yes | 5320                                | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445564      | 540/80R38 |                 | 172A8 (167D) | SB              | TL    | DW18L | DW16L                        | 556        | 1833          | 832                       | 5566                       | 875 | 320            | 320                           | 27               | R-4        | Yes | 6440                                | 6270 | 6050 | 5880 | 5770 | 5600 |
| T445773      | 650/65R38 |                 | 175A8 (170D) | SB              | TL    | DW20B | DW21B, DW23B                 | 625        | 1821          | 825                       | 5555                       | 875 | 320            | 320                           | 31               | R-4        | Yes | 6900                                | 6720 | 6480 | 6300 | 6180 | 6000 |
| T445595      | 650/65R42 |                 | 176A8 (171D) | SB              | TL    | DW20B | DW18L                        | 627        | 1912          | 871                       | 5836                       | 925 | 320            | 320                           | 31               | R-4        | Yes | 7075                                | 6890 | 6640 | 6460 | 6335 | 6150 |
| T445847      | 710/70R42 |                 | 185A8 (180D) | SB              | TL    | DW23B | DW25B                        | 704        | 2065          | 857                       | 6251                       | 975 | 320            | 320                           | 35               | R-4        | Yes | 9200                                | 8960 | 8640 | 8400 | 8240 | 8000 |


ALL SIZES FOR WHEEL LOADER

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims        | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|-----------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|-----|-------------------------------------|------|------|------|------|------|
|              |           |                 |              |                 |       |       |                       |            |               |                           |                            |     |                |                               |                  |            |                   |     | Speed (km/h)                        |      |      |      |      |      |
|              |           |                 |              |                 |       |       |                       |            |               |                           |                            |     |                |                               |                  |            |                   |     | 40                                  | 45   | 50   | 55   | 60   | 65   |
| T445665      | 340/80R18 | 12.5R18         | 143A8 (138D) | SB              | TL    | 11    | W11, 10, W10, 12, W12 | 328        | 1001          | 452                       | 3031                       | 475 | 400            | 400                           | 24               | R-4        |                   | Yes | 2715                                | 2645 | 2550 | 2480 | 2430 | 2360 |
| T445832      | 400/70R18 | 16.0/70R18      | 147A8 (143D) | SB              | TL    | 13    | W13, 12, W12          | 400        | 1018          | 458                       | 3068                       | 475 | 400            | 400                           | 26               | R-4        |                   | Yes | 3135                                | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445666      | 360/80R20 | 13.6R20         | 148A8 (143D) | SB              | TL    | 11    | W11, 10, W10, 12, W12 | 360        | 1093          | 493                       | 3311                       | 525 | 400            | 400                           | 24               | R-4        |                   | Yes | 3135                                | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445636      | 400/70R20 | 16.0/70R20      | 149A8 (144D) | SB              | TL    | 13    |                       | 394        | 1071          | 485                       | 3231                       | 500 | 400            | 400                           | 26               | R-4        |                   | Yes | 3220                                | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445586      | 420/65R24 |                 | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L, DW15L    | 402        | 1157          | 520                       | 3487                       | 550 | 400            | 400                           | 25               | R-4        | T55112            | Yes | 3450                                | 3360 | 3240 | 3150 | 3090 | 3000 |
| T445669      | 460/70R24 | 17.5LR24        | 166A8 (161D) | SB              | TL    | DW14L | DW15L                 | 460        | 1255          | 557                       | 3792                       | 600 | 500            | 500                           | 30               | R-4        | T55112            | Yes | 5320                                | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445671      | 500/70R24 | 19.5LR24        | 171A8 (166D) | SB              | TL    | DW16L | DW15L, DW18L          | 500        | 1314          | 580                       | 3971                       | 625 | 500            | 500                           | 30               | R-4        |                   | Yes | 6095                                | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445672      | 540/70R24 | 21LR24          | 175A8 (170D) | SB              | TL    | DW18L | DW16L                 | 540        | 1367          | 603                       | 4143                       | 650 | 500            | 500                           | 30               | R-4        |                   | Yes | 6900                                | 6720 | 6480 | 6300 | 6180 | 6000 |

# NOKIAN TYRES SOIL KING VF

## ADVANCED TRACTION TIRE WITH HIGHLY EFFICIENT GROUND CONTACT FOR HIGH-POWER TRACTORS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- Deep and extra wide pattern, provides big and powerful traction surface
- The center-zone pattern featuring extended and laterally supported lug tips balances behaviour and reduces loss of power on field and on road



## AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • VF540/65R28 - T445885 | • VF710/60R34 - T445864 |
| • VF600/65R28 - T445809 | • VF650/65R38 - T445884 |
| • VF600/70R28 - T445813 | • VF650/85R38 - T445808 |
| • VF540/65R30 - T445811 | • VF710/70R38 - T445812 |
| • VF600/60R30 - T445861 | • VF650/65R42 - T445810 |
| • VF600/70R30 - T445769 | • VF710/60R42 - T445873 |
| • VF600/70R34 - T445760 | • VF710/70R42 - T445768 |
| • VF650/60R34 - T445815 | • VF710/75R42 - T445759 |
| • VF650/65R34 - T445830 |                         |

# NOKIAN TYRES SOIL KING VF


## ALL SIZES

| Product code | Size        | LI/SS       | Reinforced code | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI  | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|-------------|-------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|------|----------------|-------------------------------|------------------|------------|------------------------|-------------------|------|------|------|------|------|
|              |             |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                  |            |                        | Speed (km/h)      |      |      |      |      |      |
|              |             |             |                 |       |       |                |            |               |                           |                            |      |                |                               |                  |            |                        | 40                | 50   | 55   | 60   | 65   | 70   |
| T445885      | VF540/65R28 | 157D (154E) | SB              | TL    | DW20B | DW18L, DW16L   | 558        | 1421          | 636                       | 4234                       | 675  | 200            | 280                           | 55               | R-1W       | 721                    | 4125              | 4125 | 4125 | 4125 | 4125 | 3755 |
| T445809      | VF600/65R28 | 163D (160E) | SB              | TL    | DW21B | DW20B, DW18L   | 604        | 1514          | 672                       | 4516                       | 700  | 200            | 280                           | 55               | R-1W       | 776                    | 4875              | 4875 | 4875 | 4875 | 4875 | 4435 |
| T445813      | VF600/70R28 | 167D (164E) | SB              | TL    | DW21B | DW20B, DW18L   | 614        | 1580          | 685                       | 4703                       | 725  | 200            | 280                           | 55               | R-1W       | 788                    | 5450              | 5450 | 5450 | 5450 | 5450 | 4960 |
| T445811      | VF540/65R30 | 158D (155E) | SB              | TL    | DW20B | DW18L, DW16L   | 558        | 1488          | 665                       | 4444                       | 700  | 200            | 280                           | 55               | R-1W       | 721                    | 4250              | 4250 | 4250 | 4250 | 4250 | 3870 |
| T445861      | VF600/60R30 | 162D (158E) | SB              | TL    | DW20B | DW21B, DW18L   | 588        | 1492          | 655                       | 4442                       | 700  | 200            | 280                           | 55               | R-1W       | 757                    | 4750              | 4750 | 4750 | 4750 | 4750 | 4325 |
| T445769      | VF600/70R30 | 168D (165E) | SB              | TL    | DW21B | DW18L, DW20B   | 615        | 1598          | 697                       | 4817                       | 750  | 200            | 280                           | 55               | R-1W       | 789                    | 5600              | 5600 | 5600 | 5600 | 5600 | 5095 |
| T445760      | VF600/70R34 | 170D (167E) | SB              | TL    | DW21B | DW20B, DW18L   | 613        | 1720          | 755                       | 5142                       | 800  | 200            | 280                           | 58               | R-1W       | 787                    | 6000              | 6000 | 6000 | 6000 | 6000 | 5460 |
| T445815      | VF650/60R34 | 168D (165E) | SB              | TL    | DW23B | DW21B, DW20B   | 658        | 1667          | 735                       | 4979                       | 775  | 200            | 280                           | 58               | R-1W       | 841                    | 5600              | 5600 | 5600 | 5600 | 5600 | 5095 |
| T445830      | VF650/65R34 | 170D (167E) | SB              | TL    | DW23B | DW21B, DW20B   | 660        | 1720          | 759                       | 5159                       | 825  | 200            | 280                           | 58               | R-1W       | 843                    | 6000              | 6000 | 6000 | 6000 | 6000 | 5460 |
| T445864      | VF710/60R34 | 173D (170E) | SB              | TL    | DW25B | DW24B          | 712        | 1728          | 760                       | 5169                       | 825  | 200            | 280                           | 58               | R-1W       | 905                    | 6500              | 6500 | 6500 | 6500 | 6500 | 5915 |
| T445884      | VF650/65R38 | 172D (169E) | SB              | TL    | DW23B | DW21B, DW20B   | 658        | 1835          | 823                       | 5509                       | 875  | 200            | 280                           | 59               | R-1W       | 841                    | 6300              | 6300 | 6300 | 6300 | 6300 | 5735 |
| T445808      | VF650/85R38 | 182D (179E) | SB              | TL    | DW23B | DW21B, DW20B   | 668        | 2064          | 900                       | 6190                       | 975  | 200            | 280                           | 63               | R-1W       | 853                    | 8500              | 8500 | 8500 | 8500 | 8500 | 7735 |
| T445812      | VF710/70R38 | 181D (178E) | SB              | TL    | DW25B | DW24B, DW23B   | 721        | 1959          | 862                       | 5885                       | 925  | 200            | 280                           | 63               | R-1W       | 916                    | 8250              | 8250 | 8250 | 8250 | 8250 | 7510 |
| T445810      | VF650/65R42 | 174D (170E) | SB              | TL    | DW23B | DW21B, DW20B   | 658        | 1923          | 855                       | 5770                       | 925  | 200            | 280                           | 59               | R-1W       | 841                    | 6700              | 6700 | 6700 | 6700 | 6700 | 6095 |
| T445873      | VF710/60R42 | 176D (173E) | SB              | TL    | DW25B | DW24B, DW23B   | 717        | 1930          | 861                       | 5796                       | 925  | 200            | 280                           | 63               | R-1W       | 911                    | 7100              | 7100 | 7100 | 7100 | 7100 | 6460 |
| T445768      | VF710/70R42 | 182D (179E) | SB              | TL    | DW25B | DW23B, DW24B   | 730        | 2075          | 906                       | 6274                       | 975  | 200            | 280                           | 63               | R-1W       | 927                    | 8500              | 8500 | 8500 | 8500 | 8500 | 7735 |
| T445759      | VF710/75R42 | 184D (181E) | SB              | TL    | DW25B | DW23B, DW24B   | 727        | 2150          | 943                       | 6448                       | 1000 | 200            | 280                           | 66               | R-1W       | 923                    | 9000              | 9000 | 9000 | 9000 | 9000 | 8190 |

# NOKIAN TYRES TRI 2

**A M+S BLOCK PATTERNED TIRE FOR  
WORK ON HARD GROUNDS AND ROADS  
IN ALL SEASONS**

- Use economy with durable long service life block pattern and energy efficiency.
- Reliable grip and comfortable handling also in varying weather conditions.
- Use of heavy implements enabled by high load capacity and strength of steel belted construction.



## AVAILABLE SIZES

- |                       |                       |
|-----------------------|-----------------------|
| • 250/75R16 - T845539 | • 440/80R28 - T445337 |
| • 250/80R16 - T845495 | • 480/65R28 - T445444 |
| • 340/80R18 - T445391 | • 540/65R28 - T445442 |
| • 360/70R20 - T445569 | • 440/80R30 - T445384 |
| • 360/80R20 - T445389 | • 480/80R30 - T445386 |
| • 300/80R24 - T445419 | • 540/65R30 - T445371 |
| • 340/80R24 - T445376 | • 600/70R30 - T445657 |
| • 360/80R24 - T445378 | • 440/80R34 - T445369 |
| • 400/80R24 - T445372 | • 480/80R34 - T445370 |
| • 420/65R24 - T445392 | • 600/65R34 - T445656 |
| • 440/80R24 - T445385 | • 480/80R38 - T445377 |
| • 460/65R24 - T445393 | • 540/80R38 - T445338 |
| • 500/70R24 - T445467 | • 600/65R38 - T445445 |
| • 540/65R24 - T445420 | • 650/65R38 - T445443 |
| • 320/85R28 - T445579 | • 620/80R42 - T445518 |
| • 360/80R28 - T445550 | • 650/65R42 - T445390 |
| • 400/80R28 - T445383 | • 710/70R42 - T445655 |

# NOKIAN TYRES TRI 2

## ALL SIZES

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims               | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|-----|-------------------------------------|------|------|------|------|------|
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                  |            |                   |     | Speed (km/h)                        |      |      |      |      |      |
|              |           |                 |              |                 |       |       |                              |            |               |                           |                            |     |                |                               |                  |            |                   |     | 40                                  | 45   | 50   | 55   | 60   | 65   |
| T845539      | 250/75R16 |                 | 120G         | SB              | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 258        | 783           | 363                       | 2390                       | 370 | 450            | 450                           | 16               | R-4        |                   | Yes | 1670                                | 1625 | 1565 | 1525 | 1495 | 1450 |
| T845495      | 250/80R16 | 7.5R16          | 119G         | SB              | TL    | 8     | W7, 7, 7J, W8, 8J, W9, 9, 9J | 274        | 818           | 377                       | 2494                       | 390 | 450            | 450                           | 17               | R-4        |                   | Yes | 1785                                | 1735 | 1675 | 1630 | 1595 | 1550 |
| T445391      | 340/80R18 | 12.5R18         | 143A8 (138D) | SB              | TL    | 11    | W11, 10, W10, 12, W12        | 341        | 1002          | 453                       | 3010                       | 475 | 400            | 400                           | 25               | R-4        |                   | Yes | 2715                                | 2645 | 2550 | 2480 | 2430 | 2360 |
| T445569      | 360/70R20 |                 | 136A8 (131D) | SB              | TL    | 11    | W11, 10, W10, 12, W12        | 341        | 1030          | 470                       | 3104                       | 500 | 320            | 320                           | 26               | R-4        |                   | Yes | 2245                                | 2185 | 2105 | 2050 | 2010 | 1950 |
| T445389      | 360/80R20 | 13.6R20         | 147A8 (143D) | SB              | TL    | 11    | W11, 10, W11, 12, W12        | 355        | 1095          | 495                       | 3286                       | 500 | 400            | 400                           | 26               | R-4        |                   | Yes | 3135                                | 3050 | 2945 | 2860 | 2805 | 2725 |
| T445419      | 300/80R24 | 11.2R24         | 133A8 (128D) | SB              | TL    | DW10  | W9, W10, W11, DW11           | 295        | 1090          | 502                       | 3297                       | 525 | 320            | 320                           | 24               | R-4        |                   | Yes | 2070                                | 2015 | 1945 | 1890 | 1855 | 1800 |
| T445376      | 340/80R24 | 12.4R24         | 140A8 (135D) | SB              | TL    | DW11  | DW10, DW12                   | 330        | 1154          | 521                       | 3487                       | 550 | 320            | 320                           | 25               | R-4        |                   | Yes | 2505                                | 2440 | 2355 | 2290 | 2245 | 2180 |
| T445378      | 360/80R24 | 13.6R24         | 143A8 (138D) | SB              | TL    | DW11  | DW10, DW12                   | 347        | 1184          | 539                       | 3574                       | 575 | 320            | 320                           | 26               | R-4        |                   | Yes | 2795                                | 2720 | 2625 | 2550 | 2505 | 2430 |
| T445372      | 400/80R24 | 14.9R24         | 149A8 (144D) | SB              | TL    | DW13  | DW12, DW14L                  | 395        | 1248          | 560                       | 3763                       | 600 | 320            | 320                           | 27               | R-4        | T55112            | Yes | 3220                                | 3135 | 3025 | 2940 | 2885 | 2800 |
| T445392      | 420/65R24 |                 | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14, DW15L            | 402        | 1155          | 525                       | 3493                       | 550 | 400            | 400                           | 26               | R-4        | T55112            | Yes | 3450                                | 3360 | 3240 | 3150 | 3090 | 3000 |
| T445385      | 440/80R24 | 16.9R24         | 154A8 (149D) | SB              | TL    | DW14L | DW15L                        | 432        | 1311          | 585                       | 3958                       | 625 | 320            | 320                           | 28               | R-4        | T55112            | Yes | 3740                                | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445393      | 460/65R24 |                 | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 439        | 1204          | 540                       | 3644                       | 575 | 400            | 400                           | 28               | R-4        | T55112            | Yes | 3970                                | 3865 | 3725 | 3625 | 3555 | 3450 |
| T445467      | 500/70R24 | 19.5LR24        | 164A8 (159D) | SB              | TL    | DW16L | DW15L, DW18L                 | 515        | 1307          | 585                       | 3958                       | 625 | 400            | 400                           | 28               | R-4        |                   | Yes | 5030                                | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445420      | 540/65R24 |                 | 158A8 (154D) | SB              | TL    | DW18L | DW16L                        | 546        | 1311          | 582                       | 3965                       | 625 | 320            | 320                           | 28               | R-4        |                   | Yes | 4200                                | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445579      | 320/85R28 | 12.4R28         | 141A8 (136D) | SB              | TL    | DW10  | W9, DW11, W10                | 312        | 1250          | 575                       | 3788                       | 600 | 320            | 320                           | 24               | R-4        |                   | Yes | 2645                                | 2575 | 2485 | 2415 | 2370 | 2300 |
| T445550      | 360/80R28 | 13.6R28         | 146A8 (142D) | SB              | TL    | DW11  | DW12, DW13                   | 353        | 1302          | 595                       | 3946                       | 625 | 320            | 320                           | 26               | R-4        |                   | Yes | 2960                                | 2885 | 2780 | 2705 | 2650 | 2575 |
| T445383      | 400/80R28 | 14.9R28         | 151A8 (146D) | SB              | TL    | DW13  | DW12, DW14L                  | 397        | 1351          | 620                       | 4078                       | 650 | 320            | 320                           | 27               | R-4        |                   | Yes | 3535                                | 3445 | 3320 | 3230 | 3165 | 3075 |
| T445337      | 440/80R28 | 16.9R28         | 156A8 (151D) | SB              | TL    | DW14L | DW15L, DW16L                 | 439        | 1413          | 644                       | 4266                       | 675 | 320            | 320                           | 28               | R-4        |                   | Yes | 4085                                | 3975 | 3835 | 3730 | 3655 | 3550 |
| T445444      | 480/65R28 |                 | 154A8 (149D) | SB              | TL    | DW15L | DW14L, DW16L                 | 464        | 1336          | 604                       | 4025                       | 650 | 320            | 320                           | 28               | R-4        | T55097            | Yes | 3740                                | 3640 | 3510 | 3415 | 3350 | 3250 |
| T445442      | 540/65R28 |                 | 160A8 (155D) | SB              | TL    | DW18L | DW16L                        | 540        | 1406          | 641                       | 4247                       | 675 | 320            | 320                           | 28               | R-4        | T545229           | Yes | 4455                                | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445384      | 440/80R30 | 16.9R30         | 157A8 (153D) | SB              | TL    | DW14L | DW15L, DW16L                 | 430        | 1464          | 660                       | 4448                       | 700 | 320            | 320                           | 28               | R-4        | T55371            | Yes | 4200                                | 4090 | 3940 | 3835 | 3760 | 3650 |
| T445386      | 480/80R30 | 18.4R30         | 162A8 (157D) | SB              | TL    | DW15L | DW16L, DW18L                 | 472        | 1526          | 683                       | 4636                       | 725 | 320            | 320                           | 29               | R-4        | T55371            | Yes | 4745                                | 4620 | 4455 | 4330 | 4250 | 4125 |
| T445371      | 540/65R30 |                 | 161A8 (156D) | SB              | TL    | DW18L | DW16L                        | 530        | 1460          | 644                       | 4401                       | 700 | 320            | 320                           | 30               | R-4        | T55371            | Yes | 4600                                | 4480 | 4320 | 4200 | 4120 | 4000 |
| T445657      | 600/70R30 |                 | 171A8 (166D) | SB              | TL    | DW20B | DW18L                        | 604        | 1564          | 702                       | 4756                       | 750 | 320            | 320                           | 32               | R-4        |                   | Yes | 6095                                | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445369      | 440/80R34 | 16.9R34         | 159A8 (155D) | SB              | TL    | DW14L | DW15L, DW16L                 | 430        | 1567          | 717                       | 4751                       | 750 | 320            | 320                           | 28               | R-4        | T55391            | Yes | 4455                                | 4340 | 4185 | 4070 | 3990 | 3875 |
| T445370      | 480/80R34 | 18.4R34         | 164A8 (159D) | SB              | TL    | DW15L | DW16L, DW18L                 | 472        | 1630          | 734                       | 4951                       | 775 | 320            | 320                           | 29               | R-4        | T55391            | Yes | 5030                                | 4900 | 4725 | 4595 | 4505 | 4375 |
| T445656      | 600/65R34 |                 | 169A8 (164D) | SB              | TL    | DW20B | DW18L                        | 595        | 1619          | 736                       | 4935                       | 775 | 320            | 320                           | 32               | R-4        |                   | Yes | 5750                                | 5600 | 5400 | 5250 | 5150 | 5000 |
| T445377      | 480/80R38 | 18.4R38         | 166A8 (161D) | SB              | TL    | DW15L | DW16L, DW18L                 | 466        | 1733          | 793                       | 5256                       | 825 | 320            | 320                           | 29               | R-4        |                   | Yes | 5320                                | 5180 | 4995 | 4855 | 4765 | 4625 |
| T445338      | 540/80R38 | 20.8R28         | 172A8 (167D) | SB              | TL    | DW18L | DW16L                        | 553        | 1825          | 834                       | 5523                       | 875 | 320            | 320                           | 30               | R-4        |                   | Yes | 6440                                | 6270 | 6050 | 5880 | 5770 | 5600 |

| Product code | Size      | Equivalent size | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | M+S | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|-----------------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------|-----|-------------------------------------|------|------|------|------|------|
|              |           |                 |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                  |            |                   |     | Speed (km/h)                        |      |      |      |      |      |
|              |           |                 |              |                 |       |       |                |            |               |                           |                            |     |                |                               |                  |            |                   |     | 40                                  | 45   | 50   | 55   | 60   | 65   |
| T445445      | 600/65R38 |                 | 170A8 (166D) | SB              | TL    | DW18L | DW20B          | 583        | 1740          | 790                       | 5290                       | 825 | 320            | 320                           | 30               | R-4        |                   | Yes | 6095                                | 5935 | 5725 | 5565 | 5460 | 5300 |
| T445443      | 650/65R38 |                 | 175A8 (170D) | SB              | TL    | DW20B | DW18L, DW23B   | 634        | 1811          | 819                       | 5510                       | 875 | 320            | 320                           | 33               | R-4        |                   | Yes | 6900                                | 6720 | 6480 | 6300 | 6180 | 6000 |
| T445518      | 620/80R42 |                 | 181A8 (177D) | SB              | TL    | DW20B | DW23B          | 626        | 2059          | 925                       | 6289                       | 975 | 320            | 320                           | 35               | R-4        |                   | Yes | 8395                                | 8175 | 7885 | 7665 | 7520 | 7300 |
| T445390      | 650/65R42 |                 | 176A8 (171D) | SB              | TL    | DW20B | DW18L, DW23B   | 617        | 1913          | 848                       | 5791                       | 925 | 320            | 320                           | 33               | R-4        |                   | Yes | 7075                                | 6890 | 6640 | 6460 | 6335 | 6150 |
| T445655      | 710/70R42 |                 | 185A8 (180D) | SB              | TL    | DW23B |                | 717        | 2045          | 923                       | 6255                       | 975 | 320            | 320                           | 37               | R-4        |                   | Yes | 9200                                | 8960 | 8640 | 8400 | 8240 | 8000 |


# NOKIAN TYRES TRI STEEL

## PUNCTURE PROTECTION FOR SPECIAL APPLICATIONS

- A special loader tire with a puncture-resisting block pattern.
- Steel fortification for extra durability.
- Suitable for waste treatment, recycling plants and for industrial use.



2026-03-04



## AVAILABLE SIZES

- 460/65R24 - T445245
- 480/65R24 - T445222

# NOKIAN TYRES TRI STEEL

## ALL SIZES

| Product code | Size      | LI/SS        | TL/TT | Rim   | Permitted rims                       | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|--------------|-------|-------|--------------------------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|------------|-------------------------------------|------|------|------|------|------|
|              |           |              |       |       |                                      |            |               |                           |                            |     |                |                               |                  |            | Speed (km/h)                        |      |      |      |      |      |
|              |           |              |       |       |                                      |            |               |                           |                            |     |                |                               |                  |            | 40                                  | 45   | 50   | 55   | 60   | 65   |
| T445245      | 460/65R24 | 156A8 (151D) | TL    | DW13  | W13, DW13L, W14L, DW14L, W15L, DW15L | 468        | 1208          | 545                       | 3581                       | 575 | 400            | 400                           | 27               | R-4        | 3970                                | 3865 | 3725 | 3625 | 3555 | 3450 |
| T445222      | 480/65R24 | 151A8 (146D) | TL    | DW14L | W14L, W15L, DW15L, W16L, DW16L       | 488        | 1234          | 565                       | 3740                       | 600 | 320            | 320                           | 28               | R-4        | 3450                                | 3360 | 3240 | 3150 | 3090 | 3000 |


# NOKIAN TYRES COUNTRY KING

## EFFICIENT RADIAL FLOTATION TIRE FOR AGRICULTURAL TRANSPORTATIONS ON ROAD AND FIELD

- Durability and low rolling resistance due to high positive pattern ratio and special tread compound.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.



2026-03-04



### AVAILABLE SIZES

- 500/60R22.5 - T445453
- 560/45R22.5 - T445402
- 560/60R22.5 - T445401
- 580/65R22.5 - T445405
- 600/50R22.5 - T445441
- 650/50R22.5 - T445407
- 710/35R22.5 - T445542
- 710/45R22.5 - T445496
- 600/55R26.5 - T445653
- 620/60R26.5 - T445404
- 650/65R26.5 - T445440
- 710/50R26.5 - T445406
- 800/45R26.5 - T445600
- 650/65R30.5 - T445611
- 750/60R30.5 - T445610

# NOKIAN TYRES COUNTRY KING

## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims   | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg |       |      |      |      |      |
|--------------|-------------|-------|-----------------|-------|---------|------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|-------------------|-----------------------------|-------|------|------|------|------|
|              |             |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                  |                   | Speed (km/h)                |       |      |      |      |      |
|              |             |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                  |                   | 40                          | 45    | 50   | 55   | 60   | 65   |
| T445453      | 500/60R22.5 | 155D  | SB              | TL    | AG16.00 |                  | 510        | 1172          | 521                       | 3581                       | 550 | 400            | 400                           | 17               | T55096            | 5270                        | 5000  | 4690 | 4420 | 4145 | 3875 |
| T445402      | 560/45R22.5 | 152D  | SB              | TL    | AG16.00 |                  | 538        | 1078          | 474                       | 3280                       | 525 | 400            | 400                           | 16               | T56435            | 4830                        | 4580  | 4295 | 4045 | 3800 | 3550 |
| T445401      | 560/60R22.5 | 161D  | SB              | TL    | AG16.00 | AG18.00, AG20.00 | 567        | 1237          | 557                       | 3764                       | 600 | 400            | 400                           | 18               | T55089            | 6290                        | 5965  | 5595 | 5275 | 4950 | 4625 |
| T445405      | 580/65R22.5 | 166D  | SB              | TL    | AG16.00 | AG18.00          | 584        | 1299          | 586                       | 3977                       | 625 | 400            | 400                           | 19               | T55089            | 7210                        | 6835  | 6415 | 6040 | 5670 | 5300 |
| T445441      | 600/50R22.5 | 159D  | SB              | TL    | AG20.00 |                  | 594        | 1170          | 533                       | 3575                       | 550 | 400            | 400                           | 18               | T55089            | 5950                        | 5645  | 5295 | 4990 | 4680 | 4375 |
| T445407      | 650/50R22.5 | 163D  | SB              | TL    | AG20.00 |                  | 644        | 1235          | 564                       | 3789                       | 575 | 400            | 400                           | 18               | T55089            | 6630                        | 6290  | 5900 | 5560 | 5215 | 4875 |
| T445542      | 710/35R22.5 | 157D  | SB              | TL    | AG24.00 |                  | 696        | 1070          | 484                       | 3248                       | 525 | 400            | 400                           | 22               |                   | 5610                        | 5320  | 4990 | 4705 | 4415 | 4125 |
| T445496      | 710/45R22.5 | 165D  | SB              | TL    | AG24.00 |                  | 697        | 1213          | 545                       | 3695                       | 575 | 400            | 400                           | 19               | T55092            | 7005                        | 6645  | 6230 | 5870 | 5510 | 5150 |
| T445653      | 600/55R26.5 | 165D  | SB              | TL    | AG20.00 |                  | 603        | 1335          | 604                       | 4072                       | 625 | 400            | 400                           | 22               | T55098            | 7005                        | 6645  | 6230 | 5870 | 5510 | 5150 |
| T445404      | 620/60R26.5 | 169D  | SB              | TL    | AG20.00 |                  | 632        | 1403          | 639                       | 4291                       | 675 | 400            | 400                           | 20               | T55098            | 7890                        | 7480  | 7020 | 6610 | 6205 | 5800 |
| T445440      | 650/65R26.5 | 174D  | SB              | TL    | AG20.00 |                  | 656        | 1519          | 689                       | 4656                       | 725 | 400            | 400                           | 20               | T55102            | 9110                        | 8645  | 8105 | 7640 | 7170 | 6700 |
| T445406      | 710/50R26.5 | 170D  | SB              | TL    | AG24.00 |                  | 740        | 1405          | 646                       | 4304                       | 650 | 400            | 400                           | 21               | T55102            | 8365                        | 7935  | 7440 | 7010 | 6580 | 6150 |
| T445600      | 800/45R26.5 | 174D  | SB              | TL    | AG28.00 | AG24.00          | 769        | 1394          | 622                       | 4240                       | 675 | 400            | 400                           | 26               | T55102            | 9110                        | 8645  | 8105 | 7640 | 7170 | 6700 |
| T445611      | 650/65R30.5 | 176D  | SB              | TL    | AG20.00 |                  | 647        | 1623          | 737                       | 4969                       | 775 | 400            | 400                           | 26               |                   | 9655                        | 9160  | 8590 | 8095 | 7595 | 7100 |
| T445610      | 750/60R30.5 | 181D  | SB              | TL    | AG24.00 |                  | 760        | 1679          | 757                       | 5144                       | 800 | 400            | 400                           | 26               |                   | 11220                       | 10645 | 9985 | 9405 | 8830 | 8250 |


# NOKIAN TYRES COUNTRY KING G2

## PREMIUM FLOTATION TIRE FOR HIGH-PERFORMANCE AGRICULTURAL TRANSPORT

- Deep tread offers long-lasting performance and excellent value in transport use
- Dual-purpose tread pattern design delivers performance and reduces loss of power on both on-road transport and field conditions
- Large pattern contact and rounded shoulder design for advanced soil and crop damage prevention



2026-03-04



### AVAILABLE SIZES

- 560/60R22.5 - T445876
- 600/50R22.5 - T445877
- 650/50R22.5 - T445878
- 710/45R22.5 - T445879
- VF600/55R26.5 - T445880
- VF620/60R26.5 - T445888
- VF650/55R26.5 - T445881

# NOKIAN TYRES COUNTRY KING G2


## ALL SIZES

| Product code | Size          | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims   | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Load capacity for mixed, kg |      |      |      |      |      |
|--------------|---------------|-------|-----------------|-------|---------|------------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|-----------------------------|------|------|------|------|------|
|              |               |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                  | Speed (km/h)                |      |      |      |      |      |
|              |               |       |                 |       |         |                  |            |               |                           |                            |     |                |                               |                  | 40                          | 45   | 50   | 55   | 60   | 65   |
| T445876      | 560/60R22.5   | 161D  | SB              | TL    | AG18.00 | AG16.00, AG20.00 | 560        | 1254          | 570                       | 3814                       | 600 | 400            | 400                           | 22               | 6290                        | 5965 | 5595 | 5275 | 4950 | 4625 |
| T445877      | 600/50R22.5   | 159D  | SB              | TL    | AG20.00 |                  | 613        | 1171          | 533                       | 3567                       | 550 | 400            | 400                           | 22               | 5950                        | 5645 | 5295 | 4990 | 4680 | 4375 |
| T445878      | 650/50R22.5   | 163D  | SB              | TL    | AG20.00 |                  | 644        | 1231          | 557                       | 3744                       | 575 | 400            | 400                           | 22               | 6630                        | 6290 | 5900 | 5560 | 5215 | 4875 |
| T445879      | 710/45R22.5   | 165D  | SB              | TL    | AG24.00 |                  | 733        | 1221          | 551                       | 3723                       | 575 | 400            | 400                           | 22               | 7005                        | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445880      | VF600/55R26.5 | 167D  | SB              | TL    | AG20.00 |                  | 620        | 1353          | 596                       | 4104                       | 625 | 280            | 400                           | 24               | 7030                        | 6705 | 6375 | 6050 | 5775 | 5450 |
| T445888      | VF620/60R26.5 | 171D  | SB              | TL    | AG20.00 |                  | 621        | 1439          | 631                       | 4366                       | 650 | 280            | 400                           | 24               | 7935                        | 7565 | 7195 | 6825 | 6520 | 6150 |
| T445881      | VF650/55R26.5 | 171D  | SB              | TL    | AG20.00 |                  | 653        | 1411          | 615                       | 4281                       | 650 | 280            | 400                           | 24               | 7935                        | 7565 | 7195 | 6825 | 6520 | 6150 |

# NOKIAN TYRES CT

## EARTHMOVING GRADE RADIAL FLOTATION TIRE FOR HEAVY TRANSPORTATIONS

- Exceptional mileage provided by dense and thick heavy-duty block pattern.
- Special puncture damage resistance with three layers of steel reinforcements in the tread area.
- Stable load-bearing provided by the extra-strength multilayer construction.



### AVAILABLE SIZES

- 560/60R22.5 - T445626
- 600/50R22.5 - T445627
- 600/55R26.5 - T445782
- 650/55R26.5 - T445556
- 600/60R30.5 - T445629

# NOKIAN TYRES CT

## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg |      |      |      |      |      |
|--------------|-------------|-------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|-------------------|-----------------------------|------|------|------|------|------|
|              |             |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                  |                   | Speed (km/h)                |      |      |      |      |      |
|              |             |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                  |                   | 40                          | 45   | 50   | 55   | 60   | 65   |
| T445626      | 560/60R22.5 | 165D  | SB              | TL    | AG18.00 | AG16.00        | 560        | 1245          | 555                       | 3811                       | 600 | 500            | 500                           | 22               | T55098            | 7005                        | 6645 | 6230 | 5870 | 5510 | 5150 |
| T445627      | 600/50R22.5 | 163D  | SB              | TL    | AG20.00 |                | 597        | 1173          | 528                       | 3574                       | 550 | 500            | 500                           | 22               | T55089            | 6630                        | 6290 | 5900 | 5560 | 5215 | 4875 |
| T445782      | 600/55R26.5 | 173D  | SB              | TL    | AG20.00 |                | 603        | 1335          | 612                       | 4098                       | 625 | 600            | 600                           | 24               | T55098            | 8840                        | 8385 | 7865 | 7410 | 6955 | 6500 |
| T445556      | 650/55R26.5 | 177D  | SB              | TL    | AG20.00 | AG22.00        | 632        | 1389          | 635                       | 4265                       | 725 | 600            | 600                           | 27               | T55098            | 9930                        | 9415 | 8835 | 8320 | 7810 | 7300 |
| T445629      | 600/60R30.5 | 173D  | SB              | TL    | AG20.00 |                | 606        | 1497          | 681                       | 4570                       | 725 | 500            | 500                           | 26               | T55098            | 8840                        | 8385 | 7865 | 7410 | 6955 | 6500 |


# NOKIAN TYRES ELS

## RADIAL TRACTION FLOTATION TIRE FOR AGRICULTURAL OPERATIONS IN CHALLENGING SOIL CONDITIONS

- Reliable grip due to open, well cleaning traction pattern.
- Soil and crop damage prevention with large pattern contact and rounded shoulder design.
- Directional stability and controlled handling performance with high strength steel belted construction.



2026-03-04



### AVAILABLE SIZES

- 600/50R22.5 - T445292
- 600/50R22.5 - T445708
- 710/45R22.5 - T445659
- 600/55R26.5 - T445654
- 650/65R26.5 - T445465
- 700/50R26.5 - T445641
- 750/55R26.5 - T445601
- 850/50R30.5 - T445499
- 710/55R34 - T445470
- 800/50R34 - T445469
- 800/60R34 - T445500

# NOKIAN TYRES ELS


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims      | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for mixed, kg |       |       |       |       |      |
|--------------|-------------|-------|-----------------|-------|---------|---------------------|------------|---------------|---------------------------|-----------------------------|-----|----------------|-------------------------------|------------------|-------------------|-----------------------------|-------|-------|-------|-------|------|
|              |             |       |                 |       |         |                     |            |               |                           |                             |     |                |                               |                  |                   | Speed (km/h)                |       |       |       |       |      |
|              |             |       |                 |       |         |                     |            |               |                           |                             |     |                |                               |                  |                   | 40                          | 45    | 50    | 55    | 60    | 65   |
| T445292      | 600/50R22.5 | 156D  |                 | TL    | AG20.00 | 20.00               | 625        | 1172          | 531                       | 3563                        | 550 | 360            | 360                           | 19               |                   | 5440                        | 5160  | 4840  | 4560  | 4280  | 4000 |
| T445708      | 600/50R22.5 | 159D  | SB              | TL    | AG20.00 |                     | 600        | 1164          | 523                       | 3555                        | 550 | 400            | 400                           | 19               | T55089            | 5950                        | 5645  | 5295  | 4990  | 4680  | 4375 |
| T445659      | 710/45R22.5 | 165D  | SB              | TL    | AG24.00 |                     | 691        | 1204          | 538                       | 3678                        | 575 | 400            | 400                           | 20               | T55092            | 7005                        | 6645  | 6230  | 5870  | 5510  | 5150 |
| T445654      | 600/55R26.5 | 165D  | SB              | TL    | AG20.00 |                     | 594        | 1329          | 596                       | 4072                        | 625 | 400            | 400                           | 22               | T55098            | 7005                        | 6645  | 6230  | 5870  | 5510  | 5150 |
| T445465      | 650/65R26.5 | 174D  | SB              | TL    | AG20.00 |                     | 646        | 1514          | 680                       | 4618                        | 725 | 400            | 400                           | 24               | T55102            | 9110                        | 8645  | 8105  | 7640  | 7170  | 6700 |
| T445641      | 700/50R26.5 | 170D  | SB              | TL    | AG24.00 | AG20.00             | 685        | 1369          | 615                       | 4198                        | 650 | 400            | 400                           | 22               | T55099            | 8160                        | 7740  | 7260  | 6840  | 6420  | 6000 |
| T445601      | 750/55R26.5 | 177D  | SB              | TL    | AG24.00 |                     | 738        | 1493          | 670                       | 4555                        | 700 | 400            | 400                           | 24               | T55102            | 9930                        | 9415  | 8835  | 8320  | 7810  | 7300 |
| T445499      | 850/50R30.5 | 182D  | SB              | TL    | AG28.00 | AG27.00, AG30.00    | 881        | 1625          | 734                       | 4936                        | 775 | 400            | 400                           | 27               |                   | 11560                       | 10965 | 10285 | 9690  | 9095  | 8500 |
| T445470      | 710/55R34   | 177D  | SB              | TL    | DW24B   | DW20B, DW23B        | 707        | 1641          | 748                       | 4995                        | 775 | 400            | 400                           | 26               | T55394            | 9930                        | 9415  | 8835  | 8320  | 7810  | 7300 |
| T445469      | 800/50R34   | 181D  | SB              | TL    | DW25B   | DW23B, DW24B, DW28B | 791        | 1639          | 741                       | 4988                        | 800 | 400            | 400                           | 26               | T55394            | 11220                       | 10645 | 9985  | 9405  | 8830  | 8250 |
| T445500      | 800/60R34   | 186D  | SB              | TL    | DW25B   | DW23B, DW24B, DW28B | 799        | 1813          | 813                       | 5542                        | 875 | 400            | 400                           | 30               |                   | 12920                       | 12255 | 11495 | 10830 | 10165 | 9500 |

# NOKIAN TYRES FLOAT KING VF

## NEXT-LEVEL FLOTATION FOR HIGH-CAPACITY AGRICULTURAL TRAILERS AND TANKERS IN FARMING

- Flexforce VF construction combines strength with high flexibility to produce an effective XXL-sized ground contact
- The grip pattern works great in challenging soil conditions and on road
- The center-zone pattern with continuous contact balances behaviour and reduces loss of power on field and on road



### AVAILABLE SIZES

- VF750/60R30.5 - T445739
- VF710/55R34 - T445818
- VF850/50R30.5 - T445821
- VF800/50R34 - T445820
- VF800/60R32 - T445819



# NOKIAN TYRES FLOAT KING VF

## ALL SIZES

| Product code | Size          | LI/SS | Reinforced code | TL/TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Load capacity for mixed, kg |       |       |       |       |       |
|--------------|---------------|-------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|-----------------------------|-------|-------|-------|-------|-------|
|              |               |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                  | Speed (km/h)                |       |       |       |       |       |
|              |               |       |                 |       |         |                |            |               |                           |                            |     |                |                               |                  | 40                          | 45    | 50    | 55    | 60    | 65    |
| T445739      | VF750/60R30.5 | 183D  | SB              | TL    | AG24.00 |                | 762        | 1686          | 719                       | 5143                       | 800 | 280            | 280                           | 28               | 11290                       | 10765 | 10240 | 9715  | 9275  | 8750  |
| T445821      | VF850/50R30.5 | 184D  | SB              | TL    | AG28.00 |                | 884        | 1653          | 710                       | 5015                       | 775 | 280            | 280                           | 28               | 11610                       | 11070 | 10530 | 9990  | 9540  | 9000  |
| T445819      | VF800/60R32   | 188D  | SB              | TL    | DW27B   | DW25B          | 834        | 1804          | 779                       | 5487                       | 850 | 280            | 280                           | 28               | 12900                       | 12300 | 11700 | 11100 | 10600 | 10000 |
| T445818      | VF710/55R34   | 179D  | SB              | TL    | DW23B   | DW24B          | 728        | 1672          | 734                       | 5097                       | 775 | 280            | 280                           | 28               | 10000                       | 9535  | 9070  | 8605  | 8215  | 7750  |
| T445820      | VF800/50R34   | 183D  | SB              | TL    | DW25B   | DW24B, DW28B   | 806        | 1690          | 732                       | 5138                       | 800 | 280            | 280                           | 28               | 11290                       | 10765 | 10240 | 9715  | 9275  | 8750  |

# UNDERGROUND MINING TIRES

## DRILL RIGS AND OTHER MINING MACHINES

**59**

**Nokian Tyres  
Armor Gard 2  
Mine**

**61**

**Nokian Tyres  
MINE KING E-4**

## UNDERGROUND LOADER

**63**

**Nokian Tyres  
MINE KING  
L-5S**

**65**

**Nokian Tyres  
MINE L-3S**

## WHEEL LOADER


**67**

**Nokian Tyres  
Nordman MINE  
E-4**

# NOKIAN TYRES ARMOR GARD 2 MINE

**STRONG TIRE FOR DRILL RIGS WITH MINING COMPOUND AND IMPROVED, WIDER TREAD**

- New, improved tread lowers the contact pressure and improves service life, providing excellent cut resistance.
- Stable, accurate driving response for predictable handling and a high load-bearing capacity.
- Groove depth indicator helps monitor your tire condition.



## AVAILABLE SIZES

- 9.00-20 - T445836
- 10.00-20 - T445770

# NOKIAN TYRES ARMOR GARD 2 MINE


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|----------|-------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|------|------|------|------|------|
|              |          |       |            |       |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |      |      |      |      |      |
|              |          |       |            |       |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                 | 1    | 5    | 10   | 20   | 25   |
| T445836      | 9.00-20  | 162A5 | 16         | TT    | 7.0 | 7.5            | 270        | 1040          | 479                       | 3135                       | 1000           | 1000                          | 18.5             | E-2        | T52520            | 311                    | 7175              | 6175 | 6175 | 6175 | 4750 | 4750 |
| T445770      | 10.00-20 | 164A5 | 16         | TT    | 7.5 | 8.0            | 285        | 1069          | 484                       | 3209                       | 900            | 900                           | 21               | E-2        | T52620            | 334                    | 7550              | 6500 | 6500 | 6500 | 5000 | 5000 |

# NOKIAN TYRES MINE KING E-4

## PURPOSE DESIGNED AND BUILT SPECIAL TIRE FOR DRILL RIGS AND UTILITY VEHICLES

- Strong carcass with a maximum operating pressure of 10 bars, giving a solid foundation for your drill rig.
- Deep grooves with a solid middle section for good puncture resistance and a long tire service life.
- Sharp shoulders and large contact area for better grip.



## AVAILABLE SIZES

- 12.00-20 - T445712
- 14.00-24 - T445709
- 14.00-20 - T445617

# NOKIAN TYRES MINE KING E-4

## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |       |       |      |      |      |
|--------------|----------|-------|------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|-------|-------|------|------|------|
|              |          |       |            |       |         |                |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |       |       |      |      |      |
|              |          |       |            |       |         |                |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                 | 1     | 5     | 10   | 20   | 25   |
| T445712      | 12.00-20 | 176A5 | 20         | TT    | 8.5     | 9.0, 8.0       | 330        | 1147          | 520                       | 3449                       | 1000           | 1000                          | 35               | E-4        | T52810            | 378                    | 10720             | 9230  | 9230  | 9230 | 7100 | 7100 |
| T445617      | 14.00-20 | 185A2 | 20         | TT    | 10.0    | 9.0            | 372        | 1225          | 560                       | 3669                       | 1000           | 1000                          | 40               | E-4        | T52920            | 450                    | 12025             | 10545 | 9250  | 8050 | 7770 | 7400 |
| T445709      | 14.00-24 | 188A2 | 28         | TL    | 10.00WA | 10.00VA        | 383        | 1391          | 631                       | 4153                       | 925            | 1000                          | 46               | E-4        | T55767            | 450                    | 13000             | 11400 | 10000 | 8700 | 8400 | 8000 |


# NOKIAN TYRES MINE KING L-5S

## FOR EXTREME UNDERGROUND LOADING APPLICATIONS

- More strengthening layers to ensure tire safety in demanding applications.
- High load capacity, enabling use in heavier, more effective machines.
- Cut and crack resistant tread provides a long service life.



2025-03-04



## AVAILABLE SIZES

- 12.00-20 - T445544
- 17.5-25 - T445540
- 17.5-25 - T445580
- 18.00-25 - T445545
- 26.5-25 - T445546
- 29.5-29 - T445547

# NOKIAN TYRES MINE KING L-5S


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                 | 1     | 5     | 10    |
| T445544      | 12.00-20 | 173A2 | 20         | TT    | 8.5       | 9.0                     | 342        | 1179          | 550                       | 3582                       | 850            | 1000                          | 36               | L-5S       | T52810            | 378                    | 10400             | 8450  | 7410  | 6500  |
| T445540      | 17.5-25  | 184A2 | 24         | TL    | 14.00/1.5 | 14.00/1.3               | 445        | 1400          | 661                       | 4291                       | 675            | 800                           | 66               | L-5S       | T55867            | 534                    | 14400             | 11700 | 10260 | 9000  |
| T445580      | 17.5-25  | 188A2 | 34         | TL    | 14.00/1.5 | 14.00/1.3               | 454        | 1416          | 663                       | 4307                       | 800            | 1000                          | 66               | L-5S       | T55867            | 534                    | 16000             | 13000 | 11400 | 10000 |
| T445545      | 18.00-25 | 202A2 | 32         | TL    | 13.00/2.5 | 15.00/2.5, 13.00/2.5 IF | 526        | 1675          | 772                       | 5120                       | 750            | 800                           | 79               | L-5S       | T55831            | 598                    | 24000             | 19500 | 17100 | 15000 |
| T445546      | 26.5-25  | 209A2 | 36         | TL    | 22.00/3.0 | 22.00/3.0IF             | 683        | 1791          | 829                       | 5504                       | 625            | 800                           | 90               | L-5S       |                   | 808                    | 29600             | 24050 | 21090 | 18500 |
| T445547      | 29.5-29  | 218A2 | 40         | TL    | 25.00/3.5 | 24.00/3.5               | 767        | 2020          | 925                       | 6145                       | 625            | 800                           | 98               | L-5S       |                   | 900                    | 37760             | 30680 | 26905 | 23600 |

# NOKIAN TYRES MINE L-3S

**THE FIRST UNDERGROUND LOADER TIRE  
THAT IS READY FOR PROTECTIVE  
CHAINS**

- Strong, stable tire for extreme conditions.
- Supports the chains in an optimal way and can be set instantly – no modification is needed.
- With chains compatible with the chainless L-5S tires.



## AVAILABLE SIZES

- 26.5-25 - T445522

# NOKIAN TYRES MINE L-3S


## ALL SIZES

| Product code | Size    | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg |       |       |       |
|--------------|---------|-------|------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|------------------------|-------------------|-------|-------|-------|
|              |         |       |            |       |           |                |            |               |                           |                            |                |                               |                  |            |                        | Speed (km/h)      |       |       |       |
|              |         |       |            |       |           |                |            |               |                           |                            |                |                               |                  |            |                        | 0                 | 1     | 5     | 10    |
| T445522      | 26.5-25 | 209A2 | 36         | TL    | 22.00/3.0 | 22.00/3.0IF    | 660        | 1706          | 775                       | 5136                       | 625            | 800                           | 42               | L-3S       | 808                    | 29600             | 24050 | 21090 | 18500 |

# NOKIAN TYRES NORDMAN MINE E-4

## DURABILITY FOR ARTICULATED DUMP TRUCKS

- Durable radial all-steel structure
- Excellent choice for rough conditions in quarries
- Cost effective mine tire - EUR/h



## AVAILABLE SIZES

- 26.5R25 - T845483
- 29.5R25 - T845482

# NOKIAN TYRES NORDMAN MINE E-4

## ALL SIZES

| Product code | Size    | LI/SS        | TL/TT | Rim       | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg |       |       |       |       |       |
|--------------|---------|--------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|------------------------|-------------------|-------|-------|-------|-------|-------|
|              |         |              |       |           |                |            |               |                           |                            |                |                               |                  |            |                        | Speed (km/h)      |       |       |       |       |       |
|              |         |              |       |           |                |            |               |                           |                            |                |                               |                  |            |                        | 20                | 25    | 30    | 35    | 40    | 50    |
| T845483      | 26.5R25 | 209A2 (193B) | TL    | 22.00/3.0 | 22.00/3.0IF    | 682        | 1798          | 769                       | 5353                       | 575            | 700                           | 55               | E-4        | 808                    | 15540             | 14800 | 14245 | 13690 | 12950 | 11655 |
| T845482      | 29.5R25 | 216A2 (200B) | TL    | 25.00/3.5 | 25.00/3.5IF    | 768        | 1921          | 817                       | 5749                       | 575            | 700                           | 60               | E-4        | 900                    | 18815             | 17920 | 17250 | 16575 | 15680 | 14110 |

# PORTS AND TERMINALS TIRES

## REACH STACKER



70  
Nokian Tyres  
HTS G2 E-4



72  
Nokian Tyres  
HTS G2 L-4S

## WHEELED EXCAVATOR



82  
Nokian Tyres  
Armor Gard 2

## REACH STACKER LOAD AXLE USE



74  
Nokian Tyres  
HTS G2 L-5S

## FORK LIFT



76  
Nokian Tyres  
Armor Gard

## RTG



78  
Nokian Tyres  
RTG

## TERMINAL TRACTOR




80  
Nokian Tyres  
HTS Tugger

# NOKIAN TYRES HTS G2 E-4

**KEEP THE GOODS MOVING –  
EFFICIENTLY AND ECONOMICALLY**

- Supported blocks with chamfered edges improve tire cooling and turning properties.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 14.00-24 - T445710
- 16.00-25 - T445711
- 18.00-25 - T445637
- 18.00-33 - T445662

# NOKIAN TYRES HTS G2 E-4


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)                     |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                                | 1     | 5     | 10    | 20    | 25    |
| T445710      | 14.00-24 | 188A5 | 28         | TL    | 10.00WA   | 10.00VA                 | 390        | 1397          | 640                       | 4197                       | 1000           | 1000                          | 48               | E-4        | T55767            | 450                    | 15000                            | 13000 | 13000 | 13000 | 13000 | 13000 |
| T445711      | 16.00-25 | 199A5 | 36         | TL    | 11.25/2.0 | 11.25/2.0 IF, 13.00/2.0 | 453        | 1537          | 694                       | 4606                       | 1000           | 1000                          | 57               | E-4        | T55810            | 518                    | 20400                            | 17680 | 17680 | 17680 | 17680 | 17680 |
| T445637      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 538        | 1667          | 765                       | 5100                       | 1000           | 1000                          | 58               | E-4        | T55831            | 598                    | 26250                            | 22750 | 22750 | 22750 | 22750 | 22750 |
| T445662      | 18.00-33 | 214A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF            | 512        | 1866          | 849                       | 5649                       | 1000           | 1000                          | 70               | E-4        |                   | 598                    | 31800                            | 27560 | 27560 | 27560 | 27560 | 27560 |

# NOKIAN TYRES HTS G2 L-4S

## HARD-WEARING REACH STACKER TIRE WITH SLICK, SMOOTH TREAD

- Deep, long-lasting smooth tread for extensive tire service life and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 18.00-25 - T445638
- 18.00-33 - T445663

# NOKIAN TYRES HTS G2 L-4S


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)                     |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                                | 1     | 5     | 10    | 20    | 25    |
| T445638      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 538        | 1667          | 770                       | 5000                       | 1000           | 1000                          | 59               | L-4S       | T55831            | 598                    | 26250                            | 22750 | 22750 | 22750 | 22750 | 22750 |
| T445663      | 18.00-33 | 214A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF            | 519        | 1860          | 849                       | 5667                       | 1000           | 1000                          | 60               | L-4S       |                   | 598                    | 31800                            | 27560 | 27560 | 27560 | 27560 | 27560 |

# NOKIAN TYRES HTS G2 L-5S

**LONG-LASTING FRONT TIRE FOR REACH STACKERS – THE SMOOTH, EXTRA-DEEP TREAD OFFERS MORE WORKING HOURS**

- Extra-deep, long-lasting smooth tread increases tread durability and puncture resistance.
- Bias carcass structure improves the tire stability and enables effective loading operations.
- Harbour-specific tread compound enables excellent service life.



## AVAILABLE SIZES

- 18.00-25 - T445805



# NOKIAN TYRES HTS G2 L-5S


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim       | Permitted rims          | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg |       |       |       |       |       |
|--------------|----------|-------|------------|-------|-----------|-------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|----------------------------------|-------|-------|-------|-------|-------|
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)                     |       |       |       |       |       |
|              |          |       |            |       |           |                         |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                                | 1     | 5     | 10    | 20    | 25    |
| T445805      | 18.00-25 | 207A5 | 40         | TL    | 13.00/2.5 | 13.00/2.5 IF, 15.00/2.5 | 524        | 1669          | 745                       | 5032                       | 1000           | 1000                          | 79               | L-5S       | T55831            | 598                    | 26250                            | 22750 | 22750 | 22750 | 22750 | 22750 |

# NOKIAN TYRES ARMOR GARD

## LONG SERVICE LIFE FOR MATERIAL HANDLING MACHINES AND LOADERS

- Strong tire carcass enables precise steering and stability.
- Special rubber compound optimized for harbor use gives an excellent service life.
- Sturdy structure enables long service life as well as great retreading properties.



## AVAILABLE SIZES

- 12.00-20 - T445459



# NOKIAN TYRES ARMOR GARD


## ALL SIZES

| Product code | Size     | LI/SS         | Ply rating | TL/TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity for load wheel, kg |      |      |      |      |      |
|--------------|----------|---------------|------------|-------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|----------------------------------|------|------|------|------|------|
|              |          |               |            |       |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)                     |      |      |      |      |      |
|              |          |               |            |       |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                                | 1    | 5    | 10   | 20   | 25   |
| T445459      | 12.00-20 | 176A5 (176A5) | 20         | TT    | 8.5 | 9.0            | 329        | 1149          | 521                       | 3431                       | 1000           | 1000                          | 25.5             | E-2        | T52810            | 378                    | 10720                            | 9230 | 9230 | 9230 | 9230 | 9230 |

# NOKIAN TYRES RTG

## MORE AGILITY AND DURABILITY FOR THE RTG CRANES

- Tread pattern and tire shape that allow the wheel to turn more easily.
- Low heat build-up slows down tire wear and gives it more operating hours.
- Special rubber compound optimized for harbour use.



## AVAILABLE SIZES

- 14.00-24 - T445471

# NOKIAN TYRES RTG


## ALL SIZES

| Product code | Size     | LI/SS | Ply rating | TL/TT | Rim    | Permitted rims   | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |       |       |       |       |
|--------------|----------|-------|------------|-------|--------|------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|-------|-------|-------|-------|
|              |          |       |            |       |        |                  |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |       |       |       |       |
|              |          |       |            |       |        |                  |            |               |                           |                            |                |                               |                  |            |                   |                        | 0                 | 5     | 10    | 20    | 25    |
| T445471      | 14.00-24 | 188A5 | 28         | TL    | 10.00W | 10.00WA, 10.00VA | 392        | 1363          | 629                       | 4147                       | 1000           | 1000                          | 23               | E-2        | T55767            | 450                    | 15000             | 13000 | 13000 | 13000 | 13000 |

# NOKIAN TYRES HTS TUGGER

## MASSIVE LOAD CAPACITY FOR TERMINAL TRACTORS

- Sturdy multi-layer structure enables exceptional load-bearing capacity.
- Optimized for predictable handling.
- Designed to be as low as possible without compromising other qualities, making it ideal for terminal tractor use.



## AVAILABLE SIZES

- 315/60R22.5 - T445221



# NOKIAN TYRES HTS TUGGER


## ALL SIZES

| Product code | Size        | LI/SS | Reinforced code | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|-------------|-------|-----------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|------------------------|-------------------|------|------|------|------|------|
|              |             |       |                 |       |      |                |            |               |                           |                            |                |                               |                  |            |                        | Speed (km/h)      |      |      |      |      |      |
|              |             |       |                 |       |      |                |            |               |                           |                            |                |                               |                  |            |                        | 1                 | 5    | 10   | 20   | 25   | 35   |
| T445221      | 315/60R22.5 | 174A5 | SB              | TL    | 9.00 | 9.75           | 302        | 948           | 425                       | 2890                       | 1000           | 1000                          | 21               | IND-3      | 376                    | 8710              | 8710 | 8710 | 7540 | 7540 | 6700 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size     | LI/SS        | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|----------|--------------|------------|--------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|------|------|------|------|------|
|              |          |              |            |        |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |      |      |      |      |      |
|              |          |              |            |        |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | 25                | 30   | 35   | 40   | 45   | 50   |
| T445649      | 10.00-20 | 148B (164A5) | 16         | TT     | 7.5 | 8.0            | 283        | 1066          | 500                       | 3173                       | 750            | 900                           | 21               | E-2        | T52620            | 334                    | 4000              | 3845 | 3685 | 3495 | 3340 | 3150 |
| T445650      | 11.00-20 | 151B (170A5) | 16         | TT     | 8.0 | 8.5            | 306        | 1106          | 518                       | 3361                       | 750            | 900                           | 23               | E-2        | T52720            | 352                    | 4380              | 4210 | 4035 | 3830 | 3655 | 3450 |

# EARTHMOVING AND ROAD MAINTENANCE TIRES

## WHEEL LOADER



85

Nokian Tyres  
Ground King  
Loader



87

Nokian Tyres  
Hakkapeliitta  
Loader



89

Nokian Tyres  
Loader Grip



91

Nokian Tyres  
Loader Grip 2

## BACKHOE LOADER



93

Nokian Tyres  
Ground Kare



95

Nokian Tyres  
Ground Kare  
Semi-Slick

## ROAD GRADER



87

Nokian Tyres  
Hakkapeliitta  
Loader

## WHEELED EXCAVATOR



97

Nokian Tyres  
Armor Gard 2



99

Nokian Tyres  
Excavator



93

Nokian Tyres  
Ground Kare


# NOKIAN TYRES GROUND KING LOADER

**STABLE AND VERSATILE LOADER TIRE WITH EXCELLENT SOFT SOIL GRIP AND ROAD HANDLING**

- The Hybrilug™ technology combines the advantages of block and lug pattern, enabling smooth and silent ride on various terrains.
- Excellent self-cleaning properties improve grip for increased productivity on soft soil.
- Accurate, stable and comfortable working is ensured by the strong radial carcass with tough shoulders.



2026-03-04



## AVAILABLE SIZES

- 20.5R25 - T445796

# NOKIAN TYRES GROUND KING LOADER

## ALL SIZES

| Product code | Size    | LI/SS | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims         | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|---------|-------|------------|-----------------|-------|-----------|------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|------------------------|-------------------|------|------|------|------|------|
|              |         |       |            |                 |       |           |                        |            |               |                           |                            |                |                               |                  |            |                        | Speed (km/h)      |      |      |      |      |      |
|              |         |       |            |                 |       |           |                        |            |               |                           |                            |                |                               |                  |            |                        | 20                | 25   | 30   | 35   | 40   | 50   |
| T445796      | 20.5R25 | 186A2 | ★          | SB              | TL    | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7 | 516        | 1488          | 645                       | 4506                       | 450            | 450                           | 48               | L-3        | 624                    | 7980              | 7600 | 7315 | 7030 | 6650 | 5985 |


# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL-SEASON WHEEL LOADER TIRE WITH GREAT WINTER GRIP

- Aggressive tread design with dense siping gives you the best possible grip on snow and ice.
- All-new rubber compound and non-directional tire tread design ensure long service life and even wear.
- Re-designed carcass structure gives more lifetime and better stability.



2026-03-04



## AVAILABLE SIZES

- 14.00R24 - T445691
- 17.5R25 - T445590
- 20.5R25 - T445591
- 23.5R25 - T445592

# NOKIAN TYRES HAKKAPELIITTA LOADER

## ALL SIZES FOR ROAD GRADER

| Product code | Size     | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim    | Permitted rims           | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg |      |      |      |      |  |
|--------------|----------|---------------|------------|-----------------|-------|--------|--------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-----|-------------------|------|------|------|------|--|
|              |          |               |            |                 |       |        |                          |            |               |                           |                            |                |                               |                  |            |                   |                        |     | Speed (km/h)      |      |      |      |      |  |
|              |          |               |            |                 |       |        |                          |            |               |                           |                            |                |                               |                  |            |                   |                        |     | 0                 | 10   | 20   | 30   | 40   |  |
| T445691      | 14.00R24 | 153A8 (176A2) | ★          | SB              | TL    | 8.00TG | 10.00VA, 10.00WA, 10.00W | 380        | 1363          | 624                       | 4159                       | 375            | 550                           | 24               | L-2        | T55767            | 434                    | Yes | 3650              | 3650 | 3650 | 3650 | 3650 |  |


## ALL SIZES FOR WHEEL LOADER

| Product code | Size    | LI/SS         | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims             | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg |      |      |      |      |      |  |
|--------------|---------|---------------|------------|-----------------|-------|-----------|----------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-----|-------------------|------|------|------|------|------|--|
|              |         |               |            |                 |       |           |                            |            |               |                           |                            |                |                               |                  |            |                   |                        |     | Speed (km/h)      |      |      |      |      |      |  |
|              |         |               |            |                 |       |           |                            |            |               |                           |                            |                |                               |                  |            |                   |                        |     | 20                | 25   | 30   | 35   | 40   | 50   |  |
| T445590      | 17.5R25 | 176A2 (153A8) | ★          | SB              | TL    | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 440        | 1344          | 593                       | 4078                       | 450            | 450                           | 28               | L-2        | T55867            | 534                    | Yes | 5965              | 5680 | 5465 | 5255 | 4970 | 4475 |  |
| T445591      | 20.5R25 | 186A2 (168B)  | ★          | SB              | TL    | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7     | 538        | 1487          | 650                       | 4509                       | 450            | 450                           | 32               | L-2        |                   | 624                    | Yes | 7980              | 7600 | 7315 | 7030 | 6650 | 5985 |  |
| T445592      | 23.5R25 | 195A2 (176B)  | ★          | SB              | TL    | 19.50/2.5 | 19.50/2.5IF                | 615        | 1611          | 695                       | 4850                       | 450            | 450                           | 35               | L-2        |                   | 716                    | Yes | 10205             | 9720 | 9355 | 8990 | 8505 | 7655 |  |

# NOKIAN TYRES LOADER GRIP

## STURDY GRIP FOR WHEEL LOADERS AND EARTHMOVING MACHINES

- Sturdy, hard-wearing structure for excellent mileage.
- Comfortable driving response for efficient working.
- Good winter grip makes the tire highly suitable for year-round use.



## AVAILABLE SIZES

- 17.5R25 - T445255
- 20.5R25 - T445171
- 23.5R25 - T445223



# NOKIAN TYRES LOADER GRIP


## ALL SIZES

| Product code | Size    | LI/SS        | Ply rating | Reinforced code | TL/ TT | Rim       | Permitted rims             | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | M+S | Load capacity, kg |      |      |      |      |      |
|--------------|---------|--------------|------------|-----------------|--------|-----------|----------------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-----|-------------------|------|------|------|------|------|
|              |         |              |            |                 |        |           |                            |            |               |                           |                            |                |                               |                  |            |                   |                        |     | Speed (km/h)      |      |      |      |      |      |
|              |         |              |            |                 |        |           |                            |            |               |                           |                            |                |                               |                  |            |                   |                        |     | 20                | 25   | 30   | 35   | 40   | 50   |
| T445255      | 17.5R25 | 176A2 (157B) | ★          | SB              | TL     | 14.00/1.5 | 14.00/1.3 DC, 13.00/1.4 DC | 450        | 1340          | 594                       | 4059                       | 450            | 450                           | 28               | L-3        | T55867            | 534                    | Yes | 5965              | 5680 | 5465 | 5255 | 4970 | 4475 |
| T445171      | 20.5R25 | 186A2 (168B) | ★          | SB              | TL     | 17.00/2.0 | 17.00/2.0IF, 17.00/1.7     | 532        | 1493          | 648                       | 4500                       | 450            | 450                           | 31               | L-3        |                   | 624                    | Yes | 7980              | 7600 | 7315 | 7030 | 6650 | 5985 |
| T445223      | 23.5R25 | 195A2 (176B) | ★          | SB              | TL     | 19.50/2.5 | 19.50/2.5IF                | 630        | 1607          | 700                       | 4880                       | 450            | 450                           | 34               | L-3        |                   | 716                    | Yes | 10205             | 9720 | 9355 | 8990 | 8505 | 7655 |

# NOKIAN TYRES LOADER GRIP 2

## ABSOLUTE GRIP AND DURABILITY FOR WHEEL LOADERS AND ADT MACHINES

- Specially for wheel loaders designed tread blocks create traction on soft gravel and on icy, slippery roads.
- Excellent mileage and sidewall protection against sidewall slashes and abrasions.
- Stability on every terrain due to wide tire contact area and the block-patterned tread.



## AVAILABLE SIZES

- 15.5R25 - T445463



# NOKIAN TYRES LOADER GRIP 2


## ALL SIZES

| Product code | Size    | LI/SS        | Ply rating | Reinforced code | TL/TT | Rim       | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Min. dual spacing (mm) | M+S | Load capacity, kg |      |      |      |      |      |
|--------------|---------|--------------|------------|-----------------|-------|-----------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|------------------------|-----|-------------------|------|------|------|------|------|
|              |         |              |            |                 |       |           |                |            |               |                           |                            |                |                               |                  |            |                        |     | Speed (km/h)      |      |      |      |      |      |
|              |         |              |            |                 |       |           |                |            |               |                           |                            |                |                               |                  |            |                        |     | 20                | 25   | 30   | 35   | 40   | 50   |
| T445463      | 15.5R25 | 169A2 (152B) | ★          | SB              | TL    | 12.00/1.3 | 13.00/1.4 (DC) | 387        | 1280          | 569                       | 3885                       | 450            | 450                           | 23               | L-3        | 473                    | Yes | 4870              | 4640 | 4465 | 4290 | 4060 | 3655 |

# NOKIAN TYRES GROUND KARE

## EXCAVATOR AND BACKHOE LOADER TIRE FOR VERSATILE CONTRACTING WORK

- The tread design enables low surface pressure, great traction and smooth, comfortable driving on road.
- The high load-bearing capacity enables the use of heavy auxiliary equipment.
- The special design adds stability by absorbing swings and shocks.



### AVAILABLE SIZES

- 500/45-22.5 - T445868
- 600/40-22.5 - T445828
- 600/50-22.5 - T445798
- 650/45-22.5 - T445664
- 710/40-22.5 - T445799
- 620/60B30 - T445802
- 620/60B34 - T445668



# NOKIAN TYRES GROUND KARE

## ALL SIZES FOR WHEELED EXCAVATOR

| Product code | Size        | LI/SS | Ply rating | Reinforced code | TL/ TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Min. dual spacing (mm) | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-------------|-------|------------|-----------------|--------|---------|----------------|------------|---------------|---------------------------|-----------------------------|-----|----------------|-------------------------------|------------------|-------------------|------------------------|-------------------------------------|------|------|------|------|------|
|              |             |       |            |                 |        |         |                |            |               |                           |                             |     |                |                               |                  |                   |                        | Speed (km/h)                        |      |      |      |      |      |
|              |             |       |            |                 |        |         |                |            |               |                           |                             |     |                |                               |                  |                   |                        | 25                                  | 30   | 35   | 40   | 45   | 50   |
| T445868      | 500/45-22.5 | 160A8 | 24         | SF              | TL     | AG16.00 | AG18.00        | 499        | 1036          | 472                       | 3126                        | 500 | 600            | 600                           | 24               | T56435            | 566                    | 4770                                | 4680 | 4590 | 4500 | 4320 | 4095 |
| T445828      | 600/40-22.5 | 167A8 | 24         | SF              | TL     | AG20.00 |                | 585        | 1063          | 484                       | 3206                        | 500 | 600            | 600                           | 25               | T55089            | 721                    | 5775                                | 5670 | 5560 | 5450 | 5230 | 4960 |
| T445798      | 600/50-22.5 | 173A8 | 24         | SF              | TL     | AG20.00 |                | 603        | 1156          | 511                       | 3495                        | 550 | 600            | 600                           | 26               | T55089            | 721                    | 6890                                | 6760 | 6630 | 6500 | 6240 | 5915 |
| T445664      | 650/45-22.5 | 175A8 | 24         | SF              | TL     | AG22.00 | AG20.00        | 663        | 1146          | 524                       | 3493                        | 550 | 600            | 600                           | 26               | T55092            | 774                    | 7315                                | 7175 | 7040 | 6900 | 6625 | 6280 |
| T445799      | 710/40-22.5 | 173A8 | 24         | SF              | TL     | AG24.00 |                | 698        | 1145          | 505                       | 3478                        | 550 | 550            | 550                           | 26               | T55092            | 872                    | 6890                                | 6760 | 6630 | 6500 | 6240 | 5915 |


## ALL SIZES FOR BACKHOE LOADER

| Product code | Size      | LI/SS        | Reinforced code | TL/ TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|--------------|-----------------|--------|-------|----------------|------------|---------------|---------------------------|-----------------------------|----------------|-------------------------------|------------------|-------------------|-------------------------------------|------|------|------|------|------|
|              |           |              |                 |        |       |                |            |               |                           |                             |                |                               |                  |                   | Speed (km/h)                        |      |      |      |      |      |
|              |           |              |                 |        |       |                |            |               |                           |                             |                |                               |                  |                   | 25                                  | 30   | 35   | 40   | 45   | 50   |
| T445802      | 620/60B30 | 176A8 (173B) | SB              | TL     | DW20B | DW18L          | 623        | 1500          | 667                       | 4560                        | 450            | 450                           | 25               | T55371            | 7525                                | 7385 | 7240 | 7100 | 6815 | 6460 |
| T445668      | 620/60B34 | 178A8 (175B) | SB              | TL     | DW20B | DW18L          | 630        | 1608          | 750                       | 4907                        | 450            | 450                           | 25               | T55395            | 7950                                | 7800 | 7650 | 7500 | 7200 | 6825 |

# NOKIAN TYRES GROUND KARE SEMI-SLICK

## EXTENDED SERVICE LIFE AND STABILITY FOR RAILWAY USE

- The unique structure of the Nokian Tyres Ground Kare Semi-Slick tire has been optimized to offer a much longer service life than regular backhoe loader tires.
- With stable, shock absorbing structure and high load-bearing capacity, Nokian Tyres Ground Kare Semi-Slick tire gives digging work a stable foundation and enables the use of heavy work attachments.
- Its tread pattern with larger blocks in the center makes driving more comfortable, and the stable structure improves the overall handling of the backhoe loader.



## AVAILABLE SIZES

- 620/60B34 - T445688



2026-03-04

# NOKIAN TYRES GROUND KARE SEMI-SLICK


## ALL SIZES

| Product code | Size      | LI/SS        | Reinforced code | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-----------|--------------|-----------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|-------------------|-------------------------------------|------|------|------|------|------|
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                  |                   | Speed (km/h)                        |      |      |      |      |      |
|              |           |              |                 |       |       |                |            |               |                           |                            |                |                               |                  |                   | 25                                  | 30   | 35   | 40   | 45   | 50   |
| T445688      | 620/60B34 | 178A8 (175B) | SB              | TL    | DW20B | DW18L          | 631        | 1609          | 749                       | 4901                       | 450            | 450                           | 25               | T55395            | 7950                                | 7800 | 7650 | 7500 | 7200 | 6825 |

# NOKIAN TYRES ARMOR GARD 2

## PREMIUM STABILITY FOR URBAN EXCAVATION

- Strong tire carcass enables precise steering and stability by absorbing shocks and swings.
- Long service life due to wider, improved tread pattern.
- The sharp shoulders and straight sidewalls prevent sidewall damages.



## AVAILABLE SIZES

- 10.00-20 - T445649
- 11.00-20 - T445650

# NOKIAN TYRES ARMOR GARD 2

## ALL SIZES

| Product code | Size     | LI/SS        | Ply rating | TL/ TT | Rim | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tread code | Tube product code | Min. dual spacing (mm) | Load capacity, kg |      |      |      |      |      |
|--------------|----------|--------------|------------|--------|-----|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|------------|-------------------|------------------------|-------------------|------|------|------|------|------|
|              |          |              |            |        |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | Speed (km/h)      |      |      |      |      |      |
|              |          |              |            |        |     |                |            |               |                           |                            |                |                               |                  |            |                   |                        | 25                | 30   | 35   | 40   | 45   | 50   |
| T445649      | 10.00-20 | 148B (164A5) | 16         | TT     | 7.5 | 8.0            | 283        | 1066          | 500                       | 3173                       | 750            | 900                           | 21               | E-2        | T52620            | 334                    | 4000              | 3845 | 3685 | 3495 | 3340 | 3150 |
| T445650      | 11.00-20 | 151B (170A5) | 16         | TT     | 8.0 | 8.5            | 306        | 1106          | 518                       | 3361                       | 750            | 900                           | 23               | E-2        | T52720            | 352                    | 4380              | 4210 | 4035 | 3830 | 3655 | 3450 |


# NOKIAN TYRES EXCAVATOR

## EXCAVATOR TIRE FOR SOFT SURFACES

- Excellent self-cleaning properties with curvy lug design improve traction on soft surfaces.
- High load-bearing capacity and improved stability.
- Steel fortified against punctures with a reinforced shoulder for a long service life.



2026-03-04



## AVAILABLE SIZES

- 600/50-22.5 - T445604
- 710/40-22.5 - T445606
- 650/45-22.5 - T445605

# NOKIAN TYRES EXCAVATOR

## ALL SIZES

| Product code | Size        | LI/SS | Ply rating | Reinforced code | TL/TT | Rim     | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | SRI | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | Min. dual spacing (mm) | Load capacity for constant load, kg |      |      |      |      |      |
|--------------|-------------|-------|------------|-----------------|-------|---------|----------------|------------|---------------|---------------------------|----------------------------|-----|----------------|-------------------------------|------------------|-------------------|------------------------|-------------------------------------|------|------|------|------|------|
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                  |                   |                        | Speed (km/h)                        |      |      |      |      |      |
|              |             |       |            |                 |       |         |                |            |               |                           |                            |     |                |                               |                  |                   |                        | 25                                  | 30   | 35   | 40   | 45   | 50   |
| T445604      | 600/50-22.5 | 173A8 | 24         | SF              | TL    | AG20.00 |                | 583        | 1149          | 517                       | 3531                       | 550 | 600            | 600                           | 40               | T55089            | 721                    | 6890                                | 6760 | 6630 | 6500 | 6240 | 5915 |
| T445605      | 650/45-22.5 | 175A8 | 24         | SF              | TL    | AG22.00 | AG20.00        | 643        | 1148          | 515                       | 3525                       | 550 | 600            | 600                           | 40               | T55092            | 774                    | 7315                                | 7175 | 7040 | 6900 | 6625 | 6280 |
| T445606      | 710/40-22.5 | 173A8 | 24         | SF              | TL    | AG24.00 |                | 685        | 1153          | 518                       | 3525                       | 550 | 550            | 550                           | 40               | T55092            | 872                    | 6890                                | 6760 | 6630 | 6500 | 6240 | 5915 |

# ALL TERRAIN TRUCKS AND MILITARY VEHICLES TIRES

## ALL-TERRAIN TRUCK, MILITARY VEHICLE



**102**

**Nokian Tyres  
MPT Agile**




**104**

**Nokian Tyres  
MPT Agile 2**

# NOKIAN TYRES MPT AGILE

## ON AND OFF ROAD AGILITY

- The open arrow-shaped tread pattern ensures good self-cleaning, ensuring grip under demanding circumstances.
- Improved grip on soft surfaces such as mud and snow.
- Exceptional mobility.



## AVAILABLE SIZES

- 365/80R20 - T445431



# NOKIAN TYRES MPT AGILE


## ALL SIZES

| Product code | Size      | LI/SS | Reinforced code | TL/TT | Rim | Permitted rims     | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | M+S | Load capacity for highway service, kg |      |      |      |      |      |
|--------------|-----------|-------|-----------------|-------|-----|--------------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|-----|---------------------------------------|------|------|------|------|------|
|              |           |       |                 |       |     |                    |            |               |                           |                            |                |                               |                  |     | Speed (km/h)                          |      |      |      |      |      |
|              |           |       |                 |       |     |                    |            |               |                           |                            |                |                               |                  |     | 40                                    | 50   | 60   | 70   | 80   | 90   |
| T445431      | 365/80R20 | 152G  | SB              | TL    | 11  | 11 SDC, 12, 12 SDC | 360        | 1092          | 505                       | 3343                       | 625            | 625                           | 20               | Yes | 3800                                  | 3730 | 3730 | 3730 | 3690 | 3550 |

# NOKIAN TYRES MPT AGILE 2

## NEW GENERATION TIRE FOR SPECIAL ON AND OFF ROAD VEHICLES

- Improved grip on soft surfaces such as mud and snow.
- Good steering response and stable handling on different terrains and speeds.
- Symmetrical tread pattern is designed to perform equally well regardless of the tires' rotational direction.



## AVAILABLE SIZES

- 14.00R20 - T445651

# NOKIAN TYRES MPT AGILE 2

## ALL SIZES

| Product code | Size     | LI/SS | Reinforced code | TL/TT | Rim    | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Max. inflation pressure (kPa) | Tread depth (mm) | Tube product code | M+S | Load capacity for highway service, kg |      |      |      |      |      |
|--------------|----------|-------|-----------------|-------|--------|----------------|------------|---------------|---------------------------|----------------------------|----------------|-------------------------------|------------------|-------------------|-----|---------------------------------------|------|------|------|------|------|
|              |          |       |                 |       |        |                |            |               |                           |                            |                |                               |                  |                   |     | Speed (km/h)                          |      |      |      |      |      |
|              |          |       |                 |       |        |                |            |               |                           |                            |                |                               |                  |                   |     | 40                                    | 50   | 60   | 70   | 80   | 90   |
| T445651      | 14.00R20 | 164G  | SB              | TL    | 10.00V | 10.00W         | 400        | 1265          | 588                       | 3989                       | 760            | 760                           | 25               | T52920            | Yes | 5350                                  | 5250 | 5250 | 5250 | 5200 | 5000 |

# TRUCKS AND BUSES TIRES

## STEER



107

**Nokian Tyres  
Hakkapeliitta  
City Bus**



109

**Nokian Tyres  
Hakkapeliitta  
Truck F2**



112

**Nokian Tyres  
Hakka City Bus**



114

**Nokian Tyres  
Hakka Truck  
Coach**



116

**Nokian Tyres  
Hakka Truck  
Steer**



119

**Nokian Tyres  
E-Truck Steer**



122

**Nokian Tyres  
E-Truck Steer  
17.5**



124

**Nokian Tyres  
E-Truck Steer  
19.5**



126

**Nokian Tyres  
R-Truck Steer**

## DRIVE



128

**Nokian Tyres  
Hakkapeliitta  
Truck D**



130

**Nokian Tyres  
Hakkapeliitta  
Truck E2**



133

**Nokian Tyres  
Hakka Truck  
Drive**



136

**Nokian Tyres  
E-Truck Drive**



139

**Nokian Tyres  
E-Truck Drive  
17.5**



141

**Nokian Tyres  
E-Truck Drive  
19.5**



143

**Nokian Tyres  
R-Truck Drive**

## TRAILER



145

**Nokian Tyres  
Hakkapeliitta  
Truck T**



147

**Nokian Tyres  
Hakka Truck  
844+**



149

**Nokian Tyres  
Hakka Truck  
Trailer**



151

**Nokian Tyres  
E-Truck  
Trailer**




155

**Nokian Tyres  
R-Truck  
Trailer**

# NOKIAN TYRES HAKKAPOLIITTA CITY BUS

## WINTER TIRE FOR CITY BUSES – DURABILITY AND EXCELLENT GRIP IN URBAN WINTER CONDITIONS

- Excellent winter grip in urban conditions.
- Reinforced sidewalls protect the tire against curbs.
- Siping designed for minimal heel/toe wear.



## AVAILABLE SIZES

- 275/70R22.5 - T675218
- 295/80R22.5 - T675240
- 275/70R22.5 - T675330

# NOKIAN TYRES HAKKAPELIITTA CITY BUS

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675218      | 275/70R22.5 | 150/148J (152/148E) | TL    | 8.25 | 7.50           | 275        | 969           | 455                       | 2945                       | 900            | 20.5             | 311                    | D                  | B        | B           | 72         | Yes | Yes                       |
| T675330      | 275/70R22.5 | 152/149J (150/148K) | TL    | 8.25 | 7.50           |            |               | 450                       | 2922                       | 900            | 20.5             | 311                    | D                  | B        | A           | 70         | Yes | Yes                       |
| T675240      | 295/80R22.5 | 152/148J (154/150E) | TL    | 9.00 | 8.25           | 298        | 1044          | 491                       | 3204                       | 850            | 17               | 335                    | D                  | B        | B           | 75         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675218      | 275/70R22.5 | Single  | 70              | 5470                                                                          | 5640  | 5810  | 5970  | 6140  | 6300  | 6460  | 6620  | 6780  | 6940  | 7100  |
|              |             | Dual    | 70              | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
|              |             | Single  | 100             | 5160                                                                          | 5320  | 5480  | 5640  | 5790  | 5940  | 6100  | 6250  | 6400  | 6550  | 6700  |
|              |             | Dual    | 100             | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675330      | 275/70R22.5 | Single  | 100             | 5470                                                                          | 5640  | 5810  | 5970  | 6140  | 6300  | 6460  | 6620  | 6780  | 6940  | 7100  |
|              |             | Dual    | 100             | 10020                                                                         | 10330 | 10630 | 10940 | 11240 | 11530 | 11830 | 12130 | 12420 | 12710 | 13000 |
|              |             | Single  | 110             | 5160                                                                          | 5320  | 5480  | 5640  | 5790  | 5940  | 6100  | 6250  | 6400  | 6550  | 6700  |
|              |             | Dual    | 110             | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675240      | 295/80R22.5 | Single  | 70              | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 70              | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |       |       |
|              |             | Single  | 100             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 100             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## WINTER STEER AXLE TIRE – GRIP FOR DEMANDING WINTER CONDITIONS IN REGIONAL AND LONG-DISTANCE TRANSPORT

- Aggressive pattern, deep grooves and a new shoulder design enable reference-level grip and good self-cleaning.
- Improved Spiral Sipe System keeps the siping effective even when the tire wears down.
- New, large stone ejectors protect the tire from stone trapping.



## AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • 295/80R22.5 - T675041 | • 385/55R22.5 - T675276 |
| • 295/80R22.5 - T675310 | • 385/55R22.5 - T675311 |
| • 315/70R22.5 - T675040 | • 385/65R22.5 - T675038 |
| • 315/70R22.5 - T675300 | • 385/65R22.5 - T675237 |
| • 315/80R22.5 - T675039 | • 385/65R22.5 - T675291 |
| • 315/80R22.5 - T675319 |                         |

# NOKIAN TYRES HAKKAPELIITTA TRUCK F2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675041      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 297        | 1054          | 491                       | 3203                       | 850            | 15               | 335                    | D                  | B        | A           | 71         | Yes | Yes                       |
| T675310      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           |            |               | 487                       | 3184                       | 850            | 15               | 335                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675040      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 312        | 1021          | 471                       | 3103                       | 900            | 14               | 351                    | D                  | C        | A           | 71         | Yes | Yes                       |
| T675300      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           |            |               | 466                       | 3093                       | 900            | 14.5             | 351                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675039      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 312        | 1078          | 501                       | 3277                       | 850            | 16               | 351                    | D                  | B        | B           | 73         | Yes | Yes                       |
| T675319      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           |            |               | 504                       | 3282                       | 850            | 16               | 351                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675276      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 381        | 1003          | 467                       | 3049                       | 900            | 13.5             |                        | C                  | B        | B           | 73         | Yes | Yes                       |
| T675311      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          |            |               | 456                       | 3018                       | 900            | 15.5             |                        | C                  | A        | A           | 71         | Yes | Yes                       |
| T675038      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 376        | 1086          | 502                       | 3301                       | 900            | 16               |                        | E                  | B        | B           | 73         | Yes | Yes                       |
| T675237      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 381        | 1084          | 501                       | 3295                       | 900            | 16               |                        | C                  | B        | B           | 75         | Yes | Yes                       |
| T675291      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 386        | 1074          | 493                       | 3248                       | 900            | 16               |                        | C                  | A        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675041      | 295/80R22.5 | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 130             | 10490                                                                         | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |       |       |
| T675310      | 295/80R22.5 | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 130             | 10490                                                                         | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |       |       |
| T675040      | 315/70R22.5 | Single  | 120             | 6170                                                                          | 6360  | 6540  | 6730  | 6910  | 7100  | 7280  | 7460  | 7640  | 7820  | 8000  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 130             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675300      | 315/70R22.5 | Single  | 120             | 6170                                                                          | 6360  | 6540  | 6730  | 6910  | 7100  | 7280  | 7460  | 7640  | 7820  | 8000  |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 130             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |       |       |
| T675039      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
| T675319      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
| T675276      | 385/55R22.5 | Single  | 110             | 7260                                                                          | 7480  | 7710  | 7920  | 8140  | 8360  | 8570  | 8790  | 9000  |       |       |
|              |             | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675311      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675038      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070  | 7280  | 7480  | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |
| T675237      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940  | 8180  | 8410  | 8640  | 8870  | 9100  | 9330  | 9550  | 9780  | 10000 |
| T675291      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940  | 8180  | 8410  | 8640  | 8870  | 9100  | 9330  | 9550  | 9780  | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA CITY BUS

## ALL-WEATHER TIRE FOR ALL AXLES – DURABILITY AND ALL-WEATHER PERFORMANCE FOR CITY BUSES

- Specifically designed for the modern urban needs. Increased load capacity.
- Reinforced sidewalls protect the tire against curb.
- Tread pattern for minimal heel/toe wear.



## AVAILABLE SIZES

- 275/70R22.5 - T675318

# NOKIAN TYRES HAKKA CITY BUS

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|---------------------------|-----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675318      | 275/70R22.5 | 152/149J (150/148K) | TL    | 8.25 | 7.50           | 448                       | 2922                        | 900            | 18.5             | 311                    | D                  | B        | A           | 71         | Yes | Yes                       |


## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | km/h                                                                          | 650   | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675318      | 275/70R22.5 | Single  | 100             |                                                                               | 5470  | 5640  | 5810  | 5970  | 6140  | 6300  | 6460  | 6620  | 6780  | 6940  | 7100  |
|              |             | Dual    | 100             |                                                                               | 10020 | 10330 | 10630 | 10940 | 11240 | 11530 | 11830 | 12130 | 12420 | 12710 | 13000 |
|              |             | Single  | 110             |                                                                               | 5160  | 5320  | 5480  | 5640  | 5790  | 5940  | 6100  | 6250  | 6400  | 6550  | 6700  |
|              |             | Dual    | 110             |                                                                               | 9710  | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |

# NOKIAN TYRES HAKKA TRUCK COACH

## ALL-WEATHER TIRE FOR ALL AXLES – CONFIDENT GRIP AND COMFORT FOR LONG-DISTANCE BUSES

- Grip-improving siping with unique activators and optimized open pattern design.
- Rubber compound and tread pattern optimized for smooth, quiet rides.
- Long service life and even wear pattern. Rock Resistor grooves prevent stone trapping.



### AVAILABLE SIZES

- 295/80R22.5 - T675271
- 315/80R22.5 - T675272



# NOKIAN TYRES HAKKA TRUCK COACH

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675271      | 295/80R22.5 | 154/149M | TL    | 9.00 | 8.25           | 297        | 1055          | 491                       | 3207                       | 850            | 15.5             | 335                    | D                  | C        | A           | 70         | Yes | Yes                       |
| T675272      | 315/80R22.5 | 156/150L | TL    | 9.00 | 9.75           | 314        | 1078          | 501                       | 3277                       | 850            | 15.5             | 351                    | C                  | C        | A           | 69         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   |
| T675271      | 295/80R22.5 | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |
|              |             | Dual    | 130             | 10490                                                                         | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |
| T675272      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |
|              |             | Dual    | 120             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL-WEATHER STEER AXLE TIRE – EXCELLENT MILEAGE FOR REGIONAL TRANSPORT

- Wide, slow-wearing tread for excellent mileage.
- New kind of sipe activators improve grip on snowy and wet surfaces.
- Stone ejectors protect the tire from stone trapping.



### AVAILABLE SIZES

- 295/80R22.5 - T675221
- 315/60R22.5 - T675249
- 315/70R22.5 - T675220
- 315/70R22.5 - T675302
- 315/80R22.5 - T675214
- 385/55R22.5 - T675241
- 385/65R22.5 - T675222

# NOKIAN TYRES HAKKA TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|-----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675221      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           | 298        | 1047          | 488                       | 3182                        | 850            | 15.5             | 335                    | D                  | B        | A           | 70         | Yes | Yes                       |
| T675249      | 315/60R22.5 | 154/148L            | TL    | 9.00  | 9.75           | 314        | 959           | 449                       | 2915                        | 900            | 13               | 344                    | C                  | B        | B           | 72         | Yes | Yes                       |
| T675220      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 312        | 1021          | 471                       | 3103                        | 900            | 14               | 351                    | C                  | B        | A           | 70         | Yes | Yes                       |
| T675302      | 315/70R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           |            |               | 466                       | 3093                        | 900            | 14.5             | 351                    | C                  | B        | A           | 70         | Yes | Yes                       |
| T675214      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 314        | 1079          | 501                       | 3280                        | 850            | 15.5             | 351                    | D                  | B        | A           | 70         | Yes | Yes                       |
| T675241      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 384        | 1005          | 468                       | 3055                        | 900            | 15.5             |                        | D                  | C        | A           | 70         | Yes | Yes                       |
| T675222      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 376        | 1083          | 501                       | 3292                        | 900            | 15.5             |                        | C                  | B        | A           | 70         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675221      | 295/80R22.5 | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 130             | 10490                                                                         | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |       |       |
| T675249      | 315/60R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675220      | 315/70R22.5 | Single  | 120             | 6170                                                                          | 6360  | 6540  | 6730  | 6910  | 7100  | 7280  | 7460  | 7640  | 7820  | 8000  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 130             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675302      | 315/70R22.5 | Single  | 120             | 6170                                                                          | 6360  | 6540  | 6730  | 6910  | 7100  | 7280  | 7460  | 7640  | 7820  | 8000  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
|              |             | Dual    | 130             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675214      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
| T675241      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675222      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070  | 7280  | 7480  | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER

## ALL-SEASON STEER AXLE TIRE – GOOD GRIP AND MILEAGE FOR REGIONAL TRANSPORTS

- New type of zigzag-shaped grooves prevent stone trapping.
- Even wear pattern for good mileage.
- Spiral Sipe System adds grip on all roads.



## AVAILABLE SIZES

- 295/80R22.5 - T675226
- 295/80R22.5 - T675336
- 315/70R22.5 - T675223
- 315/70R22.5 - T675297
- 315/80R22.5 - T675219
- 315/80R22.5 - T675308
- 385/55R22.5 - T675248
- 385/55R22.5 - T675333
- 385/65R22.5 - T675247
- 385/65R22.5 - T675332

# NOKIAN TYRES E-TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circum-ference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|-----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675226      | 295/80R22.5 | 152/148M            | TL    | 9.00  | 8.25           | 298        | 1044          | 487                       | 3173                        | 850            | 13.5             | 335                    | C                  | B        | A           | 70         | Yes | Yes                       |
| T675336      | 295/80R22.5 | 154/149M            | TL    | 9.00  | 8.25           |            |               | 458                       | 3212                        | 850            | 14.5             | 335                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675223      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00  | 9.75           | 318        | 1019          | 473                       | 3097                        | 900            | 13.5             | 351                    | C                  | A        | A           | 70         | Yes | Yes                       |
| T675297      | 315/70R22.5 | 156/150L            | TL    | 9.00  | 9.75           | 309        | 1015          | 469                       | 3097                        | 900            | 15.5             | 351                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675219      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00  | 9.75           | 314        | 1071          | 498                       | 3255                        | 850            | 14.5             | 351                    | C                  | A        | A           | 69         | Yes | Yes                       |
| T675308      | 315/80R22.5 | 156/150L            | TL    | 9.00  | 9.75           | 316        | 1077          | 501                       | 3297                        | 850            | 15               | 351                    | B                  | B        | A           | 71         | Yes | Yes                       |
| T675248      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 381        | 999           | 465                       | 3037                        | 900            | 12.5             |                        | B                  | B        | A           | 68         | Yes | Yes                       |
| T675333      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          |            |               | 457                       | 3040                        | 900            | 14.5             |                        | B                  | B        | A           | 70         | Yes | Yes                       |
| T675247      | 385/65R22.5 | 160K                | TL    | 11.75 | 12.25          | 378        | 1078          | 498                       | 3277                        | 900            | 13.5             |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675332      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          |            |               | 493                       | 3282                        | 900            | 14.5             |                        | C                  | B        | A           | 70         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675226      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675336      | 295/80R22.5 | Single  | 130             | 6050                                                                          | 6240  | 6420  | 6600  | 6790  | 6970  | 7140  | 7320  | 7500  |       |       |
|              |             | Dual    | 130             | 10490                                                                         | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |       |       |
| T675223      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675297      | 315/70R22.5 | Single  | 120             | 6170                                                                          | 6360  | 6540  | 6730  | 6910  | 7100  | 7280  | 7460  | 7640  | 7820  | 8000  |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
| T675219      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
| T675308      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |       |       |
| T675248      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675333      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675247      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675332      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940  | 8180  | 8410  | 8640  | 8870  | 9100  | 9330  | 9550  | 9780  | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL-SEASON STEER AXLE TIRE – STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 215/75R17.5 - T675252
- 215/75R17.5 - T675338
- 235/75R17.5 - T675253
- 235/75R17.5 - T675342

# NOKIAN TYRES E-TRUCK STEER 17.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675252      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 213        | 761           | 357                       | 2313                       | 700            | 11.7             | 239                    | C                  | C        | A           | 70         | Yes | Yes                       |
| T675338      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 210        | 772           | 358                       | 2363                       | 700            | 12.5             | 239                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675253      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 238        | 791           | 370                       | 2404                       | 775            | 12.2             | 262                    | C                  | B        | A           | 67         | Yes | Yes                       |
| T675342      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           |            |               | 369                       | 2432                       | 775            | 12.5             | 262                    | C                  | B        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |      |      |      |      |      |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|------|------|------|------|------|
|              |             |         |                 | 500                                                                           | 525  | 550  | 575  | 600  | 625  | 650  | 675  | 700  | 725  | 750  | 775  |
| T675252      | 215/75R17.5 | Single  | 130             | 2600                                                                          | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 |      |      |      |
|              |             | Dual    | 130             | 4890                                                                          | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 |      |      |      |
| T675338      | 215/75R17.5 | Single  | 130             | 2600                                                                          | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 |      |      |      |
|              |             | Dual    | 130             | 4890                                                                          | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 |      |      |      |
| T675253      | 235/75R17.5 | Single  | 130             |                                                                               |      | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
|              |             | Dual    | 130             |                                                                               |      | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |
| T675342      | 235/75R17.5 | Single  | 130             |                                                                               |      | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
|              |             | Dual    | 130             |                                                                               |      | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL-SEASON STEER AXLE TIRE – STABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Robust pattern with good stability and handling properties.
- Special zigzag-shaped wide grooves effectively reduce stone trapping.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 265/70R19.5 - T675263
- 285/70R19.5 - T675262
- 265/70R19.5 - T675343
- 285/70R19.5 - T675344



# NOKIAN TYRES E-TRUCK STEER 19.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675263      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 252        | 859           | 398                       | 2611                       | 775            | 12.7             | 295                    | C                  | B        | A           | 68         | Yes | Yes                       |
| T675343      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     |            |               | 399                       | 2638                       | 775            | 13               | 295                    | C                  | B        | A           | 71         | Yes | Yes                       |
| T675262      | 285/70R19.5 | 145/143M | TL    | 8.25 | 9.00           | 270        | 887           | 409                       | 2696                       | 850            | 13.1             | 318                    | C                  | C        | A           | 67         | Yes | Yes                       |
| T675344      | 285/70R19.5 | 146/144L | TL    | 8.25 | 9.00           |            |               | 415                       | 2739                       | 900            | 13.5             | 318                    | C                  | B        | A           | 71         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |      |      |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | km/h                                                                          | 550  | 575  | 600  | 625  | 650  | 675  | 700  | 725  | 750   | 775   | 800   | 825   | 850   | 875   |
| T675263      | 265/70R19.5 | Single  | 130             | 3800                                                                          | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000  |       |       |       |       |       |
|              |             | Dual    | 130             | 7170                                                                          | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440  |       |       |       |       |       |
| T675343      | 265/70R19.5 | Single  | 130             | 3800                                                                          | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000  |       |       |       |       |       |
|              |             | Dual    | 130             | 7170                                                                          | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440  |       |       |       |       |       |
| T675262      | 285/70R19.5 | Single  | 130             |                                                                               |      | 4390 | 4540 | 4680 | 4820 | 4970 | 5110 | 5250 | 5390  | 5530  | 5660  | 5800  |       |       |
|              |             | Dual    | 130             |                                                                               |      | 8250 | 8520 | 8790 | 9060 | 9330 | 9600 | 9860 | 10120 | 10380 | 10640 | 10900 |       |       |
| T675344      | 285/70R19.5 | Single  | 120             |                                                                               |      | 4340 | 4480 | 4620 | 4770 | 4910 | 5050 | 5190 | 5320  | 5460  | 5600  | 5730  | 5870  | 6000  |
|              |             | Dual    | 120             |                                                                               |      | 8100 | 8370 | 8630 | 8900 | 9160 | 9420 | 9680 | 9940  | 10190 | 10450 | 10700 | 10950 | 11200 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK STEER

## STEER AXLE TIRE – CONTROLLED STEERING FOR ON/OFF-ROAD USE

- Stone ejectors in the main grooves prolong operating life especially on rough surfaces.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.



## AVAILABLE SIZES

- 315/80R22.5 - T675238
- 385/65R22.5 - T675260
- 385/65R22.5 - T675239
- 385/65R22.5 - T675313

# NOKIAN TYRES R-TRUCK STEER

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675238      | 315/80R22.5 | 156/150K | TL    | 9.00  | 9.75           | 309        | 1082          | 503                       | 3289                       | 825            | 16               | 351                    | C                  | B        | A           | 70         | Yes | Yes                       |
| T675239      | 385/65R22.5 | 160K     | TL    | 11.75 | 12.25          | 378        | 1086          | 502                       | 3301                       | 900            | 16               |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675260      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          | 381        | 1086          | 502                       | 3301                       | 900            | 16               |                        | C                  | C        | A           | 70         | Yes | Yes                       |
| T675313      | 385/65R22.5 | 164K     | TL    | 11.75 | 12.25          |            |               | 492                       | 3248                       | 900            | 16               |                        | C                  | A        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |      |      |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|------|------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850  | 875  | 900   |
| T675238      | 315/80R22.5 | Single  | 110             | 6610                                                                          | 6810  | 7010  | 7210  | 7410  | 7610  | 7810  | 8000  |      |      |       |
|              |             | Dual    | 110             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |      |      |       |
| T675239      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600 | 8800 | 9000  |
| T675260      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940  | 8180  | 8410  | 8640  | 8870  | 9100  | 9330  | 9550 | 9780 | 10000 |
| T675313      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940  | 8180  | 8410  | 8640  | 8870  | 9100  | 9330  | 9550 | 9780 | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK D

## SUPERIOR GRIP AND STABILITY IN THE LONG HAUL

- The deep 3D siping maintains grip even when the tire wears down.
- The patented Twin-Block pattern design ensures superior traction especially on packed snow and icy roads.
- New design with a lower rolling resistance saves fuel and the environment.



## AVAILABLE SIZES

- 275/70R22.5 - T675233
- 295/80R22.5 - T675031
- 315/70R22.5 - T675032
- 315/80R22.5 - T675030



# NOKIAN TYRES HAKKAPELIITTA TRUCK D

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675233      | 275/70R22.5 | 148/145M            | TL    | 8.25 | 7.50           | 276        | 958           | 445                       | 2912                       | 900            | 16               | 311                    | D                  | B        | B           | 75         | Yes | Yes                       |
| T675031      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 8.25           | 296        | 1063          | 495                       | 3231                       | 850            | 20               | 335                    | D                  | C        | B           | 74         | Yes | Yes                       |
| T675032      | 315/70R22.5 | 152/148M (154/150L) | TL    | 9.00 | 9.75           | 314        | 1032          | 476                       | 3137                       | 850            | 19.5             | 351                    | D                  | C        | A           | 73         | Yes | Yes                       |
| T675030      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 312        | 1087          | 504                       | 3304                       | 825            | 20               | 351                    | D                  | D        | B           | 76         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675233      | 275/70R22.5 | Single  | 130             | 4860                                                                          | 5000  | 5150  | 5300  | 5440  | 5590  | 5730  | 5880  | 6020  | 6160  | 6300  |
|              |             | Dual    | 130             | 8940                                                                          | 9220  | 9490  | 9760  | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675031      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675032      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675030      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## WINTER DRIVE AXLE TIRE – SUPERIOR TRACTION AND OPTIMIZED PERFORMANCE ON SEVERE WINTER CONDITIONS

- Deeper reach, better grip when worn and improved stability due to peg siping.
- Consistent rigidity and even wear pattern brought by connected block system.
- Increased tire service life enabled by the open center tread design and extra deep-reaching center sipes.



## AVAILABLE SIZES

- 275/70R22.5 - T675274
- 295/80R22.5 - T675259
- 295/80R22.5 - T675290
- 315/70R22.5 - T675258
- 315/70R22.5 - T675309
- 315/80R22.5 - T675257
- 315/80R22.5 - T675289



# NOKIAN TYRES HAKKAPELIITTA TRUCK E2

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675274      | 275/70R22.5 | 148/145M            | TL    | 8.25 | 7.50           | 266        | 969           | 450                       | 2945                       | 900            | 17.5             | 311                    | E                  | C        | B           | 74         | Yes | Yes                       |
| T675259      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 9.75           | 297        | 1064          | 495                       | 3224                       | 850            | 20               | 335                    | D                  | D        | B           | 74         | Yes | Yes                       |
| T675290      | 295/80R22.5 | 152/148M            | TL    | 9    | 9.75           |            |               | 492                       | 3184                       | 850            | 19.5             | 335                    | D                  | C        | A           | 73         | Yes | Yes                       |
| T675258      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 314        | 1027          | 474                       | 3122                       | 900            | 18.5             | 351                    | D                  | D        | B           | 74         | Yes | Yes                       |
| T675309      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           |            |               | 471                       | 3093                       | 900            | 18.5             | 351                    | D                  | A        | A           | 73         | Yes | Yes                       |
| T675257      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           | 314        | 1089          | 506                       | 3310                       | 850            | 19.5             | 351                    | D                  | D        | A           | 73         | Yes | Yes                       |
| T675289      | 315/80R22.5 | 156/150L (154/150M) | TL    | 9.00 | 9.75           |            |               | 502                       | 3282                       | 850            | 20               | 351                    | D                  | A        | A           | 73         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675274      | 275/70R22.5 | Single  | 130             | 4860                                                                          | 5000  | 5150  | 5300  | 5440  | 5590  | 5730  | 5880  | 6020  | 6160  | 6300  |
|              |             | Dual    | 130             | 8940                                                                          | 9220  | 9490  | 9760  | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675259      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675290      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675258      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675309      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675257      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |       |       |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |
| T675289      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |
|              |             | Dual    | 120             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL-WEATHER DRIVE AXLE TIRE - GRIP FOR REGIONAL TRANSPORT

- Open V-shaped tread design with good self-cleaning.
- Optimized tread pattern staggering ensures even wear pattern.
- Effective siping improves grip in both acceleration and braking.



### AVAILABLE SIZES

- 295/60R22.5 - T675250
- 295/80R22.5 - T675034
- 315/60R22.5 - T675251
- 315/70R22.5 - T675036
- 315/70R22.5 - T675303
- 315/80R22.5 - T675035



# NOKIAN TYRES HAKKA TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675250      | 295/60R22.5 | 150/147L            | TL    | 9.00 | 9.75           | 299        | 931           | 437                       | 2830                       | 900            | 15               | 329                    | D                  | C        | B           | 76         | Yes | Yes                       |
| T675034      | 295/80R22.5 | 152/148M            | TL    | 9.00 | 8.25           | 296        | 1060          | 488                       | 3222                       | 850            | 18.5             | 335                    | E                  | C        | B           | 75         | Yes | Yes                       |
| T675251      | 315/60R22.5 | 152/148L            | TL    | 9.00 | 9.75           | 311        | 963           | 450                       | 2927                       | 900            | 15.5             | 344                    | C                  | C        | B           | 76         | Yes | Yes                       |
| T675036      | 315/70R22.5 | 152/148M (154/150L) | TL    | 9.00 | 9.75           | 314        | 1029          | 474                       | 3128                       | 850            | 18               | 351                    | D                  | C        | B           | 75         | Yes | Yes                       |
| T675303      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           |            |               | 472                       | 3093                       | 900            | 18               | 351                    | D                  | B        | A           | 72         | Yes | Yes                       |
| T675035      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 312        | 1085          | 504                       | 3298                       | 825            | 18.5             | 351                    | D                  | C        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675250      | 295/60R22.5 | Single  | 120             | 5160                                                                          | 5320  | 5480  | 5640  | 5790  | 5940  | 6100  | 6250  | 6400  | 6550  | 6700  |
|              |             | Dual    | 120             | 9480                                                                          | 9770  | 10060 | 10350 | 10630 | 10910 | 11190 | 11470 | 11750 | 12030 | 12300 |
| T675034      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675251      | 315/60R22.5 | Single  | 120             | 5470                                                                          | 5640  | 5810  | 5970  | 6140  | 6300  | 6460  | 6620  | 6780  | 6940  | 7100  |
|              |             | Dual    | 120             | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675036      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |
| T675303      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |     |     |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875 | 900 |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |     |     |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |     |     |
| T675035      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |     |     |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |     |     |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |     |     |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |     |     |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE

## ALL-SEASON DRIVE AXLE TIRE -RELIABLE TRACTION AND EVEN WEAR FOR REGIONAL TRANSPORT

- Effective block pattern and open center tread design ensure good traction.
- Even wear pattern for a long, trouble-free service life.
- Low rolling resistance and tire noise for fuel economy and comfort.



### AVAILABLE SIZES

- 295/80R22.5 - T675282
- 295/80R22.5 - T675335
- 315/70R22.5 - T675281
- 315/70R22.5 - T675296
- 315/80R22.5 - T675280
- 315/80R22.5 - T675307

# NOKIAN TYRES E-TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675282      | 295/80R22.5 | 152/148M            | TL    | 8.25 |                | 297        | 1054          | 491                       | 3204                       | 850            | 17.5             | 335                    | D                  | C        | B           | 75         | Yes | Yes                       |
| T675335      | 295/80R22.5 | 152/148M            | TL    | 8.25 |                |            |               | 492                       | 3238                       | 850            | 19.5             | 335                    | D                  | B        | B           | 74         | Yes | Yes                       |
| T675281      | 315/70R22.5 | 154/150L (152/148M) | TL    | 9.00 | 9.75           | 314        | 1027          | 474                       | 3122                       | 900            | 17.5             | 351                    | C                  | C        | A           | 73         | Yes | Yes                       |
| T675296      | 315/70R22.5 | 154/150L            | TL    | 9.00 | 9.75           | 308        | 1022          | 474                       | 3117                       | 900            | 19.5             | 351                    | D                  | B        | B           | 74         | Yes | Yes                       |
| T675280      | 315/80R22.5 | 154/150M (156/150L) | TL    | 9.00 | 9.75           | 314        | 1076          | 502                       | 3286                       | 825            | 17.5             | 351                    | D                  | C        | B           | 76         | Yes | Yes                       |
| T675307      | 315/80R22.5 | 156/150L            | TL    | 9.00 | 9.75           |            |               | 505                       | 3333                       | 850            | 19.5             | 351                    | C                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |  |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |  |
| T675282      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |  |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |  |
| T675335      | 295/80R22.5 | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |  |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |  |
| T675281      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |  |
|              |             | Single  | 130             | 5730                                                                          | 5900  | 6080  | 6250  | 6420  | 6590  | 6760  | 6930  | 7100  |       |       |  |
|              |             | Dual    | 130             | 10170                                                                         | 10480 | 10790 | 11090 | 11400 | 11700 | 12000 | 12300 | 12600 |       |       |  |
| T675296      | 315/70R22.5 | Single  | 120             | 5780                                                                          | 5960  | 6130  | 6310  | 6480  | 6650  | 6830  | 7000  | 7160  | 7330  | 7500  |  |
|              |             | Dual    | 120             | 10330                                                                         | 10650 | 10960 | 11270 | 11580 | 11890 | 12200 | 12500 | 12800 | 13100 | 13400 |  |
| T675280      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |       |       |  |
|              |             | Dual    | 120             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |       |       |  |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |     |     |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-----|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875 | 900 |
|              |             | Single  | 130             | 6200                                                                          | 6390  | 6580  | 6760  | 6950  | 7130  | 7320  | 7500  |       |     |     |
|              |             | Dual    | 130             | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |       |     |     |
| T675307      | 315/80R22.5 | Single  | 120             | 6450                                                                          | 6650  | 6850  | 7040  | 7240  | 7430  | 7620  | 7810  | 8000  |     |     |
|              |             | Dual    | 120             | 10810                                                                         | 11140 | 11470 | 11800 | 12120 | 12450 | 12770 | 13080 | 13400 |     |     |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL-SEASON DRIVE AXLE TIRE – DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and a long tire life.
- Abrasion-resistant rubber compound provides good mileage.



## AVAILABLE SIZES

- 215/75R17.5 - T675255
- 235/75R17.5 - T675256
- 215/75R17.5 - T675337
- 235/75R17.5 - T675339

# NOKIAN TYRES E-TRUCK DRIVE 17.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675255      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           | 213        | 763           | 358                       | 2319                       | 700            | 13.4             | 239                    | D                  | D        | A           | 72         | Yes | Yes                       |
| T675337      | 215/75R17.5 | 126/124M | TL    | 6.00 | 6.75           |            |               | 360                       | 2368                       | 700            | 14.5             | 239                    | D                  | B        | B           | 74         | Yes | Yes                       |
| T675256      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           | 238        | 791           | 370                       | 2404                       | 775            | 13.8             | 262                    | D                  | C        | A           | 72         | Yes | Yes                       |
| T675339      | 235/75R17.5 | 132/130M | TL    | 6.75 | 7.50           |            |               | 372                       | 2446                       | 775            | 14.5             | 262                    | D                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |      |      |      |      |      |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|------|------|------|------|------|
|              |             |         |                 | 500                                                                           | 525  | 550  | 575  | 600  | 625  | 650  | 675  | 700  | 725  | 750  | 775  |
| T675255      | 215/75R17.5 | Single  | 130             | 2600                                                                          | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 |      |      |      |
|              |             | Dual    | 130             | 4890                                                                          | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 |      |      |      |
| T675337      | 215/75R17.5 | Single  | 130             | 2600                                                                          | 2700 | 2800 | 2900 | 3010 | 3110 | 3200 | 3300 | 3400 |      |      |      |
|              |             | Dual    | 130             | 4890                                                                          | 5080 | 5280 | 5470 | 5660 | 5850 | 6030 | 6220 | 6400 |      |      |      |
| T675256      | 235/75R17.5 | Single  | 130             |                                                                               |      | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
|              |             | Dual    | 130             |                                                                               |      | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |
| T675339      | 235/75R17.5 | Single  | 130             |                                                                               |      | 3040 | 3150 | 3260 | 3370 | 3470 | 3580 | 3690 | 3790 | 3900 | 4000 |
|              |             | Dual    | 130             |                                                                               |      | 5780 | 5990 | 6190 | 6400 | 6600 | 6800 | 7010 | 7210 | 7400 | 7600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL-SEASON DRIVE AXLE TIRE – DURABILITY FOR LIGHT AND MEDIUM TRANSPORT

- Open block design with semi-open shoulder design improves the grip in all weather conditions.
- Optimized tread block staggering enables even wear shape and long tire life.
- Abrasion-resistant rubber compound provides good mileage.



### AVAILABLE SIZES

- 265/70R19.5 - T675265
- 285/70R19.5 - T675264
- 265/70R19.5 - T675340
- 285/70R19.5 - T675341

# NOKIAN TYRES E-TRUCK DRIVE 19.5

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675265      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     | 252        | 865           | 400                       | 2629                       | 775            | 15               | 295                    | D                  | C        | A           | 72         | Yes | Yes                       |
| T675340      | 265/70R19.5 | 140/138M | TL    | 7.50 | 6.75, 8.25     |            |               | 401                       | 2651                       | 775            | 15               | 295                    | C                  | B        | B           | 74         | Yes | Yes                       |
| T675264      | 285/70R19.5 | 145/143M | TL    | 8.25 | 9.00           | 270        | 889           | 410                       | 2702                       | 850            | 14.3             | 318                    | C                  | C        | A           | 73         | Yes | Yes                       |
| T675341      | 285/70R19.5 | 146/144L | TL    | 8.25 | 9.00           |            |               | 416                       | 2748                       | 900            | 15               | 318                    | C                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |      |      |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
|              |             |         |                 | km/h                                                                          | 550  | 575  | 600  | 625  | 650  | 675  | 700  | 725  | 750   | 775   | 800   | 825   | 850   | 875   |
| T675265      | 265/70R19.5 | Single  | 130             | 3800                                                                          | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000  |       |       |       |       |       |
|              |             | Dual    | 130             | 7170                                                                          | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440  |       |       |       |       |       |
| T675340      | 265/70R19.5 | Single  | 130             | 3800                                                                          | 3940 | 4070 | 4210 | 4340 | 4480 | 4610 | 4740 | 4870 | 5000  |       |       |       |       |       |
|              |             | Dual    | 130             | 7170                                                                          | 7430 | 7690 | 7950 | 8200 | 8450 | 8700 | 8950 | 9200 | 9440  |       |       |       |       |       |
| T675264      | 285/70R19.5 | Single  | 130             |                                                                               |      | 4390 | 4540 | 4680 | 4820 | 4970 | 5110 | 5250 | 5390  | 5530  | 5660  | 5800  |       |       |
|              |             | Dual    | 130             |                                                                               |      | 8250 | 8520 | 8790 | 9060 | 9330 | 9600 | 9860 | 10120 | 10380 | 10640 | 10900 |       |       |
| T675341      | 285/70R19.5 | Single  | 120             |                                                                               |      | 4340 | 4480 | 4620 | 4770 | 4910 | 5050 | 5190 | 5320  | 5460  | 5600  | 5730  | 5870  | 6000  |
|              |             | Dual    | 120             |                                                                               |      | 8100 | 8370 | 8630 | 8900 | 9160 | 9420 | 9680 | 9940  | 10190 | 10450 | 10700 | 10950 | 11200 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK DRIVE

## DRIVE AXLE TIRE - DURABILITY FOR DEMANDING ON/OFF-ROAD USE

- Open tread pattern ensures good self-cleaning and grip in changing driving conditions.
- High quality rubber compound for a long service life.
- Low heat build-up means the tire wears evenly and retains its good properties throughout its lifetime.



## AVAILABLE SIZES

- 315/80R22.5 - T675235

# NOKIAN TYRES R-TRUCK DRIVE

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675235      | 315/80R22.5 | 156/150K | TL    | 9.00 | 9.75           | 312        | 1076          | 500                       | 3271                       | 825            | 21               | 351                    | D                  | C        | B           | 75         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br><br>km/h | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         |                             | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   |
| T675235      | 315/80R22.5 | Single  | 110                         | 6610                                                                          | 6810  | 7010  | 7210  | 7410  | 7610  | 7810  | 8000  |
|              |             | Dual    | 110                         | 11070                                                                         | 11410 | 11750 | 12080 | 12420 | 12750 | 13070 | 13400 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKAPOLIITTA TRUCK T

**WINTER TRAILER TIRE - STABLE  
PERFORMANCE AND SECURE TRACTION  
ON SNOW AND ICE**

- Wide zigzag-shape grooves improve self-cleaning and grip on snow.
- Strong shoulders resist wear even in tight cornering.
- Marked stud locations for effective studding.



## AVAILABLE SIZES

- 265/70R19.5 - T675232

# NOKIAN TYRES HAKKAPELIITTA TRUCK T

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675232      | 265/70R19.5 | 143/141J | TL    | 7.50 | 6.75, 8.25     | 262        | 867           | 406                       | 2635                       | 850            | 14.5             | 295                    | D                  | C        | B           | 72         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed<br>km/h | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |       |       |
|--------------|-------------|---------|-------------------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|-------|-------|
|              |             |         |                         | 650                                                                           | 675  | 700  | 725  | 750  | 775  | 800  | 825   | 850   |
| T675232      | 265/70R19.5 | Single  | 100                     | 4400                                                                          | 4530 | 4670 | 4800 | 4930 | 5060 | 5190 | 5320  | 5450  |
|              |             | Dual    | 100                     | 8310                                                                          | 8570 | 8820 | 9070 | 9320 | 9570 | 9810 | 10060 | 10300 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK 844+

## STURDY TIRE FOR ALL SEASONS

- Belt structure ensures even wear and excellent mileage.
- The Spiral Sipe System maintains tire properties even when worn.
- Stone ejectors in the main grooves reduce stone trapping.



## AVAILABLE SIZES

- 275/70R22.5 - T675215

# NOKIAN TYRES HAKKA TRUCK 844+

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim  | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675215      | 275/70R22.5 | 148/145L | TL    | 8.25 | 7.50           | 272        | 964           | 448                       | 2930                       | 900            | 14.5             | 311                    | C                  | B        | A           | 67         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675  | 700  | 725  | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675215      | 275/70R22.5 | Single  | 120             | 4860                                                                          | 5000 | 5150 | 5300 | 5440  | 5590  | 5730  | 5880  | 6020  | 6160  | 6300  |
|              |             | Dual    | 120             | 8940                                                                          | 9220 | 9490 | 9760 | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL-WEATHER TRAILER TIRE – MILEAGE AND STABILITY FOR REGIONAL TRANSPORT

- New tread compound and tire construction for higher mileage and lower rolling resistance.
- Sturdy 5-rib open groove tread pattern with its dense, deep interlocking sipes ensures better grip.
- The wide shoulder design for improved stability and lateral grip as well as protection against lateral scrubbing.



## AVAILABLE SIZES

- 265/70R19.5 - T675268
- 275/70R22.5 - T675273
- 385/55R22.5 - T675267
- 385/55R22.5 - T675304
- 385/65R22.5 - T675266



# NOKIAN TYRES HAKKA TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS       | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|-------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675268      | 265/70R19.5 | 143/141J    | TL    | 7.50  | 6.75, 8.25     | 252        | 871           | 403                       | 2648                       | 850            | 14               | 295                    | C                  | C        | A           | 71         | Yes | Yes                       |
| T675273      | 275/70R22.5 | 148/145L    | TL    | 8.25  | 7.50           | 273        | 969           | 450                       | 2945                       | 900            | 14.5             | 311                    | D                  | C        | A           | 68         | Yes | Yes                       |
| T675267      | 385/55R22.5 | 160K (158L) | TL    | 11.75 | 12.25          | 381        | 1003          | 467                       | 3049                       | 900            | 15               |                        | B                  | C        | A           | 69         | Yes | Yes                       |
| T675304      | 385/55R22.5 | 160K        | TL    | 11.75 | 12.25          |            |               | 456                       | 3018                       | 900            | 15               |                        | C                  | B        | A           | 71         | Yes | Yes                       |
| T675266      | 385/65R22.5 | 160K (158L) | TL    | 11.75 | 12.25          | 380        | 1084          | 501                       | 3295                       | 900            | 15.5             |                        | B                  | C        | A           | 67         | Yes | Yes                       |

## LOAD CAPACITIES


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675  | 700  | 725  | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675268      | 265/70R19.5 | Single  | 100             | 4400                                                                          | 4530 | 4670 | 4800 | 4930  | 5060  | 5190  | 5320  | 5450  |       |       |
|              |             | Dual    | 100             | 8310                                                                          | 8570 | 8820 | 9070 | 9320  | 9570  | 9810  | 10060 | 10300 |       |       |
| T675273      | 275/70R22.5 | Single  | 120             | 4860                                                                          | 5000 | 5150 | 5300 | 5440  | 5590  | 5730  | 5880  | 6020  | 6160  | 6300  |
|              |             | Dual    | 120             | 8940                                                                          | 9220 | 9490 | 9760 | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675267      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570 | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070 | 7280 | 7480 | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |
| T675304      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570 | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675266      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570 | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070 | 7280 | 7480 | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES E-TRUCK TRAILER

## ALL-SEASON TRAILER TIRE – STABILITY AND GRIP FOR REGIONAL TRANSPORT

- New zigzag-shaped grooves improve stability.
- Groove design reduces stone trapping, resulting in longer tire life.
- Good grip on main road use.



### AVAILABLE SIZES

- |                         |                         |
|-------------------------|-------------------------|
| • 215/75R17.5 - T675334 | • 265/70R19.5 - T675244 |
| • 215/75R17.5 - T675254 | • 385/55R22.5 - T675270 |
| • 235/75R17.5 - T675245 | • 385/55R22.5 - T675306 |
| • 235/75R17.5 - T675327 | • 385/65R22.5 - T675217 |
| • 245/70R17.5 - T675246 | • 385/65R22.5 - T675275 |
| • 245/70R17.5 - T675328 | • 385/65R22.5 - T675283 |
| • 265/70R19.5 - T675329 | • 385/65R22.5 - T675305 |

# NOKIAN TYRES E-TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS               | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|---------------------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675334      | 215/75R17.5 | 135/133J            | TL    | 6.00  | 6.75           |            |               | 355                       | 2361                       | 850            | 12               | 239                    | C                  | B        | A           | 69         | Yes | Yes                       |
| T675254      | 215/75R17.5 | 135/133J            | TL    | 6.00  | 6.75           | 212        | 776           | 363                       | 2359                       | 850            | 12               | 239                    | D                  | B        | A           | 69         | Yes | Yes                       |
| T675245      | 235/75R17.5 | 143/141J            | TL    | 6.75  | 7.50           | 238        | 805           | 375                       | 2447                       | 875            | 13               | 262                    | C                  | A        | A           | 69         | Yes | Yes                       |
| T675327      | 235/75R17.5 | 143/141J            | TL    | 6.75  | 7.50           |            |               | 363                       | 2433                       | 900            | 13               | 262                    | C                  | B        | A           | 69         | Yes | Yes                       |
| T675246      | 245/70R17.5 | 143/141J (146/146F) | TL    | 7.50  | 6.75           | 244        | 797           | 368                       | 2423                       | 875            | 13               | 279                    | D                  | A        | A           | 71         | Yes | Yes                       |
| T675328      | 245/70R17.5 | 143/141J (146/146F) | TL    | 7.50  | 6.75           |            |               | 363                       | 2424                       | 900            | 13               | 279                    | C                  | B        | A           | 69         | Yes | Yes                       |
| T675329      | 265/70R19.5 | 143/141J            | TL    | 7.50  | 6.75, 8.25     |            |               | 400                       | 2646                       | 850            | 14               | 295                    | C                  | B        | A           | 69         | Yes | Yes                       |
| T675244      | 265/70R19.5 | 143/141J            | TL    | 7.50  | 6.75, 8.25     | 250        | 871           | 404                       | 2648                       | 850            | 13.5             | 295                    | D                  | A        | A           | 71         | Yes | Yes                       |
| T675270      | 385/55R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 381        | 1003          | 467                       | 3049                       | 900            | 14               |                        | C                  | B        | A           | 69         | Yes | Yes                       |
| T675306      | 385/55R22.5 | 160K                | TL    | 11.75 | 12.25          | 377        | 994           | 457                       | 3040                       | 900            | 14.5             |                        | B                  | B        | A           | 70         | Yes | Yes                       |
| T675217      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 378        | 1080          | 499                       | 3283                       | 900            | 15.5             |                        | C                  | B        | A           | 70         | Yes | Yes                       |
| T675275      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 381        | 1080          | 499                       | 3283                       | 900            | 15.5             |                        | C                  | B        | A           | 68         | Yes | Yes                       |
| T675283      | 385/65R22.5 | 160K (158L)         | TL    | 11.75 | 12.25          | 378        | 1080          | 499                       | 3283                       | 900            | 15.5             |                        | C                  | B        | A           | 68         | Yes | Yes                       |
| T675305      | 385/65R22.5 | 164K                | TL    | 11.75 | 12.25          | 378        | 1073          | 494                       | 3282                       | 900            | 15               |                        | B                  | B        | A           | 69         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |      |      |      |      |      |       |       |     |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|------|------|------|------|------|-------|-------|-----|
|              |             |         | km/h            | 650                                                                           | 675  | 700  | 725  | 750  | 775  | 800  | 825  | 850   | 875   | 900 |
| T675334      | 215/75R17.5 | Single  | 100             | 3520                                                                          | 3630 | 3730 | 3840 | 3940 | 4050 | 4150 | 4260 | 4360  |       |     |
|              |             | Dual    | 100             | 6650                                                                          | 6850 | 7050 | 7260 | 7450 | 7650 | 7850 | 8050 | 8240  |       |     |
| T675254      | 215/75R17.5 | Single  | 100             | 3520                                                                          | 3630 | 3730 | 3840 | 3940 | 4050 | 4150 | 4260 | 4360  |       |     |
|              |             | Dual    | 100             | 6650                                                                          | 6850 | 7050 | 7260 | 7450 | 7650 | 7850 | 8050 | 8240  |       |     |
| T675245      | 235/75R17.5 | Single  | 100             | 4300                                                                          | 4430 | 4560 | 4690 | 4820 | 4950 | 5070 | 5200 | 5330  | 5450  |     |
|              |             | Dual    | 100             | 8120                                                                          | 8370 | 8620 | 8860 | 9100 | 9350 | 9590 | 9830 | 10060 | 10300 |     |


| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |      |      |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675  | 700  | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675327      | 235/75R17.5 | Single  | 100             | 4200                                                                          | 4330 | 4460 | 4580  | 4710  | 4840  | 4960  | 5080  | 5210  | 5330  | 5450  |
|              |             | Dual    | 100             | 7940                                                                          | 8180 | 8420 | 8660  | 8900  | 9140  | 9370  | 9610  | 9840  | 10070 | 10300 |
| T675246      | 245/70R17.5 | Single  | 80              | 4620                                                                          | 4770 | 4910 | 5050  | 5190  | 5320  | 5460  | 5600  | 5730  | 5870  | 6000  |
|              |             | Dual    | 80              | 9250                                                                          | 9530 | 9810 | 10090 | 10370 | 10650 | 10920 | 11190 | 11460 | 11730 | 12000 |
|              |             | Single  | 100             | 4300                                                                          | 4430 | 4560 | 4690  | 4820  | 4950  | 5070  | 5200  | 5330  | 5450  |       |
|              |             | Dual    | 100             | 8120                                                                          | 8370 | 8620 | 8860  | 9100  | 9350  | 9590  | 9830  | 10060 | 10300 |       |
| T675328      | 245/70R17.5 | Single  | 80              | 4620                                                                          | 4770 | 4910 | 5050  | 5190  | 5320  | 5460  | 5600  | 5730  | 5870  | 6000  |
|              |             | Dual    | 80              | 9250                                                                          | 9530 | 9810 | 10090 | 10370 | 10650 | 10920 | 11190 | 11460 | 11730 | 12000 |
|              |             | Single  | 100             | 4200                                                                          | 4330 | 4460 | 4580  | 4710  | 4840  | 4960  | 5080  | 5210  | 5330  | 5450  |
|              |             | Dual    | 100             | 7940                                                                          | 8180 | 8420 | 8660  | 8900  | 9140  | 9370  | 9610  | 9840  | 10070 | 10300 |
| T675329      | 265/70R19.5 | Single  | 100             | 4400                                                                          | 4530 | 4670 | 4800  | 4930  | 5060  | 5190  | 5320  | 5450  |       |       |
|              |             | Dual    | 100             | 8310                                                                          | 8570 | 8820 | 9070  | 9320  | 9570  | 9810  | 10060 | 10300 |       |       |
| T675244      | 265/70R19.5 | Single  | 100             | 4400                                                                          | 4530 | 4670 | 4800  | 4930  | 5060  | 5190  | 5320  | 5450  |       |       |
|              |             | Dual    | 100             | 8310                                                                          | 8570 | 8820 | 9070  | 9320  | 9570  | 9810  | 10060 | 10300 |       |       |
| T675270      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070 | 7280 | 7480  | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |
| T675306      | 385/55R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
| T675217      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070 | 7280 | 7480  | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |
| T675275      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940 | 8180 | 8410  | 8640  | 8870  | 9100  | 9330  | 9550  | 9780  | 10000 |
| T675283      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150 | 7360 | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |
|              |             | Single  | 120             | 6860                                                                          | 7070 | 7280 | 7480  | 7690  | 7890  | 8100  | 8300  | 8500  |       |       |
| T675305      | 385/65R22.5 | Single  | 110             | 7710                                                                          | 7940 | 8180 | 8410  | 8640  | 8870  | 9100  | 9330  | 9550  | 9780  | 10000 |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

# NOKIAN TYRES R-TRUCK TRAILER

## TRAILER TIRE – RELIABLE PERFORMANCE ON VARIABLE SURFACES FOR ON/OFF-ROAD USE

- Robust design ensures excellent mileage in addition to resistance to damage.
- Special rubber compound and low heat build-up means that tire wears evenly and retains its good properties throughout its lifetime.
- Strong shoulders withstand tight cornering and the staggered tread pattern wears evenly.



## AVAILABLE SIZES

- 265/70R19.5 - T675242
- 265/70R19.5 - T675295
- 285/70R19.5 - T675269
- 275/70R22.5 - T675243
- 385/65R22.5 - T675234

# NOKIAN TYRES R-TRUCK TRAILER

## ALL SIZES

| Product code | Size        | LI/SS    | TL/TT | Rim   | Permitted rims | Width (mm) | Diameter (mm) | Loaded static radius (mm) | Rolling circumference (mm) | Pressure (kPa) | Tread depth (mm) | Min. dual spacing (mm) | Rolling resistance | Wet grip | Noise class | Noise (dB) | M+S | Snow grip marking (3PMSF) |
|--------------|-------------|----------|-------|-------|----------------|------------|---------------|---------------------------|----------------------------|----------------|------------------|------------------------|--------------------|----------|-------------|------------|-----|---------------------------|
| T675242      | 265/70R19.5 | 143/141J | TL    | 7.50  | 6.75, 8.25     | 252        | 877           | 405                       | 2666                       | 850            | 15               | 295                    | E                  | B        | B           | 73         | Yes | Yes                       |
| T675295      | 265/70R19.5 | 143/141J | TL    | 7.50  | 6.75, 8.25     | 259        | 872           | 403                       | 2601                       | 900            | 15               | 295                    | D                  | A        | A           | 71         | Yes | Yes                       |
| T675269      | 285/70R19.5 | 150/148J | TL    | 8.25  | 9.00           | 266        | 895           | 413                       | 2720                       | 900            | 14.5             | 318                    | D                  | B        | B           | 72         | Yes | Yes                       |
| T675243      | 275/70R22.5 | 148/145K | TL    | 8.25  | 7.50           | 273        | 972           | 451                       | 2955                       | 900            | 16               | 311                    | D                  | B        | B           | 74         | Yes | Yes                       |
| T675234      | 385/65R22.5 | 160K     | TL    | 11.75 | 12.25          | 389        | 1072          | 496                       | 3258                       | 900            | 15               |                        | C                  | B        | B           | 74         | Yes | Yes                       |

## LOAD CAPACITIES

| Product code | Size        | Fitting | Reference speed | Maximum load capacity per axle (kg) at various cold inflation pressures (kPa) |       |       |       |       |       |       |       |       |       |       |
|--------------|-------------|---------|-----------------|-------------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|              |             |         | km/h            | 650                                                                           | 675   | 700   | 725   | 750   | 775   | 800   | 825   | 850   | 875   | 900   |
| T675242      | 265/70R19.5 | Single  | 100             | 4400                                                                          | 4530  | 4670  | 4800  | 4930  | 5060  | 5190  | 5320  | 5450  |       |       |
|              |             | Dual    | 100             | 8310                                                                          | 8570  | 8820  | 9070  | 9320  | 9570  | 9810  | 10060 | 10300 |       |       |
| T675295      | 265/70R19.5 | Single  | 100             | 4200                                                                          | 4330  | 4460  | 4580  | 4710  | 4840  | 4960  | 5080  | 5210  | 5330  | 5450  |
|              |             | Dual    | 100             | 7940                                                                          | 8180  | 8420  | 8660  | 8900  | 9140  | 9370  | 9610  | 9840  | 10070 | 10300 |
| T675269      | 285/70R19.5 | Single  | 100             | 5160                                                                          | 5320  | 5480  | 5640  | 5790  | 5940  | 6100  | 6250  | 6400  | 6550  | 6700  |
|              |             | Dual    | 100             | 9710                                                                          | 10010 | 10310 | 10600 | 10890 | 11180 | 11470 | 11750 | 12040 | 12320 | 12600 |
| T675243      | 275/70R22.5 | Single  | 110             | 4860                                                                          | 5000  | 5150  | 5300  | 5440  | 5590  | 5730  | 5880  | 6020  | 6160  | 6300  |
|              |             | Dual    | 110             | 8940                                                                          | 9220  | 9490  | 9760  | 10030 | 10290 | 10560 | 10820 | 11080 | 11340 | 11600 |
| T675234      | 385/65R22.5 | Single  | 110             | 6940                                                                          | 7150  | 7360  | 7570  | 7780  | 7990  | 8190  | 8390  | 8600  | 8800  | 9000  |

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.